

**Notice regarding specifications**

I.U. = Indoor Unit O.U. = Outdoor Unit Qu = Quiet \* = Not decided yet

- Specifications and design are subject to change without notice for future improvement.
- For further details, check with our authorized dealers.
- Cooling and heating capacities are based on the following conditions:

Cooling	Indoor temp. : 27°C DB/19°C WB Outdoor temp. : 35°C DB/24°C WB
---------	---

Heating	Indoor temp. : 20°C DB Outdoor temp. : 7°C DB/6°C WB
---------	---

- Performance tests are conducted in accordance with EN14511.
- Seasonal efficiency tests are conducted in accordance with EN14825.
- Sound power tests are conducted in accordance with EN12102.



Fujitsu General (Thailand) Co., Ltd.



ISO 9001 Certification number: 01 100 075229  
ISO 14001 Certification number: 01 104 9245

Fujitsu General (Shanghai) Co., Ltd.



ISO 9001 Certification number: 01 100 79269  
ISO 14001 Certification number: CNBJ312244-UK

Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.



ISO 9001 Certification number: 15917Q20073R5M  
ISO 14001 Certification number: 15918E20021R5M

- The products and equipment listed in this catalog contain fluorinated greenhouse gases.
- "GENERAL" and "AIRSTAGE" are worldwide trademarks of Fujitsu General Limited, and are registered trademarks in Japan and other countries and regions.
- iPhone and iPod touch are trademarks of Apple Inc., registered in the United States and other countries.
- "Microsoft," "Windows," and "DirectX" are trademarks of Microsoft Corporation in the United States and other countries.
- "Intesis" is a registered trademark of HMS Industrial Networks in the European Union and is trademarked in the rest of the world.
- "BACnet" is a trademark and registered trademark of the American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc.
- "MODBUS" is a registered trademark of Schneider Electric.
- "LONWORKS" and "Echelon" are trademarks of Echelon Corporation registered in the United States and other countries.
- "Adobe" and "Acrobat Reader" are either registered trademarks or trademarks of Adobe in the United States and/or other countries.
- "Android" is a trademark of Google LLC.
- Other company and product names mentioned in this document may be the registered trademarks, trademarks or trade names of their respective owners.
- "Polar" is a worldwide trademark of Fujitsu General Limited.
- "Bluetooth" is a registered trademark of Bluetooth SIG, inc.

Distributed by:

**FUJITSU GENERAL LIMITED**

3-3-17, Suenaga, Takatsu-ku, Kawasaki, Kanagawa, 213-8502, Japan  
www.fujitsu-general.com



Copyright© 2008-2024 Fujitsu General Limited. All rights reserved. 3EG039-2407E



**PRODUCT CATALOGUE  
2024**

**AIR CONDITIONERS LINEUP**

GENERAL

PRODUCT CATALOGUE 2024

AIR CONDITIONERS LINEUP

FUJITSU GENERAL LIMITED

FUJITSU GENERAL LIMITED

OUR MESSAGE SOLUTIONS SPLIT MULTI-SPLIT VRF VENTILATION CONTROL SYSTEM & OPTIONAL PARTS AIR TO WATER SUPPORT

# The FUJITSU GENERAL Way

## Our mission

# Living together for our future

Through innovation and technology, we deliver a brighter future with peace of mind to our customers and societies around the world.

## Our philosophy

### Act spontaneously

We embrace new challenges by investing in ourselves for personal growth, and through continuous creativity with a spontaneous attitude.

### Develop our team

We respect and value our people, and optimize their abilities through fostering culture and diversity, and utilizing a collaborative effort focused on communication.

### Value integrity

To achieve our goals, we always act with integrity and shared ethics.

## CONTENTS

### 004 OUR MESSAGE

- 006 Sustainable
- 008 Cleanliness
- 010 Future
- 012 Comfort
- 014 Control
- 016 Design
- 018 History
- 020 Worldwide locations
- 022 Global business activities
- 024 Project references
- 026 Global development & Production bases
- 028 High-quality development & Production Facilities
- 030 2024 New Products

### 034 SOLUTIONS

- 036 For Light Commercial Use
- 044 For Commercial Use
- 046 For Apartments & Houses

#### PRODUCT LINEUP

- SPLIT & MULTI-SPLIT
- VRF
- VENTILATION
- CONTROL SYSTEM & OPTIONAL PARTS
- AIR TO WATER

### SUPPORT

- Sp-002 VRF Support
- Sp-004 HVAC System design Support Tool
- Sp-006 Air To Water Support Tool
- Sp-008 Quick Service & Maintenance
- Sp-010 AIRSTAGE Service Monitor Tool
- Sp-012 Service Tool
- Sp-013 Web monitoring tool

# OUR MESSAGE



for Sustainable



for Cleanliness



for Future

**Innovation  
and  
Globalization**



for Comfort



for Control



for Design

We create comfortable lives for people around the world with "made-in-Japan quality" and innovative manufacturing.

-  History
-  Worldwide locations
-  Global business activities
-  Project references
-  Global development & Production bases
-  High-quality development & Production facilities



# Sustainable




## Sustainable management

We see the challenge of expanding our business by contributing to the realization of a sustainable society as a core element of our growth strategy, and we are working on “sustainable management,” based on the three pillars of “harmonious coexistence with our planet,” “social contribution,” and “care for employees.”

## Basic policy on sustainable management

The sustainable development goals (SDGs) of the UN will drive business creation in the coming years. The key principle of the SDGs, “Leave no one behind,” is synonymous with our own corporate philosophy of “Living together for our future.” The promotion of sustainable management is carried out from a medium- to long-term perspective, with a promise to shape a sustainable society for the children and society of the future. We will pursue business growth by accelerating this transformation.



### Our People (Care for employees)

- Strategic implementation of health and productivity management
- Creating flexible work styles under COVID-19
- Enhancing human resource development

### Society (Social contribution)

Fostering innovation to address social issues (Providing a healthy, clean, and safe society and environment)



# Cleanliness



## Think about air quality

Fresh air is essential for comfortable air conditioning. Fujitsu General offers a wide range of air conditioning products with air purification functions, such as ventilation systems equipped with high-performance filters and heat exchangers.



## Collecting dust particles to clean the air



### Silver Ion Filter

The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.

Notice: Not a result of experiments in an actual use environment. Silver ion filter inhibits activity or growth of microorganism, but do not prevent infection.




## Different filters are used on each side



### Ion Deodorization Filter

Deodorizes the air by decomposing absorbed odors using the oxidizing and odor-reducing effects of ions generated by ultra-fine particle ceramic.




### Apple-catechin Filter

The Apple-catechin filter uses static electricity to remove fine particles and dust from the air.

## Ventilation with adequate airflow with reduced temperature changes

### Heat Exchange Ventilation

When a room is cooled or heated, the exhausted cooling or heating energy is recovered by heat exchange ventilation.





# Future




## The green refrigerant

Throughout our research and development process, we are constantly striving to create products that we can be proud of in the future. The technologies we have cultivated through these efforts are incorporated into our environmentally friendly products, and are recognized in the European market, which has extremely strict environmental regulations.

### R32 refrigerant with reduced global warming potential


- **Zero** Ozone Depletion Potential (ODP<sup>\*1</sup>)
- High environmental properties
- High performance
- Economically efficient

<sup>\*1</sup> **ODP (Ozone Depleting Potential)**: a relative value that indicates the impact per unit weight of ozone-depleting substances released into the atmosphere when CFC-11 (trichlorofluoromethane, CCl3F) is fixed at 1.0  
<sup>\*2</sup> **GWP (Global Warming Potential)**: a measurement that indicates how much other greenhouse gases are capable of warming the Earth based on carbon dioxide. This is the integrated value of radiant energy given to the Earth (i.e., the estimated impact on global warming) expressed as a ratio to CO2.




### Low GWP to a wide range of projects

We are continuously working to develop products that use R32 refrigerant and have R32 products in all product categories in our lineup (Split, Multi-Split, VRF, and ATW). This allows us to realize environmentally and regulatory friendly system designs for a wide range of projects from residential to light commercial.



### New energy labelling requirement 626/2011/EU

Our air conditioners have reached the **"Class A+++"** ranking, the highest energy efficiency level that is now shown on energy labels in Europe.



### Fujitsu General's Environmental Vision

#### Medium-Term Environmental Plan: Target and Measure

	Target	Measure
Reduction of Our Own Environmental Impact Achieve	<p><b>Achieve carbon neutrality by FY2025</b></p> <p>▲</p> <p>[Old Target]</p> <p>Greenhouse gas emissions from our Group's business activities: Completely eliminate by FY2030</p>	<ol style="list-style-type: none"> <li>1. Renewable energy conversion: Existing plants (by FY2023)</li> <li>2. Renewable energy conversion: All Group companies (by FY2025) → <b>Achieved 1 and 2 ahead of schedule (April 2022)</b></li> <li>3. Shift to use of renewable energy for all other energy used (by FY2025)</li> </ol>
Through Our Supply Network	Reduction of 30% for total greenhouse gas emissions through our supply Network by FY2035 (vs. FY2018)	<ul style="list-style-type: none"> <li>• Promotion of green electricity use by our suppliers</li> <li>• Reduction of material consumption and product weight</li> </ul>
For our Customers and Society	Reduce greenhouse gas emissions from the use of our products. Reduction of 30% by FY2030 (vs. FY2013)	<ul style="list-style-type: none"> <li>• Replace constant-speed A/C with inverter A/C (India and Middle East)</li> <li>• Enhance energy efficiency</li> </ul>



# Comfort



## Comfortable airflow design


Pursuing the potential of air conditioners and true comfort, Fujitsu General has developed and commercialized numerous world-first technologies, and these concepts are reflected in the design of our products.

### Cassette type 3D flow Series

**3 individually controlled air outlet ports**

The Comfortable airflow setting enables the right and left air outlet ports as well as the wide center port to work together to provide a comfortable room environment.

\*1: Announced 2018. In room air conditioner for the home (Our company's investigation)



### Cassette type One-way flow Series

**Wide airflow range created by triangle design and large flap**

A large flap with a wide range of movements, equipped with louvers arranged triangularly, sends air into every corner of the room.

### Cassette type Circular flow Series

**Unique circular flow design**

This Series realizes a Circular Flow to blow a large airflow in a 360° direction by using a high-performance DC fan motor, turbo fan, and a unique seamless airflow louver design.



### Auto louver grille kit for Mini duct and Slim duct

**Flexible Control**

The optional clean-looking flat Auto louver grille kit blends into any interior and provides a comfortable airflow.





# Control

## Operation from anywhere

Using the Internet of Things (IoT), Fujitsu General is actively providing services that allow users to control their air conditioners from their smartphones. We are also expanding our open co-creation activities with external partners to deepen the development of new functions and services using IoT and artificial intelligence (AI) to develop safe and convenient air conditioners.



User-friendly screen display enables easy operation.

With the WLAN adapter and the AIRSTAGE Mobile app, you can control the heating and cooling of your home anytime, anywhere.



Voice control via smart speaker

Connecting with a smart speaker allows the user to operate the air conditioner and check its operation status just by talking to it.

### Software application for WLAN Adapter

"AIRSTAGE Mobile" is a software application that allows users to control Fujitsu General air conditioners from anywhere with a mobile device while out or on the move.



+  
**AIRSTAGE  
Mobile**

Download Free



### Compact wired remote controller

Large screen and simple display

- Large screen, yet compact in size
- Large, easy-to-read letters are used.
- The controls are simple and easy to understand.



### Central remote controller for VRF system

The central remote controller uses a touch panel screen to display multiple menus on the top screen. Just touch the menu you want to operate, and the necessary window will pop up, and allow intuitive operation.

### Remote monitoring and operation

The central remote controller enables monitoring and control of a tenant's air conditioner anytime, anywhere.







# Design



## Harmonizes with the installation space

Fujitsu General offers a wide range of products for the European market, including models with unique textural designs, award-winning models that integrate with room interiors, and Cassette type models with different designs that match office spaces. We also have a lineup of models with elegant designs, such as the Ceiling type models with its beautiful curved surface.



### Light Elegant Design

**New Ceiling type design**

The light, elegant and three-dimensional expression achieved by the curved surface gives a sense of comfort and well-being.



**NEW** KN Series KL Series

### New "Elegant & Smart" Square Design

**New Wall-mounted type design**

Smart design with ridges and subtle shade  
\*Image is KN Series

**NEW**

### Sleek and Stylish Design

**New designed wired remote controller**

When not in use, the controller is a part of the interior decor. This is achieved by using mirrors, glass, and clear panel, and it appears to be on with the wall.



**NEW**

### Stylish design

**New outdoor unit for Air to Water** **Future Release**

A design that offers a sophisticated style that is quiet and blends in with the outdoor landscape.





# History

Yaou Shoten Ltd. established in 1936

## Overseas air conditioning business since 1971

Starts air conditioning business in Japan in 1960

**1971** Air conditioner exports to the Middle East.

**1977** "Super Power, Super Quiet" Series released

**1982** Window type 3 Super Series released



**AL/AX Series**

**1985** Large wall-mounted type and multi-split air conditioner released.


**1991** World's first air conditioner equipped with lambda heat exchanger

**1994** World's first air conditioner with power diffuser

**2001** AIRSTAGE Series released VRF air conditioners for large buildings



**2002** Air conditioner with the world's first automatic self-cleaning filter system



**2004** Standalone Compact VRF AIRSTAGE J Series released



**2006** VRF Heat Pump type Maximum 42 HP AIRSTAGE V Series released



**2009** VRF Heat Pump Modular type Maximum 48 HP AIRSTAGE V-II Series released



**2009** Air to water system released



**For Light commercial use**

**2011** Compact 2 Fan type VRF AIRSTAGE J-II Series released

**2014** Compact 1 Fan type VRF AIRSTAGE J-IIS Series released

**2016** Compact 2 Fan type VRF AIRSTAGE J-III Series released

**2017-19** Compact VRF AIRSTAGE J-IIIL Series for light commercial use released

**2020** Compact & lightweight outdoor unit AIRSTAGE J-IVL, J-IV, J-IVS Series released



**2019** New cassette style released 3D Flow Cassette

**For Commercial use**

**2012** VRF AIRSTAGE VR-II Series released

**2014-15** VRF AIRSTAGE VR-III Series released

**2020** Heat Recovery Modular type VRF AIRSTAGE VR-IV Series & AIRSTAGE Air handling unit released



**VRF V-IV**

**2022** Energy-saving operation model VRF V-IV Series released

**For Residential use**

**2011** Hi-spec Design model LT Series & LU Series released

**2017** Flagship Wall-mounted type "nocria X" released

**2017-19** Added to this lineup recently are the environment-friendly R32 refrigerant models. (Split & Multi-split type)

**2022** Harmonizes beautifully design model KE Series released



**For Commercial use**

## VRF J-VS

**2024** New VRF products with R32 refrigerant released



**For Light commercial use**

**For Residential use**

**Split & Multi-split** New Wall-mounted type & Duct type with high-energy saving released



**New "Elegant & Smart" Square Design model released**

**Cooling-enhanced type** High-efficiency operation even at high outdoor temperatures



**Wired Remote Controller** Simple and stylish design that harmonizes with the installation space



1950 ~

1970 ~

2000 ~

2010 ~

2024 What's New

## Manufacturing Company Establishment

**1955** Head Office established in Kawasaki

**1964** Electronic components factory in Ichinoseki



**1977** Air conditioner manufacturing company in Hamamatsu (now Hamamatsu business office)

**1991** Air conditioner manufacturing company in Thailand

**1994** Air conditioner manufacturing company in Shanghai, China

**1998** Air conditioner motor manufacturing company in Thailand

**2006** VRF air conditioner manufacturing, sale, and service company in China

**2007** Air Conditioner Technology Building becomes operational on the premises of the Kawasaki Headquarters. Air conditioner R&D Center in Kawasaki

**2009** Compressor Factory begins operation in Thailand

**2012** Joint venture in Thailand to manufacture compressors

**2016** Commercial use air conditioner R&D Center in Thailand

**2019** New building constructed at Kawasaki Head Office to strengthen development capabilities



**2020** Building IoT - based manufacturing in Thailand



**2023** FGAI R&D New Office: FGAI Research & Development office moved to the new office in New Jersey, USA



Fujitsu General (UK) Co., Ltd. (UK)



Fujitsu General (Euro) GmbH

## Sales & service maintenance company established

**1976** North America sales company

**1977** Europe sales company (UK)

**1978** Australia sales company and Europe sales company (Germany)

**1980** Brazil sales company

**1997** Asia sales company (Singapore)

**1998** Middle East sales company (UAE) and New Zealand sales company

**2000** Air conditioner manufacturing and sale technical partnership in India

**2002** Taiwan sales company

**2006** China sales company

**2016** THE AIRSTAGE on Broadway in New York



**2023** Communication Lounge EURO: New lounge in Dusseldorf, Germany



\*1: Announced 1991. In room air conditioner for the home (Our company's investigation) \*2: Announced 1994. In the category of room air conditioners for the home (Our company's investigation). \*3: Announced 2002. In the category of room air conditioners for the home (Our company's investigation).

\*4: Announced 2018. In room air conditioner for the commercial (Our company's investigation) \*5: Announced 2012. In room air conditioner for the home (Our company's investigation)



# Worldwide locations


Under a system of five bases in Europe, the Middle East, Asia and Oceania, North and South America, and Japan, the company promotes Globalization from a worldwide perspective while emphasizing the actual conditions in each region.



JAPAN Head Office



Technology research building (Japan)



## 17 Overseas Sales Companies



Fujitsu General (Taiwan) Co., Ltd. (Taiwan)



Fujitsu General (Thailand) Co.,Ltd. Bangkok Office (Thailand)



Fujitsu General Electronics (Suzhou) Co., Ltd.



Fujitsu General South East Europe S.A. (Greece)



Fujitsu General (Aust.) Pty Ltd. (Australia)



Precise Air Group (Holding) Pty Ltd. (Australia)



Fujitsu General New Zealand Ltd. (New Zealand)



Fujitsu General (Middle East) Fze (U.A.E.)



Fujitsu General New Zealand Ltd.



Fujitsu General (Euro) GmbH (Germany)



Fujitsu General Air Conditioning (UK) Ltd. (U.K.)




Fujitsu General (Italia) S.p.A (Italy)



Fujitsu General (India) Private Ltd. (India)



ABS Fujitsu General Private Ltd. (India)



Fujitsu General Do Brasil Ltda.(Brasil)



Fujitsu General America, Inc. (U.S.A.)



Kløver Vest Holdings AS (Norway)




FUJITSU GENERAL SOLUTION CENTER "THE AIRSTAGE" (U.S.A.)



# Global business activities

We have been recognized for our activities in advertising, human resource development and customer service, as well as for our community-based social contribution activities in each region, winning numerous awards and achieving a high level of customer satisfaction.



## North and South Americas



AHR Expo



HVAC trade shows in Brazil



Distributor conference in USA



Call center

## Middle East




Exhibition



Training in Kuwait



Launch event in Oman



New product seminar in UAE

## Europe



HVAC trade show in Germany



Training in Germany



HVAC trade show in Germany



Training seminar in Italy



Event in the United Kingdom

## Oceania



HVAC trade show in Australia



Launch event in New Zealand



Launch event in New Zealand

## Asia



Thanksgiving party in Taiwan



Exhibition in India



Opening ceremony in India



New product presentation seminar in Singapore



Service training in Vietnam

## International authoritative design awards



The NEWS Dealer Design Awards



Gold Award (Category: HVAC & PLUMBING) in Reader's Choice Awards



TOP OF MIND 2016 First prize in "MARCA DE EQUIPAMENTO DE AR-CONDICIONADO" category of "CLIMATIZACAO" division



Superbrands is the world's largest independent arbiter of branding.



The iF Product Design Award is given annually by iF International Forum Design GmbH for industrial products from around the world.



The Plus X Award is the world's largest innovation award for technology, sports and lifestyle.



reddot winner 2024

A product design competition that has been held since 1955. Products that win the award are given the "Red Dot" seal, a sign of international recognition of quality.



One of the famous design award in the world. Designs are judged on innovation and aesthetics, as well as their benefit to users, clients/brands, and society.



ProductReview.com.au's annual awards are selected from products and services that have been well-rated by the ProductReview community.



Voted by Australians as the "Most Trusted Brand" - Air Conditioning Category 5 Years Running



China State Construction Engineering Luban Prize





The Good Design Award is an award sponsored by the Japan Institute of Design Promotion, and is given once a year to items of outstanding design.



# Project references




Introduced in over 50 countries worldwide

Highly popular for their excellent quality, energy efficiency, and ease of installation, Fujitsu General's products are installed in a wide range of buildings around the world, including high-rise office buildings, stores, hotels, public facilities, schools, hospitals, and residences.



## For Light commercial use

- 1 Shop in Europe
- 2 Factory in Europe
- 3 School in Asia
- 4 Hospital in Asia
- 5 Office in Asia
- 6 Shop in Oceania
- 7 Office in Oceania
- 8 School in the Middle East
- 9 Public facility in the United States



## For Commercial use

- 10 Public Square in Asia
- 11 Hotel in Asia
- 12 Hotel in Asia
- 13 Public facility in Asia
- 14 Apartment in Oceania
- 15 Apartment in Oceania
- 16 Hotel in the Middle East
- 17 Hotel in the Middle East



## For Residential use

- 18 Villa in the Africa
- 19 Residence in Oceania
- 20 Residence in the United States
- 21 Villa in the Middle East



# Global development & Production bases

We have established R&D bases in five countries from Japan, Europe, Asia, China, and North America to pursue environmental properties and comfort according to the needs of each region.

- Head office
- R&D center
- Manufacturing companies

## R&D center & Technology Research Building



R&D center in Fujitsu General (Euro) GmbH (Germany)



North America R&D Center (USA)



Fujitsu General Air Conditioning R&D (Thailand) Co., Ltd. (Thailand)



R&D center in Fujitsu General (Shanghai)




JAPAN Head office, R&D center and 60 m height difference testing tower (Japan)

Technology research building in Japan Head office



**Constructing IoT-based manufacturing**  
We are implementing a real-time IoT-enabled system to immediately visualize and analyze various information such as facility operating status, assembly line production progress, and parts inventory and transportation status. This will further enhance the accuracy of production and shipping forecasts in the Head Office and factory management departments. The system will also help improve activities by employees at production sites, with the aim of improving the efficiency of the production process, the efficiency of parts distribution operations, and the utilization rates of the facilities.



• Fujitsu General (Euro) GmbH  
— R&D center

• FGAHP

• North America R&D Center  
— R&D center

• Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.

• F.G.L.S Electric Co., Ltd.

• Fujitsu General Electronics Ltd.

• Fujitsu General Limited  
— R&D center

• Fujitsu General (Shanghai) Co., Ltd.  
— R&D center

- Fujitsu General Air Conditioning R&D (Thailand) Co., Ltd. — R&D center
- Fujitsu General (Thailand) Co., Ltd.
- FGA (Thailand) Co., Ltd.
- TCFG Compressor (Thailand) Co., Ltd.

## Overseas manufacturing companies



Fujitsu General (Shanghai) Co., Ltd. (China)



F.G.L.S Electric Co., Ltd. (China)



Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd. (China)



Fujitsu General Electronics Ltd. (Japan)



FGAHP



Fujitsu General (Thailand) Co., Ltd. (Thailand)



FGA (Thailand) Co., Ltd. (Thailand)



Fujitsu General Air Conditioning R&D (Thailand) Co., Ltd. (Thailand)



TCFG Compressor (Thailand) Co., Ltd. (Thailand)



# High-quality development & Production facilities

## Advanced Research Facilities and Equipment

### Performance tests



**Airflow measurement room**  
Measure the airflow of air conditioners, from compact room air conditioner models to variable refrigerant flow (VRF) systems.




**Calorimeter**  
Measure the temperature, humidity, and airflow at the inlet and outlet of the air conditioner to evaluate its cooling and heating capacity.



**Silent room**  
Measure the operating sounds of air conditioners on walls and ceilings with reduced sound reflection.

Fujitsu General is one of Japan's leading manufacturers with R&D centers in Japan. The research and development conducted in these facilities contributes to providing our customers with the highest quality and performance.

### Reliability tests



**Constant temperature room**  
Verify product performance in cooling and heating operations under various temperature and humidity conditions.



**Practical test room**  
Check whether the performance of the air conditioner can be sustained under the conditions of the actual housing environment.



**Shower test room**  
Check if the electrical box of the outdoor unit is protected from strong wind and rain, such as during a typhoon.

### Transportation and Handling Tests



Compressibility test




Vibration test



Technology research building in Japan Head office

## Testing laboratory

Fujitsu General EMC Laboratory Limited



### 60-m Height Difference testing tower


Tests oil circulation in a compressor for reliability.



## Certification of ISO 9001 and ISO 14001

■ ISO 9001  
■ ISO 14001  
( ) Number of companies

The Group's 5 overseas production subsidiaries are individually certified with ISO 9001 and ISO 14001. The Group's 11 overseas sales subsidiaries have been certified with ISO 14001 since 2012.



## Product Quality Assurance


All Fujitsu General plants are ISO 9001 certified and operate under a unified quality control system. We deliver to customers all over the world high-quality products that have passed stringent quality inspections.

### Receiving inspection

We require all our parts suppliers to submit test reports to ensure that all parts we receive from them meet our quality standards. Our in-house test department inspects incoming parts to ensure their compliance with RoHS as required by the EU. We also conduct 100% inspection of main parts to prevent defective parts from making it to assembly lines.

### Quality inspection of products

We carry out stringent quality inspections in all production processes performed in our plants. To keep the quality of our products high, inspectors check their quality from start to finish on production lines.



# 2024 New Products



**R32** Split, Wall-mounted type  
Built-in W-LAN adapter models

**KL Series** ECO Range  
Compact Size (Cooling-enhanced type)

**S-032-033**

- 7-12 classes, 3 models
- Elegant & smart square design
- High energy saving
- Comfortable airflow & Quiet operation
- Smart device control
- Easy access to the flare pipe connection



SPLIT



MULTI-SPLIT



## Wall-mounted type Built-in W-LAN adapter models

Designer Range, Standard Range

**S-016, 020** **M-006, 022**


- Improved energy efficiency from the current products
- 7-14 classes, 8 models
- High energy saving
- Built-in WLAN adapter
- Comfortable airflow & Quiet operation
- Easy access to the flare pipe connection



**KG Series** Designer Range  
High Spec & Design



**KM Series** Standard Range  
High-Efficiency & Comfort



### Smart Device control

You need to install the "AIRSTAGE Mobile" app on your smart device in order to control the air conditioner.

### ECO Range

**S-022-023** **M-006, 023**

- 5-12 classes, 4 models \*5 class only for multi-split
- Elegant & smart square design
- High energy saving
- Comfortable airflow & Quiet operation
- Built-in WLAN adapter
- Easy access to the flare pipe connection



**KN Series** ECO Range  
Compact Size



### Impression of Soft Black

Soft Black is a natural black color with a relatively gentle tone and no strong contrast. A Soft Black harmonizes with the environment and creates a warm atmosphere.

### Soft black color models

**S-020** **M-022**

- Soft Black
- 7-14 classes, 4 models
- High energy saving
- Built-in WLAN adapter
- Easy access to the flare pipe connection



Wireless R.C.



**KM Series** Standard Range  
High-Efficiency & Comfort



## Medium static pressure duct

High-efficiency & Comfort

**S-040-043** **M-007, 025**

- 12-54 classes \*Multi-split is only 12-22 classes
- Slim & Compact design
- High energy saving
- Easy maintenance
- Drain hose as standard
- Wide range of static pressures



12-18 class



22 /24 class  
\*Multi-split is only 12-22 classes



30-54 class





## VRF J-VS

### Heat Pump for Small-capacity type

Outdoor unit

V-020-025

- **Sustainable:** R32 refrigerant with reduced global warming potential
- **Saving CO2:** Top class high energy saving
- **Small Body:** Easy carriage and installation
- **Situational Piping Design:** Long pipe length, Up to 13 indoor units\* can be connected
- **Sightliness installation:** External static pressure, cooling piping system

\*: 6 HP model



Indoor unit

V-058-065

- 4 - 24 classes, 3 type, 34 models
- Compact & Slim design
- Flexible installation



Compact Cassette



Low Static Pressure Duct  
Slim Duct/Slim Concealed Floor



Wall-mounted type

## CONTROL SYSTEM

### Wired remote controller

Design type

C-010-011

- Harmonizes with the Installation Space
- Intuitive operation
- Status LED Colors
- Refrigerant cycle monitor
- Logo Display
- AIRSTAGE Remo Set application (free download)
- Initial Settings / Indoor Unit Function



## New Monobloc system

Comfort series

Future Release

- 5-10 kW classes, 3 Models
- High energy efficiency
- Quiet operation
- Easy installation & maintenance



## SUPPORT

### AIRSTAGE Service Monitor Tool

for Single-split, Multi-split, Air to water

Sp-010-011

- Improved work efficiency
- Bluetooth communication
- Compact and lightweight design
- New application with simple design
- Refrigerant cycle graph display

UTY-ASSXZ1



AIRSTAGE Service Monitor Tool

\*Android only.  
You need to install the "AIRSTAGE Service Monitor Tool" app on your smart device.



From Business to private spaces  
**SOLUTIONS**



**Key solution points**

Fujitsu General's total solutions are tailored to each property's unique needs.

Fujitsu General provides the best control solutions for buildings.



**Target buildings**

- A casual conversation with a colleague at work
- A presentation in a large meeting room
- A restaurant you stop by Your living room

We have a comprehensive lineup of air conditioners ideal for all these situations—from business to private spaces. Fujitsu General's air conditioners are used in all aspects of everyday life.



**For Light commercial use**

Comfortable and economical air conditioning systems, ideal for small and midsize commercial buildings

- 036 Restaurants, Shops
- 038 Small offices
- 040 Hotels
- 042 Schools



**For Commercial use**

Single and modular VRF systems for high efficiency, comfort, design flexibility, ease of installation, and high reliability

- 044 Large Buildings



**For Residences**

Smart air conditioning systems with extensive control options for comfort and convenience of use

- 046 Residences

# Restaurant, shops



For Light commercial use

Fujitsu General provides perfect total air conditioning systems that offer seamless support by tenant, by purpose, and by customer visit frequency in shops and restaurants with multiple lighting and a high density of customers.



## Single split

For Restaurants



### R32 large model lineup expanded

Expanded lineup of ceiling, cassette, and duct types suitable for large spaces using environmentally friendly R32 refrigerant




### Two panel colors

Both black and white panels are available for Cassette type. Black panels are suitable for dark places such as atmospheric restaurants. White panels, by contrast, are more appropriate for use in brightly lit spaces such as offices. (Available for Single split and VRF indoor units)


## Simultaneous multi-split

For Shops




### Various indoor unit lineup

You can choose from 3 types of indoor units to suit the atmosphere and layout of your shop.



### Small, lightweight outdoor unit



Models equipped with the new R32 refrigerant. Compared to current models, the outdoor unit is more compact and easier to install. (45/54 models) Compact cassette Series for grid ceiling were added to the lineup of indoor units to improve ease of installation.



# Small offices

For Light commercial use

Fujitsu General offers a perfect total air conditioning system for small office buildings with multiple small rooms, taking into consideration energy savings, low noise, comfortable air volume, usage and purpose, and centralized control.



## Breakthrough 3D flow cassette with innovative pursuit of comfort

The left and right air outlet ports with a maximum rotation angle of 100° and the wide central air outlet port create a comfortable space with less uneven temperature.



## Central remote controller with improved operability

Controls the temperature of each room easily, and manages and sets the operation control for a week. Energy-saving management by setting upper and lower temperature limits and operating prohibitions.



Central remote controller UTY-DCGGZ3

NEW

## Remote Management

### Remote monitoring / Remote operation

New central remote controller can control your tenant's air conditioner anytime and anywhere. When the central remote controller manages the indoor units of some tenants, air conditioning of each tenant can be managed separately online.


### Increased the Number of Accounts



## VRF J Series compact outdoor units with up to 18 HP

Suitable for the buildings with multiple small rooms. Up to 42 indoor units\* can be connected.

\*Only J-IVL Series 18 HP model





## Compact outdoor unit with low noise design


Takes up little space even when installed in a machine room or on the roof. Sufficient static pressure can be maintained even with louvers. Low-noise mode suffices even for nighttime operations at low noise levels.

## Wide lineup of indoor units of low-capacity class

Various low-capacity 1.1 kW indoor units are available for small rooms and spaces.



Compact cassette Series for grid ceiling




## Compact wired remote controller

Compact size with a large screen for easy operation. The stylish design harmonizes with the interior.

# Hotels

For Light commercial use

Fujitsu General offers total air conditioning systems perfect for low-rise, small hotels that take into account energy savings, external appearance, safety, and ease of installation.



## Guest room air conditioning with superior comfort, energy efficiency, and ease of installation


**Space saving**  
Mini duct type with a height of 198 mm and a depth of 450 mm. Easily installed in a narrow ceiling space.



Mini duct



**Card key switch available**  
Linked to a card key to prevent people from forgetting to turn off the air conditioner.



External connection switch


**Comfortable airflow by switching the up/down airflow direction**  
The Auto louver grille kit creates comfortable airflow by adjusting the air direction.



Auto louver grille kit

## Centralized control of air conditioning for shared spaces

Centralized control of air conditioning for shared spaces like lobbies, hallways, and other common areas is centrally controlled. A central remote controller can manage VRF products, but split products can also be managed together via a network converter.



\*Some functions will not be available.

**Wired remote controller (design type) with sophisticated design.**  
The touch panel can be easily operated by swiping vertically and horizontally.




Wired remote controller (design type) UTY-RVRG

Select the product best suited to the characteristics of the property.

	Split	VRF J-VS	VRF VR-IV
Project size	Small	Middle	Large
Individual Air conditioning	Great	Good	Great
Reduction of installation space	Fair	Great	Great
Landscape (hide outdoor unit)	Fair*	Great	Fair
Maintenance (individualized)	Great	Good	Fair

\*Depends on pipe length constraints

Ventilation of each room can be achieved relatively inexpensively by combining an appropriate duct fan (locally procured) through a hole for fresh air in the indoor unit. If the airflow required to ventilate the room is not sufficient, use ERV (Energy Recovery Ventilator).



## Large space air conditioning for the reception area and lobby


Duct type Big duct Series suitable for large spaces with high ceilings



# Schools


For Light commercial use

Fujitsu General offers indoor units that allow multiple connections with a compact design that reduces the installation area and increases the flexibility for selecting installation locations, making them perfect for midsize educational institutions. One single outdoor unit is able to cover an entire school building.



## Centralized control of both air conditioning and ventilation equipment


Centralized control is also possible to stop the operation of not only air conditioners but also lighting and ventilation equipment. These features are useful for managing the energy efficiency of the entire building.



System controller Lite



One-way flow cassette Series



Mini duct




Ceiling type



Wall-mounted type

## Wide variety of indoor units

Support complex applications for regular classrooms, special classrooms and auditoriums. Ventilators can also be added easily.



Energy recovery ventilator




Circular flow cassette Series

## Comfortable room air conditioning without airflow sensation



Circular flow cassette blows air in all directions at a uniform temperature.



Individual airflow direction control to prevent people from being exposed to airflow



Energy-saving operation when unattended, in conjunction with a Human sensor.



Human sensor (option)



# Large buildings


For Commercial use

Fujitsu General offers modular VRF systems that pursue high efficiency, comfort, design flexibility, ease of installation, and reliability for high-rise buildings.



## Abundant lineup optimized for the operating environment

The VRF system meets a variety of needs, including energy-saving models and models with compatibility to outdoor temperatures of up to 46°C.



## VRF VR-IV

Smart, cutting-edge design Extensive lineup from 8 HP to 48 HP with the capacity ratio of indoor units connectable up to 150%.

### 34 models with 8 to 48 HP

- Space saving combination: 21 models from 8 to 48 HP
- Energy efficient combination: 13 models from 16 to 44 HP

## VRF V-IV

### 34 models from 8 to 48 HP

- Space saving combination: 21 models from 10 to 48 HP
- Energy efficient combination: 13 models from 16 to 46 HP



## Height difference up to 110 m

The height difference between the outdoor unit and the indoor unit is normally 50 m for the V-IV Series, but can be extended to 110 m by installing the Pressure sensor kit.

\* Can only be connected to the V-IV Series





## Centralized control

Not only indoor units in the building, but also facilities such as ventilation can be controlled easily by anyone




System controller (UTY-APGXZ1)  
System controller Lite (UTY-ALGXZ1 & UTY-PLGXX2)



## Linkage with various BMS

Linking with MODBUS®, BACnet®, KNX® and other interfaces allows centralized control of equipment other than air conditioning.




## High system flexibility

The industry-leading high static pressure, long pipe design, and connection capacity enable flexible installation on each floor and installation of various indoor units.


82\* Pa

\*: V-IV Series, 80Pa for VR-IV Series



## Prompt service support

Web monitoring tool and System controller remotely monitor the air conditioning of the entire building. Self-diagnosis in cooperation with the management company enables quick response in case of an emergency.




# Residences

For Apartments & Houses

From the living room, where the whole family relaxes, to bedrooms, children's rooms and other small rooms, Fujitsu General has designed systems suited to spaces that reflect the rhythm of life.



**A variety of indoor units to suit the characteristics of each room**



### For Living & Dining room

**Cool beauty design model**

This series features a special European-style design. The light, elegant and three-dimensional expression achieved by the curved surface is beautiful from all angles.



### For Large rooms

**Standard & Comfort model**

The basic functions and powerful, comfortable airflow volume controls are optimal for large spaces.



### For Bedrooms or Home offices

**ECO Range, Compact size**


High performance and compact design suitable for bedrooms, home offices and other small spaces



### For Primary bedrooms or Living rooms

**Award winning design, Quiet models**

High performance, low noise with emphasis on design



### Outdoor units suitable for residential environments



### R32 Multi-split type released

Models are now available with environment-friendly R32 refrigerant. A number of products with improved external design have been added to the indoor unit lineup.



Wall-mounted type

Ceiling type

### Operated by smart speaker

Simply talk to the smart speaker to operate the air conditioner and check its operating status while doing other things.



WLAN adapter (USB)

**AIRSTAGE Mobile**

Download Free

Download on the App Store

GET IT ON Google play

With the WLAN adapter and the AIRSTAGE Mobile app, you can control the heating and cooling of your home anytime, anywhere.





## Light Commercial & Residential SPLIT & MULTI-SPLIT

Energy saving design to provide a comfortable indoor environment while being environment-friendly.

These are air conditioners that are both user-friendly and environment-friendly. Fujitsu General air conditioners cater to a wide range of needs, from living rooms, bedrooms, stores, small offices, through to hotels.

### SPLIT

- Refrigerant R32 models
  - Wall-mounted type
  - Cassette
  - Duct
  - Floor
  - Ceiling
- Refrigerant R410A models
  - Duct

### MULTI-SPLIT

- Refrigerant R32 models
  - 2-unit to 5-unit Multi-split
  - Simultaneous Multi-split Twin/Triple
- Refrigerant R410A models
  - 6-unit Multi-split
  - Simultaneous Multi-split Twin/Triple/Double Twin



## SPLIT & MULTI-SPLIT

Light Commercial &  
Residential



## Light Commercial & Residential SPLIT

- S-004 Split Overview
- S-006 Indoor Units Lineup
- S-010 Features
- S-015 Features Explanation
- S-060 Wall-mounted Specifications
- S-063 ECO Series Lineup Specifications
- S-068 Feature Summary



### Refrigerant R32 models

**Wall-mounted type** - Built in W-LAN adapter model

- S-016 Designer Range
  - High Spec & Design
  - Cool Beauty Design
- S-020 Standard Range - High-Efficiency & Comfort
- S-022 ECO Range - Compact Size

### Wall-mounted type

- S-024 Standard Range
  - High-Efficiency & Large Rooms
- S-028 ECO Range
  - Compact Size
  - Comfort for Large Rooms
  - Cooling-enhanced type

### Cassette

- S-034 Compact 4-way Flow Range - Compact Size
- S-036 Circular Flow Range - Comfort for Large Rooms

### Duct

- S-038 Slim Duct - Slim Design
- S-040 Medium Static Pressure Duct
  - High-Efficiency & Comfort
  - Compact Size
  - Standard
- S-050 High Static Pressure Duct

### Floor, Ceiling

- S-056 Floor - Compact Size
- S-058 Ceiling



### Refrigerant R410A models

#### Duct

- S-052 High Static Pressure Duct
- S-054 Big Duct



# Split Overview

Fujitsu General provides its customers with 5 types and 149 models of air conditioning systems perfect for various customer applications and layouts. Added to this lineup recently are the environment-friendly R32 refrigerant models.



Wall-mounted type, Designer Series, Cool Beauty Design

## Existing pipes can be reused if they meet our guidelines

Please consult with our regional sales subsidiaries for details.

### Cautions when reusing the existing pipes

- The thickness of the pipes must be 0.8 mm or thicker in accordance with the pipe diameter.
- Use flares that have been reworked to be compatible with the new refrigerant, and are compliant with ISO 14903.
- Select suitable wiring in accordance with the installation manual of the new air conditioning unit.
- When pump-down is not possible or when the inner pipe walls are dirty, make sure to clean the pipes before connecting new ones.
- When using different diameters pipes from the standard sizes,
  - The performance may not reach the published specification value.
  - Dedicated flare nuts compliant with ISO 14903 should be procured locally.
  - Restrictions apply to pipe lengths, refrigerant volumes, and room sizes.



### Wall-mounted type

Simple and easy to install, all models, are expertly designed to control airflow and save energy. The design, with its flat and simple appeal, perfectly matches room interiors. Many of the models in the lineup adopt the new environmentally friendly R32 refrigerant.



### Duct

The main unit is hidden in the wall, making the room look neat and tidy. Mini Duct and Slim Duct models are also available for installation in narrow spaces between beams or above the ceiling. Large models, suitable for air conditioning vast spaces, allow multiple outlets to be installed in just one unit, and are perfect for atypical room layouts.



### Cassette

The Cassette type, which blends in perfectly with the interior design, blows air in all four directions to create an even air-conditioning for the entire space. We have a variety of series including Compact models with a uniquely designed panel to match grid ceilings, and Circular Flow models that send airflow in a 360° direction.



### Floor

The compact and slim design makes this model suitable for installation in commercial as well as residential buildings. This model is also recommended as a heating device because it delivers a warm airflow from both the top and bottom outlets.



### Ceiling

As with the wall-mounted unit, ceiling installation is very easy, and the unit's thin structure with a height of just 240 mm allows neat installation. The powerful airflow that can reach far away from the wide outlet is perfect for large meeting rooms, audiovisual rooms, and other rectangular spaces with a lot of depth.

# Indoor Units Lineup



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for AC. Check ongoing validity of certificate: www.eurovent-certification.com

Type	Range	Refrigerant	Model	Class													
				7	9	12	14	18	22	24	30	36	45	54	60	72	90
Wall-mounted type Built in WLAN adapter model	Designer Range High Spec & Design	R32 Cooling & Heating	NEW KG Series	ASHH07KGTG	ASHH09KGTG	ASHH12KGTG	ASHH14KGTG										
	Designer Range Cool Beauty Design	R32 Cooling & Heating	KE Series	ASHG07KETF ASHG07KETF-B	ASHG09KETF ASHG09KETF-B	ASHG12KETF ASHG12KETF-B	ASHG14KETF ASHG14KETF-B										
	Standard Range High-Efficiency & Comfort	R32 Cooling & Heating	NEW KM Series	ASHH07KMCG ASHH07KMCG-B	ASHH09KMCG ASHH09KMCG-B	ASHH12KMCG ASHH12KMCG-B	ASHH14KMCG ASHH14KMCG-B										
	ECO Range Compact Size	R32 Cooling & Heating	NEW KN Series	ASHH07KNCA	ASHH09KNCA	ASHH12KNCA											
Wall-mounted type	Standard Range High-Efficiency & Large Rooms	R32 Cooling & Heating	KM Series				ASHG18KMTE		ASHG24KMTE								
	Standard Range High-Efficiency & Large Rooms	R32 Cooling & Heating	KM Series								ASHH30KMTB	ASHH36KMTB					
	ECO Range Compact Size	R32 Cooling & Heating	KP Series	ASHG07KPCE	ASHG09KPCE	ASHG12KPCE											
	ECO Range Comfort for Large Rooms	R32 Cooling & Heating	KL Series				ASHG18KLCA		ASHG24KLCA								
	ECO Range Cooling-enhanced	R32 Cooling & Heating	NEW KL Series	ASHH07KLTA	ASHH09KLTA	ASHH12KLTA											

# Indoor Units Lineup



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for AC. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

Type	Range	Refrigerant	Model	Class															
				7	9	12	14	18	22	24	30	36	45	54	60	72	90		
Cassette	Compact 4-way Flow Range Compact Size	Cooling & Heating			AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA									
	Circular Flow Range Comfort for Large Rooms	Cooling & Heating	 18/22/24 30/36/45/54					AUXG18KRLB	AUXG22KRLB	AUXG24KRLB	AUXG30KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB					
Duct	Slim Duct	Cooling & Heating	 09/12/14 18		ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP											
	Medium Static Pressure Duct High-Efficiency & Comfort	Cooling & Heating	<b>NEW</b> 12/14/18 22/24 30/36/45/54			ARXH12KMTAP	ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	ARXH24KMTAP	ARXH30KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH54KMTAP					
	Medium Static Pressure Duct Compact Size	Cooling & Heating	 12/14 18/22/24/30 36/45/54			ARXG12KHTAP	ARXG14KHTAP	ARXG18KHTAP	ARXG22KHTAP	ARXG24KHTAP	ARXG30KHTAP	ARXG36KHTAP	ARXG45KHTAP	ARXG54KHTAP					
	Medium Static Pressure Duct Standard	Cooling & Heating								ARXG22KMLB	ARXG24KMLA	ARXG30KMLA	ARXG36KMLA	ARXG45KMLA					
	High Static Pressure Duct	Cooling & Heating												ARXG45KHTB	ARXG54KHTB				
																ARHG60LHTA			
Big Duct	Cooling & Heating															ARHG72LHTA	ARHG90LHTA		
Floor Compact & Comfort	Cooling & Heating				AGHG09KVCA	AGHG12KVCA	AGHG14KVCA												
Ceiling	Cooling & Heating	 18/22 24/30 36/45/54						ABHG18KRTA	ABHG22KRTA	ABHG24KRTA	ABHG30KRTA	ABHG36KRTA	ABHG45KRTA	ABHG54KRTA					

# Features


## High-Efficiency

### ALL DC All DC Inverter Technology




#### DC twin-rotary compressor

A high-efficiency 2-cylinder rotary compressor with a DC inverter optimizes the internal structure of the compressor to achieve higher energy efficiency compared to similar compressors.




#### DC fan motor

The DC fan motor produces high power, a wide operating range, and high-efficiency.



#### Sine-wave DC inverter control

High-efficiency operation is realized by using sine-wave DC inverter control.




### Heat Exchanger for Wall-mounted type

#### High-density multipath heat exchanger

Thinner and denser heat exchangers and multipath efficiency technology have substantially improved heat exchange performance.

#### High-performance sub-cool heat exchanger


A counter-type bypass circuit has been incorporated to achieve a higher performance. (Large multi-split type, VRF)



## High Energy Saving


### Human sensor control

The Human sensor monitors the movements of people in a room and operates the air conditioner at a lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.




### Economy operation

Limits maximum operation, reducing the power consumption, and thereby suppressing the maximum load.




### Setting temperature range limitation

The minimum and maximum temperature range can be set giving further energy savings while considering the comfort of the occupants.




### Set temperature auto return

- The set temperature automatically returns to the previously set temperature.
- The time range in which the set temperature can be changed is from 10 to 120 minutes.



### Auto-off timer

- The indoor unit is automatically turned off when it reaches a preset operating time frame.
- The time frame of the Auto-off timer can be flexibly scheduled.
- Auto-off times can be set from 30 to 240 minutes.




# More Comfort




## Power diffuser

These three technologies enable precise wind direction control and improve ventilation efficiency; our airflow control offers a more comfortable environment.




## Wireless LAN control

Users can control their air conditioners from anywhere with their mobile devices while out or on the move.





## Powerful operation

Maximum airflow and maximum compressor speed are maintained for the period necessary to reach the set temperature quickly.



## 10°C heat

After a person has left the room, the system switches to minimum heating operation to maintain the room temperature. (Maintained at 10°C)



## Uniform air conditioning

Circular airflow to achieve uniform air conditioning without temperature unevenness in workspaces




# Quiet and Comfort Control



## Low Noise Technology


### Outdoor unit fan

Outdoor unit fan design with a small separation vortex, minimized air volume by fan control, and top-class low noise




### Air stabilizer in Duct

Low-noise duct structure with a built-in air stabilizer




### Outdoor unit low noise operation

Users can choose low noise levels, depending on the installation environment. Operation time can be set by timer.



### Auto changeover

In an auto setting, the system automatically switches between cooling and heating modes according to the set temperature and room temperature.



### Fresh air intake for Cassette, Duct, Ceiling

Fresh air is taken in by a fan connected to an external control unit.



# Feature Explanation

## Energy-Saving Features

- Save Human sensor**  
The Human sensor detects the movement of people in the room and determines whether to switch to energy saving operation.
- Human sensor control**  
The Human sensor (option) detects movement of people in the room and decides whether to save energy or stop the unit.
- Economy operation**  
The thermostat setting is adjusted automatically according to the room temperature to avoid unnecessary cooling or heating.
- Setting temperature range limitation**  
Sets the minimum and maximum limits on room temperature to establish the right balance between energy saving and a comfortable environment.
- Set temperature auto return**  
The setting temperature automatically returns to the previously set temperature.

## Features for Comfort

- Power diffuser**  
An additional louver that opens based on input from monitoring sensors to quickly enhance immediate comfort needs.
- Powerful operation**  
Operation at maximum air flow and compressor speed, that quickly makes the room comfortable.
- 10°C Heat**  
The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied.
- Outdoor unit low noise operation**  
The noise level of the outdoor unit can be selected.
- Auto changeover**  
The unit automatically switches between heating and cooling modes based on the temperature setting and the room temperature.
- UP/DOWN swing louver**  
The vertical louver automatically swings up and down.
- Double swing automatic**  
Complex swing action of the louver enables automatic swing in both the left/right and up/down directions.
- Automatic fan speed**  
A micro-computer automatically adjusts the airflow to follow the changes in room temperature.
- Auto restart**  
In the event of a temporary power failure, the air conditioner will automatically restart in the same operating mode as before, once the power supply is restored.
- Connectable fresh air duct**  
Outside air can be introduced by attaching a locally purchased duct to the fresh air knockout and an optional part.
- Fresh air intake**  
Fresh air can be taken in by a fan connected to an external control unit.
- Connectable distributing duct**  
Locally purchased branch ducts can be attached to the systems to distribute the airflow.
- Individual airflow direction control**  
Each louver of a 4-way Cassette type can be controlled individually to provide comfortable airflow.

## Convenience Features

- Auto-off timer**  
Automatically stops operation when a fixed time has elapsed from the start of operation.
- Sleep timer**  
A micro-computer gradually changes the room temperature automatically to promote a comfortable night's sleep.
- Program timer**  
This digital timer allows selection of one of four options: ON, OFF, ON » OFF, or OFF » ON.
- Weekly timer**  
Different ON-OFF times can be set for each day.
- Weekly & Temperature setback timer**  
Weekly & Temperature setback timer can set the temperature for 2-time spans and for each day of the week.
- Filter sign**  
Indicates the filter cleaning period by blinking.
- External error output**
- External ON/OFF input**
- Wireless LAN control**  
The optional WLAN adapter enables the air conditioner to be operated by smartphone or tablet PC from outside the home.
- Multi System Control**  
Operation using "Lead Lag Operation", "Back up operation", "Lag Operation" is possible. (Page C-011)
- Special Cooling**  
"Special Cooling" is a function that supports the operation of "Multi System Control".

## Clean Features

- Ion deodorization filter**  
The filter deodorizes by powerfully decomposing absorbed odors using the oxidizing and reducing effects of ions generated by an ultra-fine-particle ceramic.
- Apple-catechin filter**  
The Apple-catechin filter uses static electricity to clean fine particles and dust from the air.
- Long-life filter**
- Washable panel**  
Since the front panel is easy to remove, maintenance is also easy.
- Silver Ion Filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.

## Installation / Support

- Automatic airflow adjustment**  
Automatically detects required airflow in each application case and adjusts the volume.
- Drain pump as standard**
- Blue fin**
- Refrigerant cycle monitor**  
The values of each sensor and actuator can be displayed, and the status of the refrigeration cycle can be checked.

**ALL DC** All DC models



NEW

# Wall-mounted type

Built-in WLAN adapter model  
Designer Range  
High Spec & Design

KG Series




## High energy saving

Top class high efficiency is achieved by high efficient lambda-shaped heat exchanger, large cross flow fan and new refrigerant.


Rank **A+++** SEER **9.80\*** SCOP **5.20\***

\*07/09/12 models \*07 model \*07/09/12 models




### Hybrid-heat exchanger

The large hybrid heat exchanger has greatly improved the heat exchange efficiency to achieve top-level SEER and SCOP.




### Ø107 Large cross-flow fan

The large-diameter fan generates air volume efficiently even at reduced power.



### Human sensor

The Human sensor monitors the movements of people in a room and operates the air conditioner at a lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.



## Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



Quiet & Comfort  
**19 dB(A)**  
(07/09/12 models)  
Cooling only

## Smart device control

A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.


\* See page C-020 for details on smart device control.



## Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.

\*Wired remote controller (UTY-RNRGZ5 or UTY-RVRG) is required.



Model: ASHH07KGTG / ASHH09KGTG / ASHH12KGTG / ASHH14KGTG



## Specifications

Model name	Indoor unit		ASHH07KGTG	ASHH09KGTG	ASHH12KGTG	ASHH14KGTG
	Outdoor unit		AOHH07KCGG	AOHH09KCGG	AOHH12KCGG	AOHH14KCGG
Power Source	Single phase, ~230 V, 50 Hz					
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2
		Min.-Max.	0.9-3.3	0.9-3.6	0.9-4.1	0.9-4.5
	Heating	Rated	2.5	2.8	4.0	5.4
Min.-Max.		0.9-5.2	0.9-5.4	0.9-6.1	0.9-6.4	
Input Power	Cooling/Heating	kW	0.400 / 0.500	0.550 / 0.600	0.870 / 0.910	1.220 / 1.450
EER	Cooling		5.00	4.55	3.91	3.44
COP	Heating	W/W	5.00	4.67	4.40	3.72
Pdesign	Cooling/Heating (-10°C)	kW	2.0 / 2.3	2.5 / 2.4	3.4 / 2.5	4.2 / 4.0
SEER	Cooling	W/W	9.80	9.40	8.80	8.00
SCOP	Heating (Average)	W/W	5.20	5.20	5.20	4.60
Energy Efficiency Class	Cooling		A+++	A+++	A+++	A++
	Heating (Average)		A+++	A+++	A+++	A++
Max. Operating Current	Cooling/Heating	A	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0	9.0 / 10.5
Annual Energy Consumption	Cooling	kWh/a	71	93	135	184
	Heating		618	646	673	1,217
Moisture Removal		l/h	1.1	1.3	1.6	1.7
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	36 / 32 / 29 / 19	38 / 34 / 29 / 19	40 / 35 / 30 / 19	43 / 36 / 30 / 20
	Indoor (Heating)	H/M/L/Q	38 / 34 / 31 / 20	39 / 34 / 31 / 20	42 / 38 / 33 / 21	44 / 39 / 33 / 24
Sound Power Level	Outdoor (Cooling/Heating)	High	42 / 43	44 / 45	50 / 50	50 / 50
	Indoor (Cooling/Heating)	High	49 / 51	52 / 52	56 / 58	57 / 59
Airflow Rate	Indoor/Outdoor (Cooling)	High	570 / 1,390	640 / 1,480	680 / 1,800	750 / 1,800
	Indoor/Outdoor (Heating)	High	610 / 1,350	630 / 1,420	750 / 1,690	780 / 1,690
Net Dimensions H x W x D	Indoor	mm	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
	Outdoor	mm	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290
Weight	Indoor	kg	10	10	10	10
	Outdoor	kg	30	30	31	32
Connection Pipe Diameter (Liquid/Gas)		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain Hose Diameter (I.D./O.D.)			13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8
Max. Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)
Max. Height Difference			15	15	15	15
Operating Range	Cooling	°CDB	-10 to 50	-10 to 50	-10 to 50	-10 to 50
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.75 (0.506)	0.75 (0.506)	0.85 (0.574)	0.85 (0.574)

## Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type): UTY-RVRG	Simple remote controller: UTY-RSRG	Network Converter for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRGZ1	External switch controller: UTY-TERX	Network Converter for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel): UTY-RNRGZ5	Communication kit: UTY-TWRXZ2	Silver Ion filter: UTR-FA16-5
Wired remote controller: UTY-RLRG	External connect kit: UTY-XWZX	External input and output PCB <sup>1</sup> : UTY-XCSXZ2
Simple remote controller (without operation mode): UTY-RHRG		

<sup>1</sup> It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)



# Wall-mounted type

Built-in WLAN adapter model  
Designer Range  
Cool Beauty Design



KE Series



## Cool beauty design

We have designed this series exclusively for the European market. The exterior design harmonizes beautifully with any decor and adds comfortable elegance to the room. The light, elegant and three-dimensional expression achieved by the curved surface is beautiful from any angle.



**CMF: COLOR MATERIAL FINISH**  
The texture of the front panel expresses the craftsmanship of Europe, and changes its expression with the changing light of the day.

## High energy saving


Top class high efficiency is achieved by high efficient lambda-shaped heat exchanger, large cross flow fan and new refrigerant.

Rank Cooling\*1: **A++**  
Rank Heating\*2: **A+**

SEER **7.4** \*1  
SCOP **4.4** \*2

\*1: 07/09 models    \*2: 12 model


### Hybrid-heat exchanger    Ø107 Large cross-flow fan



## Smart device control

A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.

\* See page C-020 for details on smart device control.



## Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



Model: ASHG07KET / ASHG09KET / ASHG12KET / ASHG14KET (Peal white X White)  
ASHG07KET-B / ASHG09KET-B / ASHG12KET-B / ASHG14KET-B (Silver X Dark gray)



## Specifications

Model name	Indoor unit		Outdoor unit		ASHG07KET / ASHG07KET-B	ASHG09KET / ASHG09KET-B	ASHG12KET / ASHG12KET-B	ASHG14KET / ASHG14KET-B	
					AOHG07KETA	AOHG09KETA	AOHG12KETA	AOHG14KETA	
Power Source					Single phase, ~230 V, 50 Hz				
Capacity	Cooling	Rated	kW	2.0		2.5		3.4	
		Min.-Max.		0.9 - 3.0		0.9 - 3.2		0.9 - 3.9	
	Heating	Rated	kW	2.5		2.8		4.0	
		Min.-Max.		0.9 - 3.4		0.9 - 4.0		0.9 - 5.3	
Input Power	Cooling/Heating		kW	0.450/0.555		0.630/0.620		0.935/0.960	
EER	Cooling			4.43		3.97		3.65	
COP	Heating		W/W	4.52		4.52		4.17	
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.3		2.5/2.4		3.4/2.5	
SEER	Cooling		W/W	7.40		7.40		6.90	
SCOP	Heating (Average)		W/W	4.10		4.10		4.40	
Energy Efficiency Class	Cooling			A++		A++		A++	
	Heating (Average)			A+		A+		A+	
Max. Operating Current	Cooling/Heating		A	6.5/9.0		6.5/9.0		6.5/9.0	
Annual Energy Consumption	Cooling		kWh/a	95		118		163	
	Heating		kWh/a	785		819		795	
Moisture Removal			l/h	1.0		1.3		1.8	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	38/33/29/20		40/34/29/20		40/35/30/20	
	Indoor (Heating)	H/M/L/Q		41/35/31/22		42/36/31/22		42/38/33/22	
Sound Power Level	Outdoor (Cooling/Heating)	High	dB(A)	46/46		46/46		50/50	
	Indoor (Cooling/Heating)	High		54/56		55/57		55/58	
	Outdoor (Cooling/Heating)	High		61/61		61/62		65/65	
	Indoor/Outdoor (Cooling)	High		650/1,650		700/1,650		700/1,700	
Airflow Rate	Indoor/Outdoor (Heating)	High	m³/h	720/1,450		750/1,450		770/1,470	
Net Dimensions H x W x D	Indoor		mm	295 x 950 (wall side: 840) x 230					
	Outdoor		mm	541 x 663 x 290		541 x 663 x 290		541 x 663 x 290	
Weight	Indoor		kg	11		11		11	
	Outdoor		kg	23		23		25	
Connection Pipe Diameter (Liquid/Gas)			mm	6.35/9.52		6.35/9.52		6.35/9.52	
Drain Hose Diameter (I.D./O.D.)			mm	13.8/15.0 to 16.8		13.8/15.0 to 16.8		13.8/15.0 to 16.8	
Max. Pipe Length (Pre-Charge)			m	20 (15)		20 (15)		20 (15)	
Max. Height Difference				15		15		15	
Operating Range	Cooling		°CDB	-10 to 46		-10 to 46		-10 to 46	
	Heating		°CDB	-15 to 24		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)			R32 (675)		R32 (675)		R32 (675)	
	Charge		kg (CO2eq-T)	0.6 (0.405)		0.6 (0.405)		0.7 (0.473)	

## Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type): UTY-RVRG	Simple remote controller: UTY-RSRG	Network Converter for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRG21	Communication kit: UTY-TWRXZ2	Network Converter for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel): UTY-RNRG25	External connect kit: UTY-XWZX	Silver Ion filter: UTR-FA16-5
Wired remote controller: UTY-RLRG	External connect kit: UTY-XWZX25	External input and output PCB*1: UTY-XCSXZ2
Simple remote controller (without operation mode): UTY-RHRG	External switch controller: UTY-TERX	

\*1 It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)



NEW

# Wall-mounted type

Built-in WLAN adapter model  
Standard Range  
High-Efficiency & Comfort



## Slim & stylish square design

The slim and stylish square design of this indoor unit is realized by using a highdensity, multipath heat exchanger and a high-efficiency wind blower.



## Warm & gentle color option

Both white and soft black color are relatively gentle tones and no strong contrast, each color harmonize with the environment and create a warm atmosphere.

## High energy saving

High-efficiency has been achieved by the lambda-shaped heat exchanger, large cross-flow fan, and the new refrigerant.

Rank Cooling A++ Heating A++\*

SEER 8.40\* SCOP 4.60\*

\*07/09/12 models

## Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.

Quiet & Comfort  
20 dB(A)  
Cooling only

## Smart device control

A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.

\* See page C-020 for details on smart device control.

AIRSTAGE Mobile

"ON" before returning home.

## Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.

\*Wired remote controller (UTY-RNRGZ5 or UTY-RVRG) is required.

Display screen example

Model: ASHH07KMCG / ASHH09KMCG / ASHH12KMCG / ASHH14KMCG  
ASHH07KMCG-B / ASHH09KMCG-B / ASHH12KMCG-B / ASHH14KMCG-B



## Specifications

Model name	Indoor unit		ASHH07KMCG ASHH07KMCG-B	ASHH09KMCG ASHH09KMCG-B	ASHH12KMCG ASHH12KMCG-B	ASHH14KMCG ASHH14KMCG-B
	Outdoor unit		AOHH07KMCG	AOHH09KMCG	AOHH12KMCG	AOHH14KMCG
Power Source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2
		Min.-Max.	0.9-3.0	0.9-3.2	0.9-3.9	0.9-4.4
	Heating	Rated	2.5	2.8	4.0	5.4
		Min.-Max.	0.9-3.4	0.9-4.0	0.9-5.3	0.9-6.0
Input Power	Cooling/Heating	kW	0.450 / 0.555	0.650 / 0.620	0.960 / 1.020	1.220 / 1.410
EER	Cooling		4.43	3.85	3.54	3.44
COP	Heating	W/W	4.52	4.52	3.92	3.83
Pdesign	Cooling/Heating (-10°C)	kW	2.0 / 2.3	2.5 / 2.4	3.4 / 2.5	4.2 / 4.0
SEER	Cooling	W/W	8.40	8.40	7.70	7.10
SCOP	Heating (Average)	W/W	4.60	4.60	4.60	4.10
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A++	A++	A++	A+
Max. Operating Current	Cooling/Heating	A	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0
Annual Energy Consumption	Cooling	kWh/a	83	104	155	207
	Heating		700	730	761	1,366
Moisture Removal		l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38 / 33 / 29 / 20	40 / 34 / 29 / 20	40 / 35 / 30 / 20	43 / 36 / 30 / 20
	Indoor (Heating)	H/M/L/Q	41 / 35 / 31 / 22	42 / 36 / 31 / 22	42 / 38 / 33 / 22	44 / 39 / 33 / 24
Sound Power Level	Outdoor (Cooling/Heating)	High	46 / 46	46 / 46	50 / 50	50 / 50
	Indoor (Cooling/Heating)	High	54 / 56	55 / 57	55 / 58	57 / 59
Airflow Rate	Indoor/Outdoor (Cooling)	High	650 / 1,650	700 / 1,650	700 / 1,700	770 / 1,680
	Indoor/Outdoor (Heating)	High	720 / 1,450	750 / 1,450	780 / 1,470	820 / 1,580
Net Dimensions	Indoor	mm	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
H x W x D	Outdoor	mm	541 × 663 × 290	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290
Weight	Indoor	kg	10	10	10	10
	Outdoor	kg	22	22	24	31
Connection Pipe Diameter (Liquid/Gas)		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain Hose Diameter (I.D./O.D.)		mm	13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8
Max. Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)
Max. Height Difference			15	15	15	15
Operating Range	Cooling	°CDB	-10 to 50	-10 to 50	-10 to 50	-10 to 50
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.60 (0.405)	0.60 (0.405)	0.70 (0.473)	0.85 (0.574)

## Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type): UTY-RVRG	Simple remote controller: UTY-RSRG	Network Converter for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRGZ1	Communication kit: UTY-TWRXZ2	Network Converter for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel): UTY-RNRGZ5	External connect kit: UTY-XWZX	Silver Ion filter: UTR-FA16-5
Wired remote controller: UTY-RLRG	External switch controller: UTY-XWZXZ5	External input and output PCB*: UTY-XCSXZ2
Simple remote controller (without operation mode): UTY-RHRG	External switch controller: UTY-TERX	

\*1 It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)



NEW

# Wall-mounted type

Built-in WLAN adapter model  
ECO Range  
Compact Size



KN Series



## Elegant & smart square design

An elegant and smart type in the eco range. The delicate shading of the ridge line makes the unit an accessory for the room.



## High energy saving

The size of the heat exchanger has increased to improve performance, making it more powerful despite its compact size.

Rank Cooling A++ Heating A+

SEER 7.8\* SCOP 4.4

\* 07 model

## Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.

Quiet & Comfort  
20 dB(A)  
Cooling only

## Smart device control

A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.

\* See page C-020 for details on smart device control.

AIRSTAGE Mobile

"ON" before returning home.

## Highly efficient operation even at high outdoor temperatures

Operation Range MAX 50°C (Cooling operation)

Even when installed in areas with high outdoor air temperatures (Max. 50°C\*), it is comfortable because it can cool the interior well.

\* suction temperature of the outdoor unit



Model: ASHH07KNCA / ASHH09KNCA / ASHH12KNCA



WLAN adapter (Built-in)



Wireless RC



## Specifications

Model name	Indoor unit		ASHH07KNCA		ASHH09KNCA		ASHH12KNCA	
	Outdoor unit		AOHH07KNCA		AOHH09KNCA		AOHH12KNCA	
Power Source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	Rated	2.0		2.5		3.4	
		Min.-Max.	0.9-2.9		0.9-3.1		0.9-3.8	
	Heating	Rated	2.5		2.8		3.8	
		Min.-Max.	0.9-3.4		0.9-4.0		0.9-4.8	
Input Power	Cooling/Heating	kW	0.50 / 0.58		0.74 / 0.70		1.05 / 1.02	
EER	Cooling	W/W	4.00		3.38		3.24	
COP	Heating	W/W	4.31		4.00		3.73	
Pdesign	Cooling/Heating (-10°C)	kW	2.0 / 2.3		2.5 / 2.4		3.4 / 2.5	
SEER	Cooling	W/W	7.8		7.4		7.0	
SCOP	Heating (Average)	W/W	4.4		4.4		4.4	
Energy Efficiency Class	Cooling		A++		A++		A++	
	Heating (Average)		A+		A+		A+	
Max. Operating Current	Cooling/Heating	A	6.5 / 9.0		6.5 / 9.0		6.5 / 9.0	
Annual Energy Consumption	Cooling	kWh/a	90		118		170	
	Heating	kWh/a	731		763		795	
Moisture Removal		l/h	1.0		1.0		1.4	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	36 / 33 / 29 / 20		38 / 35 / 29 / 20		40 / 36 / 32 / 20	
	Indoor (Heating)	H/M/L/Q	38 / 33 / 30 / 22		38 / 33 / 30 / 22		39 / 35 / 31 / 22	
Sound Power Level	Outdoor (Cooling/Heating)	High	43 / 44		44 / 45		49 / 49	
	Indoor (Cooling/Heating)	High	51 / 52		53 / 52		55 / 53	
Airflow Rate	Outdoor (Cooling/Heating)	High	53 / 54		56 / 56		60 / 61	
	Indoor/Outdoor (Cooling)	High	530 / 1,430		580 / 1,430		600 / 1,460	
Net Dimensions	Indoor	mm	270 × 784 × 222		270 × 784 × 222		270 × 784 × 222	
	Outdoor	mm	541 × 663 × 290		541 × 663 × 290		541 × 663 × 290	
Weight	Indoor	kg	9		9		9	
	Outdoor	kg	22		22		24	
Connection Pipe Diameter (Liquid/Gas)		mm	6.35 / 9.52		6.35 / 9.52		6.35 / 9.52	
Drain Hose Diameter (I.D./O.D.)		mm	13.8 / 15 to 16.8		13.8 / 15 to 16.8		13.8 / 15 to 16.8	
Max. Pipe Length (Pre-Charge)		m	20 (15)		20 (15)		20 (15)	
Max. Height Difference		m	15		15		15	
Operating Range	Cooling	°CDB	-10 to 50		-10 to 50		-10 to 50	
	Heating	°CDB	-15 to 24		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)		R32 (675)	
	Charge	kg (CO2eq-T)	0.57 (0.385)		0.57 (0.385)		0.65 (0.439)	


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Silver Ion Filter: UTR-FA16-5

## Dimensions

(Unit: mm)



# Wall-mounted type

Standard Range  
High-Efficiency & Large Rooms




KM Series



## High energy saving


High-efficiency has been achieved by the lambda-shaped heat exchanger, large cross-flow fan, and the new refrigerant.

Rank **A++** SEER **7.8** SCOP **4.6**  
\*18 model



### Hybrid-heat exchanger

The large hybrid heat exchanger has greatly improved the heat exchange efficiency to achieve top-level SEER and SCOP.



### Ø107 Large cross-flow fan

The large-diameter fan generates air volume efficiently even at reduced power.



## Smart device control (option)


With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* For more information about smart device control, please refer to the page C-020.



## Easy access to the flare pipe connection

Installation when left outlet piping is easier by removable under cover of the indoor unit chassis. Installation when center outlet piping is easier by design change of wall hook bracket.



Model: ASHG18KMTE / ASHG24KMTE



## Specifications

Model name	Indoor unit		ASHG18KMTE		ASHG24KMTE	
	Outdoor unit		AOHG18KMTA		AOHG24KMTA	
Power Source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	Rated	5.2		7.1	
		Min.-Max.	0.9-6.0		0.9-8.3	
	Heating	Rated	6.3		8.0	
Min.-Max.		0.9-8.7		0.9-10.1		
Input Power	Cooling/Heating		1.39/1.56		2.08/1.91	
EER	Cooling		3.74		3.41	
COP	Heating		4.04		4.19	
Pdesign	Cooling/Heating (-10°C)		5.2/4.8		7.1/7.1	
SEER	Cooling		7.77		7.30	
SCOP	Heating (Average)		4.60		4.20	
Energy Efficiency Class	Cooling		A++		A++	
	Heating (Average)		A++		A+	
Max. Operating Current	Cooling/Heating		9.5/13.5		13.5/16.0	
Annual Energy Consumption	Cooling		234		340	
	Heating		1,460		2,362	
Moisture Removal			1.7		2.7	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	45/40/35/29		49/40/35/29	
	Indoor (Heating)	H/M/L/Q	46/40/35/29		49/40/35/29	
Sound Power Level	Outdoor (Cooling/Heating)	High	50/50		54/52	
	Indoor (Cooling/Heating)	High	60/61		65/65	
Airflow Rate	Indoor/Outdoor (Cooling)	High	980/2,350		1,170/3,240	
	Indoor/Outdoor (Heating)	High	1,020/2,100		1,170/2,820	
Net Dimensions	Indoor		280 × 980 × 240		280 × 980 × 240	
	Outdoor		632 × 799 × 290		716 × 820 × 315	
Weight	Indoor		12.5		12.5	
	Outdoor		36		42	
Connection Pipe Diameter (Liquid/Gas)			6.35/12.70		6.35/12.70	
Drain Hose Diameter (I.D./O.D.)			13.8/15.8 to 16.7		13.8/15.8 to 16.7	
Max. Pipe Length (Pre-Charge)			25 (15)		30 (15)	
Max. Height Difference			20		25	
Operating Range	Cooling		-10 to 46		-10 to 46	
	Heating		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)	
	Charge		1.02 (0.689)		1.32 (0.891)	

## Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	External connect kit:	UTY-XWZX25	Network Converter for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RCRGZ1	Communication kit:	UTY-TWRXZ2	Network Converter for single split (AC power supply type):	UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRGZ5	External input and output PCB <sup>1)</sup> :	UTY-XCSXZ2	Silver ion filter:	UTR-FA16-5
Wired remote controller:	UTY-RLRG	WLAN adapter:	UTY-TFSXF2	External switch controller:	UTY-TERX
Simple remote controller (without operation mode):	UTY-RHRG		UTY-TFSXH3		
Simple remote controller:	UTY-RSRG		FG-AC-WIF1Z1		

\*1 It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)



# Wall-mounted type

Standard Range  
High-Efficiency & Large Rooms



KM Series



## Special Cooling


When it is necessary to be constantly cooled such as rooms with a high heat load, it is possible to operate the cooling with keeping performance even when the outside temperature is low.

- \* Wired remote controller (UTY-RNRGZ5) is required.
- \* Please note that we will not provide compensation for any damages suffered to your appliances or data as a result of using this function.
- \* Please use it in low-humidity environments. Condensation and other problems may be caused when used in high-humidity environments.




## Human sensor

The Human sensor monitors the movements of people in a room and operates the air conditioner at a lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.



## Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.  
\*Wired remote controller (UTY-RNRGZ5 or UTY-RVRG) is required.



## Smart device control (Option)

With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.  
\* For more information about smart device control, please refer to the page C-020.



## Model: ASHH30KMTB / ASHH36KMTB



## Specifications

Model name	Indoor unit		ASHH30KMTB		ASHH36KMTB		
	Outdoor unit		AOHH30KMTB		AOHH36KMTB		
Power Source			Single phase, ~230V, 50Hz				
Capacity	Cooling	Rated	kW	8.0		9.4	
		Min.-Max.		2.9-9.0		2.9-10.0	
	Heating	Rated	kW	8.8		10.1	
Min.-Max.		2.2-11.8		2.7-12.6			
Input Power	Cooling/Heating		kW	2.33/2.20		3.16/2.73	
EER	Cooling			3.43		2.97	
COP	Heating		W/W	4.00		3.70	
Pdesign	Cooling/Heating (-10°C)		kW	8.0/6.5		9.4/7.1	
SEER	Cooling		W/W	6.68		6.10	
SCOP	Heating (Average)		W/W	4.50		4.50	
Energy Efficiency Class	Cooling			A++		A++	
	Heating (Average)			A+		A+	
Max. Operating Current	Cooling/Heating		A	21.0/21.0		21.5/21.5	
Annual Energy Consumption	Cooling		kWh/a	419		534	
	Heating		kWh/a	1,994		2,189	
Moisture Removal			l/h	2.6		3.8	
	Indoor (Cooling)	H/M/L/Q		50/44/40/33		50/44/40/33	
Sound Pressure Level	Indoor (Heating)	H/M/L/Q		49/44/39/33		49/44/39/33	
	Outdoor (Cooling/Heating)	High	dB(A)	53/55		55/55	
Sound Power Level	Indoor (Cooling/Heating)	High		65/65		65/65	
	Outdoor (Cooling/Heating)	High		68/69		70/70	
Airflow Rate	Indoor/Outdoor (Cooling)	High	m <sup>3</sup> /h	1,330/3,750		1,330/3,750	
	Indoor/Outdoor (Heating)	High	m <sup>3</sup> /h	1,330/3,750		1,330/3,750	
Net Dimensions H x W x D	Indoor	mm		340 × 1,150 × 280		340 × 1,150 × 280	
	Outdoor	mm		788 × 940 × 320		788 × 940 × 320	
Weight	Indoor	kg		18.5		18.5	
	Outdoor	kg		52.0		52.0	
Connection Pipe Diameter (Liquid/Gas)			mm	9.52/15.88		9.52/15.88	
Drain Hose Diameter (I.D./O.D.)			mm	13.8/15.8 to 16.7		13.8/15.8 to 16.7	
Max. Pipe Length (Pre-Charge)			m	50(30)		50(30)	
Max. Height Difference			m	30		30	
Operating Range	Cooling	°CDB		-15to46		-15to46	
	Heating	°CDB		-15to24		-15to24	
Refrigerant	Type (Global Warming Potential)			R32(675)		R32(675)	
	Charge		kg (CO2eq-T)	1.90(1.283)		1.90(1.283)	

## Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

- Wired Remote Controller (Design type): UTY-RVRG
- Compact wired remote controller: UTY-RCRGZ1
- Wired remote controller (touch panel): UTY-RNRGZ5
- Wired remote controller: UTY-RLRG
- Simple remote controller (without operation mode): UTY-RHRG
- Simple remote controller: UTY-RSRG
- External connect kit: UTY-XWZXZ5
- Communication kit: UTY-TWRXZ2
- External input and output PCB\*: UTY-XCSXZ2
- WLAN adapter: UTY-TFSXF2, UTY-TFSXH3, FG-AC-WIFI21
- Network Converter for single split (DC power supply type): UTY-VTGX
- Network Converter for single split (AC power supply type): UTY-VTGXV
- Silver Ion Filter: UTR-FA13-3
- External switch controller: UTY-TERX

\*1 It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)



**Wall-mounted type**  
ECO Range  
Compact Size

KP Series



**Slim & stylish square design**

The slim and stylish square design of this indoor unit is realized by using a high-density, multipath heat exchanger and a high-efficiency wind blower.



**High energy saving**

High-efficiency has been achieved by the lambda-shaped heat exchanger, large cross-flow fan, and the new refrigerant.

Rank #1 Cooling A++ Heating #2 A+

SEER 6.7\*1 SCOP 4.1\*2

\*1: 07/09 models \*2: 12 model

**Comfortable airflow & Quiet operation**

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.




**Smart device control (option)**

With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.  
\* For more information about smart device control, please refer to the page C-020.



**Easy access to the flare pipe connection**

Installation when left outlet piping is easier by removable under cover of the indoor unit chassis. Installation when center outlet piping is easier by design change of wall hook bracket.



Model: ASHG07KPCE / ASHG09KPCE / ASHG12KPCE



**Specifications**

Model name	Indoor unit		Outdoor unit		ASHG07KPCE	ASHG09KPCE	ASHG12KPCE
	AOHG07KPCA		AOHG09KPCA		AOHG12KPCA		
Power Source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling	Rated	kW	2.0		2.5	
		Min.-Max.		0.9-2.8		0.9-3.0	
	Heating	Rated		2.5		2.8	
Min.-Max.		0.9-3.4		0.9-3.8		0.9-4.8	
Input Power	Cooling/Heating		kW	0.48/0.63		0.71/0.79	
EER	Cooling			4.17		3.40	
COP	Heating		W/W	3.97		3.54	
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.2		2.5/2.4	
SEER	Cooling			6.70		6.70	
SCOP	Heating (Average)		W/W	4.00		4.10	
Energy Efficiency Class	Cooling			A++		A++	
	Heating (Average)			A+		A+	
Max. Operating Current	Cooling/Heating		A	6.5/9.0		6.5/9.0	
Annual Energy Consumption	Cooling		kWh/a	104		131	
	Heating			769		840	
Moisture Removal			l/h	1.0		1.3	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	45/38/31/22		45/38/31/22	
	Indoor (Heating)	H/M/L/Q		45/40/36/26		46/40/35/27	
Sound Power Level	Outdoor (Cooling/Heating)	High	dB(A)	45/46		47/47	
	Indoor (Cooling/Heating)	High		57/58		59/59	
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	580/1,650		580/1,650	
	Indoor/Outdoor (Heating)	High		580/1,450		630/1,700	
Net Dimensions	Indoor		mm	270 × 784 × 224		270 × 784 × 224	
	Outdoor			541 × 663 × 290		541 × 663 × 290	
Weight	Indoor		kg	8		8	
	Outdoor			23		25	
Connection Pipe Diameter (Liquid/Gas)			mm	6.35/9.52		6.35/9.52	
Drain Hose Diameter (I.D./O.D.)				11.8/15.0 to 16.8		11.8/15.0 to 16.8	
Max. Pipe Length (Pre-Charge)			m	20 (15)		20 (15)	
Max. Height Difference				15		15	
Operating Range	Cooling		°CDB	-10 to 46		-10 to 46	
	Heating			-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		kg (CO2eq-T)	R32 (675)		R32 (675)	
	Charge			0.55 (0.371)		0.59 (0.398)	


**Optional parts**

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

WLAN adapter: UTY-TFSXF2  
UTY-TFSXH3  
Silver Ion Filter: UTR-FA16-5

**Dimensions**

(Unit: mm)



# Wall-mounted type

ECO Range  
Comfort for Large Rooms

KL Series




## Narrow width & Compact design

Compact and versatile. Powerful airflow is realized despite the 790-mm width compact design for small spaces such as bedrooms or home offices.




## Economy operation

Set temperature automatically increases or decreases by 1°C. The thermostat setting is adjusted automatically according to the room temperature to avoid unnecessary cooling or heating.



## Powerful operation


In powerful operation mode, the compressor operates at maximum speed for 20 minutes to provide a powerful airflow. Rapid cooling and heating makes the room comfortable quickly.



## ON-OFF programmable timer

You can set ON/OFF or OFF/ON times depending on your lifestyle needs. (Setting time: 0.5, 1, 1.5, 2, 2.5, -----9.5, 10, 11, 12 hours)

## Low ambient operation



Model: ASHG18KLCA / ASHG24KLCA



Wireless RC



For ASHG18KLCA For ASHG24KLCA

## Specifications

Model name	Indoor unit		ASHG18KLCA		ASHG24KLCA	
	Outdoor unit		AOHG18KLCA		AOHG24KLCA	
Power Source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	Rated	5.2		7.1	
		Min.-Max.	0.9-5.5		0.9-7.7	
	Heating	Rated	6.3		8.0	
Min.-Max.		0.6-7.6		0.9-9.0		
Input Power	Cooling/Heating		1.685/1.80		2.42/2.225	
EER	Cooling		3.09		2.93	
	Heating		3.50		3.60	
Pdesign	Cooling/Heating (-10°C)		5.20/4.80		7.10/7.10	
SEER	Cooling		7.20		7.10	
SCOP	Heating (Average)		4.30		4.00	
Energy Efficiency Class	Cooling		A++		A++	
	Heating (Average)		A+		A+	
Max. Operating Current	Cooling/Heating		9.5/13.5		13.5/17.5	
Annual Energy Consumption	Cooling		253		350	
	Heating		1563		2485	
Moisture Removal			1.9		3.1	
	Indoor (Cooling)	H/M/L/Q	47/44/40/35		51/45/38/33	
Sound Pressure Level	Indoor (Heating)		50/45/41/37		52/45/41/37	
	Outdoor (Cooling/Heating)	High	50/56		55/57	
Sound Power Level	Indoor (Cooling/Heating)		60/65		64/65	
	Outdoor (Cooling/Heating)		61/66		65/67	
Airflow Rate	Indoor/Outdoor (Cooling)		865/1,830		1,040/2,885	
	Indoor/Outdoor (Heating)		995/2,265		1,040/3,030	
Net Dimensions H x W x D	Indoor		293 x 790 x 249		293 x 790 x 249	
	Outdoor		542 x 799 x 290		632 x 799 x 290	
Weight	Indoor		9.5		10.0	
	Outdoor		33		38	
Connection Pipe Diameter (Liquid/Gas)			6.35/9.52		6.35/12.70	
Drain Hose Diameter (I.D./O.D.)			13.8/15.8 to 16.7		13.8/15.8 to 16.7	
Max. Pipe Length (Pre-Charge)			25 (15)		30 (15)	
Max. Height Difference			20		25	
Operating Range	Cooling		-10 to 46		-10 to 46	
	Heating		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)	
	Charge		kg (CO2eq-T)		0.85 (0.574) 1.10 (0.743)	


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Silver Ion Filter: UTR-FA16-5

## Dimensions

(Unit: mm)





# Wall-mounted type

ECO Range  
Cooling-enhanced type

KL Series



Rank **A++**  
SEER **7.1**  
\*07 model  
Operation Range **MAX 52°C**  
(Cooling operation)

## Highly efficient operation even at high outdoor temperatures

Even when installed in areas with high outdoor air temperatures (Max. 52°C\*), it is comfortable because it can cool the interior well.

\*suction temperature of the outdoor unit



## MINIMAL SMART design

The new smart design eliminates mechanical elements and offers a sophisticated, premium impression. Its compact size, with a width of 770 mm, allows for flexible installation in limited room space.



## Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



## Smart device control (option)

With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* For more information about smart device control, please refer to the page C-020.



Model: ASHH07KLTA / ASHH09KLTA / ASHH12KLTA



Wireless RC



## Specifications

Model name	Indoor unit		kW	ASHH07KLTA	ASHH09KLTA	ASHH12KLTA
	Outdoor unit			AOHH07KLTA	AOHH09KLTA	AOHH12KLTA
Power Source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	Rated	kW	2.0	2.5	3.4
		Min.-Max.		0.9-2.8	0.9-3.0	0.9-3.7
	Heating	Rated	2.4	2.5	3.4	
		Min.-Max.	0.9-3.3	0.9-3.5	0.9-3.7	
Input Power	Cooling/Heating		kW	0.54 / 0.64	0.76 / 0.67	1.05 / 0.915
EER	Cooling			3.70	3.29	3.24
COP	Heating		W/W	3.75	3.73	3.72
Pdesign	Cooling/Heating (-10°C)		kW	2.0 / 2.2	2.5 / 2.3	3.4 / 2.5
SEER	Cooling		W/W	7.10	6.80	6.70
SCOP	Heating (Average)			4.10	4.10	4.10
Energy Efficiency Class	Cooling			A++	A++	A++
	Heating (Average)			A+	A+	A+
Max. Operating Current	Cooling/Heating		A	6.0 / 6.0	6.0 / 6.0	7.0 / 7.0
Annual Energy Consumption	Cooling		kWh/a	99	129	178
	Heating			752	786	854
Moisture Removal			l/h	0.18	0.55	1.26
	Indoor (Cooling)	H/M/L/Q		41 / 36 / 29 / 21	43 / 36 / 29 / 21	43 / 37 / 30 / 21
Sound Pressure Level	Indoor (Heating)	H/M/L/Q		41 / 37 / 32 / 23	43 / 37 / 32 / 23	43 / 37 / 32 / 23
	Outdoor (Cooling/Heating)	High	dB(A)	47 / 47	47 / 47	50 / 50
Sound Power Level	Indoor (Cooling/Heating)	High		54 / 55	55 / 55	55 / 56
	Outdoor (Cooling/Heating)	High		56 / 57	58 / 57	60 / 61
Airflow Rate	Indoor/Outdoor (Cooling)	High	m <sup>3</sup> /h	600 / 1,650	620 / 1,650	620 / 1,700
	Indoor/Outdoor (Heating)	High		600 / 1,450	620 / 1,450	640 / 1,470
Net Dimensions	Indoor		mm	250 × 770 × 218	250 × 770 × 218	250 × 770 × 218
	Outdoor		mm	541 × 663 × 290	541 × 663 × 290	541 × 663 × 290
Weight	Indoor		kg	7.0	7.0	7.5
	Outdoor		kg	19	19	22
Connection Pipe Diameter (Liquid/Gas)			mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain Hose Diameter (I.D./O.D.)				13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8
Max. Pipe Length (Pre-Charge)			m	20 (15)	20 (15)	20 (15)
Max. Height Difference				15	15	15
Operating Range	Cooling		°CDB	10 to 52	10 to 52	10 to 52
	Heating			-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)			R32 (675)	R32 (675)	R32 (675)
	Charge		kg (CO2eq-T)	0.53(0.358)	0.53(0.358)	0.60(0.405)

## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.


WLAN adapter: UTY-TFSXF2

UTY-TFSXH3

Silver Ion Filter: UTR-FA16-5

## Dimensions

(Unit: mm)



# Compact Cassette

Compact 4-way Flow Range  
Compact Size




## Compact and stylish panel design

The compact and stylish panel fits nicely into a grid-type ceiling. Its linear design is a perfect fit into a grid of 620 mm x 620 mm in the ceiling.



## Easy maintenance

You can access the unit for maintenance simply by removing a ceiling panel next to the grille. As no inspection hole needs to be cut through the ceiling, no additional construction cost is incurred.



The air inlet grille can be installed to open in any direction for easy maintenance.



## Flexible installation

The unit fits nicely into the decor of a grid-type ceiling and can be installed near the lighting or a ventilation opening.



## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: AUXG09KVLA / AUXG12KVLA / AUXG14KVLA / AUXG18KVLA / AUXG22KVLA / AUXG24KVLA



## Specifications

Model name	Indoor unit		AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA
	Outdoor unit		AOHG09KBTB	AOHG12KBTB	AOHG14KBTB	AOHG18KBTB	AOHG22KBTB	AOHG24KBTB
Power Source			Single phase, ~230 V, 50 Hz					
Capacity	Cooling	Rated	2.5	3.5	4.3	5.2	6.0	6.8
		Min.-Max.	0.9-3.2	0.9-4.4	0.9-5.4	0.9-5.9	0.9-6.7	0.9-8.0
	Heating	Rated	3.2	4.1	5.0	6.0	7.0	7.5
Min.-Max.		0.9-4.7	0.9-5.7	0.9-6.5	0.9-7.5	0.9-8.0	0.9-9.1	
EER	Cooling	4.57	3.76	3.36	3.25	3.30	3.08	
COP	Cooling	4.05	3.80	3.79	3.61	3.74	3.69	
	Heating	4.05	3.80	3.79	3.61	3.74	3.69	
Pdesign	Cooling/Heating (-10°C)	2.5/2.6	3.5/3.4	4.3/3.8	5.2/4.4	6.0/4.8	6.8/6.0	
SEER	Cooling	6.70	6.60	6.50	6.60	6.60	6.10	
	Heating (Average)	4.40	4.30	4.40	4.20	4.30	4.00	
Energy Efficiency Class	Cooling	A++	A++	A++	A++	A++	A++	
	Heating (Average)	A+	A+	A+	A+	A+	A+	
Max. Operating Current	Cooling/Heating	7.9/7.9	9.7/9.7	10.2/10.2	12.1/12.1	12.6/12.6	13.6/13.6	
Annual Energy Consumption	Cooling	131	186	231	275	318	390	
	Heating	826	1,106	1,208	1,466	1,562	2,097	
Moisture Removal	Cooling	0.6	1.2	1.5	2.2	2.6	2.7	
	Heating	0.6	1.2	1.5	2.2	2.6	2.7	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	33/31/29/27	37/34/30/27	38/34/30/27	38/34/30/26	44/42/36/30	49/44/36/30
	Indoor (Heating)	H/M/L/Q	34/32/29/27	37/34/31/29	43/38/34/30	43/38/34/30	45/43/40/33	49/45/40/33
Sound Power Level	Outdoor (Cooling/Heating)	High	46/46	47/47	49/49	50/50	51/51	53/54
		High	46/47	49/49	50/55	50/55	56/57	59/61
	Outdoor (Cooling/Heating)	High	59/59	61/61	62/62	62/62	63/63	65/66
		High	59/59	61/61	62/62	62/62	63/63	65/66
Airflow Rate	Indoor/Outdoor (Cooling)	High	540/1,480	600/1,580	680/1,670	680/2,160	830/2,240	930/2,700
	Indoor/Outdoor (Heating)	High	540/1,410	600/1,520	800/1,580	800/1,830	860/1,960	930/2,700
Net Dimensions H x W x D	Indoor	mm	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570
	Outdoor	mm	542 x 799 x 290	542 x 799 x 290	542 x 799 x 290	632 x 799 x 290	632 x 799 x 290	716 x 820 x 315
Weight	Indoor	kg	15	15	15	15	16	16
	Outdoor	kg	32	33	33	36	38	42
Connection Pipe Diameter (Liquid/Gas)	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70	6.35/12.70	
	mm	25/32	25/32	25/32	25/32	25/32	25/32	
Max. Pipe Length (Pre-Charge)	m	20 (15)	25 (15)	25 (15)	30 (20)	30 (20)	30 (20)	
Max. Height Difference	°CDB	15	20	20	20	25	25	
	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	
Operating Range	Cooling	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
	Heating	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	
	Charge	kg (CO2eq-t)	0.85 (0.574)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)
Cassette Grille	Model name	UTG-UFGF-W	UTG-UFGF-W	UTG-UFGF-W	UTG-UFGF-W	UTG-UFGF-W	UTG-UFGF-W	
	Dimensions (H x W x D)	mm	49 x 620 x 620	49 x 620 x 620	49 x 620 x 620	49 x 620 x 620	49 x 620 x 620	49 x 620 x 620
Weight	kg	2.3	2.3	2.3	2.3	2.3	2.3	


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type): UTY-RVRG	Wireless remote controller: UTY-LNTG	Network Converter for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRGZ1	External switch controller: UTY-TERX	Network Converter for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel): UTY-RNRGZ5	WLAN adapter: UTY-TFSXZ1	Insulation kit for high humidity: UTZ-KXGC
Wired remote controller: UTY-RLRG	FG-RC-WIF1Z2	External input and output PCB: UTY-XCSX
UTY-RNNGM	UTY-TFSXJ3	External input and output PCB box: UTZ-GXRA
Simple remote controller (without operation mode): UTY-RVNGM	FG-AC-WIF1Z1	Silver Ion Filter: UTD-HFAA
Simple remote controller: UTY-RHRG	UTR-VDZB	Fresh air intake kit: UTZ-VXAA
UTY-RSRG	UTG-UFGF-W	External connect kit: UTY-XWZXZG

## Dimensions

(Unit: mm)



# Cassette

Circular Flow Range  
Comfort for Large Rooms

UTG-UKGA-B  
Black Grille



## Unique circular flow design

The Cassette model realizes a Circular Flow to blow a large airflow in a 360° direction by using a high-performance DC fan motor, turbo fan, and a unique seamless airflow louver design.



Airflows avoid blowing cool air directly at the occupants in the room, providing more comfortable air conditioning.

Provides efficient air conditioning based on the room layout

## Individual louver control


Each louver can be controlled individually with a wired remote controller equipped with a touch panel to provide different directional airflows according to the room layout.

\*Wired remote controller (touch panel) (UTY-RNRGZ3) only

**The Human sensor yields more energy savings.**  
Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

## Compact and lightweight outdoor unit

The outdoor units for the 45,000 BTU and 54,000 BTU models have been completely redesigned. Easier installation is achieved for this compact and lightweight outdoor unit.



## Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



## Various cassette grilles

Both black and white grilles are available. Three types of grilles are available: a white grille with a remote controller; a white grille without a remote controller; and a black grille without a remote controller. Select to match the atmosphere and/or usage of the room.



Model: AUXG18KRLB / AUXG22KRLB / AUXG24KRLB / AUXG30KRLB / AUXG36KRLB / AUXG45KRLB / AUXG54KRLB  
AUXG36KRLB [3-phase] / AUXG45KRLB [3-phase] / AUXG54KRLB [3-phase]



## Specifications

Model name	Indoor unit		AUXG18KRLB	AUXG22KRLB	AUXG24KRLB	AUXG30KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB		
	Outdoor unit		AOHG18KRTB	AOHG22KRTB	AOHG24KRTB	AOHG30KRTB	AOHG36KRTB	AOHG45KRTB	AOHG54KRTB	AOHG36KRTA	AOHG45KRTA	AOHG54KRTA		
Power Source	Single phase, ~230 V, 50 Hz									3-phase, ~400 V, 50 Hz				
Capacity	Cooling	Rated	5.2	6.0	6.8	8.5	9.5	12.1	13.4	9.5	12.1	13.4		
		Min.-Max.	0.9-5.9	0.9-6.7	0.9-8.0	2.8-10.0	2.8-11.2	4.0-14.0	4.5-14.5	2.8-11.2	4.0-14.0	4.5-14.5		
	Heating	Rated	6.0	7.0	7.5	10.0	10.8	13.5	13.7	10.8	13.5	15.5		
		Min.-Max.	0.9-7.5	0.9-8.0	0.9-9.1	2.7-11.2	2.7-12.7	4.2-16.2	4.7-16.5	2.7-12.7	4.2-16.2	4.7-16.5		
Input Power	Cooling/Heating	kW	1.36/1.58	1.71/1.82	1.89/1.90	2.44/2.51	2.91/2.45	3.61/3.21	4.41/4.16	2.91/2.45	3.61/3.21	4.41/4.16		
EER	Cooling	W/W	3.82	3.51	3.60	3.49	3.26	3.35	3.04	3.26	3.35	3.04		
COP	Heating	W/W	3.80	3.85	3.95	3.98	4.40	4.20	3.73	4.40	4.20	3.73		
Pdesign	Cooling/Heating (-10°C)	kW	5.2/4.4	6.0/4.8	6.8/6.0	8.5/8.0	9.5/8.7	-	-	9.5/8.7	-	-		
SEER	Cooling	W/W	7.00	7.00	6.60	6.70	6.55	-	-	6.55	-	-		
SCOP	Heating (Average)	W/W	4.30	4.40	4.20	4.30	4.30	-	-	4.30	-	-		
Energy Efficiency Class	Cooling		A++	A++	A+	A+	A+	-	-	A+	-	-		
	Heating (Average)		A+	A+	A+	A+	A+	-	-	A+	-	-		
Max. Operating Current	Cooling/Heating	A	12.1/12.1	12.6/12.6	13.6/13.6	22.6/22.6	22.6/22.6	28.5/28.5	28.5/28.5	10.5/10.5	14.0/14.0	14.0/14.0		
Annual Energy Consumption	Cooling	kWh/a	260	300	360	444	507	-	-	507	-	-		
	Heating	kWh/a	1,431	1,527	1,999	2,601	2,828	-	-	2,828	-	-		
Moisture Removal		l/h	1.5	2.2	2.7	2.5	3.3	4.5	5.0	3.3	4.5	5.0		
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	33/32/31/28	33/32/31/28	35/33/32/29	40/38/36/33	44/41/38/34	46/42/39/35	47/43/40/36	44/41/38/34	46/42/39/35	47/43/40/36		
	Indoor (Heating)	H/M/L/Q	33/32/31/28	33/32/31/28	35/33/32/29	40/38/36/33	44/41/38/34	46/42/39/35	47/43/40/36	44/41/38/34	46/42/39/35	47/43/40/36		
	Outdoor (Cooling/Heating)	High	50/50	51/51	53/54	53/55	55/55	57/57	57/59	55/55	57/57	57/59		
	Indoor (Cooling/Heating)	High	47/47	49/49	49/49	54/54	58/58	60/60	61/61	58/58	60/60	61/61		
Sound Power Level	Outdoor (Cooling/Heating)	High	62/62	63/63	65/66	68/69	70/70	71/71	73/73	70/70	71/71	73/73		
	Indoor/Outdoor (Cooling)	High	1,050/2,160	1,050/2,240	1,150/2,700	1,600/3,750	1,870/3,750	2,000/4,450	2,100/4,450	1,870/3,750	2,000/4,450	2,100/4,450		
Airflow Rate	Indoor/Outdoor (Heating)	High	1,050/1,830	1,050/1,960	1,150/2,700	1,600/3,750	1,870/3,750	2,000/4,450	2,100/4,450	1,870/3,750	2,000/4,450	2,100/4,450		
	Indoor/Outdoor (Cooling)	High	1,050/2,160	1,050/2,240	1,150/2,700	1,600/3,750	1,870/3,750	2,000/4,450	2,100/4,450	1,870/3,750	2,000/4,450	2,100/4,450		
Net Dimensions H x W x D	Indoor	mm	246 × 840 × 840	246 × 840 × 840	246 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840		
	Outdoor	mm	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320	998 × 940 × 320		
Weight	Indoor	kg	23	23	24	26	29	29	29	29	29	29		
	Outdoor	kg	36	38	42	52	52	67	67	53	67	67		
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/12.70	6.35/12.70	6.35/12.70	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88		
Drain Hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32	25/32	25/32	25/32	25/32	25/32			
Max. Pipe Length (Pre-Charge)		m	30 (20)	30 (20)	30 (20)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)			
Max. Height Difference			20	25	25	30	30	30	30	30	30			
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46		
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24		
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)		
	Charge	kg (CO2eq-T)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)	1.90 (1.283)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)		
Cassette Grille	Variation		UTG-UKGA-W: White wired remote controller (touch panel) UTG-UKGC-W: White/UTG-UKGA-B*1: Black									UTG-UKGA-W: White wired remote controller (touch panel) UTG-UKGC-W: White/UTG-UKGA-B*1: Black		
	Dimensions (H × W × D)	mm	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950		
	Weight	kg	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0		

\*1: IR Receiver kit and Human sensor kit cannot be connected.


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	WLAN adapter:	UTY-TFSXZ1	Cassette Grille:	UTG-UKGA-B
Compact wired remote controller:	UTY-RCRGZ1		FG-RC-WIF1Z2		UTG-UKGA-W
Wired remote controller (touch panel):	UTY-RNRGZ5		UTY-TFSXJ3		UTG-UKGC-W
Wired remote controller:	UTY-RLRG		FG-AC-WIF1Z1	Network Converter for single split (DC power supply type):	UTY-VTGX
	UTY-RNNGM	External input and output PCB:	UTY-XCSX	Network Converter for single split (AC power supply type):	UTY-VTGV
	UTY-RVNGM	External input and output PCB box:	UTZ-GXRA	Silver Ion Filter:	UTD-HFRA
Simple remote controller (without operation mode):	UTY-RHRG	Insulation kit for high humidity:	UTZ-KXRA	External connect kit:	UTY-XWZ2XZ
Simple remote controller:	UTY-RSRG	Fresh air intake kit:	UTZ-VXRA		
Human sensor kit:	UTY-SHZXC	Wide Panel:	UTG-AKXA-W	(Outdoor unit 30/36/45/54)	
External switch controller:	UTY-TERX	Panel Spacer:	UTG-BKXA-W	External connect kit:	UTY-XWZ2X3
IR receiver unit:	UTY-LBTGC	Air Outlet Shutter Plate:	UTR-YDZK		

## Dimensions

(Unit: mm)



	AUXG 18/22/24KRLB	AUXG 30/36/45/54KRLB
a	256	298
b	56	98

## Slim Duct

Slim Design



### Slim design

The slim design fits nicely into narrow spaces under the ceiling. Drain hose as standard accessory



### Compact and lightweight outdoor unit

The compact and lightweight outdoor unit offers greater flexibility in the choice of installation location. This makes it easier to use this outdoor unit.



### Wide range of static pressures

The use of a DC fan motor makes it possible to adjust the static pressure between 0 and 90 Pa. The static pressure range can be changed by a remote controller.



Static pressure range  
0 to 90 Pa

### Auto louver grille kit (Option)

The optional clean-looking flat Auto louver blends into any interior and provides a comfortable airflow.




### Link up with a variety of central control system (Option)


Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



### Model: ARXG09KLLAP / ARXG12KLLAP / ARXG14KLLAP / ARXG18KLLAP



ARXG09/12/14KLLAP



ARXG18KLLAP



For ARXG09/12/14KLLAP For ARXG18KLLAP

### Specifications

Model name	Indoor unit		ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP
	Outdoor unit		AOHG09KBTB	AOHG12KBTB	AOHG14KBTB	AOHG18KBTB
Power Source	Single phase, ~230 V, 50 Hz					
Capacity	Cooling	Rated	2.5	3.5	4.3	5.2
		Min.-Max.	0.9-3.2	0.9-4.4	0.9-5.4	0.9-5.9
	Heating	Rated	3.2	4.1	5.0	6.0
Min.-Max.		0.9-4.7	0.9-5.7	0.9-6.5	0.9-7.5	
Input Power	Cooling/Heating	kW	0.60/0.79	0.93/1.08	1.28/1.32	1.55/1.62
EER	Cooling		4.17	3.76	3.36	3.35
COP	Heating	W/W	4.05	3.80	3.79	3.70
Pdesign	Cooling/Heating (-10°C)	kW	2.5/2.6	3.5/3.4	4.3/3.8	5.2/4.4
SEER	Cooling		6.20	6.10	5.80	6.20
SCOP	Heating	W/W	4.30	4.00	3.90	4.10
Energy Efficiency Class	Cooling		A++	A++	A+	A++
	Heating		A+	A+	A	A+
Max. Operating Current	Cooling/Heating	A	7.9/7.9	9.7/9.7	10.2/10.2	12.1/12.1
Annual Energy Consumption	Cooling	kWh/a	141	201	259	293
	Heating		845	1,189	1,362	1,501
Moisture Removal		l/h	0.7	1.3	1.5	2.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	28/27/26/25	29/28/26/25	32/30/28/26	32/30/29/27
	Indoor (Heating)	H/M/L/Q	28/26/25/24	29/28/26/24	32/30/28/25	32/30/29/27
Sound Power Level	Outdoor (Cooling/Heating)	High	46/46	47/47	49/49	50/50
	Indoor (Cooling/Heating)	High	57/57	58/58	60/60	58/58
Airflow Rate	Indoor/Outdoor (Cooling)	High	600/1,480	650/1,580	800/1,670	940/2,160
	Indoor/Outdoor (Heating)	High	600/1,410	650/1,520	800/1,580	940/1,830
Static pressure range (Standard)		Pa	0 to 90 (25)	0 to 90 (25)	0 to 90 (25)	0 to 90 (25)
Net Dimensions H x W x D	Indoor	mm	198 x 700 x 620	198 x 700 x 620	198 x 700 x 620	198 x 900 x 620
	Outdoor	mm	542 x 799 x 290	542 x 799 x 290	542 x 799 x 290	632 x 799 x 290
Weight	Indoor	kg	17	17	17	20
	Outdoor	kg	32	33	33	36
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70
Drain Hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m	20 (15)	25 (15)	25 (15)	30 (20)
Max. Height Difference			15	20	20	20
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.85 (0.574)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)


### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	WLAN adapter:	UTY-TFSXZ1	Network Converter for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RRCGZ1		FG-RC-WIF1Z2	Network Converter for single split (AC power supply type):	UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRGZ5		UTY-TFSXJ3	External connect kit:	UTY-XWZXZG
Wired remote controller:	UTY-RLRG		FG-AC-WIF1Z1	Remote sensor unit:	UTY-XSZXZ1
	UTY-RNNGM	Silver Ion Filter:	UTD-HFTA (09-14)	Auto Louver Grille Kit:	UTD-GXTA-W (09-14)
	UTY-RVNGM		UTD-HFTB (18)		UTD-GXTB-W (18)
Simple remote controller (without operation mode):	UTY-RHRG	External switch controller:	UTY-TERX		
Simple remote controller:	UTY-RSRG	IR receiver unit:	UTY-LBTGM		

### Dimensions

(Unit: mm)



# Medium Static Pressure Duct

High-Efficiency & Comfort



## Slim & Compact design


The new product has reduced the height to 240 mm, making it more compact. The slim design fits nicely into narrow spaces under the ceiling.



(Unit: mm)

## High energy saving

The new model has achieved high energy efficiency rank with a compact design.



SEER **6.50**<sup>\*1</sup> SCOP **4.20**<sup>\*2</sup>

\*1: 12/22 models

\*2: 12/22/24 models

## Easy maintenance

The indoor units have large panels on both sides providing easy maintenance in narrow spaces.



**Easy inspection of drain hose**  
The whole drain hose can be removed for easy replacement and cleaning.

**Filter change**  
Filter can be installed and removed easily.

\* Long life filter is available as optional parts.



**Easy cleaning of the heat exchanger**

## Drain hose as standard

A drain hose is a standard accessory, making it easy to design drainage even in narrow spaces under the ceiling.



## Wide range of static pressures

Static pressures can be changed in the range of 30 to 150 Pa.

Static pressure range **30 to 150 Pa**

Model: ARXH12KMTAP / ARXH14KMTAP / ARXH18KMTAP / ARXH22KMTAP / ARXH24KMTAP



ARXH12/14/18KMTAP



ARXH22/24KMTAP



For ARXH12/14KMTAP For ARXH18/22KMTAP For ARXH24KMTAP

## Specifications

Model name	Indoor unit		ARXH12KMTAP	ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	ARXH24KMTAP
	Outdoor unit		AOHG12KBTB	AOHG14KBTB	AOHG18KBTB	AOHG22KBTB	AOHG24KBTB
Power Source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling	Rated	3.5	4.3	5.2	6.0	6.8
		Min.-Max.	0.9-4.4	0.9-5.4	0.9-5.9	0.9-6.7	0.9-8.0
	Heating	Rated	4.1	5.0	6.0	7.0	7.5
Min.-Max.		0.9-5.7	0.9-6.5	0.9-7.5	0.9-8.0	0.9-9.1	
Input Power	Cooling/Heating	kW	0.930 / 1.080	1.260 / 1.320	1.580 / 1.740	1.67 / 1.84	1.89 / 1.87
EER	Cooling	W/W	3.76	3.40	3.30	3.60	3.60
COP	Heating	W/W	3.80	3.79	3.45	3.80	4.01
Pdesign	Cooling/Heating (-10°C)	kW	3.5 / 3.4	4.3 / 3.8	5.2 / 4.4	6.0 / 4.8	6.8 / 6.0
SEER	Cooling	W/W	6.50	6.10	6.20	6.50	6.40
SCOP	Heating (Average)	W/W	4.20	4.00	4.10	4.20	4.20
Energy Efficiency Class	Cooling		A++	A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+	A+
Max. Operating Current	Cooling/Heating	A	9.7 / 9.7	10.2 / 10.2	12.1 / 12.1	12.6 / 12.6	13.6 / 13.6
Annual Energy Consumption	Cooling	kWh/a	196	255	301	331	380
	Heating	kWh/a	1,133	1,330	1,501	1,598	1,999
Moisture Removal		l/h	1.3	1.3	2.0	1.5	2.2
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24	34 / 30 / 28 / 26
	Indoor (Heating)	H/M/L/Q	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24	34 / 30 / 28 / 26
	Outdoor (Cooling/Heating)	High	47 / 47	49 / 49	50 / 50	51 / 51	53 / 54
Sound Power Level	Indoor (Cooling/Heating)	High	58 / 58	59 / 59	60 / 60	58 / 58	60 / 60
	Outdoor (Cooling/Heating)	High	61 / 61	62 / 62	62 / 62	63 / 63	65 / 66
	Indoor/Outdoor (Cooling)	High	650 / 1,580	800 / 1,670	840 / 2,160	1,150 / 2,240	1,230 / 2,700
Airflow Rate	Indoor/Outdoor (Cooling)	High	650 / 1,580	800 / 1,670	840 / 2,160	1,150 / 2,240	1,230 / 2,700
	Indoor/Outdoor (Heating)	High	650 / 1,520	800 / 1,580	840 / 1,830	1,150 / 1,960	1,230 / 2,700
Static pressure range (Standard)		Pa	30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (50)
Net Dimensions	Indoor	mm	240 × 700 × 700	240 × 700 × 700	240 × 700 × 700	240 × 1,000 × 700	240 × 1,000 × 700
	Outdoor	mm	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315
Weight	Indoor	kg	24	24	24	31	31
	Outdoor	kg	33	33	36	38	42
Connection Pipe Diameter (Liquid/Gas)		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.70	6.35 / 12.70
Drain Hose Diameter (I.D./O.D.)		mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Max. Pipe Length (Pre-Charge)		m	25 (15)	25 (15)	30 (20)	30 (20)	30 (20)
Max. Height Difference		m	20	20	20	25	25
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	Silver ion filter:	UTD-HFNC (12/14/18)	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRGZ1		UTD-HFNB	External input and output PCB bracket:	UTZ-GXDA
Wired remote controller (touch panel):	UTY-RNRGZ5	Long-life filter:	(22/24)	Network Converter for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RLRG		UTD-LFDC (12/14/18)	Network Converter for single split (AC power supply type):	UTY-XWZGXV
Simple remote controller (without operation mode):	UTY-RHRG	MODBUS converter:	UTD-LFDB	External connect kit:	UTY-XWZXXZG
Simple remote controller:	UTY-RSRG	KNX converter:	(22/24)	IR receiver unit:	UTY-LBTGM
Remote sensor unit:	UTY-XSZX	WLAN adapter:	UTY-VMSX	External switch controller:	UTY-TERX
	UTY-XSZXZ1		UTY-VKXS		
			UTY-TFSXZ1		
			UTY-TFSXJ3		

## Dimensions

(Unit: mm)



# Medium Static Pressure Duct

High-Efficiency & Comfort



## Slim & Compact design


The new product has reduced the height to 240 mm, making it more compact. The slim design fits nicely into narrow spaces under the ceiling.



(Unit: mm)

## High energy saving

The new model has achieved high energy efficiency rank with a compact design.



SEER **6.23**<sup>\*1</sup> SCOP **4.10**<sup>\*2</sup>

<sup>\*1</sup>: 30 model <sup>\*2</sup>: 36 model

## Easy maintenance

The indoor units have large panels on both sides providing easy maintenance in narrow spaces.



**Easy inspection of drain hose**  
The whole drain hose can be removed for easy replacement and cleaning.

**Filter change**  
Filter can be installed and removed easily.

<sup>\*</sup> Long life filter is available as optional parts.

## Drain hose as standard

A drain hose is a standard accessory, making it easy to design drainage even in narrow spaces under the ceiling.




## Wide range of static pressures

Static pressures can be changed in the range of 30 to 150 Pa.

Static pressure range **30 to 150 Pa**

Model: ARXH30KMTAP / ARXH36KMTAP / ARXH45KMTAP / ARXH54KMTAP  
ARXH36KMTAP [3-phase] / ARXH45KMTAP [3-phase] / ARXH54KMTAP [3-phase]



ARXH30/36/45/54KMTAP



For ARXH30/36KMTAP For ARXH45/54KMTAP

## Specifications

Model name	Indoor unit			ARXH30KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH54KMTAP
	Outdoor unit			AOHG30KBTB	AOHG36KBTB	AOHG45KBTB	AOHG36KRTA	AOHG45KRTA	AOHG54KRTA
Power Source	Single phase, ~230 V, 50 Hz						3-phase, ~400 V, 50 Hz		
Capacity	Cooling	Rated	kW	8.5	9.5	12.1	9.5	12.1	13.4
		Min.-Max.		2.8-10.0	2.8-11.2	4.0-13.5	2.8-11.2	4.0-13.5	4.5-14.5
	Heating	Rated	10.0	10.8	13.5	10.8	13.5	15.5	
Min.-Max.		2.7-11.2	2.7-12.7	4.2-16.2	2.7-12.7	4.2-16.2	4.7-16.5		
Input Power	Cooling/Heating	kW	2.57 / 2.50	2.97 / 2.70	3.87 / 3.73	2.97 / 2.70	3.87 / 3.73	4.62 / 4.65	
EER	Cooling	W/W	3.31	3.20	3.13	3.20	3.13	2.90	
COP	Heating	W/W	4.00	4.00	3.62	4.00	3.62	3.33	
Pdesign	Cooling/Heating (-10°C)	kW	8.5 / 8.0	9.5 / 8.7	-	9.5 / 8.7	-	-	
SEER	Cooling	W/W	6.23	6.10	-	6.10	-	-	
SCOP	Heating (Average)	W/W	4.00	4.10	-	4.10	-	-	
Energy Efficiency Class	Cooling		A++	A++	-	A++	-	-	
	Heating (Average)		A+	A+	-	A+	-	-	
Max. Operating Current	Cooling/Heating	A	22.6 / 22.6	22.6 / 22.6	28.5 / 28.5	10.5 / 10.5	14.0 / 14.0	14.0 / 14.0	
Annual Energy Consumption	Cooling	kWh/a	485	553	-	553	-	-	
	Heating	kWh/a	2,795	2,970	-	2,970	-	-	
Moisture Removal		l/h	1.8	2.0	4.0	2.0	4.0	5.0	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38 / 34 / 31 / 28	38 / 34 / 31 / 28	40 / 36 / 32 / 29	38 / 34 / 31 / 28	40 / 36 / 32 / 29	40 / 36 / 32 / 29	
	Indoor (Heating)	H/M/L/Q	38 / 34 / 31 / 28	38 / 34 / 31 / 28	40 / 36 / 32 / 29	38 / 34 / 31 / 28	40 / 36 / 32 / 29	40 / 36 / 32 / 29	
	Outdoor (Cooling/Heating)	High	53 / 55	55 / 55	57 / 57	55 / 55	57 / 57	57 / 59	
Sound Power Level	Indoor (Cooling/Heating)	High	64 / 64	65 / 65	67 / 67	65 / 65	67 / 67	67 / 67	
	Outdoor (Cooling/Heating)	High	68 / 69	70 / 70	71 / 71	70 / 70	71 / 71	73 / 73	
	Indoor/Outdoor (Cooling)	High	1,950 / 3,750	2,070 / 3,750	2,160 / 4,450	2,070 / 3,750	2,160 / 4,450	2,160 / 4,450	
Airflow Rate	Indoor/Outdoor (Heating)	High	1,950 / 3,750	2,070 / 3,750	2,160 / 4,450	2,070 / 3,750	2,160 / 4,450	2,160 / 4,450	
Static pressure range (Standard)		Pa	30 to 150 (50)	30 to 150 (50)	30 to 150 (60)	30 to 150 (50)	30 to 150 (60)	30 to 150 (60)	
Net Dimensions H x W x D	Indoor	mm	240 x 1,400 x 700	240 x 1,400 x 700	240 x 1,400 x 700	240 x 1,400 x 700	240 x 1,400 x 700	240 x 1,400 x 700	
	Outdoor	mm	788 x 940 x 320	788 x 940 x 320	998 x 940 x 320	788 x 940 x 320	998 x 940 x 320	998 x 940 x 320	
Weight	Indoor	kg	42	42	42	42	42	42	
	Outdoor	kg	52	52	67	53	67	67	
Connection Pipe Diameter (Liquid/Gas)		mm	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88	
Drain Hose Diameter (L.D./O.D.)		mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	
Max. Pipe Length (Pre-Charge)		m	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)	
Max. Height Difference			30	30	30	30	30	30	
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	
	Charge	kg (CO2eq-T)	1.90 (1.283)	1.90 (1.283)	2.70 (1.823)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)	


## Optional parts

<sup>\*</sup> For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	IR receiver unit:	UTY-LBTGM	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRG21	Silver ion filter:	UTY-HFNA	External input and output PCB bracket:	UTZ-GXDA
Wired remote controller (touch panel):	UTY-RNRG25	Long-life filter:	UTD-LFDA	Network Converter for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RLRG	MODBUS converter:	UTY-VMSX	Network Converter for single split (AC power supply type):	UTY-VTGXV
Simple remote controller (without operation mode):	UTY-RHRG	KNX converter:	UTY-VKSX	External connect kit:	UTY-XWZXZG
Simple remote controller:	UTY-RSRG	WLAN adapter:	UTY-TFSXZ1	(Outdoor unit)	
Remote sensor unit:	UTY-XSZX	External switch controller:	UTY-TFSXJ3	External connect kit:	UTY-XWZXZ3
	UTY-XSZXZ1		UTY-TERX		


## Dimensions

(Unit: mm)




# Medium Static Pressure Duct

Compact Size



## High-efficiency & Quiet operation

The combination of the V-shaped heat exchanger, air stabilizer, and the high-efficiency DC fan motor enable high-efficiency and quiet operation.



## Small, lightweight outdoor unit

The outdoor unit in this series is smaller and lighter than previous-generation outdoor units. It can be installed in a narrow space.



## Automatic airflow adjustment function

This unique and innovative function detects required air flow in each application case and automatically adjust the volume.



## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARXG12KHTAP / ARXG14KHTAP / ARXG18KHTAP / ARXG22KHTAP / ARXG24KHTAP / ARXG30KHTAP



### Specifications

Model name	Indoor unit		ARXG12KHTAP	ARXG14KHTAP	ARXG18KHTAP	ARXG22KHTAP	ARXG24KHTAP	ARXG30KHTAP
	Outdoor unit		AOHG12KBTB	AOHG14KBTB	AOHG18KBTB	AOHG22KBTB	AOHG24KBTB	AOHG30KBTB
Power Source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	Rated	3.5	4.3	5.2	6.0	6.8	8.5
		Min.-Max.	0.9-4.4	0.9-5.4	0.9-5.9	0.9-6.7	0.9-8.0	2.8-10.0
	Heating	Rated	4.1	5.0	6.0	7.0	7.5	10.0
Min.-Max.		0.9-5.7	0.9-6.5	0.9-7.5	0.9-8.0	0.9-9.1	2.7-11.2	
Input Power	Cooling/Heating	kW	0.87/1.00	1.17/1.25	1.36/1.56	1.71/1.81	1.89/1.85	2.65/2.63
EER	Cooling	W/W	4.02	3.68	3.82	3.51	3.60	3.21
COP	Heating	W/W	4.10	4.00	3.85	3.87	4.06	3.80
Pdesign	Cooling/Heating (-10°C)	kW	3.5/3.4	4.3/3.8	5.2/4.4	6.0/4.8	6.8/6.0	8.5/8.0
SEER	Cooling	W/W	6.30	6.20	6.50	6.50	6.50	6.23
SCOP	Heating (Average)	W/W	4.10	4.00	4.10	4.20	4.10	4.00
Energy Efficiency Class	Cooling		A++	A++	A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+	A+	A+
Max. Operating Current	Cooling/Heating	A	9.7/9.7	10.2/10.2	12.1/12.1	12.6/12.6	13.6/13.6	22.6/22.6
Annual Energy Consumption	Cooling	kWh/a	194	243	280	323	366	477
	Heating	kWh/a	1,159	1,328	1,501	1,597	2,048	2,796
Moisture Removal		l/h	0.7	0.9	1.2	1.5	1.8	2.3
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	32/27/26/24	33/28/27/25	28/25/22/20	28/25/22/20	32/28/24/21	36/33/30/29
	Indoor (Heating)	H/M/L/Q	32/27/26/24	33/28/27/25	28/25/22/20	28/25/22/20	32/28/24/21	36/33/30/29
	Outdoor (Cooling/Heating)	High	47/47	49/49	50/50	51/51	53/54	53/55
Sound Power Level	Indoor (Cooling/Heating)	High	57/58	59/60	54/54	57/57	57/57	63/65
	Outdoor (Cooling/Heating)	High	61/61	62/62	62/62	63/63	65/66	68/69
	Indoor/Outdoor (Cooling)	High	850/1,580	950/1,670	1,050/2,160	1,050/2,240	1,360/2,700	1,700/3,750
Airflow Rate	Indoor/Outdoor (Heating)	High	850/1,520	950/1,580	1,050/1,830	1,050/1,960	1,360/2,700	1,700/3,750
Static pressure range (Standard)		Pa	30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (47)
Net Dimensions H x W x D	Indoor	mm	300 x 700 x 700	300 x 700 x 700	300 x 1,000 x 700	300 x 1,000 x 700	300 x 1,000 x 700	300 x 1,000 x 700
	Outdoor	mm	542 x 799 x 290	542 x 799 x 290	632 x 799 x 290	632 x 799 x 290	716 x 820 x 315	788 x 940 x 320
Weight	Indoor	kg	27	27	35	35	36	36
	Outdoor	kg	33	33	36	38	42	52
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70	6.35/12.70	9.52/15.88
Drain Hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m	25 (15)	25 (15)	30 (20)	30 (20)	30 (20)	50 (30)
Max. Height Difference	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)	1.90 (1.283)


### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	Long-life filter: UTD-LFNB (18-30)	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRGZ1	UTD-LFNC (12-14)	External connect kit:	UTY-XWZXZG
Wired remote controller (touch panel):	UTY-RNRGZ5	Silver Ion Filter: UTD-HFNB (18-30)	External input and output PCB bracket:	UTZ-GXNA
Wired remote controller:	UTY-RLRG	UTD-HFNC (12/14)	Network Converter for single split (DC power supply type):	UTY-VTGX
	UTY-RNNGM	WLAN adapter: UTY-TFSXZ1	Network Converter for single split (AC power supply type):	UTY-VTGXV
	UTY-RVNGM	FG-RC-WIF1Z2	External switch controller:	UTY-TERX
Simple remote controller (without operation mode):	UTY-RHRG	UTY-TFSXJ3		
Simple remote controller:	UTY-RSRG	FG-AC-WIF1Z1	(Outdoor unit 30)	
Remote sensor unit:	UTY-XS2XZ1	IR receiver unit: UTY-LBTGM	External connect kit:	UTY-XWZXZ3

### Dimensions

(Unit: mm)




	ARXG 12 / 14 KHTAP	ARXG 18 / 22 / 24 / 30 KHTAP
a	650	895
b	P100x5=500	P100x8=800
c	740	1,040
d	700	1,000
e	462	762
f	P100x4=400	P100x7=700

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.


# Medium Static Pressure Duct

Compact Size




## High-efficiency & Quiet operation

The combination of the V-shaped heat exchanger, air stabilizer, and the high-efficiency DC fan motor enable high-efficiency and quiet operation.



## Small, lightweight outdoor unit

The outdoor unit in this series is smaller and lighter than previous-generation outdoor units. It can be installed in a narrow space.



## Automatic airflow adjustment function

This unique and innovative function detects required air flow in each application case and automatically adjust the volume.




## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARXG36KHTAP / ARXG45KHTAP / ARXG54KHTAP  
ARXG36KHTAP [3-phase] / ARXG45KHTAP [3-phase] / ARXG54KHTAP [3-phase]



### Specifications

Model name	Indoor unit			Outdoor unit				
	ARXG36KHTAP	ARXG45KHTAP	ARXG54KHTAP	AOHG36KBTB	AOHG45KBTB	AOHG54KBTB		
Power Source	Single phase, ~230 V, 50 Hz			3-phase, ~400 V, 50 Hz				
Capacity	Cooling	Rated	9.5	12.1	13.4	9.5	12.1	13.4
		Min.-Max.	2.8-11.2	4.0-14.0	4.5-14.5	2.8-11.2	4.0-14.0	4.5-14.5
	Heating	Rated	10.8	13.5	15.5	10.8	13.5	15.5
Input Power	Cooling/Heating (-10°C)	Min.-Max.	2.7-12.7	4.2-16.2	4.7-16.5	2.7-12.7	4.2-16.2	4.7-16.5
		Rated	2.86/2.48	3.53/3.37	4.42/3.89	2.86/2.48	3.53/3.37	4.42/3.89
EER	Cooling	W/W	3.32	3.43	3.03	3.32	3.43	3.03
COP	Heating	W/W	4.35	4.01	3.98	4.35	4.01	3.98
Pdesign	Cooling/Heating (-10°C)	kW	9.5/8.7	-	-	9.5/8.7	-	-
SEER	Cooling	W/W	6.10	-	-	6.10	-	-
SCOP	Heating (Average)	W/W	4.20	-	-	4.20	-	-
Energy Efficiency Class	Cooling		A++	-	-	A++	-	-
	Heating (Average)		A+	-	-	A+	-	-
Max. Operating Current	Cooling/Heating	A	22.6/22.6	28.5/28.5	28.5/28.5	10.5/10.5	14.0/14.0	14.0/14.0
Annual Energy Consumption	Cooling	kWh/a	544	-	-	544	-	-
	Heating	kWh/a	2,898	-	-	2,898	-	-
Moisture Removal		l/h	2.0	2.6	3.7	2.0	2.6	3.7
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	36/31/28/26	39/35/31/29	39/35/31/29	36/31/28/26	39/35/31/29	39/35/31/29
	Indoor (Heating)	H/M/L/Q	33/31/28/26	39/35/31/29	39/35/31/29	33/31/28/26	39/35/31/29	39/35/31/29
	Outdoor (Cooling/Heating)	High	55/55	57/57	57/59	55/55	57/57	57/59
Sound Power Level	Indoor (Cooling/Heating)	High	64/63	67/69	67/69	64/63	67/69	67/69
	Outdoor (Cooling/Heating)	High	70/70	71/71	73/73	70/70	71/71	73/73
	Indoor/Outdoor (Cooling)	High	2,050/3,750	2,550/4,450	2,550/4,450	2,050/3,750	2,550/4,450	2,550/4,450
Airflow Rate	Indoor/Outdoor (Heating)	High	1,850/3,750	2,550/4,450	2,550/4,450	1,850/3,750	2,550/4,450	2,550/4,450
	Static pressure range (Standard)	Pa	30 to 200 (47)	30 to 200 (60)	30 to 200 (60)	30 to 200 (47)	30 to 200 (60)	30 to 200 (60)
Net Dimensions H x W x D	Indoor	mm	300 x 1,400 x 700	300 x 1,400 x 700	300 x 1,400 x 700	300 x 1,400 x 700	300 x 1,400 x 700	300 x 1,400 x 700
	Outdoor	mm	788 x 940 x 320	998 x 940 x 320	998 x 940 x 320	788 x 940 x 320	998 x 940 x 320	998 x 940 x 320
Weight	Indoor	kg	46	46	46	46	46	46
	Outdoor	kg	52	67	67	53	67	67
Connection Pipe Diameter (Liquid/Gas)		mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain Hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)
Max. Height Difference			30	30	30	30	30	30
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)


### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	Long-life filter:	UTD-LFNA	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRGZ1	Silver Ion Filter:	UTD-HFNA	External input and output PCB bracket:	UTZ-GXNA
Wired remote controller (touch panel):	UTY-RNRGZ5		UTY-TFSXZ1	Network Converter for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RLRG	WLAN adapter:	FG-RC-WIF1Z2	Network Converter for single split (AC power supply type):	UTY-VTGXV
	UTY-RNNGM		UTY-TFSXJ3		
	UTY-RVNGM		FG-AC-WIF1Z1	(Outdoor unit 36/45/54)	
Simple remote controller (without operation mode):	UTY-RHRG	External switch controller:	UTY-TERX	External connect kit:	UTY-XWZXZ3
Simple remote controller:	UTY-RSRG	IR receiver unit:	UTY-LBTGM		
Remote sensor unit:	UTY-XSZXZ1	External connect kit:	UTY-XWZXZG		

### Dimensions

(Unit: mm)






# Medium Static Pressure Duct Standard




## Easy maintenance

Structural improvement is attained by making the bottom panel in two pieces—front and rear. The internal fan casing is also manufactured in two pieces—upper and lower. As a result, the motor and fan can be easily accessed and maintained by removing the rear panel and the lower casing while leaving the main chassis in place.




## Slim & Compact design


**Indoor Unit**  
The slim and compact design of the indoor unit, with the control box mounted on the side, allows installation in narrow spaces.



**Outdoor Unit**  
The outdoor units for the 45,000 BTU and 54,000 BTU models have been completely redesigned. Easier installation is achieved for this compact and lightweight outdoor unit.



## Two-direction drain piping



## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARXG22KMLB / ARXG24KMLA / ARXG30KMLA / ARXG36KMLA / ARXG45KMLA  
ARXG36KMLA [3-phase] / ARXG45KMLA [3-phase]



## Specifications

Model name	Indoor unit		ARXG22KMLB	ARXG24KMLA	ARXG30KMLA	ARXG36KMLA	ARXG45KMLA	ARXG36KMLA	ARXG45KMLA
	Outdoor unit		AOHG22KBTB	AOHG24KBTB	AOHG30KBTB	AOHG36KBTB	AOHG45KBTB	AOHG36KRTA	AOHG45KRTA
Power Source	Single phase, ~230 V, 50 Hz							3-phase, ~400 V, 50 Hz	
Capacity	Cooling	Rated	6.0	6.8	8.5	9.5	12.1	9.5	12.1
		Min.-Max.	0.9-6.7	0.9-8.0	2.8-10.0	2.8-11.2	4.0-13.0	2.8-11.2	4.0-13.0
	Heating	Rated	7.0	7.5	10.0	10.8	13.5	10.8	13.5
		Min.-Max.	0.9-8.0	0.9-9.1	2.7-11.2	2.7-12.7	4.2-15.2	2.7-12.7	4.2-15.2
Input Power	Cooling/Heating	kW	1.78/1.87	2.14/1.97	2.65/2.63	2.97/2.88	4.22/3.84	2.97/2.88	4.22/3.84
EER	Cooling	W/W	3.37	3.18	3.21	3.20	2.87	3.20	2.87
COP	Heating	W/W	3.74	3.80	3.80	3.75	3.52	3.75	3.52
Pdesign	Cooling/Heating (-10°C)	kW	6.0/4.8	6.8/6.0	8.5/8.0	9.5/8.7	-	9.5/8.7	-
SEER	Cooling	W/W	6.10	6.20	6.23	6.10	-	6.10	-
SCOP	Heating	W/W	4.10	4.10	4.00	4.00	-	4.00	-
Energy Efficiency Class	Cooling		A++	A++	A++	A++	-	A++	-
	Heating		A+	A+	A+	A+	-	A+	-
Max. Operating Current	Cooling/Heating	A	12.6/12.6	13.6/13.6	22.6/22.6	22.6/22.6	28.5/28.5	10.5/10.5	14.0/14.0
Annual Energy Consumption	Cooling	kWh/a	344	384	477	545	-	545	-
	Heating		1,637	2,045	2,797	3,044	-	3,044	-
Moisture Removal		l/h	2.1	2.5	2.5	3.0	4.0	3.0	4.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	31/29/27/25	31/29/27/25	39/35/30/26	39/35/30/26	42/38/32/28	39/35/30/26	42/38/32/28
	Indoor (Heating)	H/M/L/Q	31/29/27/25	31/29/27/25	42/35/30/26	42/35/30/26	42/38/32/28	42/35/30/26	42/38/32/28
Sound Power Level	Outdoor (Cooling/Heating)	High	51/51	53/54	53/55	55/55	57/57	55/55	57/57
	Outdoor (Cooling/Heating)	High	60/62	60/62	65/69	65/70	68/70	65/70	68/70
Airflow Rate	Indoor/Outdoor (Cooling)	High	1,100/2,240	1,100/2,700	1,900/3,750	1,900/3,750	2,100/4,450	1,900/3,750	2,100/4,450
	Indoor/Outdoor (Heating)	High	1,100/1,960	1,100/2,700	2,100/3,750	2,100/3,750	2,100/4,450	2,100/3,750	2,100/4,450
Static pressure range (Standard)		Pa	30 to 150 (35)	30 to 150 (35)	30 to 150 (47)	30 to 150 (47)	30 to 150 (60)	30-150 (47)	30-150 (60)
Net Dimensions	Indoor	mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
	Outdoor	mm	632 × 799 × 290	716 × 820 × 315	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320
Weight	Indoor	kg	35	35	38	38	39	38	39
	Outdoor	kg	38	42	52	52	67	53	67
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/12.70	6.35/12.70	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain Hose Diameter (I.D./O.D.)		mm	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1
Max. Pipe Length (Pre-Charge)		m	30 (20)	30 (20)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)
Max. Height Difference			25	25	30	30	30	30	30
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	1.25 (0.844)	1.25 (0.844)	1.90 (1.283)	1.90 (1.283)	2.70 (1.823)	1.90 (1.283)	2.70 (1.823)


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	WLAN adapter:	UTY-TFSXZ1	Network Converter for single split (DC power supply type):	UTY-VTGC
Compact wired remote controller:	UTY-RCRGZ1		FG-RC-WIF122	Network Converter for single split (AC power supply type):	UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRGZ5		UTY-TFSXJ3	Long-life filter:	UTD-LF25NA
Wired remote controller:	UTY-RLRG		FG-AC-WIF121	Silver Ion Filter:	UTD-HFND
	UTY-RNNGM	Flange (Round):	UTD-RF204	External connect kit:	UTY-XWZXZG
	UTY-RVNGM	Flange (Square):	UTD-SF045T		
Simple remote controller (without operation mode):	UTY-RHRG	IR receiver unit:	UTY-LBTGM	(Outdoor unit 30/36/45)	
Simple remote controller:	UTY-RSRG	Remote sensor unit:	UTY-XSZXZ1	External connect kit:	UTY-XWZXZ3
External switch controller:	UTY-TERX	Drain pump unit:	UTZ-PX1NBA		

## Dimensions

(Unit: mm)





\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

# High Static Pressure Duct



## Easy installation (Compact & Lightweight)

The indoor and outdoor units are designed to be compact and light by reducing the basic chassis size and the overall material weight.




## Design also suits high static pressure



## Low noise

Slanted corners at the top help reduce turbulent airflow. Low noise is realized by adopting a plastic case and a plastic fan.



## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



## Model: ARXG45KHTB / ARXG54KHTB ARXG45KHTB [3-phase] / ARXG54KHTB [3-phase]



### Specifications

Model name	Indoor unit		ARXG45KHTB	ARXG54KHTB	ARXG45KHTB	ARXG54KHTB
	Outdoor unit		AOHG45KHTB	AOHG54KHTB	AOHG45KRTA	AOHG54KRTA
Power Source	Single phase, ~230 V, 50 Hz			3-phase, ~400 V, 50 Hz		
Capacity	Cooling	Rated	12.1	13.4	12.1	13.4
		Min.-Max.	4.0-14.0	5.0-14.5	4.0-14.0	5.0-14.5
	Heating	Rated	13.5	15.5	13.5	15.5
		Min.-Max.	5.0-16.2	5.5-18.0	5.0-16.2	5.5-18.0
Input Power	Cooling/Heating	kW	4.16/3.61	4.77/4.18	4.16/3.61	4.77/4.18
EER	Cooling	W/W	2.91	2.81	2.91	2.81
COP	Heating	W/W	3.74	3.71	3.74	3.71
Pdesign	Cooling/Heating (-10°C)	kW	-	-	-	-
SEER	Cooling	W/W	-	-	-	-
SCOP	Heating	W/W	-	-	-	-
Energy Efficiency Class	Cooling	-	-	-	-	-
	Heating	-	-	-	-	-
Max. Operating Current	Cooling/Heating	A	28.5/28.5	28.5/28.5	14.0/14.0	14.0/14.0
Annual Energy Consumption	Cooling	kWh/a	-	-	-	-
	Heating	kWh/a	-	-	-	-
Moisture Removal		l/h	1.5	2.0	1.5	2.0
Sound Pressure Level	Indoor (Cooling)	H/M/L	47/43/40	47/43/40	47/43/40	47/43/40
	Indoor (Heating)	H/M/L	47/43/40	47/43/40	47/43/40	47/43/40
Sound Power Level	Outdoor (Cooling/Heating)	High	57/57	57/59	57/57	57/59
	Indoor (Cooling/Heating)	High	75/74	75/74	75/74	75/74
Airflow Rate	Indoor/Outdoor (Cooling)	High	3,350/4,450	3,350/4,450	3,350/4,450	3,350/4,450
	Indoor/Outdoor (Heating)	High	3,350/4,450	3,350/4,450	3,350/4,450	3,350/4,450
Static pressure range (Standard)		Pa	100 to 250 (100)	100 to 250 (100)	100 to 250 (100)	100 to 250 (100)
Net Dimensions H x W x D	Indoor	mm	400 x 1,050 x 500	400 x 1,050 x 500	400 x 1,050 x 500	400 x 1,050 x 500
	Outdoor	mm	998 x 940 x 320	998 x 940 x 320	998 x 940 x 320	998 x 940 x 320
Weight	Indoor	kg	46	46	46	46
	Outdoor	kg	67	67	67	67
Connection Pipe Diameter (Liquid/Gas)		mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain port Diameter (L.D./O.D.)		mm	23.4/25.4	23.4/25.4	23.4/25.4	23.4/25.4
Max. Pipe Length (Pre-Charge)		m	50 (30)	50 (30)	50 (30)	50 (30)
Max. Height Difference			30	30	30	30
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	2.70 (1.823)	2.70 (1.823)	2.70 (1.823)	2.70 (1.823)


### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type): UTY-RVRG	Remote sensor unit: UTY-XSZXZ1	Network Converter for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRGZ1	Long-life filter: UTD-LF60KA	Network Converter for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel): UTY-RNRGZ5	External switch controller: UTY-TERX	Silver Ion Filter: UTD-HFKB
Wired remote controller: UTY-RLRG	WLAN adapter: UTY-TFSXZ1	External connect kit: UTY-XWZXZG
Simple remote controller: UTY-RSRG	FG-AC-WIF1Z1	
UTY-RHRG		(Outdoor unit)
UTY-LBTGM	External input and output PCB: UTY-XCSX+UTZ-GXEA	External connect kit: UTY-XWZXZ3

### Dimensions

(Unit: mm)





# High Static Pressure Duct



## High energy efficiency


Much greater efficiency is achieved by the use of all-DC inverter technology.

## Design also corresponding to high static pressure




## Easy installation (Compact & Lightweight)

The indoor unit is designed to be compact and light by reducing the basic chassis size and the overall material weight.



## Low noise

Slanted corners at the top help reduce turbulent airflow. Low noise is realized by adopting a plastic case and a plastic fan.



## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



## Model: ARHG60LHTA [3-phase]



## Specifications

Model name	Indoor unit		Outdoor unit		ARHG60LHTA	AOHG60LATT
	Indoor unit		Outdoor unit			
Power Source					3-phase, ~400 V, 50 Hz	
Capacity	Cooling	Rated	kW			
		Min.-Max.				
	Heating	Rated				
		Min.-Max.				
Input Power	Cooling/Heating		kW	4.70/5.15		
EER	Cooling		W/W	3.19		
COP	Heating		W/W	3.50		
Max. Operating Current	Cooling/Heating		A	12.5 /12.5		
Moisture Removal			l/h	2.0		
Sound Pressure	Indoor (Cooling)	H/M/L/Q	dB(A)	45/40/36/-		
	Indoor (Heating)	H/M/L/Q		45/40/36/-		
	Outdoor (Cooling/Heating)	High	56/58			
	Indoor/Outdoor (Cooling)	High	3,550/6,900			
Airflow Rate	Indoor/Outdoor (Heating)	High	3,550/7,300			
	Static pressure range (Standard)		Pa	60 to 260 (60)		
Net Dimensions	Indoor	mm	425 × 1,250 × 490			
H x W x D	Outdoor	mm	1,290 × 900 × 330			
Weight	Indoor	kg	54			
	Outdoor	kg	104			
Connection Pipe Diameter (Liquid/Gas)			mm	9.52/15.88		
Drain Hose Diameter (I.D./O.D.)				23.4/25.4		
Max. Pipe Length (Pre-Charge)			m	75 (30)		
Max. Height Difference				30		
Operating Range	Cooling	°CDB		-15 to 46		
	Heating	°CDB		-15 to 24		
Refrigerant	Type (Global Warming Potential)			R410A (2,098)		
	Charge	kg (CO2eq-T)	3.45 (7.204)			


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired remote controller:	UTY-RNNGM	Network Converter for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RVNGM	Network Converter for single split (AC power supply type):	UTY-VTGXV
External switch controller:	UTY-TERX	External connect kit:	UTD-EC55A
WLAN adapter:	UTY-TFNXZ1		
	FG-RC-WIF1Z2	(Outdoor unit)	
Remote sensor unit:	UTY-XSXXZ1	External connect kit:	UTY-XWXXZ2
IR receiver unit:	UTY-LRHGM		

## Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

# Big Duct



## Model: ARHG72LHTA / ARHG90LHTA



Wired RC




### Specifications

Model name	Indoor unit	ARHG72LHTA		ARHG90LHTA		
	Outdoor unit	AOHG72LRLA		AOHG90LRLA		
Power Source	Indoor	Single phase, ~230 V, 50 Hz				
	Outdoor	3-phase, ~400 V, 50 Hz				
Capacity	Cooling	Rated	19.0	22.0		
		Min.-Max.	8.4-20.9	10.3-24.2		
	Heating	Rated	22.4	27.0		
		Min.-Max.	7.2-24.6	8.5-29.7		
Input Power	Cooling/Heating	kW		kW		
EER	Cooling	W/W		W/W		
COP	Heating	W/W		W/W		
Max. Operating Current	Indoor (Cooling/Heating)	A		A		
	Outdoor (Cooling/Heating)	A		A		
Moisture Removal		l/h		l/h		
Sound Pressure	Indoor (Cooling)	H/M/L/Q	dB(A)		dB(A)	
	Indoor (Heating)	H/M/L/Q	dB(A)		dB(A)	
	Outdoor (Cooling/Heating)	High	dB(A)		dB(A)	
Airflow Rate	Indoor/Outdoor (Cooling)	High	m <sup>3</sup> /h		m <sup>3</sup> /h	
	Indoor/Outdoor (Heating)	High	m <sup>3</sup> /h		m <sup>3</sup> /h	
Static pressure range (Standard)		Pa		Pa		
Net Dimensions H x W x D	Indoor	mm		mm		
	Outdoor	mm		mm		
Weight	Indoor	kg		kg		
	Outdoor	kg		kg		
Connection Pipe Diameter (Liquid/Gas)		mm		mm		
Drain Hose Diameter (I.D./O.D.)		mm		mm		
Max. Pipe Length (Pre-Charge)		m		m		
		m		m		
Operating Range	Cooling	°CDB		°CDB		
	Heating	°CDB		°CDB		
Refrigerant	Type (Global Warming Potential)	R410A (2,088)		R410A (2,088)		
	Charge	kg (CO2eq-T)		kg (CO2eq-T)		


## Splittable, lightweight, and compact design

The indoor unit can be split into a fan unit and a heat exchanger unit to make installation easier.



## Quiet operation

The combination of a V-shaped heat exchanger, an air stabilizer, and a high-efficiency DC fan motor enables this compact unit to operate quietly.



## Automatic airflow adjustment function

The optimum airflow can be set automatically to facilitate faster installation.

Automatically adjust!



Static pressure  
**??? Pa**  
It was necessary to calculate

## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.




### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	WLAN adapter:	UTY-TFSXZ1	Network Converter for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RCRGZ1		FG-RC-WIF1Z2	Network Converter for single split (AC power supply type):	UTY-VTGV
Wired remote controller (touch panel):	UTY-RNRGZ5		UTY-TFSXJ3	IR receiver unit:	UTY-LBTGM
Wired remote controller:	UTY-RLRG		FG-AC-WIF1Z1		UTY-LRHGM
	UTY-RNNGM	External input and output PCB:	UTY-XCSX	Silver Ion Filter:	UTD-HFKA
	UTY-RVNGM	Remote sensor unit:	UTY-XSZXZ1		
Simple remote controller (without operation mode):	UTY-RHRG	Long-life filter:	UTD-LFKA	(Outdoor unit)	
Simple remote controller:	UTY-RSRG	External connect kit:	UTY-XWZXZG	External connect kit:	UTY-XWZXZ3
External switch controller:	UTY-TERX	Drain pump unit:	UTZ-PX1NAB		

### Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

# Floor Compact Size



Model: AGHG09KVCA / AGHG12KVCA / AGHG14KVCA



Wireless RC




For AGHG09/12KVCA For AGHG14KVCA

### Specifications

Model name	Indoor unit		AGHG09KVCA		AGHG12KVCA		AGHG14KVCA			
	Outdoor unit		AOHG09KVCA		AOHG12KVCA		AOHG14KVCA			
Power Source			Single phase, ~230 V, 50 Hz							
Capacity	Cooling	Rated	2.5		3.5		4.2			
		Min.-Max.	0.9-3.5		0.9-4.0		0.9-5.2			
	Heating	Rated	3.5		4.5		5.2			
Min.-Max.		0.9-5.1		0.9-5.3		0.9-6.3				
Input Power	Cooling/Heating		kW		0.53/0.81		0.88/1.22		1.06/1.41	
EER	Cooling		W/W		4.70		4.00		3.95	
COP	Heating		W/W		4.30		3.70		3.70	
Pdesign	Cooling/Heating (-10°C)		kW		2.50/2.60		3.50/3.50		4.20/4.20	
SEER	Cooling		W/W		8.50		8.20		8.10	
SCOP	Heating (Average)		W/W		4.30		4.10		4.00	
Energy Efficiency Class	Cooling		A+++		A++		A+		A+	
	Heating (Average)		A+		A+		A+		A+	
Max. Operating Current	Cooling/Heating		A		7.0/8.5		7.0/8.5		11.0/12.0	
Annual Energy Consumption	Cooling		kWh/a		103		149		181	
	Heating (Average)		kWh/a		845		1,192		1,466	
Moisture Removal	Cooling		l/h		1.3		1.8		2.1	
	Heating		l/h		1.3		1.8		2.1	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	40/35/29/22		40/35/29/22		44/38/31/22			
	Indoor (Heating)	H/M/L/Q	41/35/29/22		41/35/29/22		43/37/29/22			
Sound Power Level	Outdoor (Cooling/Heating)	High	dB(A)		43/47		45/51		51/50	
	Indoor (Cooling/Heating)	High	53/54		53/54		57/56			
	Outdoor (Cooling/Heating)	High	58/61		61/64		63/63			
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h		570/1,530		570/1,530		650/2,210	
	Indoor/Outdoor (Heating)	High	600/1,510		600/1,510		650/2,100			
Net Dimensions H x W x D	Indoor	mm	600 x 740 x 200		600 x 740 x 200		600 x 740 x 200			
	Outdoor	mm	542 x 799 x 290		542 x 799 x 290		632 x 799 x 290			
Weight	Indoor	kg	14		14		14			
	Outdoor	kg	31		31		38			
Connection Pipe Diameter (Liquid/Gas)			mm		6.35/9.52		6.35/9.52		6.35/9.52	
Drain Hose Diameter (I.D./O.D.)			mm		13.8/15.8 to 16.7		13.8/15.8 to 16.7		13.8/15.8 to 16.7	
Max. Pipe Length (Pre-Charge)			m		20 (15)		20 (15)		20 (15)	
Max. Height Difference			m		15		15		15	
Operating Range	Cooling	°CDB	-10 to 46		-10 to 46		-10 to 46			
	Heating	°CDB	-15 to 24		-15 to 24		-15 to 24			
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)		R32 (675)			
	Charge	kg (CO2eq-T)	0.85 (0.574)		0.85 (0.574)		0.94 (0.635)			


### High energy saving

The Floor 09 class achieves a top-class SEER of 8.50 and an A+++ seasonal efficiency rank for cooling. The Floor 09 class achieves an improved SCOP of 4.30 and an A+ seasonal efficiency rank for heating.



### Flexible & easy installation


The compact and whole-surface suction design provides flexible installation options, including floor-standing, embedded, half concealed, and wall mount installation to match the room layout.



\* Concave position installation with concealment is prohibited.

### Low ambient operation

Factory-guaranteed cooling operation down to -10°C ambient temperature.



### Smart device control (option)


With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* See page C-020 for details on smart device control.



### 10°C heat

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied.




### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.


Wired Remote Controller (Design type): UTY-RVRG	External switch controller: UTY-TERX	Network Converter for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRGZ1	WLAN adapter: UTY-TFSXZ1	Network Converter for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel): UTY-RNRGZ5	FG-AC-WIF1Z1	Silver Ion Filter: UTR-FA03-5
Wired remote controller: UTY-RLRG	UTY-TFSXJ3	External connect kit: UTY-XWZX25
Simple remote controller (without operation mode): UTY-RHRG	Half concealed kit: UTR-STA	
Simple remote controller: UTY-RSRG	Communication kit: UTY-TWRXZ3	

### Dimensions

(Unit: mm)



# Ceiling




## Light elegant design

The light-elegant, gently curved surface gives a sense of comfort and well-being.



## Easy installation

The indoor unit can be easily installed under the ceiling thanks to the uniquely designed mounting kit.



## Easy maintenance

The front panel can be opened without removing it for safe & speedy maintenance.



The drain pan can be removed for cleaning.



Components in the control box can be easily accessed from the wide side opening.



## Flexible installation

The drain hose and pipe can be contained in the casing and connected in the right, left, angled, or downward direction.



## Link up with a variety of central control system (option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ABHG18KRTA / ABHG22KRTA / ABHG24KRTA / ABHG30KRTA / ABHG36KRTA / ABHG45KRTA  
ABHG36KRTA [3-phase] / ABHG45KRTA [3-phase] / ABHG54KRTA [3-phase]



## Specifications

Model name	Indoor unit						Outdoor unit				
	ABHG18KRTA	ABHG22KRTA	ABHG24KRTA	ABHG30KRTA	ABHG36KRTA	ABHG45KRTA	AOHG36KRTB	AOHG45KRTB	AOHG54KRTB		
Power Source	Single phase, ~230 V, 50 Hz						3-phase, ~400 V, 50 Hz				
Capacity	Cooling	Rated	5.2	6.0	6.8	8.5	9.5	12.1	9.5	12.1	13.4
		Min.-Max.	0.9-5.9	0.9-6.7	0.9-8.0	2.8-10.0	2.8-11.2	4.0-13.5	2.8-11.2	4.0-13.5	4.5-14.5
	Heating	Rated	6.0	7.0	7.5	10.0	10.8	13.5	10.8	13.5	15.5
Input Power	Cooling/Heating	Min.-Max.	0.9-7.5	0.9-8.0	0.9-9.1	2.7-11.2	2.7-12.7	4.2-16.2	2.7-12.7	4.2-16.2	4.7-16.5
		Min.-Max.	1.55/1.62	1.87/1.95	2.14/1.97	2.65/2.77	2.96/2.88	4.22/3.84	2.96/2.88	4.22/3.84	4.45/4.43
EER	Cooling	W/W	3.35	3.21	3.18	3.21	3.21	2.87	3.21	2.87	3.01
COP	Heating	W/W	3.70	3.59	3.81	3.61	3.75	3.52	3.75	3.52	3.50
Pdesign	Cooling/Heating (-10°C)	kW	5.2/4.4	6.0/4.8	6.8/6.0	8.5/8.0	9.5/8.7	-	9.5/8.7	-	-
SEER	Cooling	W/W	6.2	6.1	6.2	6.1	6.37	-	6.37	-	-
SCOP	Heating (Average)	W/W	4.1	4.0	4.1	4.0	4.21	-	4.21	-	-
Energy Efficiency Class	Cooling		A++	A++	A++	A++	A++	-	A++	-	-
	Heating (Average)		A+	A+	A+	A+	A+	-	A+	-	-
Max. Operating Current	Cooling/Heating	A	12.1/12.1	12.6/12.6	13.6/13.6	22.6/22.6	22.6/22.6	28.5/28.5	10.5/10.5	14.0/14.0	14.0/14.0
Annual Energy Consumption	Cooling	kWh/a	293	344	384	486	524	-	524	-	-
	Heating	kWh/a	1,501	1,677	2,042	2,796	2,904	-	2,904	-	-
Moisture Removal		l/h	2.0	2.5	2.2	3.0	2.6	4.5	2.6	4.5	5.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/36/33/31	42/37/34/31	41/36/32/29	45/40/35/32	44/40/37/32	45/41/39/34	44/40/37/32	45/41/39/34	48/44/41/38
	Indoor (Heating)	H/M/L/Q	38/36/33/31	42/37/34/31	41/36/32/29	45/40/35/32	44/40/37/32	45/41/39/34	44/40/37/32	45/41/39/34	48/44/41/38
Sound Power Level	Outdoor (Cooling/Heating)	High	50/50	51/51	53/54	53/55	55/55	57/57	55/55	57/57	57/59
	Indoor (Cooling/Heating)	High	53/53	57/57	56/56	60/60	59/59	60/60	59/59	60/60	63/63
Airflow Rate	Indoor/Outdoor (Cooling)	High	840/2,160	900/2,240	1,230/2,700	1,400/3,750	1,850/3,750	1,900/4,450	1,850/3,750	1,900/4,450	2,100/4,450
	Indoor/Outdoor (Heating)	High	840/1,830	900/1,960	1,230/2,700	1,400/3,750	1,800/3,750	1,850/4,450	1,800/3,750	1,850/4,450	2,100/4,450
Net Dimensions	Indoor	mm	235 × 1,080 × 705	235 × 1,080 × 705	235 × 1,390 × 705	235 × 1,390 × 705	235 × 1,700 × 705	235 × 1,700 × 705	235 × 1,700 × 705	235 × 1,700 × 705	235 × 1,700 × 705
	Outdoor	mm	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320	998 × 940 × 320
Weight	Indoor	kg	24	24	31	31	38	38	38	38	38
	Outdoor	kg	36	38	42	52	52	67	53	67	67
Connection Pipe Diameter (Liquid/Gas)	Indoor	mm	6.35/12.7	6.35/12.7	6.35/12.7	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
	Outdoor	mm	25/32	25/32	25/32	25/32	25/32	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m	30 (20)	30 (20)	30 (20)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)
Max. Height Difference		m	20	25	25	30	30	30	30	30	30
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)	1.90 (1.283)	1.90 (1.283)	2.70 (1.823)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)


## Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRG	WLAN adapter:	UTY-TFSXZ1	Network Converter for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RCRGZ1		UTY-TFSXJ3	Network Converter for single split (AC power supply type):	UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRGZ5		FG-AC-WIF121	External switch controller:	UTY-TERX
Wired remote controller:	UTY-RLRG	Drain pump unit:	UTR-DPB24T	External connect kit:	UTY-XWZXZG
Simple remote controller (without operation mode):	UTY-RHRG	IR receiver unit:	UTY-LBTGH		
Simple remote controller:	UTY-RSRG	L-type piping kit:	UTP-FX24A (18/22/24)	(Outdoor unit 30/36/45/54)	
External input and output PCB:	UTY-XCSX		UTP-FX35A (30/36/45/54)	External connect kit:	UTY-XWZXZ3
External input and output PCB box:	UTZ-GXEA	Communication kit:	UTY-TWRXZ3		

## Dimensions

(Unit: mm)



	ABHG 18/22KRTA	ABHG 24/30KRTA	ABHG 36/45/54 KRTA
a	1,080	1,390	1,700
b	923	1,233	1,543



# Wall-mounted Specifications

## Designer Series High-Spec & Design (WLAN adapter Internal Models)

Model name	Indoor unit		ASHG07KGTF	ASHG09KGTF	ASHG12KGTF	ASHG14KGTF	
	Outdoor unit		AOHG07KGCB	AOHG09KGCB	AOHG12KGCB	AOHG14KGCB	
Power Source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2	
		Min.-Max.	0.9-3.2	0.9-3.4	0.9-4.1	0.9-4.5	
	Heating	Rated	2.5	2.8	4.0	5.4	
		Min.-Max.	0.9-5.2	0.9-5.4	0.9-6.1	0.9-6.4	
Input Power	Cooling/Heating		kW	0.400/0.500	0.555/0.560	0.805/0.910	1.175/1.350
EER	Cooling		W/W	5.00	4.50	4.22	3.57
COP	Heating		W/W	5.00	5.00	4.40	4.00
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0
SEER	Cooling		W/W	8.10	8.90	8.70	7.90
SCOP	Heating (Average)		W/W	5.30	5.20	5.20	4.50
Energy Efficiency Class	Cooling			A++	A+++	A+++	A++
	Heating (Average)			A+++	A+++	A+++	A+
Max. Operating Current	Cooling/Heating		A	6.5/9.0	6.5/9.0	6.5/9.0	9.0/10.5
Annual Energy Consumption	Cooling		kWh/a	86	98	137	186
	Heating		kWh/a	606	645	673	1,242
Moisture Removal			l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	38/33/29/19	40/34/29/19	40/35/30/19	43/36/30/20
	Indoor (Heating)	H/M/L/Q		41/35/31/21	42/36/31/21	42/38/33/21	44/39/33/24
Outdoor (Cooling/Heating)	High	46/46		46/48	50/50	50/50	
Indoor (Cooling/Heating)	High	54/56		55/57	56/58	57/59	
Sound Power Level	Outdoor (Cooling/Heating)	High	61/62	61/63	65/66	65/66	
	Indoor/Outdoor (Cooling)	High	650/1,610	700/1,610	700/1,680	770/1,680	
Airflow Rate	Indoor/Outdoor (Heating)	High	720/1,560	750/1,610	770/1,580	800/1,580	
	Indoor	mm	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	
Net Dimensions H x W x D	Outdoor	mm	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290	
	Indoor	kg	10	10	10	10	
Weight	Indoor	kg	30	30	31	32	
	Outdoor	kg	30	30	31	32	
Connection Pipe Diameter (Liquid/Gas)			mm	6.35/9.52			
Drain Hose Diameter (I.D./O.D.)			mm	13.8/15.0 to 16.8			
Max. Pipe Length (Pre-Charge)			m	20 (15)			
Max. Height Difference				15			
Operating Range	Cooling		°CDB	-10 to 46			
	Heating		°CDB	-15 to 24			
Refrigerant	Type (Global Warming Potential)			R32 (675)			
	Charge	kg (CO2eq-T)		0.75 (0.506)	0.75 (0.506)	0.85 (0.574)	0.85 (0.574)

## Designer Series High Spec & Design (WLAN adapter Option Models)

Model name	Indoor unit		ASHG07KGTE	ASHG09KGTE	ASHG12KGTE	ASHG14KGTE	
	Outdoor unit		AOHG07KGCA	AOHG09KGCA	AOHG12KGCA	AOHG14KGCA	
Power Source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2	
		Min.-Max.	0.9-3.2	0.9-3.4	0.9-4.1	0.9-4.5	
	Heating	Rated	2.5	2.8	4.0	5.4	
		Min.-Max.	0.9-5.2	0.9-5.4	0.9-6.1	0.9-6.4	
Input Power	Cooling/Heating		kW	0.400/0.500	0.555/0.560	0.805/0.910	1.175/1.350
EER	Cooling		W/W	5.00	4.50	4.22	3.57
COP	Heating		W/W	5.00	5.00	4.40	4.00
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0
SEER	Cooling		W/W	9.10	9.20	9.20	8.30
SCOP	Heating (Average)		W/W	5.30	5.20	5.20	4.50
Energy Efficiency Class	Cooling			A+++	A+++	A+++	A++
	Heating (Average)			A+++	A+++	A+++	A+
Max. Operating Current	Cooling/Heating		A	6.5/9.0	6.5/9.0	6.5/9.0	9.0/10.5
Annual Energy Consumption	Cooling		kWh/a	77	95	129	177
	Heating		kWh/a	607	645	672	1,242
Moisture Removal			l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	38/33/29/19	40/34/29/19	40/35/30/19	43/36/30/20
	Indoor (Heating)	H/M/L/Q		41/35/31/21	42/36/31/21	42/38/33/21	44/39/33/24
Outdoor (Cooling/Heating)	High	46/46		46/48	50/50	50/50	
Indoor (Cooling/Heating)	High	54/56		55/57	56/58	57/59	
Sound Power Level	Outdoor (Cooling/Heating)	High	61/62	61/63	65/66	65/66	
	Indoor/Outdoor (Cooling)	High	650/1,610	700/1,610	700/1,680	770/1,680	
Airflow Rate	Indoor/Outdoor (Heating)	High	720/1,560	750/1,610	770/1,580	800/1,580	
	Indoor	mm	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	
Net Dimensions H x W x D	Outdoor	mm	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290	
	Indoor	kg	10	10	10	10	
Weight	Indoor	kg	30	30	31	32	
	Outdoor	kg	30	30	31	32	
Connection Pipe Diameter (Liquid/Gas)			mm	6.35/9.52			
Drain Hose Diameter (I.D./O.D.)			mm	13.8/15.0 to 16.8			
Max. Pipe Length (Pre-Charge)			m	20 (15)			
Max. Height Difference				15			
Operating Range	Cooling		°CDB	-10 to 46			
	Heating		°CDB	-15 to 24			
Refrigerant	Type (Global Warming Potential)			R32 (675)			
	Charge	kg (CO2eq-T)		0.75 (0.506)	0.75 (0.506)	0.85 (0.574)	0.85 (0.574)

**Designer Series**  
Cool Beauty Design



Model name	Indoor unit		ASHG07KETE ASHG07KETE-B	ASHG09KETE ASHG09KETE-B	ASHG12KETE ASHG12KETE-B	ASHG14KETE ASHG14KETE-B
	Outdoor unit		AOHG07KETA	AOHG09KETA	AOHG12KETA	AOHG14KETA
Power Source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2
		Min.-Max.	0.9 - 3.0	0.9 - 3.2	0.9 - 3.9	0.9 - 4.4
Capacity	Heating	Rated	2.5	2.8	4.0	5.4
		Min.-Max.	0.9 - 3.4	0.9 - 4.0	0.9 - 5.3	0.9 - 6.0
Input Power	Cooling/Heating		0.450/0.555	0.630/0.620	0.935/0.960	1.220/1.410
EER	Cooling		4.43	3.97	3.65	3.44
COP	Heating		4.52	4.52	4.17	3.83
Pdesign	Cooling/Heating (-10°C)		2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0
SEER	Cooling		7.40	7.40	7.30	6.90
SCOP	Heating (Average)		4.10	4.10	4.40	4.10
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+
Max. Operating Current	Cooling/Heating		6.5/9.0	6.5/9.0	6.5/9.0	6.5/9.0
Annual Energy Consumption	Cooling		95	118	163	213
	Heating		785	819	795	1,367
Moisture Removal			1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/33/29/20	40/34/29/20	40/35/30/20	43/36/30/20
	Indoor (Heating)	H/M/L/Q	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Outdoor (Cooling/Heating)	High	46/46	46/46	50/50	50/50
	Indoor (Cooling/Heating)	High	54/56	55/57	55/58	57/59
Airflow Rate	Indoor/Outdoor (Cooling)	High	650/1,650	700/1,650	700/1,700	770/1,680
	Indoor/Outdoor (Heating)	High	720/1,450	750/1,450	770/1,470	800/1,580
Net Dimensions	Indoor		295 × 950 (wall side: 840) × 230			
H x W x D	Outdoor		541 × 663 × 290	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290
	Indoor		11	11	11	11.5
Weight	Indoor		23	23	25	31
	Outdoor		11	11	11	11.5
Connection Pipe Diameter (Liquid/Gas)			6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
Drain Hose Diameter (I.D./O.D.)			13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8
Max. Pipe Length (Pre-Charge)			20 (15)	20 (15)	20 (15)	20 (15)
Max. Height Difference			15	15	15	15
Operating Range	Cooling		-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.6 (0.405)	0.6 (0.405)	0.7 (0.473)	0.85 (0.574)

**Standard Series**  
High-Efficiency & Comfort



Model name	Indoor unit	W-LAN Adapter Internal Models	ASHG07KMCF	ASHG09KMCF	ASHG12KMCF	ASHG14KMCF
		W-LAN Adapter Option Models	ASHG07KMCE	ASHG09KMCE	ASHG12KMCE	ASHG14KMCE
		Outdoor unit	AOHG07KMCC	AOHG09KMCC	AOHG12KMCC	AOHG14KMCC
Power Source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2
		Min.-Max.	0.9-3.0	0.9-3.2	0.9-3.9	0.9-4.4
Capacity	Heating	Rated	2.5	2.8	4.0	5.4
		Min.-Max.	0.9-3.4	0.9-4.0	0.9-5.3	0.9-6.0
Input Power	Cooling/Heating		0.450/0.555	0.630/0.620	0.935/0.960	1.220/1.410
EER	Cooling		4.43	3.97	3.65	3.44
COP	Heating		4.52	4.52	4.17	3.83
Pdesign	Cooling/Heating (-10°C)		2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0
SEER	Cooling		7.40	7.40	7.30	6.90
SCOP	Heating (Average)		4.10	4.10	4.40	4.10
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+
Max. Operating Current	Cooling/Heating		6.5/9.0	6.5/9.0	6.5/9.0	6.5/9.0
Annual Energy Consumption	Cooling		95	118	163	213
	Heating		785	819	795	1,367
Moisture Removal			1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/33/29/20	40/34/29/20	40/35/30/20	43/36/30/20
	Indoor (Heating)	H/M/L/Q	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Outdoor (Cooling/Heating)	High	46/46	46/46	50/50	50/50
	Indoor (Cooling/Heating)	High	54/56	55/57	55/58	57/59
Airflow Rate	Indoor/Outdoor (Cooling)	High	650/1,650	700/1,650	700/1,700	770/1,680
	Indoor/Outdoor (Heating)	High	720/1,450	750/1,450	780/1,470	820/1,580
Net Dimensions	Indoor		270 × 834 × 222			
H x W x D	Outdoor		541 × 663 × 290	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290
	Indoor		10	10	10	10
Weight	Indoor		22	22	24	31
	Outdoor		11	11	11	11.5
Connection Pipe Diameter (Liquid/Gas)			6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
Drain Hose Diameter (I.D./O.D.)			13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8
Max. Pipe Length (Pre-Charge)			20 (15)	20 (15)	20 (15)	20 (15)
Max. Height Difference			15	15	15	15
Operating Range	Cooling		-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.6 (0.405)	0.6 (0.405)	0.7 (0.473)	0.85 (0.574)

**ECO Series Lineup**  
Specifications





Compact Cassette



Model name	Indoor unit			AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA
	Outdoor unit			AOHG09KATA	AOHG12KATA	AOHG14KATA	AOHG18KATA	AOHG22KATA	AOHG24KATA
Power Source	Single phase, ~230 V, 50 Hz								
Capacity	Cooling	Rated	kW	2.5	3.5	4.3	5.2	6.0	6.8
		Min.-Max.		0.9-2.7	0.9-3.7	0.9-4.5	0.9-5.4	0.9-6.3	0.9-7.4
	Rated	3.2		4.1	5.0	6.0	7.0	7.5	
	Min.-Max.	0.9-3.9		0.9-4.4	0.9-5.3	0.9-6.3	0.9-7.4	0.9-8.6	
Input Power	Cooling/Heating		kW	0.68/0.88	1.09/1.17	1.37/1.42	1.69/1.72	1.95/2.00	2.26/2.08
	Cooling	W/W		3.68	3.21	3.14	3.08	3.08	3.01
EER	Cooling/Heating		W/W	3.64	3.50	3.52	3.49	3.50	3.61
	Heating								
Pdesign	Cooling/Heating (-10°C)		kW	2.5/2.3	3.5/2.8	4.3/3.2	5.2/3.8	6.0/4.4	6.8/5.4
	Cooling	W/W		6.2	6.1	6.1	6.1	6.1	5.9
SEER	Cooling/Heating		W/W	4.0	4.0	4.0	3.9	3.9	3.8
	Heating								
Energy Efficiency Class	Cooling		Class	A++	A++	A++	A++	A++	A+
	Heating			A+	A+	A+	A	A	A
Max. Operating Current	Cooling/Heating		A	6.9/6.9	7.7/7.7	9.2/9.2	10.1/10.1	11.6/11.6	12.6/12.6
	Cooling	kWh/a		141	201	247	298	344	403
Annual Energy Consumption	Cooling/Heating		kWh/a	804	979	1,120	1,362	1,578	1,988
	Heating								
Moisture Removal			l/h	0.6	1.2	1.5	2.2	2.6	2.7
	Indoor (Cooling)	H/M/L/Q		33/31/29/27	37/34/30/27	38/34/30/27	38/34/30/26	44/42/36/30	49/44/36/30
Sound Pressure Level	Indoor (Heating)	H/M/L/Q	dB(A)	34/32/29/27	37/34/31/29	43/38/34/30	43/38/34/30	45/43/40/33	49/45/40/33
	Outdoor (Cooling/Heating)	High		47/48	49/50	50/51	51/52	52/53	54/55
	Indoor (Cooling/Heating)	High		46/47	49/49	50/55	50/55	56/57	59/61
	Outdoor (Cooling/Heating)	High		60/60	62/62	63/63	63/64	64/65	66/67
Airflow Rate	Indoor/Outdoor (Cooling)	High	m <sup>3</sup> /h	540/1,610	600/1,630	680/1,670	680/1,710	830/2,240	930/2,885
	Indoor/Outdoor (Heating)	High		540/1,550	600/1,410	800/1,580	800/1,840	860/2,240	930/2,350
Net Dimensions H x W x D	Indoor	mm	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570
	Outdoor	mm	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	632 × 799 × 290
Weight	Indoor	kg	15	15	15	15	16	16	16
	Outdoor	kg	23	25	32	33	36	38	38
Connection Pipe Diameter (Liquid/Gas)			mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70	6.35/12.70
Drain port Diameter (I.D./O.D.)			mm	25/32	25/32	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)			m	15 (15)	15 (15)	20 (15)	20 (15)	25 (15)	25 (20)
Max. Height Difference			m	15	15	15	15	20	20
Operating Range	Cooling	°CDB		-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating			-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		kg (CO2eq-T)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge			0.6 (0.405)	0.7 (0.473)	0.85 (0.574)	0.9 (0.608)	1.1 (0.743)	1.25 (0.844)
Cassette Grille	Model name			UTG-UKGA-W: White wired remote controller (touch panel)					
	Dimensions (H × W × D)			mm					
	Weight			kg					

Circular Cassette (Large type)



Model name	Indoor unit			AUXG30KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB
	Outdoor unit			AOHG30KATA	AOHG36KATA	AOHG45KATA	AOHG54KATA	AOHG36KQTA	AOHG45KQTA	AOHG54KQTA
Power Source	Single phase, ~230 V, 50 Hz							3-phase, ~400 V, 50 Hz		
Capacity	Cooling	Rated	kW	8.5	9.5	12.1	13.4	9.5	12.1	13.4
		Min.-Max.		2.8-9.6	2.8-10.6	4.0-12.6	4.5-13.8	2.8-10.6	4.0-12.6	4.5-13.8
	Rated	10.0		10.8	13.5	13.7	10.8	13.5	13.7	
	Min.-Max.	2.7-10.8		2.7-12.5	4.2-15.0	4.7-16.0	2.7-12.5	4.2-15.0	4.7-16.0	
Input Power	Cooling/Heating		kW	2.56/2.64	3.06/2.58	4.32/3.77	4.87/4.86	3.06/2.58	4.32/3.77	4.87/4.86
	Cooling	W/W		3.32	3.10	2.80	2.75	3.10	2.80	2.75
EER	Cooling/Heating		W/W	3.79	4.19	3.58	3.19	4.19	3.58	3.19
	Heating									
Pdesign	Cooling/Heating (-10°C)		kW	8.5/8.0	9.5/8.7	-	-	9.5/8.7	-	-
	Cooling	W/W		6.1	6.1	-	-	6.1	-	-
SEER	Cooling/Heating		W/W	4.0	4.0	-	-	4.0	-	-
	Heating									
Energy Efficiency Class	Cooling		Class	A++	A++	-	-	A++	-	-
	Heating			A+	A+	-	-	A+	-	-
Max. Operating Current	Cooling/Heating		A	22.5/22.5	22.5/22.5	28.1/28.1	28.1/28.1	10.5/10.5	13.6/13.6	13.6/13.6
	Cooling	kWh/a		488	545	-	-	545	-	-
Annual Energy Consumption	Cooling/Heating		kWh/a	2,794	3,044	-	-	3,044	-	-
	Heating									
Moisture Removal			l/h	2.5	3.3	4.5	5.0	3.3	4.5	5.0
	Indoor (Cooling)	H/M/L/Q		40/38/36/33	44/41/38/34	46/42/39/35	47/43/40/36	44/41/38/34	46/42/39/35	47/43/40/36
Sound Pressure Level	Indoor (Heating)	H/M/L/Q	dB(A)	40/38/36/33	44/41/38/34	46/42/39/35	47/43/40/36	44/41/38/34	46/42/39/35	47/43/40/36
	Outdoor (Cooling/Heating)	High		53/55	55/55	58/59	58/61	55/55	60/60	61/61
	Indoor (Cooling/Heating)	High		54/54	58/58	60/60	61/61	58/58	-/-	-/-
	Outdoor (Cooling/Heating)	High		68/69	70/70	72/73	74/75	70/70	72/73	74/75
Airflow Rate	Indoor/Outdoor (Cooling)	High	m <sup>3</sup> /h	1,600/3,750	1,870/3,750	2,000/4,450	2,100/4,450	1,870/3,750	2,000/4,450	2,100/4,450
	Indoor/Outdoor (Heating)	High		1,600/3,750	1,870/3,750	2,000/4,450	2,100/4,780	1,870/3,750	2,000/4,450	2,100/4,780
Net Dimensions H x W x D	Indoor	mm	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840
	Outdoor	mm	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320	998 × 940 × 320	998 × 940 × 320
Weight	Indoor	kg	26	29	29	29	29	29	29	29
	Outdoor	kg	52	52	61	63	53	62	63	
Connection Pipe Diameter (Liquid/Gas)			mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain port Diameter (I.D./O.D.)			mm	25/32	25/32	25/32	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)			m	30 (30)	30 (30)	30 (30)	30 (30)	30 (30)	30 (30)	30 (30)
Max. Height Difference			m	30	30	30	30	30	30	30
Operating Range	Cooling	°CDB		-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating			-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		kg (CO2eq-T)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge			1.90 (1.283)	1.90 (1.283)	2.4 (1.620)	2.4 (1.620)	1.90 (1.283)	2.4 (1.620)	2.4 (1.620)
Cassette Grille	Model name			UTG-UKGA-W: White wired remote controller (touch panel)						
	Dimensions (H × W × D)			mm						
	Weight			kg						

\*1: IR Receiver kit and Human sensor kit cannot be connected.

Circular Cassette (Slim type)



Model name	Indoor unit			AUXG18KRLB	AUXG22KRLB	AUXG24KRLB
	Outdoor unit			AOHG18KATA	AOHG22KATA	AOHG24KATA
Power Source	Single phase, ~230 V, 50 Hz					
Capacity	Cooling	Rated	kW	5.2	6.0	6.8
		Min.-Max.		0.9-5.4	0.9-6.3	0.9-7.4
	Rated	6.0		7.0	7.5	
	Min.-Max.	0.9-6.3		0.9-7.4	0.9-8.6	
Input Power	Cooling/Heating		kW	1.60/1.66	1.85/1.93	2.12/1.97
	Cooling	W/W		3.25	3.24	3.21
EER	Cooling/Heating		W/W	3.61	3.63	3.81
	Heating					
Pdesign	Cooling/Heating (-10°C)		kW	5.2/3.8	6.0/4.4	6.8/5.4
	Cooling	W/W		6.2	6.2	6.1
SEER	Cooling/Heating		W/W	4.1	4.1	4.0
	Heating					
Energy Efficiency Class	Cooling		Class	A++	A++	A++
	Heating			A+	A+	A+
Max. Operating Current	Cooling/Heating		A	10.1/10.1	11.6/11.6	12.6/12.6
	Cooling	kWh/a		293	338	390
Annual Energy Consumption	Cooling/Heating		kWh/a	1,297	1,502	1,887
	Heating					
Moisture Removal			l/h	1.5	2.2	2.7
	Indoor (Cooling)	H/M/L/Q		33/32/31/28	33/32/31/28	35/33/27/29
Sound Pressure Level	Indoor (Heating)	H/M/L/Q	dB(A)	33/32/31/28	33/32/31/28	35/33/27/29
	Outdoor (Cooling/Heating)	High		51/52	52/53	54/55
	Indoor (Cooling/Heating)	High		47/47	49/49	49/49
	Outdoor (Cooling/Heating)	High		63/64	64/65	66/67
Airflow Rate	Indoor/Outdoor (Cooling)	High	m <sup>3</sup> /h	1,050/1,710	1,050/2,240	1,150/2,895
	Indoor/Outdoor (Heating)	High		1,050/1,840	1,050/2,240	1,150/2,350
Net Dimensions H x W x D	Indoor	mm	246 × 840 × 840	246 × 840 × 840	246 × 840 × 840	
	Outdoor	mm	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	
Weight	Indoor	kg	23	24	24	
	Outdoor	kg	33	36	38	
Connection Pipe Diameter (Liquid/Gas)			mm	6.35/12.70	6.35/12.70	6.35/12.70
Drain port Diameter (I.D./O.D.)			mm	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)			m	20 (15)	25 (15)	25 (20)
Max. Height Difference			m	15	20	20
Operating Range	Cooling	°CDB		-10 to 46	-10 to 46	-10 to 46
	Heating			-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		kg (CO2eq-T)	R32 (675)	R32 (675)	R32 (675)
	Charge			0.9 (0.608)	1.1 (0.743)	1.25 (0.844)
Cassette Grille	Model name			UTG-UKGA-W: White wired remote controller (touch panel)		
	Dimensions (H × W × D)			mm		
	Weight			kg		

\*1: IR Receiver kit and Human sensor kit cannot be connected.

Slim Duct



Model name	Indoor unit			ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP
	Outdoor unit			AOHG09KATA	AOHG12KATA	AOHG14KATA	AOHG18KATA

Medium Static Pressure Duct (High-Efficiency & Comfort)



Model name	Indoor unit		ARXH12KMTAP	ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	ARXH24KMTAP
	Outdoor unit		AOHG12KATA	AOHG14KATA	AOHG18KATA	AOHG22KATA	AOHG24KATA
Power Source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling	Rated	3.5	4.3	5.2	6.0	6.8
		Min.-Max.	0.9-3.7	0.9-4.5	0.9-5.4	0.9-6.3	0.9-7.4
Capacity	Heating	Rated	4.1	5.0	6.0	7.0	7.5
		Min.-Max.	0.9-4.4	0.9-5.3	0.9-6.3	0.9-7.4	0.9-8.6
Input Power	Cooling/Heating	kW	1.060 / 1.170	1.340 / 1.420	1.730 / 1.820	1.85 / 1.97	2.06 / 1.97
EER	Cooling	W/W	3.30	3.21	3.00	3.24	3.30
COP	Heating	W/W	3.50	3.52	3.30	3.55	3.81
Pdesign	Cooling/Heating (-10°C)	kW	3.5 / 2.8	4.3 / 3.2	5.2 / 3.8	6.0 / 4.4	6.8 / 5.4
SEER	Cooling	W/W	6.00	5.80	5.90	6.00	6.00
SCOP	Heating (Average)	W/W	3.90	3.90	3.90	3.90	3.90
Energy Efficiency Class	Cooling		A+	A+	A+	A+	A+
	Heating (Average)		A	A	A	A	A
Max. Operating Current	Cooling/Heating	A	7.7 / 7.7	9.2 / 9.2	10.1 / 10.1	11.6 / 11.6	12.6 / 12.6
Annual Energy Consumption	Cooling	kWh/a	212	267	316	358	405
	Heating	kWh/a	1,005	1,148	1,363	1,578	1,936
Moisture Removal		l/h	1.3	1.3	2.0	1.5	2.2
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24	34 / 30 / 28 / 26
	Indoor (Heating)	H/M/L/Q	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24	34 / 30 / 28 / 26
Sound Power Level	Outdoor (Cooling/Heating)	High	49 / 50	50 / 51	51 / 52	52 / 53	54 / 55
	Indoor (Cooling/Heating)	High	58 / 58	59 / 59	60 / 60	58 / 58	60 / 60
Sound Power Level	Outdoor (Cooling/Heating)	High	62 / 62	63 / 63	63 / 64	64 / 65	66 / 67
	Indoor/Outdoor (Cooling)	High	650 / 1,630	800 / 1,670	840 / 1,710	1,150 / 2,240	1,230 / 2,885
Airflow Rate	Indoor/Outdoor (Heating)	High	650 / 1,410	800 / 1,580	840 / 1,840	1,150 / 2,240	1,230 / 2,350
Static pressure range (Standard)		Pa	30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (50)
Net Dimensions	Indoor	mm	240 × 700 × 700	240 × 700 × 700	240 × 700 × 700	240 × 1,000 × 700	240 × 1,000 × 700
H x W x D	Outdoor	mm	541 × 663 × 290	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290
Weight	Indoor	kg	24	24	24	31	31
	Outdoor	kg	25	32	33	36	38
Connection Pipe Diameter (Liquid/Gas)		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.70	6.35 / 12.70
Drain Hose Diameter (I.D./O.D.)		mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Max. Pipe Length (Pre-Charge)		m	15 (15)	20 (15)	20 (15)	25 (15)	25 (20)
Max. Height Difference		m	15	15	15	20	20
Operating Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.70 (0.473)	0.85 (0.574)	0.90 (0.608)	1.10 (0.743)	1.25 (0.844)

Medium Static Pressure Duct (High-Efficiency & Comfort)



Model name	Indoor unit		ARXH30KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH36KMTAP	ARXH45KMTAP
	Outdoor unit		AOHG30KATA	AOHG36KATA	AOHG45KATA	AOHG36KQTA	AOHG45KQTA
Power Source	Single phase, ~230 V, 50 Hz					3-phase, ~400 V, 50 Hz	
Capacity	Cooling	Rated	8.5	9.5	12.1	9.5	12.1
		Min.-Max.	2.8-9.6	2.8-10.6	4.0-12.6	2.8-10.6	4.0-12.6
Capacity	Heating	Rated	10.0	10.8	13.5	10.8	13.5
		Min.-Max.	2.7-10.8	2.7-12.5	4.2-15.0	2.7-12.5	4.2-15.0
Input Power	Cooling/Heating	kW	2.69 / 2.63	3.13 / 2.88	4.84 / 4.18	3.13 / 2.88	4.84 / 4.18
EER	Cooling	W/W	3.16	3.04	2.50	3.04	2.50
COP	Heating	W/W	3.80	3.75	3.23	3.75	3.23
Pdesign	Cooling/Heating (-10°C)	kW	8.5 / 8.0	9.5 / 8.7	-	9.5 / 8.7	-
SEER	Cooling	W/W	5.80	5.60	-	5.60	-
SCOP	Heating (Average)	W/W	3.90	3.90	-	3.90	-
Energy Efficiency Class	Cooling		A+	A+	-	A+	-
	Heating (Average)		A	A	-	A	-
Max. Operating Current	Cooling/Heating	A	22.5 / 22.5	22.5 / 22.5	28.1 / 28.1	10.5 / 10.5	13.6 / 13.6
Annual Energy Consumption	Cooling	kWh/a	520	601	-	601	-
	Heating	kWh/a	2,867	3,118	-	3,118	-
Moisture Removal		l/h	1.8	2.0	4.0	2.0	4.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38 / 34 / 31 / 28	38 / 34 / 31 / 28	40 / 36 / 32 / 29	38 / 34 / 31 / 28	40 / 36 / 32 / 29
	Indoor (Heating)	H/M/L/Q	38 / 34 / 31 / 28	38 / 34 / 31 / 28	40 / 36 / 32 / 29	38 / 34 / 31 / 28	40 / 36 / 32 / 29
Sound Power Level	Outdoor (Cooling/Heating)	High	53 / 55	55 / 55	58 / 59	55 / 55	58 / 59
	Indoor (Cooling/Heating)	High	64 / 64	65 / 65	67 / 67	65 / 65	67 / 67
Sound Power Level	Outdoor (Cooling/Heating)	High	68 / 69	70 / 70	72 / 73	68 / 69	72 / 73
	Indoor/Outdoor (Cooling)	High	1,950 / 3,750	2,070 / 3,750	2,160 / 4,450	2,070 / 3,750	2,160 / 4,450
Airflow Rate	Indoor/Outdoor (Heating)	High	1,950 / 3,750	2,070 / 3,750	2,160 / 4,450	2,070 / 3,750	2,160 / 4,450
Static pressure range (Standard)		Pa	30 to 150 (50)	30 to 150 (50)	30 to 150 (60)	30 to 150 (50)	30 to 150 (60)
Net Dimensions	Indoor	mm	240 × 1,400 × 700	240 × 1,400 × 700	240 × 1,400 × 700	240 × 1,400 × 700	240 × 1,400 × 700
H x W x D	Outdoor	mm	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320
Weight	Indoor	kg	42	42	42	42	42
	Outdoor	kg	52	52	61	53	62
Connection Pipe Diameter (Liquid/Gas)		mm	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88	9.52 / 15.88
Drain Hose Diameter (I.D./O.D.)		mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Max. Pipe Length (Pre-Charge)		m	30 (30)	30 (30)	30 (30)	30 (30)	30 (30)
Max. Height Difference		m	30	30	30	30	30
Operating Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	1.90 (1.283)	1.90 (1.283)	2.40 (1.620)	1.90 (1.283)	2.40 (1.620)

Medium Static Pressure Duct (Standard)




























































Model name	Indoor unit		ARXG22KMLB	ARXG24KMLA	ARXG30KMLA	ARXG36KMLA	ARXG45KMLA	ARXG36KMLA	ARXG45KMLA
	Outdoor unit		AOHG22KATA	AOHG24KATA	AOHG30KATA	AOHG36KATA	AOHG45KATA	AOHG36KQTA	AOHG45KQTA
Power Source	Single phase, ~230 V, 50 Hz							3-phase, ~400 V, 50 Hz	
Capacity	Cooling	Rated	6.0	6.8	8.5	9.5	12.1	9.5	12.1
		Min.-Max.	0.9-6.3	0.9-7.4	2.8-9.6	2.8-10.6	4.0-12.6	2.8-10.6	4.0-12.6
Capacity	Heating	Rated	7.0	7.5	10.0	10.8	13.5	10.8	13.5
		Min.-Max.	0.9-7.4	0.9-8.6	2.7-10.8	2.7-12.5	4.2-15.0	2.7-12.5	4.2-15.0
Input Power	Cooling/Heating	kW	1.92/2.00	2.19/2.00	2.78/2.77	3.13/3.03	4.84/4.18	3.13/3.03	4.84/4.18
EER	Cooling	W/W	3.13	3.11	3.06	3.04	2.50	3.04	2.50
COP	Heating	W/W	3.50	3.75	3.61	3.56	3.23	3.56	3.23
Pdesign	Cooling/Heating (-10°C)	kW	6.0/4.4	6.8/5.4	8.5/8.0	9.5/8.7	-	9.5/8.7	-
SEER	Cooling	W/W	5.8	5.9	5.8	5.6	-	5.6	-
SCOP	Heating (Average)	W/W	3.8	3.9	3.9	3.9	-	3.9	-
Energy Efficiency Class	Cooling		A+	A+	A+	A+	-	A+	-
	Heating		A	A	A	A	-	A	-
Max. Operating Current	Cooling/Heating	A	11.6/11.6	12.6/12.6	22.5/22.5	22.5/22.5	28.1/28.1	10.5/10.5	13.6/13.6
Annual Energy Consumption	Cooling	kWh/a	362	403	513	594	-	594	-
	Heating	kWh/a	1,620	1,935	2,871	3,122	-	3,122	-
Moisture Removal		l/h	2.1	2.5	2.5	3.0	4.0	3.0	4.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	31/29/27/25	31/29/27/25	39/35/30/26	39/35/30/26	42/38/32/28	39/35/30/26	42/38/32/28
	Indoor (Heating)	H/M/L/Q	31/29/27/25	31/29/27/25	42/35/30/26	42/35/30/26	42/38/32/28	42/35/30/26	42/38/32/28
Sound Power Level	Outdoor (Cooling/Heating)	High	52/53	54/55	53/55	55/55	58/59	55/55	58/59
	Indoor (Cooling/Heating)	High	60/62	60/62	65/69	65/70	68/70	65/70	68/70
Sound Power Level	Outdoor (Cooling/Heating)	High	64/65	66/67	68/69	70/70	72/73	70/70	72/73
	Indoor/Outdoor (Cooling)	High	1,100/2,240	1,100/2,885	1,900/3,750	1,900/3,750	2,100/4,450	1,900/3,750	2,100/4,450
Airflow Rate	Indoor/Outdoor (Heating)	High	1,100/2,240	1,100/2,350	2,100/3,750	2,100/3,750	2,100/4,450	2,100/3,750	2,100/4,450
Static pressure range (Standard)		Pa	30 - 150 (35)	30 - 150 (35)	30 - 150 (47)	30 - 150 (47)	30 - 150 (60)	30 - 150 (47)	30 - 150 (60)
Net Dimensions	Indoor	mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
H x W x D	Outdoor	mm	632 × 799 × 290	632 × 799 × 290	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320
Weight	Indoor	kg	35	35	38	38	39	38	39
	Outdoor	kg	36	38	52	52	61	53	62
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/12.70	6.35/12.70	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain port Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32	25/32	35/38.1	35/38.1
Max. Pipe Length (Pre-Charge)		m	25 (15)	25 (20)	30 (30)	30 (30)	30 (30)	30 (30)	30 (30)
Max. Height Difference		m	20	20	30	30	30	30	30
Operating Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	1.1 (0.743)	1.25 (0.844)	1.90 (1.283)	1.90 (1.283)	2.4 (1.620)	1.9 (1.283)	2.4 (1.620)

Ceiling



Model name	Indoor unit		ABHG18KRTA	ABHG22KRTA	ABHG24KRTA	ABHG30KRTA	ABHG36KRTA	ABHG45KRTA	ABHG36K
------------	-------------	--	------------	------------	------------	------------	------------	------------	---------

# Feature Summary

Type	Wall-mounted type				Wall-mounted type						
Series	Designer Range		Standard Range		Standard Range		ECO Range				
Model name											
Model name	ASHH07/09/12/14KGTG, ASHG07/09/12/14KGTG, ASHG07/09/12/14KGTG	ASHG07/09/12/14KETF ASHG07/09/12/14KETF-B, ASHG07/09/12/14KETE ASHG07/09/12/14KETE-B	ASHH07/09/12/14KMCG, ASHH07/09/12/14KMCG-B, ASHG07/09/12/14KMCF, ASHG07/09/12/14KMCE		ASHG18/24KMTE	ASHH30/36KMTB	ASHH07/09/12KNCA	ASHG07/09/12KPCE	ASHG18/24KLCA	ASHH07/09/12KLTA	
Model name											
Energy-Saving Features	 Save Human sensor	●					●				
	 Human sensor control										
	 Economy operation	●	●	●		●	●	●	●	●	
	 Setting temperature range limitation	○	○	○		○	○				
	 Set temperature auto return	○	○	○		○	○				
Features for Comfort	 Power diffuser										
	 Powerful operation	●	●	●		●	●	●	●	●	
	 10°C Heat	●	●	●		●	●	●			
	 Outdoor unit low noise operation	●	●	●		●	●				
	 Auto changeover	●	●	●		●	●	●	●	●	
	 UP/DOWN swing louver	●	●	●		●	●	●	●	●	
	 Double swing automatic					●	●				
	 Automatic fan speed	●	●	●		●	●	●	●	●	
	 Auto restart	●	●	●		●	●	●	●	●	
	 Connectable fresh air duct										
	 Fresh air intake										
	 Connectable distributing duct										
	 Individual airflow direction control										
	Convenience Features	 Auto-off timer	○	○	○		○	○			
 Sleep timer		●	●	●		●	●	●	●	●	
 Program timer		●	●	●		●	●	●	●	●	
 Weekly timer		●	●	○		●	●	●*3			
 Weekly & Temperature setback timer		○	○	○		○	○				
 Filter sign		●	●	●		●	●	●	●	●	
 External error output		○	○	○		○	○				
 External ON/OFF input		○	○	○		○	○				
 Wireless LAN control		● (KGTG, KGTG) ○ (KGTG)	● (KETF, KETF-B) ○ (KETE, KETE-B)	● (KMCF, KMCG, KMCG-B) ○ (KMCE)		○	○	●	○		○
 Multi system control							○				
 Special cooling							●*2				
Clean Features	 Ion deodorization filter	●	●	●		●	●				
	 Apple-catechin filter	●	●	●		●	●				
	 Long-life filter										
	 Washable panel	●	●	●		●	●	●	●	●	
	 Silver Ion Filter	○	○	○		○	○	○	○	○	
Installation / Support	 Automatic airflow adjustment										
	 Drain pump as standard										
	 Blue fin					●	●			●	
	 Refrigerant cycle monitor	○ (KGTG)		○ (KMCG, KMCG-B)		○	○			○	

\*1 For details of Multi System Control function, refer to C-013. \*2 Wired remote controller (UTY-RNRGZ5) is required to use Special Cooling function. \*3: It is only available on the AIRSTAGE Mobile application and wired remote controller. It can not be used via wireless remote controller. ○: Optional function

# Feature Summary

Type	Cassette		Duct			Duct				Floor	Ceiling
Series	Compact 4-way Flow Series	Circular Flow Series	Slim (With drain pump)	Medium Static Pressure (High-Efficiency & Comfort)	Medium Static Pressure (Compact size)	Medium Static Pressure (Standard)	High Static Pressure		Big		
Model name	AUXG 09/12/14/18/22/24 KVLA	AUXG 18/22/24/30/36/45/54 KRLB	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18/22/24/30/36/45/54 KMTAP	ARXG 12/14/18/22/24/30/36/45/54 KHTAP	ARXG22KMLB ARXG24/30/36/45KMLA	ARXG45/54KHTB	ARHG60LHTA	ARHG72/90LHTA	AGHG09/12/14KVCA	ABHG 18/22/24/30/36/45/54 KRTA
Energy-Saving Features	Save Human sensor										
	Human sensor control		○								
	Economy operation	●	●	●	○	●	●	●	●	●	●
	Setting temperature range limitation	○	●	○	○	●	○	○	○	●	●
	Set temperature auto return	●	●	●	○	●	●	○	○	●	●
Features for Comfort	Power diffuser										
	Powerful operation									●	
	10°C Heat	●	○	○	○	○	○	○	○	●	○
	Outdoor unit low noise operation		○ (45/54)			○ (45/54)	○ (45) (36LMLA)	○	○	●	○
	Auto changeover	●	●	●	●	●	●	●	●	●	●
	UP/DOWN swing louver	●	●	○						●	●
	Double swing automatic										
	Automatic fan speed	●	●	●	●	●	●	●	●	●	●
	Auto restart	●	●	●	●	●	●	●	●	●	●
	Connectable fresh air duct		●		●	●	●				●
	Fresh air intake	○	○	○	○	○	○	○	○	○	○
	Connectable distributing duct		●				●				
	Individual airflow direction control		●								
Convenience Features	Auto-off timer	●	●	●	●	●	●	○	●	○	●
	Sleep timer	●	○	○	○	○	○	○	○	●	○
	Program timer	●	○	○	●	○	○	○	○	●	○
	Weekly timer	●	●	●	○	●	●	●	●	●	●
	Weekly & Temperature setback timer	○		●			●	●	●		
	Filter sign	●	●	●	●	●	●	●	●	●	●
	External error output		○		●	○		○	○	○	○
	External ON/OFF input	●	●	●	●	●	●	○	●	○	●
	Wireless LAN control	○	○	○	○	○	○	○	○	○	○
	Multi system control										
Clean Features	Special cooling										
	Ion deodorization filter									●	
	Apple-catechin filter									●	
	Long-life filter				○	○	○	○	○		
	Washable panel										
Installation / Support	Silver Ion Filter	○	○	○	○	○	○	○	○	○	
	Automatic airflow adjustment				●	●			●		
	Drain pump as standard	●	●	●	●	●	○		○		○
	Blue fin		● (30/36/45/54)		● (30/36/45/54)	● (30/36/45/54)	● (30/36/45)	●	●	●	● (30/36/45/54)
	Refrigerant cycle monitor				○						

\*1 For details of Multi System Control function, refer to C-013. \*2 Wired remote controller (UTY-RNRGZ5) is required to use Special Cooling function. \*3: It is only available on the AIRSTAGE Mobile application and wired remote controller. It can not be used via wireless remote controller. ○: Optional function



## Light Commercial & Residential MULTI-SPLIT

- M-002 Multi-split Overview
- M-004 Multi-split Outdoor Units Lineup
- M-006 2-unit to 5-unit Multi-split Connectable Indoor Units
- M-008 6-unit Multi-split Connectable Indoor Units
- M-010 Simultaneous Multi-split Connectable Indoor Units
- M-044 Feature Summary



### Refrigerant type R32 models

- M-012 2-unit to 5-unit Multi-split
  - M-018 Simultaneous Multi-split Twin/Triple
- 
- M-022 2-unit to 5-unit Multi-split Indoor Units Specifications
- 
- M-028 2-unit to 5-unit Multi-split Combination Table



### Refrigerant type R410A models

- M-016 6-unit Multi-split
  - M-020 Simultaneous Multi-split Twin/Triple/Double Twin
- 
- M-026 6-unit Multi-split Indoor Units Specifications
- 
- M-038 6-unit Multi-split Combination Table



A single outdoor unit drives multiple indoor units, offering greater flexibility in system configuration.

If you wish to keep an entire floor or two or more rooms comfortable, we recommend you choose a multi-split air conditioning system with a single outdoor unit. Choose one that meets your air conditioning requirements from the variety of models we offer. You can mix and match indoor and outdoor units as you wish to build the system that best suits your needs.

# Multi-split Overview

Multi-split's space-saving outdoor unit allows for connections of up to eight indoor units for multiple rooms. Added to the lineup are models compatible with the new R32 refrigerant, offering environmentally friendly comfort in homes, offices, stores, and various other settings.



## 3-unit, 4-unit, 5-unit Multi-split Types



3-unit 18/24 class



4-unit 30 class  
5-unit 36 class



## 2-unit Multi-split



14 class



18 class

## 2-unit to 6-unit Multi-split

Recommended for residences, offices, and other situations where multiple rooms require air conditioning. Each of the 2 to 6 connected indoor units can also be operated individually. Operation control, time scheduling for each room, and energy-saving options can be set on both individual and central remote controllers. The outdoor unit is designed to save space and is flexible enough to be installed on a balcony or underneath a waist-high window.

## 6-unit Multi-split



6-unit 45 class

## Twin / Triple



Twin 36 class  
(Single-phase/3-phase)



Twin/Triple 45/54 class  
(Single-phase/3-phase)



## Twin / Triple / Double Twin



72/90 class  
(3-phase)

## Simultaneous Multi-split Type

Suitable for a small building, the entrance hall of a small office, meeting rooms, educational facilities, and other roomy areas where multiple indoor units need to be operated simultaneously. Up to 4 indoor units can be operated simultaneously, making the system perfect for air conditioning not only offices with large spaces, but also spaces with atypical layouts.

# Multi-split Outdoor Units Lineup



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for AC. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)  
\*Models so marked are not ECC certified.

		Class	14	18	18	24	30	36	45		54	72	90
		Cooling rated capacity (kW)	4.0	5.0	5.4	6.8	8.0	10.0	12.5	14.0	14.0	19.0	22.0
2-unit, 3-unit, 4-unit, 5-unit Multi-split	2-unit Multi-split Up to 2 units		AOHG14KBTA2	AOHG18KBTA2									
	3-unit Multi-split Up to 3 units				AOHG18KBTA3	AOHG24KBTA3							
	4-unit Multi-split Up to 4 units						AOHG30KBTA4						
	5-unit Multi-split Up to 5 units							AOHG36KBTA5*1					
6-unit Multi-split	6-unit Multi-split Up to 6 units								AOHG45LBLA6*				
Simultaneous Multi-split	Twin Single-phase							AOHG36KBTB	AOHG45KBTB				
	Twin 3-phase							AOHG36KRTA	AOHG45KRTA				
	Twin/Triple Single-phase										AOHG54KBTB		
	Twin/Triple 3-phase										AOHG54KRTA		
	Twin/Triple/Double Twin 3-phase											AOHG72LRLA	AOHG90LRLA

Notes:  
**1. 2-unit Multi-split:**  
 Connectable indoor units are 2 units.  
 AOHG14KBTA2: Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.  
 AOHG18KBTA2: Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.  
**2. 3-unit Multi-split:**  
 Connectable indoor units are 2 to 3 units.  
 AOHG18KBTA3: Total capacity of indoor units connected must be between 4.0 kW and 8.5 kW.  
 AOHG24KBTA3: Total capacity of indoor units connected must be between 4.0 kW and 10.5 kW.

**3. 4-unit Multi-split:**  
 Connectable indoor units are 2 to 4 units.  
 AOHG30KBTA4: Total capacity of indoor units connected must be between 7.5 kW and 14.0 kW.  
**4. 5-unit Multi-split:**  
 Connectable indoor units are 2 to 5 units.  
 AOHG36KBTA5: Total capacity of indoor units connected must be between 7.5 kW and 15.5 kW.

**5. 6-unit Multi-split:**  
 Connectable indoor units are 2 to 6 units.  
 AOHG45LBLA6: Total capacity of indoor units connected must be between 9.5 kW and 18.0 kW.

\*For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1

Cooling rated capacity: \*1: 9.5 kW

# 2-unit to 5-unit Multi-split Connectable Indoor Units



Type	2-unit		3-unit		4-unit	5-unit	
Model name	AOHG14KBTA2	AOHG18KBTA2	AOHG18KBTA3	AOHG24KBTA3	AOHG30KBTA4	AOHG36KBTA5	
Multi-split Type Outdoor Unit							
Capacity (kW)	Cooling	4.0	5.0	5.4	6.8	8.0	9.5
	Heating	4.4	5.6	6.8	8.0	9.6	10.6

Indoor Unit	BTU	kW Class	2-unit	3-unit	4-unit	5-unit
<b>NEW</b>  ASHH07/09/12/14KGTG ASHG07/09/12/14KGTE	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
 ASHG07/09/12/14KETF ASHG07/09/12/14KETE ASHG07/09/12/14KETE-B	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
<b>NEW</b>  ASHH07/09/12/14KMG ASHG07/09/12/14KMCE	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
<b>NEW</b>  ASHH05/07/09/12KNCA	5,000	1.5	●*	●*	●*	●*
	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
 ASHG18/22/24KMTE	18,000	5.0	—	—	●	●
	22,000	6.0	—	—	●	●
	24,000	7.0	—	—	●	●
 AGHG09/12/14KVCA	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
 AUXG07/09/12/14/18/22KVLA	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
	18,000	5.0	—	—	●	●
	22,000	6.0	—	—	●	●

\*For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1



Type	2-unit		3-unit		4-unit	5-unit	
Model name	AOHG14KBTA2	AOHG18KBTA2	AOHG18KBTA3	AOHG24KBTA3	AOHG30KBTA4	AOHG36KBTA5	
Multi-split Type Outdoor Unit							
Capacity (kW)	Cooling	4.0	5.0	5.4	6.8	8.0	9.5
	Heating	4.4	5.6	6.8	8.0	9.6	10.6



Indoor Unit	BTU	kW Class	2-unit	3-unit	4-unit	5-unit
 ARXG07/09/12/14/18KSLAP	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
 ARXG07/09/12/14/18KLLAP	7,000	2.0	●	●	●	●
	9,000	2.5	●	●	●	●
	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
<b>NEW</b>  ARXH12/14/18/22KMTAP	12,000	3.5	●	●	●	●
	14,000	4.0	—	●	●	●
	18,000	5.0	—	—	●	●
	22,000	6.0	—	—	●	●
 ARXG22KMLB	22,000	6.0	—	—	●	●
 ABHG18/22KRTA	18,000	5.0	—	—	●	●
	22,000	6.0	—	—	●	●



# 6-unit Multi-split Connectable Indoor Units



Type	6-unit	
Model name	AOHG45LBA6	
Multi-split Type Outdoor Unit		
Capacity (kW)	Cooling	12.5
	Heating	13.5

Indoor Unit	BTU	kW Class	
 ASHG07/09/12/14LMCA	7,000	2.0	●
	9,000	2.5	●
 ASHG07/09/12/14LUCA	12,000	3.5	●
	14,000	4.0	●
 ASHG18/24LF	18,000	5.0	●
	24,000	7.0	●
 AGHG09/12/14LV	9,000	2.5	●
	12,000	3.5	●
	14,000	4.0	●
 AUHG07/09/12/14/18LV	7,000	2.0	●
	9,000	2.5	●
	12,000	3.5	●
	14,000	4.0	●
 ABHG14LVTA ABHG18LVTB	14,000	4.0	●
	18,000	5.0	●
 ARHG07/09/12/14/18LSLAP	7,000	2.0	●
	9,000	2.5	●
	12,000	3.5	●
	14,000	4.0	●
 ARHG07/09/12/14/18LL	18,000	5.0	●
	7,000	2.0	●
	9,000	2.5	●
	12,000	3.5	●
 ARHG07/09/12/14/18LL	14,000	4.0	●
	18,000	5.0	●



# Simultaneous Multi-split Connectable Indoor Units



Type	4HP		5HP		6HP	
Model name	AOHG36KBTB	AOHG36KRTA	AOHG45KBTB	AOHG45KRTA	AOHG54KBTB	AOHG54KRTA
Simultaneous Multi-split Type Outdoor Unit						
Capacity (kW)	Cooling	9.5	12.1	13.4	13.4	13.4
	Heating	10.8	13.5	15.5	15.5	15.5

Indoor Unit	BTU	kW Class	Twin			Triple
 AUHG18/22/24KVLV	18,000	5.0	● × 2	—	—	● × 3
	22,000	6.5	—	● × 2	—	—
	24,000	7.0	—	—	● × 2	—
 ARXG18KLLAP	18,000	5.0	● × 2	—	—	● × 3
	22,000	6.5	—	● × 2	—	—
	24,000	7.0	—	—	● × 2	—
 ARXG22KMLB ARXG24KMLA	22,000	6.5	—	● × 2	—	—
	24,000	7.0	—	—	● × 2	—
	Separation tube			UTP-SX236A (18/22/24)		

Note : Please be aware that 2-wired group control is not possible with Simultaneous Multi-split.



Type	8HP		10HP	
Model name	AOHG72LRLA		AOHG90LRLA	
Simultaneous Multi-split Outdoor Unit				
Capacity (kW)	Cooling	19.0	22.0	27.0
	Heating	22.4	27.0	27.0

Indoor Unit	BTU	kW Class	Twin	Triple	Double Twin	Twin	Triple	Double Twin
 AUHG18/22/24LV	18,000	5.0	—	—	● × 4	—	—	—
	22,000	6.5	—	—	—	—	—	● × 4
	24,000	7.0	—	● × 3	—	—	—	—
 AUHG30/36/45LR	30,000	8.8	—	—	—	—	● × 3	—
	36,000	10.6	● × 2	—	—	—	—	—
	45,000	12.5	—	—	—	● × 2	—	—
 ARHG18LLTB	18,000	5.0	—	—	● × 4	—	—	—
	22,000	6.5	—	—	—	—	—	● × 4
	24,000	7.0	—	● × 3	—	—	—	—
 ARHG22/24/30/36/45LM	30,000	8.8	—	—	—	—	● × 3	—
	36,000	10.6	● × 2	—	—	—	—	—
	45,000	12.5	—	—	—	● × 2	—	—
	Separation tube			UTP-SX272A × 1	UTP-SX372A × 1	UTP-SX272A × 1, UTP-SX236A × 2	UTP-SX272A × 1	UTP-SX372A × 1
 ABHG18/22/24LV	18,000	5.0	—	—	● × 4	—	—	—
	22,000	6.5	—	—	—	—	—	● × 4
	24,000	7.0	—	● × 3	—	—	—	—
 ABHG30/36/45LR	30,000	8.8	—	—	—	—	● × 3	—
	36,000	10.6	● × 2	—	—	—	—	—
	45,000	12.5	—	—	—	● × 2	—	—

2-unit,  
3-unit,  
4-unit,  
5-unit,  
Multi-split




### High energy saving

With the adoption of a high-efficiency DC twin-rotary compressor, all models achieved an energy efficiency scale of A+++ for cooling and A++ for heating.

Rank Cooling A+++ Heating A++  
SEER 8.7\* SCOP 4.7

\*: 2-units 14 class when connected with a wall mounted [KG/KM] unit.




### R32 refrigerant model

In addition to its high energy efficiency, the R32 refrigerant has a larger volumetric capacity than the R410A refrigerant, which means the R32 refrigerant models require less refrigerant charge than the R410A models.

	Pre-charge refrigerant amount (kg)	
	R32	R410A
2-unit 14 class	0.9	1.25
2-unit 18 class	1.02	1.30
3-unit 18 class	1.8	2.2
3-unit 24 class	1.8	2.2
4-unit 30 class	2.2	3.3
5-unit 36 class	2.5	4.0

### Quiet operation

The sound power level is reduced by up to 7 dB compared to the current R410 models.




### Space-saving installation

Multiple indoor units can be connected to 1 outdoor unit by long piping as well. Unlike a single type, the outdoor unit can be installed in the most space-saving location.




### Compact design

Unlike a single type, the outdoor unit can be installed in the most space-saving location.



### Easy evacuation

All connected pipes and indoor units can be evacuated quickly via our centralized valve method. Requires evacuation only once.



### Wide range of indoor units with various models

We offer 41 models in 5 types in a capacity range from 2.0 kW to 6.0 kW. Wide range of requirements can be realized from private homes through to large shops and hotels



### Models equipped with the New R32 Refrigerant

Wall-mounted type with sophisticated design



Middle and small capacity models are available. This makes installation easier in small spaces.



2-unit: AOHG14KBTA2 / AOHG18KBTA2  
 3-unit: AOHG18KBTA3 / AOHG24KBTA3  
 4-unit: AOHG30KBTA4  
 5-unit: AOHG36KBTA5



Specifications (2-unit)

Model name		AOHG14KBTA2		AOHG18KBTA2	
Power Source					
Single phase, ~230 V, 50 Hz					
Rated Capacity	Cooling	Rated	kW	4.0	5.0
		Min.-Max.		1.4-4.6	1.7-5.8
Rated Capacity	Heating	Rated	kW	4.4	5.6
		Min.-Max.		1.1-5.5	1.8-6.6
EER	Cooling	W/W	4.12	4.03	
	Heating		4.63	4.59	
COP	Cooling	dB(A)	47	47	
	Heating		49	50	
Sound Pressure Level (High)	Cooling	dB(A)	60	60	
	Heating		62	62	
Sound Power Level (High)	Cooling/Heating	m³/h	1,670/1,670	1,960/2,020	
	Cooling/Heating		mm	542 × 799 × 290	632 × 799 × 290
Net Dimensions H × W × D		kg	33	37	
Weight		mm	mm	6.35 × 2	6.35 × 2
Connection Pipe				9.52 × 2	9.52 × 2
Diameter		m	m	30/20	30/20
Max. Pipe Length				15	15
Max. Height Difference		°CDB	°CDB	-10 to 46	-10 to 46
Operating Range				-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)	kg (CO2eq-T)	R32 (675)	R32 (675)	
	Charge		0.9 (0.608)	1.02 (0.689)	

Specifications (3-unit)

Model name		AOHG18KBTA3		AOHG24KBTA3	
Power Source					
Single phase, ~230 V, 50 Hz					
Rated Capacity	Cooling	Rated	kW	5.4	6.8
		Min.-Max.		1.8-7.0	1.8-8.5
Rated Capacity	Heating	Rated	kW	6.8	8.0
		Min.-Max.		2.0-8.0	2.0-9.2
EER	Cooling	W/W	4.78	3.90	
	Heating		4.89	4.40	
COP	Cooling	dB(A)	46	48	
	Heating		49	53	
Sound Pressure Level (High)	Cooling	dB(A)	59	61	
	Heating		61	67	
Sound Power Level (High)	Cooling/Heating	m³/h	2,220/2,160	2,270/2,730	
	Cooling/Heating		mm	716 × 820 × 315	716 × 820 × 315
Net Dimensions H × W × D		kg	46	46	
Weight		mm	mm	6.35 × 3	6.35 × 3
Connection Pipe				9.52 × 3	9.52 × 2, 12.70 × 1 adapter [12.70 → 9.52] × 1
Diameter		m	m	50/25	50/25
Max. Pipe Length				15	15
Max. Height Difference		°CDB	°CDB	-10 to 46	-10 to 46
Operating Range				-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)	kg (CO2eq-T)	R32 (675)	R32 (675)	
	Charge		1.8 (1.215)	1.8 (1.215)	

Specifications (4-unit, 5-unit)


Model name		AOHG30KBTA4		AOHG36KBTA5	
Power Source					
Single phase, ~230 V, 50 Hz					
Rated Capacity	Cooling	Rated	kW	8.0	9.5
		Min.-Max.		2.4-10.1	3.0-11.0
Rated Capacity	Heating	Rated	kW	9.6	10.6
		Min.-Max.		3.0-11.2	3.5-12.0
EER	Cooling	W/W	3.90	3.80	
	Heating		4.55	4.50	
COP	Cooling	dB(A)	50	52	
	Heating		54	55	
Sound Pressure Level (High)	Cooling	dB(A)	63	65	
	Heating		66	68	
Sound Power Level (High)	Cooling/Heating	m³/h	2,400/2,950	2,450/2,900	
	Cooling/Heating		mm	884 × 820 × 315	884 × 820 × 315
Net Dimensions H × W × D		kg	55	59	
Weight		mm	mm	6.35 × 4	6.35 × 5
Connection Pipe				9.52 × 2, 12.70 × 2 adapter [12.70 → 9.52] × 2	9.52 × 3, 12.70 × 2 adapter [12.70 → 9.52] × 2 adapter [9.52 → 12.70] × 1
Diameter		m	m	70/25	75/25
Max. Pipe Length*				15	15
Max. Height Difference		°CDB	°CDB	-10 to 46	-10 to 46
Operating Range				-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)	kg (CO2eq-T)	R32 (675)	R32 (675)	
	Charge		2.2 (1.485)	2.5 (1.688)	

\*Length not applicable when floor units are connected. For details, refer to the installation manual.


Dimensions

(Unit: mm)


2-unit: AOHG14KBTA2




2-unit: AOHG18KBTA2



3-unit: AOHG18KBTA3 / AOHG24KBTA3



4-unit: AOHG30KBTA4  
5-unit: AOHG36KBTA5



# 6-unit Multi-split



## 6-unit: AOHG45LBA6




### Specifications

Model name			AOHG45LBA6	
Power Source			Single phase, ~230 V, 50 Hz	
Rated Capacity	Cooling	Rated	kW	12.5
		Min.-Max.		3.5-14.0
	Heating	Rated		13.5
		Min.-Max.		3.5-16.0
EER	Cooling	W/W	3.50	
COP	Heating	W/W	4.00	
Sound Pressure Level (High)	Cooling	dB(A)	53	
	Heating		55	
Sound Power Level (High)	Cooling		-	
	Heating		-	
Airflow Rate	Cooling/Heating	m <sup>3</sup> /h	4,200/4,200	
Net Dimensions H × W × D			mm	998 × 970 × 370
Weight			kg	94
Connection Pipe Diameter	Liquid	mm	6.35 × 6	
	Gas		9.52 × 4, 12.70 × 2	
Max. Pipe Length	Total/Each		80/25	
	Between Outdoor Unit and Each Indoor Unit.		15	
Max. Height Difference	Between Indoor Units.		10	
	Cooling	°CDB	-10 to 46	
Heating	-15 to 24			
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	
	Charge	kg (CO <sub>2</sub> eq-T)	4.00 (8.352)	

### A wide variety of models to choose from

We offer 26 models in 5 types in a capacity range from 2.0 kW to 7.0 kW. Wide range of requirements can be realized from private homes through to large shops and hotels.




### Compact design

Multiple indoor units can be connected to 1 outdoor unit by long piping as well. Unlike a single type, the outdoor unit can be installed in the most space-saving location.



### Easy installation

All connected pipes and indoor units can be evacuated quickly via our centralized valve method. Requires evacuation only once.



### Central & Individual control





- Batched control of up to 6 indoor units. Unified setting of room temperature, airflow volume, and local control restrictions across units.
- Language can be selected from English, French, German, Greek, Italian, Portuguese, Russian, Spanish, or Turkish.
- Large backlit LED screen
- Large easy-to-see operation panel

Max. Controllable  
**1 multi-system**  
Max. Controllable  
**6 indoor units**



### Dimensions

(Unit: mm)



# Simultaneous Multi-split Type


Twin / Triple




**Meets a variety of installation needs from offices to commercial spaces, with up to 3 indoor units in the same room connected to an outdoor unit.**

Select indoor units according to floor layout and heat load estimated by the number of people working in the room and the direction and intensity of sunlight entering the room. Perfect airflow distribution can be achieved for optimum comfort.

Installation according to floor layout




Installation according to lighting conditions



## Design flexibility


### Slim & Compact Design

The outdoor unit in this series is 22.7% shorter\* than a twin-fan outdoor unit. The reduced height makes it easy to install in tight spaces.



## Flexible installation

Pipe length of up to 50 m and a height difference of up to 30 m can be accommodated. Multi-split systems can be installed in large residences and multi-story buildings.



## New lineup of indoor units

The indoor units, available in 6 models of 3 types, can be selected according to room size and conditions.



Note : Please be aware that 2-wired group control is not possible with Simultaneous Multi-split.

Model: AOHG36KBTB / AOHG45KBTB / AOHG54KBTB  
AOHG36KRTA [3-phase] / AOHG45KRTA [3-phase] / AOHG54KRTA [3-phase]



## Specifications (Indoor units/Outdoor units)

Indoor Units Model name				Compact Cassette		
				AUXG18KVLA	AUXG22KVLA	AUXG24KVLA
Power Source				Single phase, ~230 V, 50 Hz		
Airflow Rate	Cooling	H/M/L/Q	m <sup>3</sup> /h	680/580/490/410	830/740/600/450	930/830/600/450
	Heating	H/M/L/Q		800/680/580/450	860/760/700/530	930/850/700/530
Net Dimensions H × W × D				245 × 570 × 570		245 × 570 × 570
Weight				15		16
Cassette Grille				UTG-UFGF-W		UTG-UFGF-W

Indoor Units Model name				Duct		
				ARXG18KLLAP	ARXG22KMLB	ARXG24KMLA
Power Source				Single phase, ~230 V, 50 Hz		
Airflow Rate	Cooling	H/M/L/Q	m <sup>3</sup> /h	940/880/820/750	1,100/910/750/580	1,100/910/750/580
	Heating	H/M/L/Q		940/880/820/750	1,100/910/750/580	1,100/910/750/580
Net Dimensions H × W × D				198 × 900 × 620		270 × 1,135 × 700
Weight				20		35



Outdoor Units Model name			AOHG36KBTB	AOHG45KBTB	AOHG54KBTB	AOHG36KRTA	AOHG45KRTA	AOHG54KRTA
Capacity	Cooling	kW	9.5	12.1	13.4	9.5	12.1	13.4
	Heating		10.8	13.5	15.5	10.8	13.5	15.5
Power Source			Single phase, ~230 V, 50 Hz			3-phase, ~400 V, 50 Hz		
Pdesign	Cooling	kW	9.5	-	-	9.5	-	-
	Heating (-10°C)		8.7	-	-	8.7	-	-
SEER	Cooling		6.10	-	-	6.10	-	-
SCOP	Heating	W/W	4.00	-	-	4.00	-	-
Annual Energy Consumption	Cooling	kWh/a	545	-	-	545	-	-
	Heating		3,044	-	-	3,044	-	-
Energy Efficiency Class	Cooling		A++	-	-	A++	-	-
	Heating		A+	-	-	A+	-	-
Sound Pressure Level (High)	Cooling	dB(A)	55	57	57	55	57	57
	Heating		55	57	59	55	57	59
Sound Power Level (High)	Cooling	dB(A)	70	71	73	70	71	73
	Heating		70	71	73	70	71	73
Airflow Rate	Cooling/Heating	m <sup>3</sup> /h	3,750/3,750	4,450/4,450	4,450/4,450	3,750/3,750	4,450/4,450	4,450/4,450
Net Dimensions H × W × D			788 × 940 × 320		998 × 940 × 320	788 × 940 × 320		998 × 940 × 320
Weight			52		67	53		67
Connection Pipe Diameter (Liquid/Gas)			9.52/15.88		9.52/15.88	9.52/15.88		9.52/15.88
Max. Pipe Length (Pre-Charge)			50 (30)		50 (30)	50 (30)		50 (30)
Max. Height Difference			30		30	30		30
Operating Range	Cooling	°CDB	-15 to 46		-15 to 46	-15 to 46		-15 to 46
	Heating		-15 to 24		-15 to 24	-15 to 24		-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)	1.90 (1.283)	2.70 (1.823)	2.70 (1.823)
Separation tube			UTP-SX236A (Twin)		UTP-SX236A (Twin) UTP-SX354A (Triple)	UTP-SX236A (Twin)		UTP-SX236A (Twin) UTP-SX354A (Triple)

• Indoor units of different types and capacity cannot be connected.  
• The above specifications apply when used with a cassette type indoor unit.



## Dimensions

(Unit: mm)

### AOHG36KBTB / AOHG36KRTA



### AOHG45KBTB / AOHG54KBTB AOHG45KRTA / AOHG54KRTA





# 2-unit to 5-unit Multi-split Indoor Units Specifications



## Wall-mounted type

**NEW**

Model name	Indoor unit		ASHH07KGTG ASHG07KGTE	ASHH09KGTG ASHG09KGTE	ASHH12KGTG ASHG12KGTE	ASHH14KGTG ASHG14KGTE
kW Class	kW		2.0	2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating		41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	54	55	56	57
	Heating		56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
	Heating		720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions	mm		270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
Weight	kg		10	10	10	10
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52



## Wall-mounted type

**NEW**

Model name	Indoor unit		ASHH05KNCA	ASHH07KNCA	ASHH09KNCA	ASHH12KNCA
kW Class	kW		1.5	2.0	2.5	3.5
Power Source	Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	34 / 33 / 29 / 21	36 / 33 / 29 / 21	41 / 35 / 29 / 21	42 / 36 / 32 / 21
	Heating		34 / 32 / 30 / 22	36 / 33 / 30 / 22	41 / 34 / 30 / 22	42 / 35 / 31 / 22
Sound Power Level	Cooling	H	50	51	56	57
	Heating		50	51	56	57
Airflow Rate	Cooling	H/M/L/Q	500 / 450 / 390 / 250	530 / 460 / 390 / 250	640 / 500 / 390 / 250	660 / 520 / 440 / 250
	Heating		500 / 450 / 420 / 280	530 / 460 / 420 / 280	640 / 500 / 420 / 280	660 / 520 / 440 / 280
Net Dimensions	mm		270 × 784 × 222	270 × 784 × 222	270 × 784 × 222	270 × 784 × 222
Weight	kg		9	9	9	9
Connection Pipe Diameter	Liquid/Gas	mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52



## Wall-mounted type

Model name	Indoor unit		ASHG07KETF ASHG07KETF-B ASHG07KETE ASHG07KETE-B	ASHG09KETF ASHG09KETF-B ASHG09KETE ASHG09KETE-B	ASHG12KETF ASHG12KETF-B ASHG12KETE ASHG12KETE-B	ASHG14KETF ASHG14KETF-B ASHG14KETE ASHG14KETE-B
kW Class	kW		2.0	2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating		41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	54	55	55	57
	Heating		56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
	Heating		720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions	mm		295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230
Weight	kg		11	11	11	11.5
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52



## Wall-mounted type

Model name	Indoor unit		ASHG18KMTE	ASHG22KMTE	ASHG24KMTE
kW Class	kW		5.0	6.0	7.0
Power Source	Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	45/40/35/29	48/40/35/29	49/40/35/29
	Heating		46/40/35/29	48/40/35/29	49/40/35/29
Sound Power Level	Cooling	H	60	62	65
	Heating		61	62	65
Airflow Rate	Cooling	H/M/L/Q	980/810/640/510	1,060/810/640/510	1,170/850/640/510
	Heating		1,020/850/640/510	1,060/850/640/510	1,170/850/640/510
Net Dimensions	mm		280 × 980 × 240	280 × 980 × 240	280 × 980 × 240
Weight	kg		12.5	12.5	12.5
Connection Pipe Diameter	Liquid/Gas	mm	6.35/12.70	6.35/12.70	6.35/12.70



## Wall-mounted type

**NEW**

Model name	Indoor unit		ASHH07KMCG ASHH07KMCG-B ASHG07KMCE	ASHH09KMCG ASHH09KMCG-B ASHG09KMCE	ASHH12KMCG ASHH12KMCG-B ASHG12KMCE	ASHH14KMCG ASHH14KMCG-B ASHG14KMCE
kW Class	kW		2.0	2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating		41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	54	55	55	57
	Heating		56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	650/540/430/320	700/560/430/320	700/560/430/320	770/600/450/310
	Heating		720/580/460/330	750/610/470/330	780/640/520/330	820/660/520/340
Net Dimensions	mm		270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
Weight	kg		10	10	10	10
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52



## Floor

Model name	Indoor unit		AGHG09KVCA	AGHG12KVCA	AGHG14KVCA
kW Class	kW		2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	39/34/28/22	42/36/30/22	44/38/31/22
	Heating		39/35/30/22	42/38/32/22	44/39/33/22
Sound Power Level	Cooling	H	52	55	56
	Heating		52	55	56
Airflow Rate	Cooling	H/M/L/Q	530/440/360/270	600/490/380/270	650/520/400/270
	Heating		530/460/380/270	600/510/410/270	650/540/430/270
Net Dimensions	mm		600 × 740 × 200	600 × 740 × 200	600 × 740 × 200
Weight	kg		14	14	14
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52





# 2-unit to 5-unit Multi-split Indoor Units Specifications

## Ceiling



Model name	Indoor unit		ABHG18KRTA		ABHG22KRTA		
kW Class	kW		5.0		6.0		
Power Source	Single phase, ~230 V, 50 Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/36/33/31		42/37/34/31	
	Heating			38/36/33/31		42/37/34/31	
Sound Power Level	Cooling	H	dB(A)	53		57	
	Heating			53		57	
Airflow Rate	Cooling	H/M/L/Q	m³/h	840/790/710/650		900/790/710/650	
	Heating			840/790/710/650		900/790/710/650	
Net Dimensions	mm		235 × 1,080 × 705		235 × 1,080 × 705		
Weight	kg		24		24		
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70		6.35/12.70	

## Compact Cassette Grid Type




Model name	Indoor unit		AUXG07KVLA	AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	
kW Class	kW		2.0	2.5	3.5	4.0	5.0	6.0	
Power Source	Single phase, ~230 V, 50 Hz								
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27		37/34/31/28		38/35/32/29	
	Heating			34/32/29/27		43/38/34/30		45/43/40/33	
Sound Power Level	Cooling	H	dB(A)	46		49		50	
	Heating			47		55		57	
Airflow Rate	Cooling	H/M/L/Q	m³/h	540/490/440/390		610/530/470/410		680/580/490/410	
	Heating			540/490/440/390		790/680/580/450		860/760/700/530	
Net Dimensions	mm		245 × 570 × 570		245 × 570 × 570		245 × 570 × 570		
Weight	kg		15		15		16		
Panel			UTG-UFGF-W		UTG-UFGF-W		UTG-UFGF-W		
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52		6.35/9.52		6.35/12.70	

## Mini duct



Model name	Indoor unit		ARXG07KSLAP	ARXG09KSLAP	ARXG12KSLAP	ARXG14KSLAP	ARXG18KSLAP		
kW Class	kW		2.0	2.5	3.5	4.0	5.0		
Power Source	Single phase, ~230 V, 50 Hz								
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29/26/24/23		31/27/25/23		35/30/27/23	
	Heating			29/26/24/23		31/27/25/23		33/29/26/23	
Sound Power Level	Cooling	H	dB(A)	52		55		60	
	Heating			53		57		59	
Airflow Rate	Cooling	H/M/L/Q	m³/h	550/440/390/360		650/490/430/360		800/640/530/360	
	Heating			550/440/390/360		650/490/430/360		800/640/530/360	
Net Dimensions	mm		198 × 700 × 450		198 × 700 × 450		198 × 700 × 450		
Weight	kg		15.5		15.5		18.5		
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52		6.35/9.52		6.35/12.70	
External static pressure	Pa		0 to 30		0 to 30		0 to 50		
Drain pump			Standard		Standard		Standard		

## Slim duct



Model name	Indoor unit		ARXG07KLLAP	ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP		
kW Class	kW		2.0	2.5	3.5	4.0	5.0		
Power Source	Single phase, ~230 V, 50 Hz								
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	28/26/25/24		29/28/27/26		32/30/28/26	
	Heating			28/26/25/24		29/28/27/24		32/30/28/25	
Sound Power Level	Cooling	H	dB(A)	57		58		60	
	Heating			57		58		58	
Airflow Rate	Cooling	H/M/L/Q	m³/h	550/490/470/440		650/600/550/480		800/700/600/480	
	Heating			550/490/470/440		650/600/550/480		800/700/600/480	
Net Dimensions	mm		198 × 700 × 620		198 × 700 × 620		198 × 700 × 620		
Weight	kg		16		17		20		
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52		6.35/9.52		6.35/12.70	
External static pressure	Pa		0 to 90		0 to 90		0 to 90		
Drain pump			Standard		Standard		Standard		

## Medium Static Pressure Duct

NEW



Model name	Indoor unit		ARXH12KMTAP	ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	
kW Class	kW		3.5	4.0	5.0	6.0	
Power Source	Single-phase, ~230V, 50Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29 / 27 / 25 / 23		32 / 29 / 27 / 25	
	Heating			29 / 27 / 25 / 23		33 / 30 / 28 / 26	
Sound Power Level	Cooling	H	dB(A)	58		59	
	Heating			58		60	
Airflow Rate	Cooling	H/M/L/Q	m³/h	650 / 520 / 460 / 390		800 / 640 / 560 / 480	
	Heating			650 / 520 / 460 / 390		840 / 720 / 630 / 540	
Net Dimensions	mm		240 × 700 × 700		240 × 700 × 700		
Weight	kg		24		24		
Connection Pipe Diameter	Liquid/Gas	mm		6.35 / 9.52		6.35 / 12.7	
External static pressure	Pa		30 to 150		30 to 150		
Drain pump			Standard		Standard		

## Medium Static Pressure Duct



Model name	Indoor unit		ARXG22KMLB			
kW Class	kW		6.0			
Power Source	Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	31/29/27/25		
	Heating			31/29/27/25		
Sound Power Level	Cooling	H	dB(A)	60		
	Heating			62		
Airflow Rate	Cooling	H/M/L/Q	m³/h	1,100/910/750/580		
	Heating			1,100/910/750/580		
Net Dimensions	mm		270 × 1,135 × 700			
Weight	kg		35			
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70		
External static pressure	Pa		30 to 150			
Drain pump			Option			

# 6-unit Multi-split Indoor Units Specifications

## Compact wall-mounted



Model name	Indoor unit			ASHG07LUCA	ASHG09LUCA	ASHG12LUCA	ASHG14LUCA
kW Class	kW			2.0	2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	35/30/28/21	36/32/28/21	37/34/31/21	41/36/33/25
	Heating			35/30/28/21	36/32/28/21	37/34/31/21	41/36/34/27
Sound Power Level	Cooling	H	dB(A)	53	54	55	59
	Heating			53	54	55	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	570/520/470/330	600/550/470/330	660/600/530/330	710/640/570/390
	Heating			570/520/470/330	600/550/470/330	660/600/530/330	710/640/590/430
Net Dimensions	mm			282 × 870 × 185	282 × 870 × 185	282 × 870 × 185	282 × 870 × 185
Weight	kg			9.5	9.5	9.5	9.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70

## Wall-mounted type



Model name	Indoor unit			ASHG18LFCA	ASHG24LFCC
kW Class	kW			5.0	7.0
Power Source	Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	43/37/33/26	49/42/37/33
	Heating			42/37/33/25	48/42/37/33
Sound Power Level	Cooling	H	dB(A)	58	64
	Heating			58	64
Airflow Rate	Cooling	H/M/L/Q	m³/h	900/740/620/550	1,120/900/740/620
	Heating			900/740/620/550	1,100/900/740/620
Net Dimensions	mm			320 × 998 × 238	320 × 998 × 238
Weight	kg			14	14
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70	6.35/15.88

## Compact wall-mounted



Model name	Indoor unit			ASHG07LMCA	ASHG09LMCA	ASHG12LMCA	ASHG14LMCA
kW Class	kW			2.0	2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/32/29/21	37/33/29/21	40/36/30/21	42/38/33/25
	Heating			36/32/29/22	37/33/29/22	40/36/31/22	42/38/35/27
Sound Power Level	Cooling	H	dB(A)	51	52	54	56
	Heating			51	52	55	57
Airflow Rate	Cooling	H/M/L/Q	m³/h	560/500/430/310	600/520/430/310	660/560/450/310	730/600/530/360
	Heating			560/500/430/330	600/520/430/330	660/560/470/330	730/615/560/375
Net Dimensions	mm			268 × 840 × 203	268 × 840 × 203	268 × 840 × 203	268 × 840 × 203
Weight	kg			8.5	8.5	8.5	8.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70

## Floor



Model name	Indoor unit			AGHG09LVCA	AGHG12LVCA	AGHG14LVCA
kW Class	kW			2.5	3.5	4.0
Power Source	Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	39/34/28/22	42/36/30/22	44/38/31/22
	Heating			39/35/30/22	42/38/32/22	44/39/33/22
Sound Power Level	Cooling	H	dB(A)	52	55	56
	Heating			52	55	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	530/440/360/270	600/490/380/270	650/520/400/270
	Heating			530/460/380/270	600/510/410/270	650/540/430/270
Net Dimensions	mm			600 × 740 × 200	600 × 740 × 200	600 × 740 × 200
Weight	kg			14	14	14
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/12.70

## Floor ceiling



Model name	Indoor unit			ABHG14LVTA	ABHG18LVTB
kW Class	kW			4.0	5.0
Power Source	Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
	Heating			36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
Sound Power Level	Cooling	H	dB(A)	51	55
	Heating			51	55
Airflow Rate	Cooling	H/M/L/Q	m³/h	640/590/540/480	780/700/560/500
	Heating			640/590/540/480	780/700/560/500
Net Dimensions	mm			199 × 990 × 655	199 × 990 × 655
Weight	kg			27	27
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70	6.35/12.70

## Compact cassette




Model name	Indoor unit			AUHG07LVLA	AUHG09LVLA	AUHG12LVLB	AUHG14LVLB	AUHG18LVLB
kW Class	kW			2.0	2.5	3.5	4.0	5.0
Power Source	Single phase, ~230 V, 50 Hz							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	33/31/29/27	37/33/31/28	40/35/32/29	42/37/33/29
	Heating			34/32/29/27	34/32/29/27	37/33/31/28	40/37/34/29	44/40/37/30
Sound Power Level	Cooling	H	dB(A)	46	46	49	52	54
	Heating			47	47	49	52	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	750/610/520/410
	Heating			540/490/440/390	540/490/440/390	610/530/470/410	700/620/550/430	800/710/600/450
Net Dimensions	mm			245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570
Weight	kg			15	15	15	15	15
Panel	UTG-UFGD-W							
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70

## Mini duct



Model name	Indoor unit			ARHG07LSLAP	ARHG09LSLAP	ARHG12LSLAP	ARHG14LSLAP	ARHG18LSLAP
kW Class	kW			2.0	2.5	3.5	4.0	5.0
Power Source	Single phase, ~230 V, 50 Hz							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
	Heating			29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
Sound Power Level	Cooling	H	dB(A)	52	54	55	60	58
	Heating			53	56	57	62	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
	Heating			550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
Net Dimensions	mm			198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 900 × 450
Weight	kg			15.5				18.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52			6.35/12.70	
External static pressure	Pa			0 to 30			0 to 50	
Drain pump	Standard							

## Slim duct



Model name	Indoor unit			ARHG07LLTA	ARHG09LLTA	ARHG12LLTB	ARHG14LLTB	ARHG18LLTB
kW Class	kW			2.0	2.5	3.5	4.0	5.0
Power Source	Single phase, ~230 V, 50 Hz							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	28/26/25/24	28/27/26/25	29/28/27/26	32/30/28/26	32/31/30/29
	Heating			28/26/25/24	28/26/25/24	29/28/27/24	33/30/28/25	33/32/31/29
Sound Power Level	Cooling	H	dB(A)	57	57	58	60	58
	Heating			57	57	58	61	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
	Heating			550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
Net Dimensions	mm			198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 900 × 620
Weight	kg			17	19	19	19	23
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7	6.35/12.70
External static pressure	Pa			0 to 90				
Drain pump	Standard							

# 2-unit Multi-split Combination Table-Cooling/Heating

## 2-unit Multi-split cooling

AOHG14KBTA2	Combination of Indoor Units		Cooling Operation					Seasonal Data		
			Cooling Capacity			Input Power (Min. - Max.) kW	EER	Pdesign kW	SEER	Energy efficiency class
			Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW					
2-unit connection	5	5	1.50	1.50	3.00 (1.40-3.60)	0.74 (0.25-0.95)	4.03	3.0	6.8	A++
	5	7	1.50	2.00	3.50 (1.40-4.30)	0.84 (0.25-1.10)	4.15	3.5	6.8	A++
	5	9	1.50	2.50	4.00 (1.40-4.39)	1.07 (0.25-1.25)	3.75	4.0	6.8	A++
	5	12	1.18	2.82	4.00 (1.40-4.61)	1.02 (0.25-1.25)	3.92	4.0	6.8	A++
	7	7	2.00	2.00	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	7	9	1.75	2.25	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	7	12	1.47	2.53	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	9	9	2.00	2.00	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	9	12	1.71	2.29	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++

- Notes: •5: 5000 Btu/h/7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h models  
 •The above specifications apply when connected with a indoor model except a wall-mounted [KM/KG] unit.  
 •2 or more indoor units should be connected.  
 •Cooling capacity is determined based on 27°CDB/19°CWB (indoor temperature) and 35°CDB (outdoor temperature).  
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)  
 •Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.  
 •Please refer to the Design & Technical manual for the combination tables with a wall-mounted [KM/KG] model.  
 •For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1

AOHG18KBTA2	Combination of Indoor Units		Cooling Operation					Seasonal Data		
			Cooling Capacity			Input Power (Min. - Max.) kW	EER	Pdesign kW	SEER	Energy efficiency class
			Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW					
2-unit connection	5	5	1.50	1.50	3.00 (1.70-3.60)	0.53 (0.25-0.94)	5.65	3.0	6.9	A++
	5	7	1.50	2.00	3.50 (1.70-4.30)	0.75 (0.25-1.12)	4.65	3.5	6.9	A++
	5	9	1.50	2.50	4.00 (1.70-5.00)	0.97 (0.25-1.29)	4.10	4.0	6.9	A++
	5	12	1.41	3.39	4.80 (1.70-5.70)	1.20 (0.25-1.58)	4.00	5.0	6.7	A++
	5	14	1.32	3.68	5.00 (1.70-5.80)	1.32 (0.25-1.63)	3.78	5.0	6.7	A++
	7	7	2.00	2.00	4.00 (1.7-5.0)	0.92 (0.25-1.23)	4.35	4.0	8.8	A+++
	7	9	2.00	2.50	4.50 (1.7-5.7)	1.07 (0.25-1.45)	4.22	4.5	8.7	A+++
	7	12	1.84	3.16	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	7	14	1.67	3.33	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	9	9	2.50	2.50	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	9	12	2.14	2.86	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	9	14	1.96	3.04	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	12	12	2.50	2.50	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	12	14	2.31	2.69	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++

- Notes: •5: 5000 Btu/h/7: 7000 Btu/h/9:9000 Btu/h/12: 12000 Btu/h/14: 14000 Btu/h models  
 •The above specifications apply when connected with a indoor model except a wall-mounted [KM/KG] unit.  
 •2 or more indoor units should be connected.  
 •Cooling capacity is determined based on 27°CDB/19°CWB (indoor temperature) and 35°CDB (outdoor temperature).  
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)  
 •Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.  
 •Please refer to the Design & Technical manual for the combination tables with a wall-mounted [KM/KG] model.  
 •For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1

## 2-unit Multi-split heating

AOHG14KBTA2	Combination of Indoor Units		Heating Operation					Seasonal Data		
			Heating Capacity			Input Power (Min. - Max.) kW	COP	Pdesign kW	SCOP	Energy efficiency class
			Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW					
2-unit connection	5	5	1.80	1.80	3.60 (1.10-4.20)	0.80 (0.25-1.25)	4.52	2.9	4.08	A+
	5	7	1.67	2.33	4.00 (1.10-4.80)	0.92 (0.25-1.50)	4.36	3.4	4.1	A+
	5	9	1.57	2.83	4.40 (1.10-5.10)	1.06 (0.25-1.70)	4.16	3.5	4.1	A+
	5	12	1.29	3.11	4.40 (1.10-5.40)	1.01 (0.25-1.70)	4.34	3.5	4.1	A+
	7	7	2.20	2.20	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	7	9	1.92	2.48	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	7	12	1.62	2.78	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	9	9	2.20	2.20	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	9	12	1.89	2.51	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++

- Notes: •5: 5000 Btu/h/7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h models  
 •The above specifications apply when connected with a indoor model except a wall-mounted [KM/KG] unit.  
 •2 or more indoor units should be connected.  
 •Heating capacity is determined based on 20°CDB (indoor temperature) and 7°CDB/6°CWB (outdoor temperature).  
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)  
 •Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.  
 •Please refer to the Design & Technical manual for the combination tables with a wall-mounted [KM/KG] model.  
 •For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1

AOHG18KBTA2	Combination of Indoor Units		Heating Operation					Seasonal Data		
			Heating Capacity			Input Power (Min. - Max.) kW	COP	Pdesign kW	SCOP	Energy efficiency class
			Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW					
2-unit connection	5	5	1.80	1.80	3.60 (1.70-4.20)	0.80 (0.25-0.94)	4.50	2.9	4.1	A+
	5	7	1.80	2.40	4.20 (1.70-4.90)	0.92 (0.25-1.18)	4.54	3.4	4.1	A+
	5	9	1.80	3.00	4.80 (1.70-5.60)	1.05 (0.25-1.41)	4.57	3.8	4.1	A+
	5	12	1.59	3.81	5.40 (1.70-6.40)	1.24 (0.25-1.76)	4.36	4.2	4.0	A+
	5	14	1.47	4.13	5.60 (1.70-6.60)	1.30 (0.25-1.88)	4.30	4.2	4.0	A+
	7	7	2.40	2.40	4.80 (1.7-5.6)	0.99 (0.25-1.35)	4.85	3.8	4.7	A++
	7	9	2.40	3.00	5.40 (1.7-6.4)	1.15 (0.25-1.60)	4.70	4.0	4.7	A++
	7	12	2.06	3.54	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	7	14	1.87	3.73	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	9	9	2.80	2.80	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	9	12	2.40	3.20	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	9	14	2.19	3.41	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	12	12	2.80	2.80	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	12	14	2.58	3.02	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++

- Notes: •5: 5000 Btu/h/7: 7000 Btu/h/9:9000 Btu/h/12: 12000 Btu/h/14: 14000 Btu/h models  
 •The above specifications apply when connected with a indoor model except a wall-mounted [KM/KG] unit.  
 •2 or more indoor units should be connected.  
 •Heating capacity is determined based on 20°CDB (indoor temperature) and 7°CDB/6°CWB (outdoor temperature).  
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)  
 •Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.  
 •Please refer to the Design & Technical manual for the combination tables with a wall-mounted [KM/KG] model.  
 •For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1

# 3-unit Multi-split Combination Table-cooling/Heating

## 3-unit Multi-split cooling

AOHG18KBT3	Combination of Indoor Units		Cooling Operation					Seasonal Data				
			Cooling Capacity			Input Power (Min. - Max.)	EER	Pdesign kW	SEER	Energy efficiency		
			Unit 1 kW	Unit 2 kW	Unit 3 kW						Total Capacity (Min. - Max.) kW	
2-unit connection	5	9	-	1.50	2.50	-	4.00 (1.80-5.00)	0.88 (0.43-1.37)	4.55	4.0	6.7	A++
	5	12	-	1.41	3.39	-	4.80 (1.80-6.10)	1.11 (0.43-1.65)	4.32	5.0	6.5	A++
	5	14	-	1.42	3.98	-	5.40 (1.80-6.40)	1.39 (0.43-1.83)	3.88	5.4	6.4	A++
	7	7	-	2.00	2.00	-	4.00 (1.8-5.0)	0.86 (0.35-1.35)	4.65	4.0	8.3	A++
	7	9	-	2.00	2.50	-	4.50 (1.8-5.7)	1.03 (0.35-1.50)	4.36	4.5	8.2	A++
	7	12	-	1.99	3.41	-	5.40 (1.8-6.8)	1.41 (0.35-1.81)	3.83	5.4	8.0	A++
	7	14	-	1.80	3.60	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	9	9	-	2.50	2.50	-	5.00 (1.8-6.4)	1.23 (0.35-1.70)	4.06	5.0	8.1	A++
	9	12	-	2.31	3.09	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	9	14	-	2.11	3.29	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	12	12	-	2.70	2.70	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	12	14	-	2.49	2.91	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	14	14	-	2.70	2.70	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	5	5	5	1.50	1.50	1.50	4.50 (1.80-5.40)	0.68 (0.43-1.46)	6.65	4.5	7.1	A++
5	5	7	1.41	1.41	1.98	4.80 (1.80-6.10)	0.83 (0.43-1.65)	5.78	5.0	7.0	A++	
5	5	9	1.42	1.42	2.56	5.40 (1.80-6.80)	0.98 (0.43-1.83)	5.49	5.4	6.9	A++	
5	5	12	1.23	1.23	2.95	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	5	14	1.13	1.13	3.15	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	7	7	1.42	1.99	1.99	5.40 (1.80-6.80)	0.98 (0.43-1.83)	5.49	5.4	6.9	A++	
5	7	9	1.29	1.80	2.31	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	7	12	1.13	1.58	2.70	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	7	14	1.04	1.45	2.91	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	9	9	1.17	2.11	2.11	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	9	12	1.04	1.87	2.49	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	9	14	0.96	1.74	2.70	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
5	12	12	0.93	2.23	2.23	5.40 (1.80-7.00)	1.14 (0.43-1.91)	4.74	5.4	6.9	A++	
7	7	7	1.80	1.80	1.80	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
7	7	9	1.64	1.64	2.12	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
7	7	12	1.45	1.45	2.50	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
7	7	14	1.35	1.35	2.70	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
7	9	9	1.52	1.94	1.94	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
7	9	12	1.35	1.74	2.31	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
7	9	14	1.26	1.62	2.52	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
9	9	9	1.80	1.80	1.80	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
9	9	12	1.62	1.62	2.16	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	

AOHG24KBT3	Combination of Indoor Units		Cooling Operation					Seasonal Data				
			Cooling Capacity			Input Power (Min. - Max.)	EER	Pdesign kW	SEER	Energy efficiency		
			Unit 1 kW	Unit 2 kW	Unit 3 kW						Total Capacity (Min. - Max.) kW	
2-unit connection	5	9	-	1.80	3.00	-	4.80 (2.00-5.60)	1.06 (0.30-1.36)	4.53	4.0	6.7	A++
	5	12	-	1.68	4.02	-	5.70 (2.00-6.80)	1.38 (0.30-1.70)	4.12	5.0	6.5	A++
	5	14	-	1.80	4.80	-	6.60 (2.00-7.60)	1.78 (0.30-1.89)	3.71	5.5	6.4	A++
	5	18	-	1.67	6.03	-	7.70 (2.00-8.60)	2.03 (0.30-2.37)	3.79	6.5	5.5	A
	7	7	-	2.00	2.00	-	4.00 (1.8-5.0)	0.86 (0.35-1.35)	4.65	4.0	8.3	A++
	7	9	-	2.00	2.50	-	4.50 (1.8-5.7)	1.03 (0.35-1.50)	4.36	4.5	8.2	A++
	7	12	-	2.00	3.50	-	5.50 (1.8-6.8)	1.45 (0.35-1.85)	3.77	5.5	8.0	A++
	7	14	-	2.00	4.00	-	6.00 (1.8-7.5)	1.73 (0.35-2.20)	3.48	6.0	7.6	A++
	7	18	-	1.90	4.90	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	9	9	-	2.50	2.50	-	5.00 (1.8-6.4)	1.23 (0.35-1.74)	4.06	5.0	8.1	A++
	9	12	-	2.50	3.50	-	6.00 (1.8-7.5)	1.73 (0.35-2.20)	3.48	6.0	7.6	A++
	9	14	-	2.50	4.00	-	6.50 (1.8-8.2)	2.04 (0.35-2.46)	3.19	6.5	7.2	A++
	9	18	-	2.27	4.53	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	12	12	-	3.40	3.40	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	12	14	-	3.14	3.66	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	12	18	-	2.72	4.08	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	14	14	-	3.40	3.40	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	14	18	-	2.98	3.82	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	5	5	5	1.70	1.70	1.70	5.10 (2.00-6.00)	1.23 (0.30-1.47)	4.16	4.5	6.6	A++
	5	5	7	1.68	1.68	2.35	5.70 (2.00-6.80)	1.37 (0.30-1.70)	4.17	5.0	6.5	A++
	5	5	9	1.80	1.80	3.00	6.60 (2.00-7.60)	1.51 (0.30-1.89)	4.38	5.5	6.4	A++
	5	5	12	1.70	1.70	4.09	7.50 (2.00-8.80)	1.72 (0.30-2.26)	4.37	6.5	6.2	A++
	5	5	14	1.67	1.67	4.67	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++
	5	5	18	1.43	1.43	5.14	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.34	6.8	6.2	A++
	5	7	7	1.80	2.40	2.40	6.60 (2.00-7.60)	1.51 (0.30-1.89)	4.38	5.5	6.4	A++
	5	7	9	1.80	1.80	3.00	7.20 (2.00-8.40)	1.65 (0.30-2.11)	4.37	6.0	6.3	A++
5	7	12	1.67	2.33	4.00	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
5	7	14	1.54	2.15	4.31	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
5	7	18	1.33	1.87	4.80	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.34	6.8	6.2	A++	
5	9	9	1.80	3.00	3.00	7.80 (2.00-9.20)	1.79 (0.30-2.37)	4.36	6.5	6.2	A++	
5	9	12	1.54	2.77	3.69	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
5	9	14	1.43	2.57	4.00	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
5	9	18	1.25	2.25	4.50	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.34	6.8	6.2	A++	
5	12	12	1.38	3.31	3.31	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
5	12	14	1.29	3.10	3.61	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
5	12	18	1.14	2.74	4.11	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.34	6.8	6.2	A++	
5	14	14	1.21	3.39	3.39	8.00 (2.00-9.20)	1.84 (0.30-2.37)	4.35	6.8	6.2	A++	
3-unit connection	7	7	7	2.00	2.00	2.00	6.00 (1.8-7.5)	1.37 (0.35-2.20)	4.37	6.0	8.6	A+++
	7	7	9	2.00	2.00	2.50	6.50 (1.8-8.2)	1.59 (0.35-2.46)	4.08	6.5	8.5	A+++
	7	7	12	1.83	3.14	3.14	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	7	14	1.70	3.40	3.40	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	7	18	1.49	3.82	3.82	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	9	9	1.90	2.45	2.45	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	9	12	1.70	2.19	2.91	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	9	14	1.59	2.04	3.17	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	9	18	1.40	1.80	3.60	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	12	12	1.54	2.63	2.63	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	12	14	1.44	2.47	2.89	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7	14	14	1.36	2.72	2.72	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9	9	9	2.27	2.27	2.27	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9	9	12	2.04	2.04	2.72	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9	9	14	1.91	1.91	2.98	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9	9	18	1.70	1.70	3.40	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9	12	12	1.86	2.47	2.47	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9	12	14	1.75	2.33	2.72	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	12	12	12	2.27	2.27	2.27	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++

Notes: \*5: 5000 Btu/h/7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h/14: 14000 Btu/h/18: 18000 Btu/h models  
 \*The above specifications apply when connected with a indoor model except a wall-mounted [KM/KG] unit.  
 \*2 or more indoor units should be connected.  
 \*Cooling capacity is determined based on 27°CDB/19°CWB (indoor temperature) and 35°CDB (outdoor temperature).  
 \*Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)  
 \*Total capacity of indoor units connected must be between 4.0 kW and 10.5 kW.  
 \*Please refer to the Design & Technical manual for the combination tables with a wall-mounted [KM/KG] model.  
 \*For compatible Outer Units with 5,000BTU models, please refer to the Design & Technical manual Part. 1-1

## 3-unit Multi-split heating

AOHG18KBT3	Combination of Indoor Units		Heating Operation					Seasonal Data				
			Heating Capacity			Input Power (Min. - Max.)	COP	Pdesign kW	SCOP	Energy efficiency		
			Unit 1 kW	Unit 2 kW	Unit 3 kW						Total Capacity (Min. - Max.) kW	
2-unit connection	5	9	-	1.80	3.00	-	4.80 (2.00-5.60)	1.04 (0.30-1.34)	4.61	4.0	4.0	A+
	5	12										

# 4-unit Multi-split Combination Table-cooling

## 4-unit Multi-split cooling

AOHG30KBTA4	Combination of Indoor Units		Cooling Operation						Seasonal Data					
			Cooling Capacity				Input Power (Min. - Max.)	EER	Pdesign kW	SEER	Energy efficiency			
			Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW						Total Capacity (Min. - Max.) kW		
2-unit connection	5	22	-	-	1.50	6.00	-	-	7.50 (2.40-9.40)	2.50 (0.45-3.00)	3.00	7.5	6.0	A+
	5	24	-	-	1.38	6.62	-	-	8.00 (2.40-9.50)	2.72 (0.45-3.30)	2.94	8.0	5.9	A+
	7	22	-	-	2.00	6.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	7	24	-	-	1.81	6.19	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	9	22	-	-	2.32	5.68	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	9	24	-	-	2.18	5.82	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	12	18	-	-	3.20	4.80	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	12	22	-	-	2.82	5.18	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	12	24	-	-	2.67	5.33	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	14	18	-	-	3.50	4.50	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	14	22	-	-	3.11	4.89	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	14	24	-	-	2.95	5.05	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	18	18	-	-	4.00	4.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	18	22	-	-	3.60	4.40	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	18	24	-	-	3.43	4.57	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	22	22	-	-	4.00	4.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	22	24	-	-	3.83	4.17	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	24	24	-	-	4.00	4.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	7.5	A++
	5	5	18	-	1.50	1.50	5.00	-	8.00 (2.40-9.60)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++
	5	5	22	-	1.25	1.25	5.50	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++
	5	5	24	-	1.18	1.18	5.65	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++
	5	7	18	-	1.33	1.87	4.80	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++
	5	7	22	-	1.18	1.65	5.18	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++
	5	7	24	-	1.11	1.56	5.33	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++
5	9	14	-	1.50	2.50	4.00	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	9	18	-	1.25	2.25	4.50	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	9	22	-	1.11	2.00	4.89	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	9	24	-	1.05	1.89	5.05	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	12	12	-	1.38	3.31	3.31	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	12	14	-	1.29	3.10	3.61	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	12	18	-	1.14	2.74	4.11	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	12	22	-	1.03	2.46	4.51	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	12	24	-	0.98	2.34	4.68	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	14	14	-	1.21	3.39	3.39	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	14	18	-	1.08	3.03	3.89	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	14	22	-	0.98	2.73	4.29	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	14	24	-	0.93	2.60	4.47	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	18	18	-	0.98	3.51	3.51	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	18	22	-	0.89	3.20	3.91	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
5	18	24	-	0.85	3.06	4.09	-	8.00 (2.40-10.0)	2.37 (0.45-3.30)	3.38	8.0	6.3	A++	
7	7	12	-	2.00	2.00	3.50	-	7.50 (2.4-9.3)	2.10 (0.45-2.84)	3.57	7.5	8.1	A++	
7	7	14	-	2.00	2.00	4.00	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	7	18	-	1.75	1.75	4.50	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	7	22	-	1.56	1.56	4.88	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	7	24	-	1.47	1.47	5.06	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	9	9	-	2.00	2.50	2.50	-	7.00 (2.4-8.9)	1.90 (0.45-2.65)	3.69	7.0	8.2	A++	
7	9	12	-	2.00	2.50	3.50	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	9	14	-	1.87	2.40	3.73	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	9	18	-	1.64	2.12	4.24	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	9	22	-	1.47	1.89	4.64	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	9	24	-	1.40	1.80	4.80	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	12	12	-	1.80	3.10	3.10	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	12	14	-	1.70	2.91	3.39	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	12	18	-	1.51	2.59	3.90	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	12	22	-	1.37	2.34	4.29	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	12	24	-	1.30	2.23	4.47	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	14	14	-	1.60	3.20	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	14	18	-	1.44	2.87	3.69	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	14	22	-	1.30	2.60	4.10	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	14	24	-	1.24	2.49	4.27	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	18	18	-	1.30	3.35	3.35	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	18	22	-	1.19	3.06	3.75	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
7	18	24	-	1.14	2.94	3.92	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	9	9	-	2.50	2.50	2.50	-	7.50 (2.4-9.6)	2.10 (0.45-3.01)	3.57	7.5	8.1	A++	
9	9	12	-	2.40	2.40	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	9	14	-	2.25	2.25	3.50	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	9	18	-	2.00	2.00	4.00	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	9	22	-	1.80	1.80	4.40	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	9	24	-	1.71	1.71	4.58	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	12	12	-	2.18	2.91	2.91	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	12	14	-	2.06	2.74	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	12	18	-	1.85	2.46	3.69	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	12	22	-	1.67	2.23	4.10	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	12	24	-	1.60	2.13	4.27	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	14	14	-	1.94	3.03	3.03	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	14	18	-	1.76	2.73	3.51	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	14	22	-	1.60	2.49	3.91	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	14	24	-	1.53	2.38	4.09	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
9	18	18	-	1.60	3.20	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	12	12	-	2.67	2.67	2.67	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	12	14	-	2.53	2.53	2.94	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	12	18	-	2.29	2.29	3.42	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	12	22	-	2.09	2.09	3.82	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	12	24	-	2.00	2.00	4.00	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	14	14	-	2.40	2.80	2.80	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	14	18	-	2.18	2.55	3.27	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
12	14	22	-	2.00	2.40	3.60	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
14	14	14	-	2.67	2.67	2.67	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	
14	14	18	-	2.43	2.43	3.14	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	8.0	A++	

## 4-unit Multi-split cooling

AOHG30KBTA4	Combination of Indoor Units		Cooling Operation						Seasonal Data					
			Cooling Capacity				Input Power (Min. - Max.)	EER	Pdesign kW	SEER	Energy efficiency			
			Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW						Total Capacity (Min. - Max.) kW		
4-unit connection	5	5	5	12	1.39	1.39	1.39	3.33	7.50 (2.40-9.30)	1.99 (0.45-3.00)	3.77	8.0	6.7	A++
	5	5	5	14	1									



# 4-unit Multi-split Combination Table-Heating

### 4-unit Multi-split heating

AOHG30KBTA4	Combination of Indoor Units		Heating Operation						Seasonal Data				
			Heating Capacity				Input Power (Min. - Max.)	COP	Pdesign	SCOP	Energy efficiency		
			Unit 1	Unit 2	Unit 3	Unit 4						Total Capacity (Min. - Max.)	
			kW	kW	kW	kW	kW	kW					
2-unit connection	5	22	-	-	-	-	9.00 (3.00-10.60)	2.46 (0.30-2.83)	3.66	6.0	4.0	A+	
	5	24	-	-	-	-	9.60 (3.00-10.70)	2.55 (0.30-3.03)	3.76	6.5	3.9	A	
	7	22	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	7	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	9	22	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	9	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	12	18	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	12	22	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	12	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	14	18	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	14	22	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	14	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	18	18	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	18	22	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	18	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	22	22	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	22	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	24	24	-	-	-	-	9.60 (3.0-11.2)	2.47 (0.30-2.95)	3.89	6.5	4.1	A+	
	5	5	18	-	-	6.17	-	9.60 (3.00-10.70)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+
	5	5	22	-	-	6.60	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+
	5	5	24	-	-	6.78	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+
	5	7	18	-	-	5.76	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+
	5	7	22	-	-	6.21	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+
	5	7	24	-	-	6.40	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+
5	9	14	-	-	4.80	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	9	18	-	-	5.40	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	9	22	-	-	5.87	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	9	24	-	-	6.06	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	12	12	-	-	3.97	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	12	14	-	-	4.34	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	12	18	-	-	4.94	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	12	22	-	-	5.42	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	12	24	-	-	5.62	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	14	14	-	-	4.07	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	14	18	-	-	4.67	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	14	22	-	-	5.15	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	14	24	-	-	5.36	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	18	18	-	-	4.21	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	18	22	-	-	4.69	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
5	18	24	-	-	4.90	-	9.60 (3.00-11.20)	2.36 (0.30-3.03)	4.07	6.5	4.0	A+	
7	7	12	-	-	2.40	-	9.00 (3.0-10.4)	2.11 (0.30-2.60)	4.27	6.0	4.4	A+	
7	7	14	-	-	2.40	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	7	18	-	-	2.10	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	7	22	-	-	1.87	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	7	24	-	-	1.77	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	9	9	-	-	3.00	-	8.40 (3.0-10.0)	1.94 (0.30-2.45)	4.32	6.0	4.4	A+	
7	9	12	-	-	3.00	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	9	14	-	-	2.88	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	9	18	-	-	2.54	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	9	22	-	-	2.27	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	9	24	-	-	2.16	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	12	12	-	-	3.72	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	12	14	-	-	3.49	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	12	18	-	-	3.11	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	12	22	-	-	2.81	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	12	24	-	-	2.68	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	14	14	-	-	3.84	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	14	18	-	-	4.43	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	14	22	-	-	3.13	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	14	24	-	-	2.99	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	18	18	-	-	4.02	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	18	22	-	-	3.68	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
7	18	24	-	-	3.53	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	9	9	-	-	3.00	-	9.00 (3.0-10.8)	2.11 (0.30-2.76)	4.27	6.0	4.4	A+	
9	9	12	-	-	2.88	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	9	14	-	-	2.70	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	9	18	-	-	2.40	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	9	22	-	-	2.16	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	9	24	-	-	2.06	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	12	12	-	-	3.49	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	12	14	-	-	3.29	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	12	18	-	-	2.95	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	12	22	-	-	2.68	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	12	24	-	-	2.56	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	14	14	-	-	3.63	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	14	18	-	-	4.21	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	14	22	-	-	2.99	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	14	24	-	-	2.86	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
9	18	18	-	-	3.84	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	12	12	-	-	3.20	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	12	14	-	-	3.03	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	12	18	-	-	2.74	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	12	22	-	-	2.50	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	12	24	-	-	2.40	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	14	14	-	-	3.36	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	14	18	-	-	3.93	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
12	14	22	-	-	3.60	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
14	14	14	-	-	3.20	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	
14	14	18	-	-	2.92	-	9.60 (3.0-11.2)	2.27 (0.30-2.95)	4.22	6.5	4.3	A+	

### 4-unit Multi-split heating

AOHG30KBTA4	Combination of Indoor Units		Heating Operation						Seasonal Data				
			Heating Capacity				Input Power (Min. - Max.)	COP	Pdesign	SCOP	Energy efficiency		
			Unit 1	Unit 2	Unit 3	Unit 4						Total Capacity (Min. - Max.)	
			kW	kW	kW	kW	kW	kW					



# 5-unit Multi-split Combination Table-Cooling

## 5-unit Multi-split cooling

AOHG36K8TA5	Combination of Indoor Units					Cooling Operation						Seasonal Data				
						Cooling Capacity					Input Power (Min. - Max.) kW	EER	Pdesign kW	SEER	Energy efficiency	
						Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW						Total Capacity (Min. - Max.) kW
2-unit connection	5	22	-	-	-	1.50	6.00	-	-	-	7.50 (3.00-9.60)	1.70 (0.30-2.84)	4.42	7.5	6.1	A++
	5	24	-	-	-	1.50	7.00	-	-	-	8.50 (3.00-10.30)	2.19 (0.30-3.13)	3.88	8.5	6.0	A+
	7	24	-	-	-	2.00	7.00	-	-	-	9.00 (3.00-11.0)	2.91 (0.30-3.45)	3.09	9.0	7.9	A+
	9	22	-	-	-	2.50	6.00	-	-	-	8.50 (3.00-11.0)	2.67 (0.30-3.45)	3.18	8.5	7.9	A++
	9	24	-	-	-	2.50	7.00	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	12	22	-	-	-	3.50	6.00	-	-	-	9.00 (3.00-11.0)	1.03 (0.30-4.54)	3.00	9.0	7.8	A++
	12	24	-	-	-	3.17	6.33	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	14	22	-	-	-	3.69	5.81	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	14	24	-	-	-	3.50	6.00	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	18	18	-	-	-	4.75	4.75	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	18	22	-	-	-	4.27	5.23	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	18	24	-	-	-	4.07	5.43	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	22	22	-	-	-	4.75	4.75	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	22	24	-	-	-	4.54	4.96	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	24	24	-	-	-	4.75	4.75	-	-	-	9.50 (3.00-11.0)	3.17 (0.30-3.45)	3.00	9.5	7.8	A++
	5	5	18	-	-	1.43	1.43	5.14	-	-	8.00 (3.00-9.70)	2.36 (0.30-2.98)	3.38	8.0	6.3	A++
	5	5	22	-	-	1.41	1.41	6.19	-	-	9.00 (3.00-11.0)	2.69 (0.30-3.46)	3.35	9.0	6.2	A++
	5	5	24	-	-	1.40	1.40	6.71	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	7	18	-	-	1.42	1.98	5.10	-	-	8.50 (3.00-10.40)	2.61 (0.30-3.28)	3.26	8.5	6.2	A++
	5	7	22	-	-	1.40	1.96	6.15	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	7	24	-	-	1.32	1.85	6.33	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	9	14	-	-	1.43	2.57	4.00	-	-	8.00 (3.00-10.0)	2.36 (0.30-2.98)	3.38	8.0	6.3	A++
	5	9	18	-	-	1.41	2.53	5.06	-	-	9.00 (3.00-11.0)	2.69 (0.30-3.46)	3.35	9.0	6.2	A++
	5	9	22	-	-	1.32	2.38	5.81	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	9	24	-	-	1.25	2.25	6.00	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	12	12	-	-	1.38	3.31	3.31	-	-	8.00 (3.00-10.40)	2.47 (0.30-3.13)	3.23	8.5	6.2	A++
	5	12	14	-	-	1.45	3.48	4.06	-	-	9.00 (3.00-11.0)	2.69 (0.30-3.46)	3.35	9.0	6.2	A++
	5	12	18	-	-	1.36	3.26	4.89	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	12	22	-	-	1.22	2.92	5.36	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	12	24	-	-	1.16	2.78	5.56	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	14	14	-	-	1.44	4.03	4.03	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	14	18	-	-	1.38	3.59	4.62	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	14	22	-	-	1.16	3.24	5.10	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	14	24	-	-	1.10	3.09	5.30	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	18	18	-	-	1.16	4.17	4.17	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	18	22	-	-	1.06	3.80	4.64	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	18	24	-	-	1.01	3.64	4.85	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	22	22	-	-	0.97	4.27	4.27	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	22	24	-	-	0.93	4.10	4.47	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	5	24	24	-	-	0.90	4.30	4.30	-	-	9.50 (3.00-11.0)	2.92 (0.30-3.46)	3.26	9.5	6.1	A++
	7	7	14	-	-	2.00	2.00	5.00	-	-	8.00 (3.00-10.0)	2.76 (0.30-3.88)	3.54	8.0	8.2	A++
	7	7	18	-	-	2.00	2.00	5.00	-	-	9.00 (3.00-11.0)	2.68 (0.30-3.45)	3.36	9.0	8.1	A++
	7	7	22	-	-	1.85	1.85	5.80	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	7	24	-	-	1.75	1.75	6.00	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	9	12	-	-	2.00	2.50	3.50	-	-	8.00 (3.00-10.0)	2.26 (0.30-2.88)	3.54	8.0	8.2	A++
	7	9	14	-	-	2.00	2.50	4.00	-	-	8.50 (3.00-10.7)	2.46 (0.30-3.27)	3.45	8.5	8.1	A++
	7	9	18	-	-	2.00	2.50	5.00	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	9	22	-	-	1.75	2.25	5.50	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	9	24	-	-	1.66	2.14	5.70	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	12	12	-	-	2.00	3.50	4.00	-	-	8.00 (3.00-10.0)	2.76 (0.30-3.88)	3.54	8.0	8.2	A++
	7	12	14	-	-	2.00	3.50	4.00	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	12	18	-	-	1.80	3.08	4.62	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	12	22	-	-	1.62	2.78	5.10	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	12	24	-	-	1.55	2.65	5.30	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	14	14	-	-	1.90	3.80	3.80	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	14	18	-	-	1.71	3.41	4.38	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	14	22	-	-	1.55	3.09	4.86	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	14	24	-	-	1.47	2.96	5.07	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	18	18	-	-	1.54	3.98	3.98	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	18	22	-	-	1.41	3.64	4.45	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	7	18	24	-	-	1.36	3.49	4.65	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	9	9	-	-	2.50	2.50	2.50	-	-	7.50 (3.00-9.6)	2.07 (0.30-2.70)	3.63	7.5	8.2	A++
	9	9	12	-	-	2.50	2.50	3.50	-	-	8.50 (3.00-10.7)	2.46 (0.30-3.27)	3.45	8.5	8.1	A++
	9	9	14	-	-	2.50	2.50	4.00	-	-	9.00 (3.00-11.0)	2.68 (0.30-3.45)	3.36	9.0	8.1	A++
	9	9	18	-	-	2.38	2.38	4.74	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	9	22	-	-	2.14	2.14	5.22	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	9	24	-	-	2.04	2.04	5.42	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	12	12	-	-	2.50	3.50	3.50	-	-	8.00 (3.00-10.0)	2.76 (0.30-3.88)	3.54	8.0	8.2	A++
	9	12	14	-	-	2.44	3.46	3.80	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	12	18	-	-	2.19	2.92	4.39	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	12	22	-	-	1.99	2.65	4.86	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	12	24	-	-	1.90	2.53	5.07	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	14	14	-	-	2.32	3.59	3.59	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	14	18	-	-	2.09	3.24	4.17	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	14	22	-	-	1.90	2.96	4.64	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	14	24	-	-	1.82	2.83	4.85	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	18	18	-	-	1.90	3.80	3.90	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	18	22	-	-	1.74	3.49	4.27	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	9	18	24	-	-	1.68	3.35	4.47	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	12	12	12	-	-	3.17	3.17	3.17	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	12	12	14	-	-	3.00	3.00	3.50	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	12	12	18	-	-	2.71	2.71	4.08	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	12	12	22	-	-	2.48	2.48	4.54	-	-	9.50 (3.00-11.0)	2.91 (0.30-3.45)	3.27	9.5	8.0	A++
	12	12														

# 5-unit Multi-split Combination Table-cooling

## 5-unit Multi-split cooling

AOHG36K8TA5	Combination of Indoor Units					Cooling Operation				Seasonal Data						
						Cooling Capacity					Input Power (Min. - Max.)	EER	Pdesign	SEER	Energy efficiency	
						Unit 1	Unit 2	Unit 3	Unit 4	Unit 5						Total Capacity (Min. - Max.)
					kW	kW	kW	kW	kW	kW						
4-unit connection	9	9	12	14	-	1.94	1.94	2.59	3.03	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	9	12	18	-	1.78	1.78	2.38	3.56	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	9	12	22	-	1.64	1.64	2.19	4.03	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	9	12	24	-	1.58	1.58	2.11	4.23	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	9	14	14	-	1.86	1.86	2.89	2.89	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	9	14	18	-	1.71	1.71	2.66	3.42	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	9	18	18	-	1.58	1.58	3.17	3.17	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	12	12	12	-	1.91	2.53	2.53	2.53	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	12	12	14	-	1.81	2.43	2.43	2.83	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	12	12	18	-	1.67	2.24	2.24	3.35	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	12	14	14	-	1.74	2.34	2.71	2.71	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
	9	12	14	18	-	1.61	2.15	2.51	3.23	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++
9	14	14	14	-	1.67	2.61	2.61	2.61	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++	
12	12	12	12	-	2.38	2.38	2.38	2.38	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++	
12	12	12	14	-	2.28	2.28	2.28	2.66	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++	
12	12	12	18	-	2.11	2.11	2.11	3.17	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++	
12	12	14	14	-	2.19	2.19	2.56	2.56	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++	
12	14	14	14	-	2.12	2.46	2.46	2.46	-	9.50 (3.0-11.0)	2.69 (0.30-3.45)	3.53	9.5	8.3	A++	
5	5	5	5	7	1.39	1.39	1.39	1.94	1.94	7.50 (3.00-9.60)	1.72 (0.30-2.84)	4.35	8.5	6.6	A++	
5	5	5	5	9	1.38	1.38	1.38	2.48	2.48	8.00 (3.00-10.40)	1.92 (0.30-3.13)	4.17	9.5	6.5	A++	
5	5	5	5	12	1.41	1.41	1.41	3.38	3.38	9.00 (3.00-11.00)	2.21 (0.30-3.46)	4.06	9.5	6.5	A++	
5	5	5	5	14	1.40	1.40	1.40	3.91	3.91	9.50 (3.00-11.00)	2.41 (0.30-3.46)	3.94	9.5	6.5	A++	
5	5	5	5	18	1.25	1.25	1.25	4.50	4.50	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	5	22	1.13	1.13	1.13	4.98	4.98	9.50 (3.00-11.00)	2.69 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	5	24	1.08	1.08	1.08	5.18	5.18	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	7	7	1.38	1.38	1.38	1.93	1.93	8.00 (3.00-10.40)	1.92 (0.30-3.13)	4.17	9.0	6.6	A++	
5	5	5	7	9	1.45	1.45	1.45	2.03	2.03	9.00 (3.00-11.00)	2.12 (0.30-3.46)	4.25	9.5	6.5	A++	
5	5	5	7	12	1.40	1.40	1.40	1.96	1.96	9.50 (3.00-11.00)	2.41 (0.30-3.46)	3.94	9.5	6.5	A++	
5	5	5	7	14	1.32	1.32	1.32	1.85	1.85	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	7	18	1.19	1.19	1.19	1.66	1.66	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	7	22	1.08	1.08	1.08	1.51	1.51	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	7	24	1.03	1.03	1.03	1.45	1.45	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	9	9	1.44	1.44	1.44	2.59	2.59	9.50 (3.00-11.00)	2.51 (0.30-3.46)	4.11	9.5	6.5	A++	
5	5	5	9	12	1.32	1.32	1.32	2.38	2.38	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	9	14	1.25	1.25	1.25	2.25	2.25	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	9	18	1.13	1.13	1.13	2.04	2.04	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	9	22	1.03	1.03	1.03	1.86	1.86	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	9	24	0.99	0.99	0.99	1.78	1.78	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	12	12	1.22	1.22	1.22	2.92	2.92	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	12	14	1.16	1.16	1.16	2.78	2.78	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	12	18	1.06	1.06	1.06	2.53	2.53	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	12	22	0.97	0.97	0.97	2.37	2.37	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	12	24	0.93	0.93	0.93	2.24	2.24	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	14	14	1.10	1.10	1.10	3.09	3.09	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	14	18	1.01	1.01	1.01	2.83	2.83	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	14	22	0.93	0.93	0.93	2.61	2.61	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	14	24	0.90	0.90	0.90	2.51	2.51	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	5	18	18	0.93	0.93	0.93	3.35	3.35	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.0	6.6	A++	
5	5	7	7	7	1.45	1.45	2.03	2.03	2.03	9.00 (3.00-11.00)	2.12 (0.30-3.46)	4.25	9.5	6.5	A++	
5	5	7	7	9	1.44	1.44	2.02	2.02	2.59	9.50 (3.00-11.00)	2.51 (0.30-3.46)	4.11	9.5	6.5	A++	
5	5	7	7	12	1.32	1.32	1.85	1.85	3.17	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	7	14	1.25	1.25	1.75	1.75	3.50	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	7	18	1.13	1.13	1.58	1.58	4.07	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	7	22	1.03	1.03	1.45	1.45	4.54	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	7	24	0.99	0.99	1.39	1.39	4.75	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	9	9	1.36	1.36	1.90	2.44	2.44	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	9	12	1.25	1.25	1.75	2.25	3.00	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	9	14	1.19	1.19	1.66	2.14	3.33	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	9	18	1.08	1.08	1.44	1.94	3.89	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	9	22	0.99	0.99	1.39	1.78	4.35	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	9	24	0.95	0.95	1.33	1.71	4.56	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	12	12	1.16	1.16	1.62	2.78	2.78	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	12	14	1.10	1.10	1.55	2.65	3.09	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	12	18	1.01	1.01	1.41	2.43	3.64	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	12	22	0.93	0.93	1.30	2.24	4.10	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	12	24	0.90	0.90	1.25	2.15	4.30	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	14	14	1.06	1.06	1.48	2.96	2.96	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	14	18	0.97	0.97	1.36	2.71	3.49	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	14	22	0.90	0.90	1.25	2.51	3.94	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	7	18	18	0.90	0.90	1.25	2.23	3.23	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	9	9	1.28	1.28	2.31	2.31	2.31	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	9	12	1.19	1.19	2.14	2.14	2.85	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	9	14	1.13	1.13	2.04	2.04	3.17	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	9	18	1.03	1.03	1.86	1.86	3.72	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	9	22	0.95	0.95	1.71	1.71	4.18	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	9	24	0.91	0.91	1.64	1.64	4.38	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	12	12	1.10	1.10	1.99	2.65	2.65	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	12	14	1.06	1.06	1.90	2.53	2.96	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	12	18	0.97	0.97	1.74	2.33	3.49	9.50 (3.00-11.00)	2.51 (0.30-3.46)	3.78	9.5	6.5	A++	
5	5	9	12													





# 5-unit Multi-split Combination Table-Heating

## 5-unit Multi-split heating

AOHG36K8TA5	Combination of Indoor Units	Heating Operation							Seasonal Data			
		Heating Capacity					Input Power (Min. - Max.) kW	COP	Pdesign kW	SCOP	Energy efficiency	
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW						Total Capacity (Min. - Max.) kW
2-unit connection	5 22 - - - 1.67 7.33 - - - 9.00 (3.50-10.80) 2.28 (0.25-2.84) 3.94 6.0 4.1 A++											
	5 24 - - - 1.66 7.94 - - - 9.60 (3.50-11.60) 2.41 (0.25-3.12) 3.98 6.8 4.0 A+											
	7 24 - - - 2.39 8.21 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	9 22 - - - 3.00 7.20 - - - 10.20 (3.5-12.0) 2.52 (0.25-3.25) 4.04 6.8 4.3 A+											
	9 24 - - - 2.89 7.71 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	12 22 - - - 3.74 6.86 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	12 24 - - - 3.53 7.07 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	14 22 - - - 4.12 6.48 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	14 24 - - - 3.91 6.69 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	18 18 - - - 5.30 5.30 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	18 22 - - - 4.77 5.83 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	18 24 - - - 4.54 6.06 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	22 22 - - - 5.30 5.30 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	22 24 - - - 5.07 5.53 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	24 24 - - - 5.30 5.30 - - - 10.60 (3.5-12.0) 2.65 (0.25-3.25) 4.00 7.0 4.3 A+											
	5 5 18 - - - 1.71 1.71 6.17 - - - 9.60 (3.50-10.90) 2.34 (0.25-2.96) 4.10 6.5 4.2 A++											
	5 5 22 - - - 1.66 1.66 7.29 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 5 24 - - - 1.56 1.56 7.48 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 7 18 - - - 1.70 2.38 6.12 - - - 10.20 (3.50-11.60) 2.43 (0.25-3.26) 4.19 6.8 4.1 A++											
	5 7 22 - - - 1.56 2.18 6.86 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 7 24 - - - 1.47 2.06 7.07 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 9 14 - - - 1.71 3.09 4.80 - - - 9.60 (3.50-11.20) 2.34 (0.25-2.96) 4.10 6.5 4.2 A++											
	5 9 18 - - - 1.66 2.98 5.96 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 9 22 - - - 1.47 2.65 6.48 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 9 24 - - - 1.39 2.51 6.69 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 12 12 - - - 1.71 4.10 4.10 - - - 9.90 (3.50-11.60) 2.41 (0.25-3.12) 4.11 6.8 4.1 A++											
	5 12 14 - - - 1.71 4.10 4.79 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 12 18 - - - 1.51 3.63 5.45 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 12 22 - - - 1.36 3.26 5.98 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 12 24 - - - 1.29 3.10 6.20 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 14 14 - - - 1.61 4.50 4.50 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 14 18 - - - 1.43 4.01 5.16 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 14 22 - - - 1.29 3.62 5.69 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 14 24 - - - 1.23 3.45 5.92 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 18 18 - - - 1.29 4.65 4.65 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 18 22 - - - 1.18 4.24 5.18 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 18 24 - - - 1.13 4.06 5.41 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 22 22 - - - 1.08 4.76 4.76 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 22 24 - - - 1.04 4.57 4.99 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
	5 24 24 - - - 1.00 4.80 4.80 - - - 10.60 (3.50-12.00) 2.55 (0.25-3.26) 4.16 7.0 4.1 A++											
7 7 14 - - - 2.40 2.40 4.80 - - - 9.60 (3.5-11.2) 2.25 (0.25-2.87) 4.26 6.5 4.5 A+												
7 7 18 - - - 2.32 3.42 5.96 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 7 22 - - - 2.06 2.06 6.48 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 7 24 - - - 1.95 1.95 6.70 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 9 12 - - - 2.40 3.00 4.20 - - - 9.60 (3.5-11.2) 2.25 (0.25-2.87) 4.26 6.5 4.5 A+												
7 9 14 - - - 2.40 3.00 4.80 - - - 10.20 (3.5-12.0) 2.42 (0.25-3.25) 4.21 6.8 4.4 A+												
7 9 18 - - - 2.18 2.81 5.61 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 9 22 - - - 1.95 2.51 6.14 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 9 24 - - - 1.85 2.39 6.36 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 12 12 - - - 2.40 4.10 4.10 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 12 14 - - - 2.25 3.85 4.50 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 12 18 - - - 2.00 3.44 5.16 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 12 22 - - - 1.81 3.10 5.69 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 12 24 - - - 1.72 2.96 5.92 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 14 14 - - - 2.12 4.24 4.24 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 14 18 - - - 1.90 3.81 4.89 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 14 22 - - - 1.73 3.45 5.42 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 14 24 - - - 1.65 3.30 5.65 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 18 18 - - - 1.72 4.44 4.44 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 18 22 - - - 1.58 4.06 4.96 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
7 18 24 - - - 1.51 3.89 5.20 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 9 9 - - - 3.00 3.00 3.00 - - - 9.00 (3.5-10.8) 2.09 (0.25-2.70) 4.31 6.0 4.5 A+												
9 9 12 - - - 3.00 3.00 4.20 - - - 10.20 (3.5-12.0) 2.42 (0.25-3.25) 4.21 6.8 4.4 A+												
9 9 14 - - - 2.98 2.98 4.64 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 9 18 - - - 2.65 2.65 5.30 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 9 22 - - - 2.39 2.39 5.82 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 9 24 - - - 2.27 2.27 6.06 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 12 12 - - - 2.00 3.85 3.85 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 12 14 - - - 1.79 3.63 4.44 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 12 18 - - - 2.45 3.26 4.89 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 12 22 - - - 2.22 2.96 5.42 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 12 24 - - - 2.12 2.83 5.65 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 14 14 - - - 2.58 4.01 4.01 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 14 18 - - - 2.33 3.62 4.65 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 14 22 - - - 2.12 3.30 5.18 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 14 24 - - - 2.03 3.16 5.41 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 18 18 - - - 2.44 4.24 4.24 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 18 22 - - - 1.95 3.89 4.76 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
9 18 24 - - - 1.87 3.74 4.99 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 12 12 - - - 3.53 3.53 3.53 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 12 14 - - - 3.35 3.35 3.90 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 12 18 - - - 3.03 3.03 4.54 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 12 22 - - - 2.77 2.77 5.06 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 12 24 - - - 2.65 2.65 5.30 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 14 14 - - - 3.18 3.71 3.71 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 14 18 - - - 2.89 3.37 4.34 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 14 22 - - - 2.65 3.09 4.86 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 14 24 - - - 2.54 2.97 5.09 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 18 18 - - - 2.64 3.98 3.98 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 18 22 - - - 2.45 3.67 4.48 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
12 18 24 - - - 2.36 3.53 4.71 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
14 14 14 - - - 3.53 3.53 3.53 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
14 14 18 - - - 3.23 3.23 4.14 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
14 14 22 - - - 2.97 2.97 4.66 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
14 14 24 - - - 2.85 2.85 4.90 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
14 18 18 - - - 2.96 3.82 3.82 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
18 18 18 - - - 3.53 3.53 3.53 - - - 10.60 (3.5-12.0) 2.54 (0.25-3.25) 4.18 7.0 4.4 A+												
5 5 5 12 - - - 1.67 1.67 1.67 4.00 - 9.00 (3.50-10.80) 2.21 (0.25-2.84) 4.07 6.5 4.3 A++												
5 5 5 14 - - - 1.66 1.66 1.66 4.63 - 9.60 (3.50-11.60) 2.31 (0.25-3.12) 4.16 6.8 4.2 A++												
5 5 5 18 - - - 1.61 1.61 1.61 5.78 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 5 22 - - - 1.43 1.43 1.43 6.30 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 5 24 - - - 1.36 1.36 1.36 6.52 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 7 12 - - - 1.66 1.66 2.32 3.97 - 9.60 (3.50-11.60) 2.31 (0.25-3.12) 4.16 6.8 4.2 A++												
5 5 7 14 - - - 1.71 1.71 2.39 4.79 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 7 18 - - - 1.51 1.51 2.12 5.45 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 7 22 - - - 1.36 1.36 1.90 5.98 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 7 24 - - - 1.29 1.29 1.81 6.20 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 9 9 - - - 1.71 1.71 3.09 3.09 - 9.60 (3.50-11.20) 2.26 (0.25-2.96) 4.25 6.5 4.3 A++												
5 5 9 12 - - - 1.71 1.71 3.08 4.10 - 10.60 (3.50-12.00) 2.40 (0.25-3.26) 4.41 7.0 4.2 A++												
5 5 9 14 - - - 1.61 1.61 2.89 4.50 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 9 18 - - - 1.43 1.43 2.58 5.16 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 9 22 - - - 1.29 1.29 2.33 5.69 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 9 24 - - - 1.23 1.23 2.22 5.92 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 12 12 - - - 1.56 1.56 3.74 3.74 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												
5 5 12 14 - - - 1.47 1.47 3.53 4.12 - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++												

## 5-unit Multi-split heating

AOHG36K8TA5	Combination of Indoor Units	Heating Operation							Seasonal Data			
		Heating Capacity					Input Power (Min. - Max.) kW	COP	Pdesign kW	SCOP	Energy efficiency	
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW						Total Capacity (Min. - Max.) kW
2-unit connection	5 5 12 18 - - - 1.33 1.33 3.18 4.77 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 12 22 - - - 1.20 1.20 2.89 5.30 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 12 24 - - - 1.15 1.15 2.77 5.53 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 14 14 - - - 1.39 1.39 3.91 3.91 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 14 18 - - - 1.26 1.26 3.53 4.54 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 14 22 - - - 1.15 1.15 3.23 5.07 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 14 24 - - - 1.10 1.10 3.09 5.30 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 18 18 - - - 1.15 1.15 4.15 4.15 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 18 22 - - - 1.06 1.06 3.82 4.66 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 5 18 24 - - - 1.02 1.02 3.67 4.89 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 7 7 9 - - - 1.71 2.40 2.40 3.09 - - - 9.60 (3.50-11.20) 2.26 (0.25-2.96) 4.25 7.0 4.2 A++											
	5 7 7 12 - - - 1.71 2.39 2.39 4.10 - - - 10.60 (3.50-12.00) 2.40 (0.25-3.26) 4.41 7.0 4.2 A++											
	5 7 7 14 - - - 1.61 2.25 2.25 4.50 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 7 7 18 - - - 1.43 2.01 2.01 5.16 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 7 12 12 - - - 1.29 1.81 1.81 5.69 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 7 7 24 - - - 1.23 1.73 1.73 5.92 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 6.8 4.2 A++											
	5 7 9 9 - - - 1.70 2.38 3.06 3.06 - - - 10.20 (3.50-12.00) 2.34 (0.25-3.26) 4.35 7.0 4.2 A++											
	5 7 9 12 - - - 1.61 2.25 2.89 3.85 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 7 9 14 - - - 1.51 2.12 2.73 4.24 - - - 10.60 (3.50-12.00) 2.45 (0.25-3.26) 4.32 7.0 4.2 A++											
	5 7 9 18 - - - 1.36 1.9											



# 5-unit Multi-split Combination Table-Heating

## 5-unit Multi-split heating

AOHG36K8TA5	Combination of Indoor Units					Heating Operation						Seasonal Data				
						Heating Capacity					Input Power (Min. - Max.)	COP	Pdesign	SCOP	Energy efficiency	
						Unit 1	Unit 2	Unit 3	Unit 4	Unit 5						Total Capacity (Min. - Max.)
						kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
4-unit connection	9	9	12	14	-	2.17	2.17	2.89	3.37	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	9	12	18	-	1.99	1.99	2.64	3.98	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	9	12	22	-	1.83	1.83	2.45	4.49	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	9	12	24	-	1.77	1.77	2.35	4.71	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	9	14	14	-	2.07	2.07	3.23	3.23	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	9	14	18	-	1.91	1.91	2.96	3.82	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	9	18	18	-	1.77	1.77	3.53	3.53	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	12	12	12	-	2.11	2.83	2.83	2.83	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	12	12	14	-	2.02	2.71	2.71	3.16	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	12	12	18	-	1.87	2.49	2.49	3.75	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	12	14	14	-	1.94	2.60	3.03	3.03	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	12	14	18	-	1.80	2.40	2.80	3.60	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	9	14	14	14	-	1.87	2.91	2.91	2.91	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	12	12	12	12	-	2.65	2.65	2.65	2.65	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	12	12	14	9	-	2.54	2.54	2.54	2.98	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	12	12	18	-	-	2.36	2.36	2.36	3.52	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	12	12	14	14	-	2.45	2.45	2.85	2.85	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	12	14	14	14	-	2.35	2.75	2.75	2.75	-	10.60 (3.5-12.0)	2.44 (0.25-3.25)	4.34	7.0	4.5	A+
	5	5	5	5	7	1.39	1.39	1.39	1.99	1.94	7.50 (3.50-10.80)	1.98 (0.25-2.84)	3.78	6.8	4.3	A+
	5	5	5	5	9	1.38	1.38	1.38	1.98	2.48	8.00 (3.50-11.60)	2.08 (0.25-3.12)	3.85	7.0	4.3	A++
	5	5	5	5	12	1.41	1.41	1.41	1.41	3.38	9.00 (3.50-12.00)	2.37 (0.25-3.26)	3.80	7.0	4.3	A++
	5	5	5	5	14	1.40	1.40	1.40	1.40	3.91	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	5	18	1.25	1.25	1.25	1.25	4.50	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	5	22	1.13	1.13	1.13	1.13	4.98	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	5	24	1.08	1.08	1.08	1.08	5.18	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	6.8	4.3	A++
	5	5	5	7	7	1.38	1.38	1.38	1.93	1.93	8.00 (3.50-11.60)	2.08 (0.25-3.12)	3.85	7.0	4.3	A++
	5	5	5	7	9	1.45	1.45	1.45	2.03	2.61	9.00 (3.50-12.00)	2.18 (0.25-3.26)	4.14	7.0	4.3	A++
	5	5	5	7	12	1.40	1.40	1.40	1.96	3.35	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	7	14	1.32	1.32	1.32	1.85	3.69	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	7	18	1.19	1.19	1.19	1.66	4.28	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	7	22	1.08	1.08	1.08	1.51	4.75	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	7	24	1.03	1.03	1.03	1.45	4.96	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	9	9	1.44	1.44	1.44	1.59	2.59	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	9	12	1.32	1.32	1.32	2.38	3.17	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	9	14	1.25	1.25	1.25	2.25	3.50	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	9	18	1.13	1.13	1.13	2.04	4.07	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	9	22	1.03	1.03	1.03	1.86	4.54	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	9	24	0.99	0.99	0.99	1.78	4.75	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	12	12	1.22	1.22	1.22	2.92	2.92	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	12	14	1.16	1.16	1.16	2.78	3.24	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	12	18	1.06	1.06	1.06	2.53	3.80	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	12	22	0.97	0.97	0.97	2.33	4.27	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	12	24	0.93	0.93	0.93	2.24	4.47	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	14	14	1.10	1.10	1.10	3.09	3.09	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	14	18	1.01	1.01	1.01	2.83	3.64	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	14	22	0.93	0.93	0.93	2.61	4.10	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	14	24	0.90	0.90	0.90	2.51	4.30	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	5	18	18	0.93	0.93	0.93	3.35	3.35	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.2	A++
	5	5	7	7	7	1.45	1.45	2.03	2.03	2.03	9.00 (3.50-12.00)	2.18 (0.25-3.26)	4.14	7.0	4.3	A++
	5	5	7	7	9	1.44	1.44	2.02	2.02	2.59	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	7	12	1.32	1.32	1.85	1.85	3.17	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	7	14	1.25	1.25	1.75	1.75	3.50	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	7	18	1.13	1.13	1.58	1.58	4.07	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	7	22	1.03	1.03	1.45	1.45	4.54	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	7	24	0.99	0.99	1.39	1.39	4.75	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	9	9	1.36	1.36	1.90	2.44	2.44	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	9	12	1.25	1.25	1.75	2.25	3.00	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	9	14	1.19	1.19	1.66	2.14	3.33	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	9	18	1.08	1.08	1.44	1.94	3.99	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	9	22	0.99	0.99	1.39	1.78	4.36	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	9	24	0.95	0.95	1.33	1.71	4.56	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	12	12	1.16	1.16	1.62	2.78	2.78	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	12	14	1.10	1.10	1.55	2.65	3.09	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	12	18	1.01	1.01	1.41	2.43	3.64	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	12	22	0.93	0.93	1.30	2.24	4.10	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	12	24	0.90	0.90	1.25	2.15	4.30	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	14	14	1.06	1.06	1.48	2.96	2.96	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	14	18	0.97	0.97	1.36	2.71	3.49	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	14	22	0.90	0.90	1.25	2.51	3.94	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	7	18	18	0.90	0.90	1.25	3.23	3.23	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	9	9	1.28	1.28	2.31	2.31	2.31	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	9	12	1.19	1.19	2.14	2.14	2.85	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	9	14	1.13	1.13	2.04	2.04	3.17	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	9	18	1.03	1.03	1.86	1.86	3.72	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	9	22	0.95	0.95	1.71	1.71	4.18	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	9	24	0.91	0.91	1.64	1.64	4.38	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	12	12	1.10	1.10	1.99	2.65	2.65	9.50 (3.50-12.00)	2.37 (0.25-3.26)	4.01	7.0	4.3	A++
	5	5	9	12	1											

# 6-unit Multi-split Combination Table-Cooling

### 6-unit Multi-split cooling

AOHG45LBA6	Combination of Indoor Units							Cooling Operation				Input Power (Min. - Max.) kW	EER			
								Cooling Capacity						Total Capacity (Min. - Max.) kW		
								Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW				Unit 5 kW	Unit 6 kW
2-unit connection	12	24	-	-	-	-	-	3.50	7.00	-	-	-	10.5 (3.5-11.5)	3.06 (0.8-3.32)	3.43	
	14	24	-	-	-	-	-	4.00	7.00	-	-	-	11.0 (3.5-12.1)	3.28 (0.8-3.70)	3.35	
	18	18	-	-	-	-	-	5.00	5.00	-	-	-	10.0 (3.5-11.5)	2.92 (0.8-3.32)	3.42	
	18	24	-	-	-	-	-	5.00	7.00	-	-	-	12.0 (3.5-13.4)	3.75 (0.8-4.46)	3.20	
	24	24	-	-	-	-	-	6.25	6.25	-	-	-	12.5 (3.5-14.0)	4.01 (0.8-4.84)	3.12	
	7	7	24	-	-	-	-	2.00	2.00	7.00	-	-	11.0 (3.5-12.1)	3.19 (0.8-3.70)	3.45	
	7	9	18	-	-	-	-	2.00	2.50	5.00	-	-	9.5 (3.5-10.8)	2.55 (0.8-2.93)	3.73	
	7	9	24	-	-	-	-	2.00	2.50	7.00	-	-	11.5 (3.5-12.7)	3.41 (0.8-4.08)	3.37	
	7	12	18	-	-	-	-	2.00	3.50	5.00	-	-	10.5 (3.5-11.8)	3.02 (0.8-3.51)	3.48	
	7	12	24	-	-	-	-	2.00	3.50	6.90	-	-	12.4 (3.5-13.7)	3.82 (0.8-4.65)	3.25	
7	14	14	-	-	-	-	2.00	4.00	4.00	-	-	10.0 (3.5-11.1)	2.81 (0.8-3.13)	3.56		
7	14	18	-	-	-	-	2.00	4.00	5.00	-	-	11.0 (3.5-12.4)	3.23 (0.8-3.89)	3.41		
7	14	24	-	-	-	-	1.94	3.89	6.67	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21		
7	18	18	-	-	-	-	2.00	5.00	5.00	-	-	12.0 (3.5-13.7)	3.69 (0.8-4.65)	3.25		
7	18	24	-	-	-	-	1.79	4.59	6.12	-	-	12.5 (3.5-14.0)	3.87 (0.8-4.84)	3.23		
7	24	24	-	-	-	-	1.60	5.45	5.45	-	-	12.5 (3.5-14.0)	3.83 (0.8-4.84)	3.26		
9	9	18	-	-	-	-	2.50	2.50	5.00	-	-	10.0 (3.5-11.5)	2.84 (0.8-3.32)	3.52		
9	9	24	-	-	-	-	2.50	2.50	7.00	-	-	12.0 (3.5-13.4)	3.65 (0.8-4.46)	3.29		
9	12	14	-	-	-	-	2.50	3.50	4.00	-	-	10.0 (3.5-11.1)	2.81 (0.8-3.13)	3.56		
9	12	18	-	-	-	-	2.50	3.50	5.00	-	-	11.0 (3.5-12.4)	3.23 (0.8-3.89)	3.41		
9	12	24	-	-	-	-	2.50	3.33	6.67	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21		
9	14	14	-	-	-	-	2.50	4.00	4.00	-	-	10.5 (3.5-11.8)	3.02 (0.8-3.51)	3.48		
9	14	18	-	-	-	-	2.50	4.00	5.00	-	-	11.5 (3.5-13.0)	3.45 (0.8-4.27)	3.33		
9	14	24	-	-	-	-	2.40	3.72	6.38	-	-	12.5 (3.5-14.0)	3.88 (0.8-4.84)	3.22		
9	18	18	-	-	-	-	2.50	5.00	5.00	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21		
9	18	24	-	-	-	-	2.21	4.41	5.88	-	-	12.5 (3.5-14.0)	3.86 (0.8-4.84)	3.24		
9	24	24	-	-	-	-	1.98	5.26	5.26	-	-	12.5 (3.5-14.0)	3.82 (0.8-4.84)	3.27		
12	12	12	-	-	-	-	3.50	3.50	3.50	-	-	10.5 (3.5-11.5)	2.98 (0.8-3.32)	3.52		
12	12	14	-	-	-	-	3.50	3.50	4.00	-	-	11.0 (3.5-12.1)	3.19 (0.8-3.70)	3.45		
12	12	18	-	-	-	-	3.50	3.50	5.00	-	-	12.0 (3.5-13.4)	3.65 (0.8-4.46)	3.29		
12	12	24	-	-	-	-	3.13	3.13	6.24	-	-	12.5 (3.5-14.0)	3.87 (0.8-4.84)	3.23		
12	14	14	-	-	-	-	3.50	4.00	4.00	-	-	11.5 (3.5-12.7)	3.41 (0.8-4.08)	3.37		
12	14	18	-	-	-	-	3.50	4.00	5.00	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21		
12	14	24	-	-	-	-	3.00	3.50	6.00	-	-	12.5 (3.5-14.0)	3.86 (0.8-4.84)	3.24		
12	18	18	-	-	-	-	3.12	4.69	4.69	-	-	12.5 (3.5-14.0)	3.87 (0.8-4.84)	3.23		
12	18	24	-	-	-	-	2.78	4.17	5.55	-	-	12.5 (3.5-14.0)	3.85 (0.8-4.84)	3.25		
12	24	24	-	-	-	-	2.50	5.00	5.00	-	-	12.5 (3.5-14.0)	3.81 (0.8-4.84)	3.28		
14	14	14	-	-	-	-	4.00	4.00	4.00	-	-	12.0 (3.5-13.4)	3.65 (0.8-4.46)	3.29		
14	14	18	-	-	-	-	3.80	3.80	4.90	-	-	12.5 (3.5-14.0)	3.88 (0.8-4.84)	3.22		
14	14	24	-	-	-	-	3.37	3.37	5.76	-	-	12.5 (3.5-14.0)	3.85 (0.8-4.84)	3.25		
14	18	18	-	-	-	-	3.50	4.50	4.50	-	-	12.5 (3.5-14.0)	3.86 (0.8-4.84)	3.24		
14	18	24	-	-	-	-	3.13	4.02	5.35	-	-	12.5 (3.5-14.0)	3.83 (0.8-4.84)	3.26		
14	24	24	-	-	-	-	2.82	4.84	4.84	-	-	12.5 (3.5-14.0)	3.80 (0.8-4.84)	3.29		
18	18	18	-	-	-	-	4.17	4.17	4.17	-	-	12.5 (3.5-14.0)	3.85 (0.8-4.84)	3.25		
18	18	24	-	-	-	-	3.75	3.75	5.00	-	-	12.5 (3.5-14.0)	3.81 (0.8-4.84)	3.28		
7	7	7	14	-	-	-	2.00	2.00	2.00	4.00	-	10.0 (3.5-11.1)	2.50 (0.8-3.13)	4.00		
7	7	7	18	-	-	-	2.00	2.00	2.00	5.00	-	11.0 (3.5-12.4)	3.06 (0.8-3.89)	3.59		
7	7	7	24	-	-	-	1.94	1.94	1.94	6.68	-	12.5 (3.5-14.0)	3.77 (0.8-4.84)	3.32		
7	7	9	12	-	-	-	2.00	2.00	2.50	3.50	-	10.0 (3.5-11.1)	2.50 (0.8-3.13)	4.00		
7	7	9	14	-	-	-	2.00	2.00	2.50	4.00	-	10.5 (3.5-11.8)	2.79 (0.8-3.51)	3.76		
7	7	9	18	-	-	-	2.00	2.00	2.50	5.00	-	11.5 (3.5-13.0)	3.33 (0.8-4.27)	3.45		
7	7	9	24	-	-	-	1.86	1.86	2.39	6.39	-	12.5 (3.5-14.0)	3.75 (0.8-4.84)	3.33		
7	7	12	12	-	-	-	2.00	2.00	3.50	3.50	-	11.0 (3.5-12.1)	3.00 (0.8-3.70)	3.67		
7	7	12	14	-	-	-	2.00	2.00	3.50	4.00	-	11.5 (3.5-12.7)	3.27 (0.8-4.08)	3.52		
7	7	12	18	-	-	-	2.00	2.00	3.50	5.00	-	12.5 (3.5-14.0)	3.78 (0.8-4.84)	3.31		
7	7	12	24	-	-	-	1.75	1.75	3.00	6.00	-	12.5 (3.5-14.0)	3.74 (0.8-4.84)	3.34		
7	7	14	14	-	-	-	2.00	2.00	4.00	4.00	-	12.0 (3.5-13.4)	3.51 (0.8-4.46)	3.42		
7	7	14	18	-	-	-	1.90	1.90	3.80	4.90	-	12.5 (3.5-14.0)	3.77 (0.8-4.84)	3.32		
7	7	14	24	-	-	-	1.68	1.68	3.37	5.77	-	12.5 (3.5-14.0)	3.73 (0.8-4.84)	3.35		
7	7	18	18	-	-	-	1.75	1.75	4.50	4.50	-	12.5 (3.5-14.0)	3.74 (0.8-4.84)	3.34		
7	7	18	24	-	-	-	1.56	1.56	4.02	5.36	-	12.5 (3.5-14.0)	3.70 (0.8-4.84)	3.38		
7	7	24	24	-	-	-	1.41	1.41	4.84	4.84	-	12.5 (3.5-14.0)	3.67 (0.8-4.84)	3.41		
7	9	9	9	-	-	-	2.00	2.50	2.50	2.50	-	9.5 (3.5-10.8)	2.31 (0.8-2.93)	4.11		
7	9	9	12	-	-	-	2.00	2.50	2.50	3.50	-	10.5 (3.5-11.8)	2.79 (0.8-3.51)	3.76		
7	9	9	14	-	-	-	2.00	2.50	2.50	4.00	-	11.0 (3.5-12.4)	3.06 (0.8-3.89)	3.59		
7	9	9	18	-	-	-	2.00	2.50	2.50	5.00	-	12.0 (3.5-13.7)	3.57 (0.8-4.65)	3.36		
7	9	9	24	-	-	-	1.79	2.30	2.30	6.11	-	12.5 (3.5-14.0)	3.74 (0.8-4.84)	3.34		
7	9	12	12	-	-	-	2.00	2.50	3.50	3.50	-	11.5 (3.5-12.7)	3.27 (0.8-4.08)	3.52		
7	9	12	14	-	-	-	2.00	2.50	3.50	4.00	-	12.0 (3.5-13.4)	3.51 (0.8-4.46)	3.42		
7	9	12	18	-	-	-	1.90	2.45	3.26	4.89	-	12.5 (3.5-14.0)	3.77 (0.8-4.84)	3.32		
7	9	12	24	-	-	-	1.68	2.16	2.88	5.78	-	12.5 (3.5-14.0)	3.73 (0.8-4.84)	3.35		
7	9	14	14	-	-	-	2.00	2.50	4.00	4.00	-	12.5 (3.5-14.0)	3.78 (0.8-4.84)	3.31		
7	9	14	18	-	-	-	1.82	2.34	3.65	4.69	-	12.5 (3.5-14.0)	3.75 (0.8-4.84)	3.33		
7	9	14	24	-	-	-	1.62	2.08	3.24	5.56	-	12.5 (3.5-14.0)	3.71 (0.8-4.84)	3.37		
7	9	18	18	-	-	-	1.68	2.16	4.33	4.33	-	12.5 (3.5-14.0)	3.73 (0.8-4.84)	3.35		
7	9	18	24	-	-	-	1.51	1.94	3.88	5.17	-	12.5 (3.5-14.0)	3.69 (0.8-4.84)	3.39		
7	12	12	12	-	-	-	1.90	3.50	3.50	3.50	-	12.4 (3.5-13.7)	3.69 (0.8-4.65)	3.36		
7	12	12	14	-	-	-	1.94	3.33	3.33	3.90	-	12.5 (3.5-14.0)	3.77 (0.8-4.84)	3.32		
7	12	12	18	-	-	-	1.79	3.06	3.06	4.59	-	12.5 (3.5-14.0)	3.74 (0.8-4.84)	3.34		
7	12	12	24	-	-	-	1.59	2.73	2.73	5.45	-	12.5 (3.5-14.0)	3.71 (0.8-4.84)	3.37		
7	12	14	14	-	-	-	1.87	3.19	3.72	3.72	-	12.5 (3.5-14.0)	3.75 (0.8-4.84)	3.33		
7	12	14	18	-	-	-	1.72	2.94	3.43	4.41	-	12.5 (3.5-14.0)	3.73 (0.8-4.84)	3.35		
7	12	14	24	-	-	-	1.54	2.63	3.07	5.26	-	12.5 (3.5-14.0)	3.70 (0.8-4.84)	3.38		
7	12	18	18	-	-	-	1.59	2.73	4.09	4.09	-	12.5 (3.5-14.0)	3.71 (0.8-4.84)	3.37		
7	12	18	24	-	-	-	1.43	2.46	3.69	4.92	-	12.5 (3.5-14.0)	3.68 (0.8-4.84)	3.40		
7	14	14	14	-	-	-	1.79	3.57	3.57	3.57	-	12.5 (3.5-14.0)	3.74 (0.8-4.84)	3.34		
7	14	14	18	-	-	-	1.65	3.30	3.30	4.25	-	12.5 (3.5-14.0)	3.72 (0.8-4.84)	3.36		
7	14	14	24	-	-	-	1.48	2.97	2.97	5.08	-	12.5 (3.5-14.0)	3.69 (0.8-4.84)	3.39		
7	14	18	18	-	-	-	1.53									



# 6-unit Multi-split Multi Combination Table-Cooling/Heating

### 6-unit Multi-split cooling












AOHG45LBLA6	Combination of Indoor Units								Cooling Operation				Input Power (Min. - Max.)	EER				
									Cooling Capacity						Total Capacity (Min. - Max.)			
	Unit 1	Unit 2	Unit 3	Unit 4	Unit 5	Unit 6	Unit 1	Unit 2	Unit 3	Unit 4	Unit 5	Unit 6	Total Capacity (Min. - Max.)	Input Power (Min. - Max.)		EER		
5-unit connection	7	9	12	14	18	-	-	-	-	1.46	1.88	2.50	2.92	3.74	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	7	9	14	14	14	-	-	-	-	1.50	1.94	3.02	3.02	3.02	-	12.5 (3.5-14.0)	3.57 (0.8-4.84)	3.50
	7	9	14	14	18	-	-	-	-	1.41	1.81	2.82	2.82	3.64	-	12.5 (3.5-14.0)	3.55 (0.8-4.84)	3.52
	7	12	12	12	12	-	-	-	-	1.58	2.73	2.73	2.73	2.73	-	12.5 (3.5-14.0)	3.59 (0.8-4.84)	3.48
	7	12	12	12	14	-	-	-	-	1.54	2.63	2.63	2.63	3.07	-	12.5 (3.5-14.0)	3.58 (0.8-4.84)	3.49
	7	12	12	12	18	-	-	-	-	1.43	2.46	2.46	2.46	3.69	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	7	12	12	14	14	-	-	-	-	1.48	2.54	2.54	2.97	2.97	-	12.5 (3.5-14.0)	3.57 (0.8-4.84)	3.50
	7	12	14	14	14	-	-	-	-	1.43	2.46	2.87	2.87	2.87	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	9	9	9	9	9	-	-	-	-	2.50	2.50	2.50	2.50	2.50	-	12.5 (3.5-14.0)	3.65 (0.8-4.84)	3.42
	9	9	9	9	12	-	-	-	-	2.34	2.34	2.34	2.34	3.14	-	12.5 (3.5-14.0)	3.64 (0.8-4.84)	3.43
	9	9	9	9	14	-	-	-	-	2.25	2.25	2.25	2.25	3.50	-	12.5 (3.5-14.0)	3.62 (0.8-4.84)	3.45
	9	9	9	9	18	-	-	-	-	2.08	2.08	2.08	2.08	4.18	-	12.5 (3.5-14.0)	3.60 (0.8-4.84)	3.47
	9	9	9	9	24	-	-	-	-	1.88	1.88	1.88	1.88	4.98	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	9	9	9	12	12	-	-	-	-	2.21	2.21	2.21	2.94	2.94	-	12.5 (3.5-14.0)	3.62 (0.8-4.84)	3.45
	9	9	9	12	14	-	-	-	-	2.12	2.12	2.12	2.83	3.31	-	12.5 (3.5-14.0)	3.60 (0.8-4.84)	3.47
	9	9	9	12	18	-	-	-	-	1.97	1.97	1.97	2.63	3.96	-	12.5 (3.5-14.0)	3.58 (0.8-4.84)	3.49
	9	9	9	14	14	-	-	-	-	2.05	2.05	2.05	3.18	3.18	-	12.5 (3.5-14.0)	3.59 (0.8-4.84)	3.48
	9	9	9	14	18	-	-	-	-	1.91	1.91	1.91	2.97	3.80	-	12.5 (3.5-14.0)	3.57 (0.8-4.84)	3.50
	9	9	12	12	12	-	-	-	-	2.08	2.08	2.78	2.78	2.78	-	12.5 (3.5-14.0)	3.60 (0.8-4.84)	3.47
	9	9	12	12	14	-	-	-	-	2.01	2.01	2.68	2.68	3.12	-	12.5 (3.5-14.0)	3.59 (0.8-4.84)	3.48
	9	9	12	12	18	-	-	-	-	1.88	1.88	2.50	2.50	3.74	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	9	9	12	14	14	-	-	-	-	1.94	1.94	2.58	3.02	3.02	-	12.5 (3.5-14.0)	3.57 (0.8-4.84)	3.50
	9	9	12	14	18	-	-	-	-	1.81	1.81	2.42	2.82	3.64	-	12.5 (3.5-14.0)	3.55 (0.8-4.84)	3.52
	9	9	14	14	14	-	-	-	-	1.87	1.87	2.92	2.92	2.92	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	9	12	12	12	12	-	-	-	-	1.98	2.63	2.63	2.63	2.63	-	12.5 (3.5-14.0)	3.58 (0.8-4.84)	3.49
	9	12	12	12	14	-	-	-	-	1.91	2.54	2.54	2.54	2.97	-	12.5 (3.5-14.0)	3.57 (0.8-4.84)	3.50
	9	12	12	14	14	-	-	-	-	1.84	2.46	2.46	2.87	2.87	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	12	12	12	12	12	-	-	-	-	2.50	2.50	2.50	2.50	2.50	-	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	12	12	12	12	14	-	-	-	-	2.42	2.42	2.42	2.42	2.82	-	12.5 (3.5-14.0)	3.55 (0.8-4.84)	3.52
	7	7	7	7	7	7	7	7	7	2.00	2.00	2.00	2.00	2.00	2.00	12.0 (3.5-13.4)	3.32 (0.8-4.46)	3.61
	7	7	7	7	7	7	7	9	2.00	2.00	2.00	2.00	2.00	2.50	2.50	12.5 (3.5-14.0)	3.57 (0.8-4.84)	3.50
	7	7	7	7	7	7	12	1.86	1.86	1.86	1.86	1.86	1.86	3.20	3.20	12.5 (3.5-14.0)	3.55 (0.8-4.84)	3.52
	7	7	7	7	7	14	1.79	1.79	1.79	1.79	1.79	1.79	3.55	3.55	3.55	12.5 (3.5-14.0)	3.54 (0.8-4.84)	3.53
	7	7	7	7	7	18	1.65	1.65	1.65	1.65	1.65	1.65	4.25	4.25	4.25	12.5 (3.5-14.0)	3.51 (0.8-4.84)	3.56
	7	7	7	7	7	24	1.48	1.48	1.48	1.48	1.48	1.48	5.10	5.10	5.10	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59
	7	7	7	7	9	9	1.90	1.90	1.90	1.90	2.45	2.45	2.45	2.45	2.45	12.5 (3.5-14.0)	3.56 (0.8-4.84)	3.51
	7	7	7	7	9	12	1.79	1.79	1.79	1.79	2.29	3.05	3.05	3.05	3.05	12.5 (3.5-14.0)	3.54 (0.8-4.84)	3.53
	7	7	7	7	9	14	1.72	1.72	1.72	1.72	2.20	3.42	3.42	3.42	3.42	12.5 (3.5-14.0)	3.53 (0.8-4.84)	3.54
	7	7	7	7	9	18	1.59	1.59	1.59	1.59	2.05	4.09	4.09	4.09	4.09	12.5 (3.5-14.0)	3.50 (0.8-4.84)	3.57
	7	7	7	7	9	24	1.43	1.43	1.43	1.43	1.85	4.93	4.93	4.93	4.93	12.5 (3.5-14.0)	3.47 (0.8-4.84)	3.60
	7	7	7	7	12	1.68	1.68	1.68	1.68	1.68	2.89	2.89	2.89	2.89	2.89	12.5 (3.5-14.0)	3.52 (0.8-4.84)	3.55
	7	7	7	7	12	14	1.62	1.62	1.62	1.62	2.78	3.24	3.24	3.24	3.24	12.5 (3.5-14.0)	3.51 (0.8-4.84)	3.56
	7	7	7	7	12	18	1.51	1.51	1.51	1.51	2.59	3.87	3.87	3.87	3.87	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59
	7	7	7	7	14	1.56	1.56	1.56	1.56	1.56	3.13	3.13	3.13	3.13	3.13	12.5 (3.5-14.0)	3.50 (0.8-4.84)	3.57
	7	7	7	7	14	1.46	1.46	1.46	1.46	1.46	2.92	3.74	3.74	3.74	3.74	12.5 (3.5-14.0)	3.47 (0.8-4.84)	3.60
7	7	7	9	9	1.82	1.82	1.82	2.34	2.34	2.34	2.34	2.34	2.34	2.34	12.5 (3.5-14.0)	3.55 (0.8-4.84)	3.52	
7	7	7	9	9	1.72	1.72	1.72	2.21	2.21	2.92	2.92	2.92	2.92	2.92	12.5 (3.5-14.0)	3.53 (0.8-4.84)	3.54	
7	7	7	9	14	1.65	1.65	1.65	2.12	2.12	3.31	3.31	3.31	3.31	3.31	12.5 (3.5-14.0)	3.51 (0.8-4.84)	3.56	
7	7	7	9	18	1.54	1.54	1.54	1.97	1.97	3.94	3.94	3.94	3.94	3.94	12.5 (3.5-14.0)	3.49 (0.8-4.84)	3.58	
7	7	7	9	12	1.62	1.62	1.62	2.08	2.78	2.78	2.78	2.78	2.78	2.78	12.5 (3.5-14.0)	3.51 (0.8-4.84)	3.56	
7	7	7	9	12	14	1.56	1.56	1.56	2.01	2.68	3.13	3.13	3.13	3.13	12.5 (3.5-14.0)	3.50 (0.8-4.84)	3.57	
7	7	7	9	12	18	1.46	1.46	1.46	1.88	2.50	3.74	3.74	3.74	3.74	12.5 (3.5-14.0)	3.47 (0.8-4.84)	3.60	
7	7	7	9	14	1.51	1.51	1.51	1.93	3.02	3.02	3.02	3.02	3.02	3.02	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59	
7	7	7	12	12	1.54	1.54	1.54	2.63	2.63	2.63	2.63	2.63	2.63	2.63	12.5 (3.5-14.0)	3.49 (0.8-4.84)	3.58	
7	7	7	12	14	1.48	1.48	1.48	2.54	2.98	2.98	2.98	2.98	2.98	2.98	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59	
7	7	7	12	14	1.43	1.43	1.43	2.47	2.87	2.87	2.87	2.87	2.87	2.87	12.5 (3.5-14.0)	3.47 (0.8-4.84)	3.60	
7	7	9	9	9	1.75	1.75	2.25	2.25	2.25	2.25	2.25	2.25	2.25	2.25	12.5 (3.5-14.0)	3.53 (0.8-4.84)	3.54	
7	7	9	9	9	1.65	1.65	2.12	2.12	2.12	2.84	2.84	2.84	2.84	2.84	12.5 (3.5-14.0)	3.51 (0.8-4.84)	3.56	
7	7	9	9	14	1.59	1.59	2.05	2.05	2.05	3.17	3.17	3.17	3.17	3.17	12.5 (3.5-14.0)	3.50 (0.8-4.84)	3.57	
7	7	9	9	18	1.48	1.48	1.91	1.91	1.91	3.81	3.81	3.81	3.81	3.81	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59	
7	7	9	12	1.56	1.56	2.01	2.01	2.68	2.68	2.68	2.68	2.68	2.68	2.68	12.5 (3.5-14.0)	3.50 (0.8-4.84)	3.57	
7	7	9	12	14	1.51	1.51	1.94	1.94	2.59	3.01	3.01	3.01	3.01	3.01	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59	
7	7	9	12	18	1.41	1.41	1.81	1.81	2.42	3.64	3.64	3.64	3.64	3.64	12.5 (3.5-14.0)	3.46 (0.8-4.84)	3.61	
7	7	9	14	1.46	1.46	1.88	1.88	2.91	2.91	2.91	2.91	2.91	2.91	2.91	12.5 (3.5-14.0)	3.47 (0.8-4.84)	3.60	
7	7	9	12	1.48	1.48	1.92	2.54	2.54	2.54	2.54	2.54	2.54	2.54	2.54	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59	
7	7	9	12	14	1.43	1.43	1.85	2.46	2.46	2.87	2.87	2.87	2.87	2.87	12.5 (3.5-14.0)	3.47 (0.8-4.84)	3.60	
7	7	12	12	1.41	1.41	2.42	2.42	2.42	2.42	2.42	2.42	2.42	2.42	2.42	12.5 (3.5-14.0)	3.46 (0.8-4.84)	3.61	
7	9	9	9	9	1.70	2.16	2.16	2.16	2.16	2.16	2.16	2.16	2.16	2.16	12.5 (3.5-14.0)	3.52 (0.8-4.84)	3.55	
7	9	9	9	12	1.59	2.05	2.05	2.05	2.05	2.71	2.71	2.71	2.71	2.71	12.5 (3.5-14.0)	3.50 (0.8-4.84)	3.57	
7	9	9	9	14	1.54	1.97	1.97	1.97	1.97	3.08	3.08	3.08	3.08	3.08	12.5 (3.5-14.0)	3.49 (0.8-4.84)	3.58	
7	9	9	9	12	1.50	1.94	1.94	1.94	1.94	2.59	2.59	2.59	2.59	2.59	12.5 (3.5-14.0)	3.48 (0.8-4.84)	3.59	
7	9	9	9	12	1.46	1.88	1.88	1.88	1.88	2.50	2.90							

# 6-unit Multi-split Combination Table-Heating

## 6-unit Multi-split heating

AOHG45LBA6	Combination of Indoor Units		Heating Operation							Input Power (Min. - Max.) kW	COP					
			Heating Capacity													
			Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW	Unit 6 kW	Total Capacity (Min. - Max.) kW							
4-unit connection	9	9	9	14	-	-	2.85	2.85	2.85	4.45	-	-	13.0 (3.5-14.9)	3.46 (0.7-4.09)	3.76	
	9	9	9	18	-	-	2.70	2.70	2.70	5.40	-	-	13.5 (3.5-16.0)	3.61 (0.7-4.41)	3.74	
	9	9	9	24	-	-	2.38	2.38	2.38	6.36	-	-	13.5 (3.5-16.0)	3.59 (0.7-4.41)	3.76	
	9	9	12	12	-	-	2.83	2.83	3.77	3.77	-	-	13.2 (3.5-15.3)	3.52 (0.7-4.20)	3.75	
	9	9	12	14	-	-	2.76	2.76	3.68	4.30	-	-	13.5 (3.5-16.0)	3.61 (0.7-4.41)	3.74	
	9	9	12	18	-	-	2.53	2.53	3.38	5.06	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75	
	9	9	12	24	-	-	2.25	2.25	3.00	6.00	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77	
	9	9	14	14	-	-	2.64	2.64	4.11	4.11	-	-	13.5 (3.5-16.0)	3.61 (0.7-4.41)	3.74	
	9	9	14	18	-	-	2.43	2.43	3.78	4.86	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75	
	9	9	14	24	-	-	2.17	2.17	3.38	5.78	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77	
	9	9	18	18	-	-	2.25	2.25	4.50	4.50	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77	
	9	9	18	24	-	-	2.03	2.03	4.05	5.39	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78	
	9	12	12	12	-	-	2.70	3.60	3.60	3.60	-	-	13.5 (3.5-16.0)	3.61 (0.7-4.41)	3.74	
	9	12	12	14	-	-	2.59	3.45	3.45	4.01	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75	
	9	12	12	18	-	-	2.38	3.18	3.18	4.76	-	-	13.5 (3.5-16.0)	3.59 (0.7-4.41)	3.76	
	9	12	12	24	-	-	2.13	2.84	2.84	5.69	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78	
	9	12	14	14	-	-	2.48	3.30	3.86	3.86	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75	
	9	12	14	18	-	-	2.29	3.06	3.57	4.58	-	-	13.5 (3.5-16.0)	3.59 (0.7-4.41)	3.76	
	9	12	14	24	-	-	2.06	2.75	3.20	5.49	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78	
	9	12	18	18	-	-	2.13	2.85	4.26	4.26	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78	
9	14	14	14	-	-	2.37	3.71	3.71	3.71	-	-	13.5 (3.5-16.0)	3.59 (0.7-4.41)	3.76		
9	14	14	18	-	-	2.21	3.44	3.44	4.41	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77		
9	14	14	24	-	-	1.99	3.10	3.10	5.31	-	-	13.5 (3.5-16.0)	3.56 (0.7-4.41)	3.79		
9	14	18	18	-	-	2.06	3.20	4.12	4.12	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78		
12	12	12	12	-	-	3.38	3.38	3.38	3.38	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75		
12	12	12	14	-	-	3.24	3.24	3.24	3.78	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75		
12	12	12	18	-	-	3.00	3.00	3.00	4.50	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77		
12	12	12	24	-	-	2.70	2.70	2.70	5.40	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78		
12	12	14	14	-	-	3.12	3.12	3.63	3.63	-	-	13.5 (3.5-16.0)	3.59 (0.7-4.41)	3.76		
12	12	14	18	-	-	2.89	2.89	3.38	4.34	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77		
12	12	14	24	-	-	2.61	2.61	3.05	5.23	-	-	13.5 (3.5-16.0)	3.56 (0.7-4.41)	3.79		
12	12	18	18	-	-	2.70	2.70	4.05	4.05	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78		
12	14	14	14	-	-	3.00	3.50	3.50	3.50	-	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77		
12	14	14	18	-	-	2.79	3.26	3.26	4.19	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78		
12	14	18	18	-	-	2.61	3.05	3.92	3.92	-	-	13.5 (3.5-16.0)	3.56 (0.7-4.41)	3.79		
7	7	7	7	7	-	-	2.40	2.40	2.40	2.40	-	-	12.0 (3.5-12.7)	2.82 (0.7-3.44)	4.26	
7	7	7	7	9	-	-	2.33	2.33	2.33	2.98	-	-	12.3 (3.5-13.5)	3.03 (0.7-3.65)	4.06	
7	7	7	7	12	-	-	2.24	2.24	2.24	3.84	-	-	12.8 (3.5-14.5)	3.29 (0.7-3.98)	3.89	
7	7	7	7	14	-	-	2.20	2.20	2.20	4.40	-	-	13.2 (3.5-15.3)	3.40 (0.7-4.20)	3.88	
7	7	7	7	18	-	-	2.05	2.05	2.05	5.30	-	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87	
7	7	7	7	24	-	-	1.82	1.82	1.82	6.22	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89	
7	7	7	9	9	-	-	2.28	2.28	2.28	2.93	-	-	12.7 (3.5-14.2)	3.23 (0.7-3.87)	3.93	
7	7	7	9	12	-	-	2.20	2.20	2.20	3.77	-	-	13.2 (3.5-15.3)	3.40 (0.7-4.20)	3.88	
7	7	7	9	14	-	-	2.15	2.15	2.15	4.29	-	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87	
7	7	7	9	18	-	-	1.97	1.97	1.97	5.06	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88	
7	7	7	9	24	-	-	1.75	1.75	1.75	6.00	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90	
7	7	7	12	12	-	-	2.10	2.10	2.10	3.60	3.60	-	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
7	7	7	12	14	-	-	2.01	2.01	2.01	4.02	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88	
7	7	7	12	18	-	-	1.85	1.85	1.85	4.77	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89	
7	7	7	12	24	-	-	1.66	1.66	1.66	5.68	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91	
7	7	7	14	14	-	-	1.93	1.93	1.93	3.86	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88	
7	7	7	14	18	-	-	1.78	1.78	1.78	4.59	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89	
7	7	7	14	24	-	-	1.60	1.60	1.60	5.50	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91	
7	7	7	18	18	-	-	1.66	1.66	1.66	4.26	4.26	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
7	7	9	9	9	-	-	2.22	2.22	2.85	2.85	-	-	13.0 (3.5-14.9)	3.34 (0.7-4.09)	3.89	
7	7	9	9	12	-	-	2.15	2.15	2.76	3.68	-	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87	
7	7	9	9	14	-	-	2.05	2.05	2.64	4.12	-	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87	
7	7	9	9	18	-	-	1.89	1.89	2.43	4.86	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88	
7	7	9	9	24	-	-	1.69	1.69	2.17	5.78	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90	
7	7	9	12	12	-	-	2.01	2.01	2.58	3.45	3.45	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
7	7	9	12	14	-	-	1.93	1.93	2.48	3.31	3.85	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
7	7	9	12	18	-	-	1.78	1.78	2.29	3.06	4.59	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
7	7	9	12	24	-	-	1.60	1.60	2.06	2.75	5.49	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
7	7	9	14	14	-	-	1.85	1.85	2.38	3.71	3.71	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
7	7	9	14	18	-	-	1.72	1.72	2.21	3.44	4.41	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
7	7	9	14	24	-	-	1.55	1.55	1.99	3.10	5.31	-	-	13.5 (3.5-16.0)	3.44 (0.7-4.41)	3.92
7	7	9	18	18	-	-	1.60	1.60	2.06	4.12	4.12	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
7	7	12	12	12	-	-	1.89	1.89	3.24	3.24	3.24	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
7	7	12	12	14	-	-	1.82	1.82	3.12	3.12	3.62	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
7	7	12	12	18	-	-	1.69	1.69	2.89	2.89	4.34	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
7	7	12	12	24	-	-	1.52	1.52	2.61	2.61	5.24	-	-	13.5 (3.5-16.0)	3.44 (0.7-4.41)	3.92
7	7	12	14	14	-	-	1.75	1.75	3.00	3.50	3.50	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
7	7	12	14	18	-	-	1.63	1.63	2.79	3.26	4.19	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
7	7	12	18	18	-	-	1.52	1.52	2.62	3.92	3.92	-	-	13.5 (3.5-16.0)	3.44 (0.7-4.41)	3.92
7	7	14	14	14	-	-	1.68	1.68	3.38	3.38	3.38	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
7	7	14	14	18	-	-	1.58	1.58	3.15	3.15	4.04	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
7	9	9	9	9	-	-	2.18	2.18	2.78	2.78	2.78	-	-	13.3 (3.5-15.6)	3.44 (0.7-4.30)	3.87
7	9	9	9	12	-	-	2.05	2.05	2.64	2.64	3.53	-	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
7	9	9	9	14	-	-	1.97	1.97	2.53	2.53	3.94	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
7	9	9	9	18	-	-	1.82	1.82	2.34	2.34	4.66	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
7	9	9	9	24	-	-	1.63	1.63	2.09	2.09	5.60	-	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
7	9	9	12	12	-	-	1.92	1.92	2.48	3.31	3.31	-	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
7	9	9	12	14	-	-	1.85	1.85	2.38	3.18	3.71	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
7	9	9	12	18	-	-	1.72	1.72	2.21	2.95	4.41	-	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
7	9	9	12	24	-	-	1.55	1.55	1.99	2.66	5.31	-	-	13.5 (3.5-16.0)	3.44 (0.7-4.41)	3.92
7	9	9	14	14	-	-	1.78	1.78	2.29	3.57	3.57	-	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
7	9	9	14	18	-	-										

# Feature Summary

Type	Wall-mounted type				Wall-mounted type			
	Series	Designer Series	Standard Series	Standard Series	Designer Series	Standard Series	Standard Series	
Model name	 ASHH07/09/12/14KGTG ASHG07/09/12/14KETE	 ASHG07/09/12/14KETF, ASHG07/09/12/14KETF-B, ASHG07/09/12/14KETE, ASHG07/09/12/14KETE-B	 ASHH07/09/12/14KMCG ASHH07/09/12/14KMCG-B ASHG07/09/12/14KMCE	 ASHH05/07/09/12KNCA	 ASHG18/22/24KMTE	 ASHG07/09/12/14LUCA	 ASHG07/09/12/14LMCA	 ASHG18LFCA, ASHG24LFCC
Refrigerant								
Energy-saving Features	Save Occupancy sensor	●						
	Economy operation	●	●	●	●	●	●	●
	Setting temperature range limitation	○	○	○		○	○	○
	Set temperature auto return	○	○	○		○	○	○
Features for Comfort	Power diffuser						●	●
	Powerful operation	●	●	●	●	●		
	10°C Heat	●	●	●	●	●	●	●
	Outdoor unit low noise operation	●	●	●	●	●		
	Auto changeover	●	●	●	●	●	●	●
	UP/DOWN swing louver	●	●	●	●	●	●	
	Double swing automatic				●	●		●
	Automatic fan speed	●	●	●	●	●	●	●
	Auto restart	●	●	●	●	●	●	●
	Connectable fresh air duct							
	Fresh air intake							
	Connectable distributing duct							
	Convenience Features	Auto-off timer	○	○	○	●	○	○
Sleep timer		●	●	●	●	●	●	●
Program timer		●	●	●	●	●	●	●
Weekly timer		●	●	○	○	●	●	
Weekly & Temperature setback timer		○	○	○		○	○	○
Filter sign		●	●	●	●	●	●	●
External error output		○	○	○		○	○	○
External ON/OFF input		○	○	○		○	○	○
Wireless LAN control	● (KGTG), ○ (KGTE)	● (KETF, KETF-B), ○ (KETE, KETE-B)	● (KMCG, KMCG-B), ○ (KMCE)	●	○	○	○	
Clean Features	Ion deodorization filter	●	●	●		●	●	●
	Apple-catechin filter	●	●	●		●	●	●
	Long-life filter							
	Washable panel	●	●	●	●	●	●	●
	Silver Ion Filter	○	○	○	○	○	○	○
Installation/Support	Automatic airflow adjustment							
	Drain pump as standard							
	Blue fin				●			● (30)
	Refrigerant cycle monitor							

○: Optional function

# Feature Summary

	Type	Cassette			Duct			Duct				Floor		Floor/Ceiling	Ceiling	
	Series	Compact 4-way Flow Grid type Series	Compact 4-way Flow Series	4-way Flow Series	Mini (With drain pump)	Slim (With drain pump)	Slim (With drain pump)	Medium Static Pressure								
Model name																
		AUXG 07/09/12/14/18/22/24 KVLA	AUHG07/09LVLA, AUHG12/14/18LVLB, AUHG22/24LVLA	AUHG30/36LRLE, AUHG36/45LRLA	ARXG 07/09/12/14/18 KSLAP	ARHG 07/09/12/14/18 LSLAP	ARXG 07/09/12/14/18 KLLAP	ARHG07/09LLTA, ARHG12/14/18LLTB	ARXH 12/14/18/22 KMTAP	ARXG22KMLB, ARXG24KMLA	ARHG 22/24/36/45 LMLA, ARHG 30/36LMLE	AGHG 09/12/14 KVCA	AGHG 09/12/14 LVCA	ABHG 14/22/24 LVTA, ABHG18LVTB	ABHG18/22KRTA	ABHG30/36LRTE, ABHG36/45LRTA
Refrigerant																
Energy-saving Features	Save Occupancy sensor															
	Economy operation	●	●	●	●	●	●	●	○	●	●	●	●	●	●	●
	Setting temperature range limitation	○	○	○	●	●	○	○	○	○	○	○	○	○	●	○
	Set temperature auto return	●	○	○	●	●	●	○	○	●	○	○	○	○	●	○
Features for Comfort	Power diffuser															
	Powerful operation											●				
	10°C Heat	●	●	○	○	○	○	○	○	○	○	●	●	●	○	●
	Outdoor unit low noise operation											●		○	○	○
	Auto changeover	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	UP/DOWN swing louver	●	●	●	○	○	○	○				●	●		●	
	Double swing automatic													●		●
	Automatic fan speed	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Auto restart	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Connectable fresh air duct		○	●					●	●	●				●	●
Fresh air intake	○	○	○			○	○	○	○	○				○	○	
Connectable distributing duct								●	●							
Convenience Features	Auto-off timer	●	○	○	●	●	●	○	●	●	○	○	○	○	●	○
	Sleep timer	●	●	○	○	○	○	○	○	○	○	●	●	●	○	●
	Program timer	●	●	○	○	○	○	○	○	○	○	●	●	●	○	●
	Weekly timer	●			●	●	●					●			●	
	Weekly & Temperature setback timer	○	○	●			●	●	●	●	●		○	○		○
	Filter sign	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	External error output				○	○						○			○	
Clean Features	External ON/OFF input	●	○	○	●	●	●	○	●	●	○	○	○	○	●	○
	Wireless LAN control	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	Ion deodorization filter											●	●			
	Apple-catechin filter											●	●			
	Long-life filter								○	○	○	●	●			
Installation/Support	Washable panel															
	Silver Ion Filter	○	○	○	○	○	○	○	○	○	○	○	○			
	Automatic airflow adjustment								●							
	Drain pump as standard	●	●	●	●	●	●	●	●	○	○				○	○
	Blue fin			(45/54)											(30/36/45/54)	(45)
Refrigerant cycle monitor								○								

○: Optional function

## Light Commercial & Commercial, Residential VRF

VRF systems provide air conditioning solutions that meet the requirements of a diverse range of buildings.

VRF systems provide air conditioning solutions for large residences as well as large commercial buildings.

V-002 VRF Series Overview  
V-004 VRF Outdoor Units Lineup  
V-006 Features

### VRF Outdoor Units



#### VRF J Series Heat Pump for Small-capacity type

V-020 VRF J-VS  
V-026 VRF J-IVS  
V-030 VRF J-IV  
V-034 VRF J-IVL



#### VRF V Series Heat Recovery Modular type

V-040 VRF VR-IV

#### Heat Pump Modular type

V-050 VRF V-IV

### VRF INDOOR UNITS

V-058 VRF Indoor Unit Lineup for J-VS  
V-066 VRF Indoor Unit Lineup for J-IVS, J-IV, J-IVL, VR-IV, V-IV



## VRF

Light Commercial  
& Commercial,  
Residential



FUJITSU GENERAL (Euro) GmbH  
participates in the ECP program for VRF.  
Check ongoing validity of certificate:  
[www.eurovent-certification.com](http://www.eurovent-certification.com)

**FUJITSU GENERAL LIMITED**



# VRF Series Overview

Recommended VRF products for various buildings



## NEW VRF J-VS



### Maximum 6 HP Heat Pump

This product uses R32, a new environmentally friendly refrigerant. With TOP-class energy efficiency and compact design, it can be installed in a limited and narrow space without being conspicuous. Indoor unit connectable up to 130%.

- Sustainable(R32)
- Saving CO2
- Small Body
- Situational Piping Design
- Sightliness installation



Page V-020

## VRF VR-IV



### Maximum 48 HP Heat Recovery

Smart, cutting-edge design Available in a wide range of models from 8 to 48 HP in 2 HP increments with the capacity ratio of indoor units connectable up to 150%.

- Excellent energy saving
- High design flexibility for placement in any building
- Easy installation and maintenance



Page V-040

## VRF J-IVS



### Maximum 6 HP Heat Pump

The 998 mm compact design does not obstruct the view even when installed underneath a waist-high window, ideal for large houses and retail stores. Indoor unit connectable up to 130%.

- Spaces saving and low sound level design
- Flexible system configuration for homes, stores, and small buildings



Page V-026

## VRF V-IV



### Maximum 48 HP Heat Pump

Smart, cutting-edge design Extensive lineup from 8 HP to 48 HP with the capacity ratio of indoor units connectable up to 150%.

- Simultaneous cooling and heating operation using a single refrigerant system
- Annual cooling operation
- Accommodating changes in temperature difference



Page V-050

## VRF J-IV



### Maximum 6 HP Heat Pump

J-IV is connectable with up to 14 indoor units (Indoor unit connectable up to 150%) making it suitable for commercial facilities housing a number of small stores.

- High energy efficiency
- Flexible system configuration for small and midsize buildings



Page V-030

## VRF J-IVL



### Maximum 18 HP Heat Pump

J-IVL is an outdoor unit with a slim design. Its flexibility in installation makes it ideal for midsize office buildings and hotels. With the newly added 14/16/18 HP models, up to 42 indoor units\* are connectable, making them ideal for hotels and educational facilities with many rooms.


- Slim Outdoor Unit
- Small room application
- Class-leading Low Operating Sound



Page V-034

### Design Simulator

When installing air conditioning equipment in each room of a building, it is necessary to select an indoor unit suitable for the heat load in the room and derive an outdoor unit that can cover the capacity of all indoor units. In addition, remote controls and converters are selected according to how the customer will manage the air conditioner, and in some cases, a design combined with options may be required to comply with established standards. The "Design Simulator" can be used to facilitate the selection of such complex equipment and the output of system drawings and estimates. (Software for PC)



For more information



# VRF Outdoor Units Lineup



Capacity (kW)		Capacity (kW)																									
HP		HP																									
Refrigerant		12.1	14.0	15.1-15.5	22.4	28.0	33.5	40.0	45.0	50.0-50.4	55.9	61.5	67.0	73.5	78.5	85.0	90.0	95.0	100.5	107.0	112.0	118.5	123.5	130.0	135.0		
		4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48		
NEW	J-VS Series	R32																									
			AJH040 KCTAH	AJH045 KCTAH	AJH054 KCTAH																						
	J-IVS Series	R410A																									
	J-IVS Series	R410A	AJH040 LCLDH	AJH045 LCLDH	AJH054 LCLDH																						
	J-IV Series	R410A																									
	J-IV Series	R410A	AJH040 LBLDH, AJH040 LELDH	AJH045 LBLDH, AJH045 LELDH	AJH054 LBLDH, AJH054 LELDH																						
	J-IVL Series	R410A																									
	J-IVL Series	R410A				AJH072 LELDH	AJH090 LELDH	AJH108 LELDH	AJH126 LELDH	AJH144 LELDH	AJH162 LELDH																
VR-IV Series Heat Recovery	Space Saving	R410A																									
	Set Model	R410A				AJH072 GALDH	AJH090 GALDH	AJH108 GALDH	AJH126 GALDH	AJH144 GALDH	AJH162 GALDH	AJH180 GALDH	AJH198 GALDH		AJH216 GALDH	AJH234 GALDH	AJH252 GALDH	AJH270 GALDH	AJH288 GALDH	AJH306 GALDH	AJH324 GALDH	AJH342 GALDH	AJH360 GALDH	AJH378 GALDH	AJH396 GALDH	AJH414 GALDH	AJH432 GALDH
	Energy Efficiency	R410A																									
	Set Model	R410A								AJH144 GALDHH			AJH198 GALDHH		AJH216 GALDHH	AJH234 GALDHH	AJH252 GALDHH	AJH270 GALDHH	AJH288 GALDHH	AJH306 GALDHH	AJH324 GALDHH	AJH342 GALDHH	AJH360 GALDHH	AJH378 GALDHH	AJH396 GALDHH		
V-IV Series Heat Pump	Space Saving	R410A																									
	Set Model	R410A				AJH072 LALDH	AJH090 LALDH	AJH108 LALDH	AJH126 LALDH	AJH144 LALDH	AJH162 LALDH	AJH180 LALDH	AJH198 LALDH		AJH216 LALDH	AJH234 LALDH	AJH252 LALDH	AJH270 LALDH	AJH288 LALDH	AJH306 LALDH	AJH324 LALDH	AJH342 LALDH	AJH360 LALDH	AJH378 LALDH	AJH396 LALDH	AJH414 LALDH	AJH432 LALDH
	Energy Efficiency	R410A																									
	Set Model	R410A								AJH144 LALDHH		AJH180 LALDHH		AJH216 LALDHH	AJH234 LALDHH	AJH252 LALDHH	AJH270 LALDHH	AJH288 LALDHH	AJH306 LALDHH	AJH324 LALDHH	AJH342 LALDHH	AJH360 LALDHH	AJH378 LALDHH	AJH396 LALDHH			



# Features

## High-efficiency




High-efficiency is achieved significantly by the use of a DC twin-rotary compressor, inverter technology, and a large heat exchanger.



\* These specifications are determined by ducted combination.

### ALL DC High-efficiency design with top-class SEER/SCOP


All the VRF Series, including the J-IVL Series, have DC technology to achieve high-efficiency operation. This enhances the durability and reliability of the VRF Series.



## Efficient control of operation


### Setting temperature range limitation

Sets the minimum and maximum limits on room temperature to establish an optimum balance between energy-saving performance and a comfortable environment.




### Auto-off timer

The wired remote controller is equipped with an auto-off timer function that automatically stops operation after a fixed period of time has elapsed from the start of operation to avoid wasting energy. The function also allows you to set the interval for stopping operations.




### Energy-saving management

A variety of energy-saving operations can be set and managed depending on the season, climate, and time period. Excellent energy-saving operation using the system controller.




### Capacity-saving mode

Operation capacity can be reduced in 5 steps from the rated capacity. This mode cuts down on peak power consumption and eases the maximum load on the unit.



### Intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with subtle control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.




#### Current refrigerant control

Thermostat-ON/OFF occurs frequently. → Frequent changes in room temperature interfere with comfort. The compressor starts and stops repeatedly, wasting energy.

#### New refrigerant control

The thermostat is turned on and off less frequently than under current control to maintain the room temperature at the target temperature. Compared to current control, the compressor will run longer, thus saving energy.




\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

# More Comfort




## Auto changeover

In Auto setting, the air conditioner switches between cooling and heating modes automatically according to the set temperature and the room temperature.




Auto changeover settings enable the indoor unit to easily switch between cooling and heating regardless of the operating mode of other indoor units. These settings can be made using a wired remote controller for a specific indoor unit. Provides a comfortable environment all year round.

## Automatic cooling/heating operation for each room is possible



## Precise control of refrigerant flow


The combination of DC inverter control and individual control of electronic expansion valves of an indoor unit enables precise and smooth control of the refrigerant flow. This means the room temperature can be set in increments of 0.5°C.



## Quiet operation


### Quiet operation

Two low noise modes can be switched over automatically between one in which low noise is prioritized over performance, and the other in which performance is prioritized over low noise, depending on the room temperature and outdoor temperature. This feature can be controlled by external input from the outdoor unit or a system controller.




## Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



## NEW Switching room temperature sensing position for improved heating comfort (Option)


The optional remote sensor kit (UTY-XSZXZ1) can be connected to the indoor unit to improve comfort by installing the unit at a height appropriate for the living environment.



# High Reliability

## Outdoor unit rotation

The compressor starting order is rotated to equalize the cumulative running time of each unit.




The start and stop timings are alternated among connected compressors.

## Backup operation


If one compressor fails, the other compressors will initiate backup operation\*.

Note: Backup operation may not be possible depending on the cause of failure.




## Advanced refrigerant control

Compressor control logic controls the inverter speed to balance the mass airflow rate of refrigerant in each outdoor unit.





## Protection against liquid flowback

The use of a large accumulator means that refrigerant that has not been completely vaporized stays inside the accumulator to ensure no liquid refrigerant is fed into the compressor.



## Blue fin heat exchanger

The anti-corrosion blue fin treatment is applied to the heat exchanger of the outdoor unit.



# Design Flexibility


## Class-leading compact design

An industry-leading compact outdoor unit with optimal airflow pattern design. (Up to 18 HP)




## Long pipe design

Pipe design suitable for long and narrow office buildings with elevation differences and low-rise stores with long distances (VRF J-IVL Series)



## Max. allowable overall pipe length: 1,000 m

The class-leading pipe length of 1,000 m increases flexibility of installation in a wide variety of buildings.



\*1: V-IV and VR-IV Series. The pipe length between the nearest indoor unit and the farthest indoor unit, originating from the first separation tube, must be 60 m or less.

## High-capacity connection

Series	Connectable indoor unit capacity range	Connectable indoor units
VRF J-VS Series Heat pump type	50% to 130%	up to 13 <sup>*5</sup>
VRF J-IVS Series Heat pump type	50% to 130%	up to 13 <sup>*5</sup>
VRF J-IV Series Heat pump type	50% to 150%	up to 14 <sup>*5</sup>
VRF J-IVL Series 14/16/18 HP Heat pump type	50% to 150%	up to 42 <sup>*3</sup>
VRF J-IVL Series 8/10/12 HP Heat pump type	50% to 150%	up to 30 <sup>*4</sup>
VRF VR-IV Series Heat Recovery Modular type	25% <sup>*5</sup> to 150%	up to 64
VRF V-IV Series Heat Pump Modular type	50% to 150% <sup>*2</sup>	up to 64

\*2: The maximum capacity of the combination that includes the 18-HP outdoor unit is below 150%.  
 \*3: J-IVL Series 18-HP model only.  
 \*4: J-IVL Series 12-HP model only.  
 \*5: 6-HP model only.

## Designed for low refrigerant charge

The optimal design of the indoor and outdoor units reduces the amount of refrigerant required and can be easily installed in a room as small as 15 m<sup>2</sup>.



## Various optional parts

- Fresh air intake kit to bring in fresh air
- Comfortable temperature control with a remote sensor
- DX kit links ventilation equipment and air handling units.



## Low ambient operation


Our refrigeration cycle technology enables cooling operation even at -15°C.



## Wide operating temperature range

All outdoor units have a wide operating temperature range and can operate in extreme temperature conditions.

\*6: When multiple outdoor units are connected, their operating temperature range is from -5°C to 46°C in cooling.  
 \*7: The operating range is -15°C to 46°C only for systems with all indoor units rated at 5.6 kW or more.




# Easy Installation




## Easily transported



A lifting strap can be hooked onto an outdoor unit. Design of outdoor unit allows for lifting straps to be used.




Transportable by forklift. The outdoor unit can be lifted and transported by forklift.



Fits into a small elevator.

## Easy access


The removable L-shaped front panel provides more room for installation and service work. Multiple installations can be performed easily and efficiently even in tight spaces.



Front access reduces installation intervals.


## Flexible pipe connection

Piping and wiring can be accessed from the front, left, right, and bottom.



## Simplified wiring work

The communication wiring can be installed seamlessly among indoor, outdoor, and RB units, which makes the installation of the wiring system easier.




Maximum wiring length: **3,600 m**

Note: The automatic address setting is not available on a serially connected multiple refrigerant system.


## Vacuum mode function for easy evacuation

The vacuum mode function enables all expansion valves of an indoor unit to be opened fully, allowing for easier evacuation of air inside pipe lines and indoor units.



## Automatic address setting

Addresses of connected indoor units, RB units, and Signal amplifier can all be set automatically from the PCB in the outdoor unit.




## Easy commissioning with Tools

### • Service Tool (UTY-ASGXZ1)

The Service Tool checks the refrigerant temperature and pressure, and the operating status of the electronic expansion valves, making it easy to determine if the units are connected properly.

### NEW • Central Remote Controller (UTY-DCGGZ3)

After the VRF system has been installed. Conveniently, the "test run" required to verify proper system operation can be performed from a nearby Central RC.






# Easy Service and Maintenance

## Designed for easy maintenance

A 7-segment indicator lamp panel provides detailed information on the function setting status, refrigerant temperature and pressure, compressor operation time, and other factors, facilitating self-diagnosis for each unit.




### Easy-to-read 7-segment indicator lamp

Shows the following detailed operation and error status without need of any special tools.

### Error status can be checked on an outdoor unit's display

- System operation mode
- Discharge temperature and pressure
- Compressor operation status
- Address, type, and number of outdoor unit



- Error status can easily be checked on an outdoor unit's display.


### Movable PCB panel

Enables easier access behind the PCB for maintenance work.



The error status can be checked via a wired remote controller for indoor units.


Error codes are displayed on an LCD screen.



## Error diagnosis by Service tool


### Connection to Service tool

- A detailed operation status and recent error history can be checked and analyzed using Service tool.
- The last 5 minutes of operation status can be recorded continuously.



## Remote monitoring

The Web Monitoring system enables the monitoring of the system's operation status at any time via the internet to ensure trouble-free operation. The operating VRF network system in the building can be monitored real time over the internet.






**Heat Pump**  
for Small-capacity type

VRF **J-VS**



**System configuration example**

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



R32 refrigerant with reduced global warming potential

- **Zero** Ozone Depletion Potential (ODP<sup>\*1</sup>)
- High environmental properties
- High performance
- Economically efficient



# Sustainable

## European F-Gas Regulation Plan

The European Union has tightened F-gas rules as part of European Green Deal policy, which aims for Europe climate neutral by 2050. The F-gas Regulation mainly includes


- (1) Reducing the total volume of HFCs and phasing out HFC in 2050.
- (2) The GWP limits for certain products are required to be strengthened.

Fujitsu General as one of its proactive efforts to preserve the global environment, we are working on technological development to achieve the best balance between refrigerants with lower GWP and energy efficiency of equipment adopting safety measures.

2029	2033	2035	2050
Available at J-VS			
Split AC & HP Over 12 kW: GWP 750 and above prohibited 12 kW or less: GWP 150 and above prohibited	Split AC & HP Over 12 kW: GWP 150 and above prohibited	Split AC & HP HFC use prohibited	an economy with <b>net-zero</b> greenhouse gas emissions.


## Refrigerant saving design

Refrigerant saving design the compact indoor unit, piping design, and optimization of heat exchanger volume significantly reduce the system refrigerant volume.



## Enhanced disaster safety measures

The system is designed to meet the environmental safety requirements specified in the IEC 603352-40 standard for the use of R32 refrigerant. The environment requiring safety measures is determined by the size of the room in relation to the amount of refrigerant required. For example, if the system is designed for maximum pipe length and the refrigerant charge is 6 kg, safety measures are required for rooms of 15 m2 or less.




# Saving CO2

## TOP Class High Energy Saving


The use of large heat exchanger and a high-efficiency Rotary compressor achieves class-leading SEER/SCOP in all models.

SEER **8.27** \*045 model  
SCOP **5.37** \*040 model




## More Energy-Saving compressor control

When the room temperature approaches the set temperature after the start of operation, the capacity required for the outdoor unit becomes lower. The minimum compressor speed at this time can now be controlled at a lower value than with conventional products, enabling more energy-efficient operation.




## Small Body

### Easy to carry, easy to install



### Small, lightweight outdoor unit

The outdoor units in this series are much more compact than conventional outdoor units of comparable capacity. They can be installed on a balcony, fitting below the height of the railing. With a height of less than 1 m, they can be installed in tight spaces such as under windows.



### Low noise design



Significantly low noise levels are achieved by the use of a DC twin-rotary compressor, inverter technology, and an advanced airflow pattern design.

## Situational Piping Design

### Long pipe length

Our advanced refrigerant control technology extends the maximum allowable length of refrigerant piping to 120 m. This provides high flexibility in system design.

Long piping lengths are achieved by installing a large-capacity accumulator. No liquid refrigerant is supplied to the compressor even when the required amount of refrigerant is charged in the long piping.



### Up to 13 indoor units\* can be connected

The combination of smaller but sufficiently powerful indoor units and a new outdoor unit with an optimized heat exchanging structure makes it possible to connect up to 13 indoor units, which is the best in its class.

\*: 6 HP model


Rating Capacity range (HP)	4	5	6
Max. Connectable indoor unit	1-11	1-12	1-13

## Sightliness installation

### External static pressure

External static pressure measures up to 30 Pa for 4/5/6 HP models.


Even if the outdoor unit is installed in a small space to hide it, the grille and duct airflow path required for exhaust air can be installed up to a static pressure value of 30 Pa.



### Cooling piping system

New Heat Rejection Technology Cooling piping system "Cooling piping system" is adopted to ensure reliability in high outside air.

Even when the outdoor unit is installed in an environment where heat tends to stay (small space), the cooling system using refrigerant can reduce damage caused by heat from PCBs.




### Specifications

Rated capacity range		HP	4	5	6
Model name			AJH040KCTAH	AJH045KCTAH	AJH054KCTAH
Maximum connectable indoor units			1-11	1-12	1-13
Power source			Single phase, ~230 V, 50 Hz		
Capacity	Cooling	kW	14.0	14.0	15.1
	Nominal Heating		12.1	14.0	15.1
	Max. Heating		13.6	16.0	16.5
Input power	Cooling	kW	3.15	3.82	4.48
	Nominal Heating		2.55	2.91	3.20
	Max. Heating		3.09	3.62	3.90
EER	Cooling	W/W	3.84	3.66	3.37
	Nominal Heating		4.74	4.80	4.71
	Max. Heating		4.40	4.41	4.22
SEER	Cooling		8.20	8.27	7.79
	Heating		5.37	4.93	4.82
SCOP	Cooling		325.0	328.0	308.6
	Heating		212.0	194.0	189.8
η <sub>c</sub>	Cooling	%	325.0	328.0	308.6
η <sub>h</sub>	Heating		212.0	194.0	189.8
Airflow rate		m <sup>3</sup> /h	4,240	4,450	4,450
Sound pressure level/Power level	Cooling	dB(A)	52 / 70	53 / 71	54 / 72
	Heating		54 / 71	55 / 72	56 / 73
Heat exchanger fin			Blue fin	Blue fin	Blue fin
Net Dimensions	Height	mm	998	998	998
	Width		940	940	940
	Depth		320	320	320
Weight		kg	74	74	74
	Refrigerant		Type (Global Warming Potential)	R32 (675)	R32 (675)
Connection pipe diameter	Charge	kg (CO <sub>2</sub> eq-T)	2.7 (1.823)	2.7 (1.823)	2.7 (1.823)
	Liquid		9.52	9.52	9.52
Total pipe length	Gas	mm	15.88	15.88	15.88
Max. height difference		m	120	120	120
			30	30	30
Operating Range	Cooling	°C	-5 to 46	-5 to 46	-5 to 46
	Heating		-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.  
 The protective function may work when using it outside the operation range.

### Dimensions

(Unit: mm)






**Heat Pump**  
for Small-capacity type

VRF **J-IVS**


**System configuration example**

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



**New intelligent refrigerant control**

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.



\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

**External static pressure**

External static pressure measures up to 25 Pa for 4/5/6 HP models.



**Advanced high-efficiency technology**

**Large propeller fan**  
A large propeller fan with an optimized blade angle achieves both high performance and low noise operation.

**DC fan motor**  
A small, multi-stage DC fan motor provides high-efficiency and low noise operation.

**Large heat exchanger**  
The large 3-row heat exchanger substantially improves heat-exchanging performance.

High heat-transfer copper tube (Improved lead angle)


**DC inverter control**  
The active filter module improves efficiency.

- Low noise rubber
- High-efficiency compressor motor
- Optimized refrigerant flow design
- Highly accurate parts

**Compact and high-performance DC twin-rotary compressor**


High-efficiency is achieved across compressor loads. Especially good performance is achieved in the low- to medium-load range.

### Easy to carry, easy to install



### Small, lightweight outdoor unit

The outdoor units in this series are much more compact than conventional outdoor units of comparable capacity. They can be installed on a balcony, fitting below the height of the railing. With a height of less than 1 m, they can be installed in tight spaces such as under windows.




### Low noise design

Significantly low noise levels are achieved by the use of a DC twin-rotary compressor, inverter technology, and an advanced airflow pattern design.



### Long pipe length

Our advanced refrigerant control technology extends the maximum allowable length of refrigerant piping to 80 m. This provides high flexibility in system design.



### Up to 13 indoor units\* can be connected


The combination of smaller but sufficiently powerful indoor units and a new outdoor unit with an optimized heat exchanging structure makes it possible to connect up to 13 indoor units, which is the best in its class.

\*: 6 HP model

Model	Current model (J-IIS)			New model (J-IVS)		
	4	5	6	4	5	6
Rating Capacity range (HP)	4	5	6	4	5	6
Max. Connectable indoor unit	1-7	1-8	1-8	1-11	1-12	1-13


### Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



### Easier installation

**Connection check function:** Wiring connections and address settings can be checked thanks to the quick check run function.



- Displays the number of each connected indoor unit.
- Displays the duplicate address number assigned to an indoor unit.


### Specifications

Rated capacity range	HP	4	5	6
Model name		AJH040LCDH	AJH045LCDH	AJH054LCDH
Maximum connectable indoor units		1-11	1-12	1-13
Power source		Single phase, ~230 V, 50 Hz		
Capacity	Cooling	14.0	14.0	15.1
	Nominal Heating	12.1	14.0	15.1
	Max. Heating	13.6	16.0	16.5
Input power	Cooling	3.75	4.71	5.55
	Nominal Heating	3.22	3.77	4.33
	Max. Heating	3.99	5.04	5.32
EER	Cooling	3.22	2.97	2.72
	Nominal Heating	3.75	3.71	3.48
	Max. Heating	3.40	3.17	3.10
COP	Cooling	5.83	5.58	5.47
	Heating	3.82	3.96	3.99
SEER	Cooling	230.2	220.2	215.8
	Heating	149.8	155.4	156.6
SCOP	Cooling	4.240	4.400	4.400
	Heating	53 / 67	53 / 69	54 / 70
Airflow rate	Cooling	54 / 68	56 / 69	56 / 70
	Heating	Blue fin	Blue fin	Blue fin
Sound pressure level/Power level	Height	998	998	998
	Width	970	970	970
	Depth	370	370	370
Weight	kg	88	88	88
	Type (Global Warming Potential)	R410A (2,088)	R410A (2,088)	R410A (2,088)
Refrigerant	Charge	4.0 (8.4)	4.0 (8.4)	4.0 (8.4)
	Liquid	9.52	9.52	9.52
Connection pipe diameter	Gas	15.88	15.88	15.88
	Total pipe length	80	80	80
Max. height difference	m	30	30	30
	Operating Range	Cooling	-5 to 46	-5 to 46
	Heating	-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.  
The protective function may work when using it outside the operation range.

### Dimensions

(Unit: mm)






# Heat Pump for Small-capacity type

# VRF J-IV


### System configuration example

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.



\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

### External static pressure

External static pressure measures up to 30 Pa for 4/5/6 HP.



### Advanced high-efficiency technology

**Large propeller fan**  
A large propeller fan with an optimized blade angle achieves both high performance and low noise operation.

**DC fan motor**  
A small, multi-stage DC fan motor contributes to high-efficiency and low noise operation.

**Large heat exchanger**  
The large 3-row heat exchanger substantially improves heat-exchanging performance.

**DC twin-rotary compressor**  
High-efficiency is achieved across compressor loads. Especially good performance is achieved in the low-to medium-load range.

**Subcooling heat exchanger**  
The dual-tube heat exchanger improves cooling performance.

**DC inverter control**  
The active filter module improves efficiency.


**High-efficiency compressor motor**  
**Optimized refrigerant flow design**  
**Highly accurate parts**

**Pressure-Enthalpy graph:** Shows 'effect' and 'Cooling performance improved'.

**Compressor efficiency graph:** Shows 'DC Twin-Rotary Compressor' with high efficiency across capacity.


### Efficiency in actual operating conditions

The use of a large heat exchanger and a high-efficiency Scroll compressor achieves class-leading EER/COP (Max. Heating) in all models.



### Long pipe length

Our advanced refrigerant control technology allows us to achieve a total refrigerant pipe length of 180 m. This provides high flexibility in system design.



### Up to 14 indoor units\* can be connected

The combination of smaller but sufficiently powerful indoor units and outdoor units with an optimized heat exchanging structure makes it possible to connect up to 14 indoor units, which is the best in its class.

\*: 6 HP model

Model	Current model (J-III)			New model (J-IV)		
	4	5	6	4	5	6
Rating Capacity range (HP)	4	5	6	4	5	6
Max. Connectable indoor unit	1-9	1-10	1-13	1-11	1-12	1-14

### 4,5,6HP: AJH040LBDH / AJH045LBDH / AJH054LBDH / AJH040LELDH [3-phase] / AJH045LELDH [3-phase] / AJH054LELDH [3-phase]


#### Specifications

		HP	4	5	6			
Model name			AJH040LBDH	AJH045LBDH	AJH054LBDH	AJH040LELDH	AJH045LELDH	AJH054LELDH
Maximum connectable indoor units			1-11	1-12	1-14	1-11	1-12	1-14
Power source			Single phase, ~230 V, 50 Hz			3-phase, ~400 V, 50 Hz		
Capacity	Cooling	kW	12.1	14.0	15.5	12.1	14.0	15.5
	Nominal Heating		12.1	14.0	15.5	12.1	14.0	15.5
	Max. Heating		13.6	16.0	18.0	13.6	16.0	18.0
Input power	Cooling	kW	3.44	4.15	4.96	3.44	4.15	4.96
	Nominal Heating		3.14	3.60	4.17	3.14	3.60	4.17
	Max. Heating		3.80	4.50	5.41	3.80	4.50	5.41
EER	Cooling		3.51	3.37	3.12	3.51	3.37	3.12
COP	Nominal Heating	W/W	3.85	3.88	3.71	3.85	3.88	3.71
	Max. Heating		3.57	3.55	3.32	3.57	3.55	3.32
	SEER	Cooling		6.50	6.30	6.08	6.50	6.30
SCOP	Heating		3.83	3.93	3.94	3.83	3.93	3.94
ηc	Cooling	%	257.0	249.0	240.0	257.0	249.0	240.0
ηh	Heating		150.0	154.0	155.0	150.0	154.0	155.0
Airflow rate		m³/h	6,200	6,600	7,000	6,200	6,600	7,000
Sound pressure level/Power level	Cooling	dB(A)	50 / 65	52 / 66	53 / 67	50 / 65	52 / 66	53 / 67
	Heating		52 / 67	55 / 69	56 / 69	52 / 67	55 / 69	56 / 69
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin
	Height	mm	1,334	1,334	1,334	1,334	1,334	1,334
	Width		970	970	970	970	970	970
Net Dimensions	Depth		370	370	370	370	370	370
			117	117	119	118	119	119
Weight		kg	117	117	119	118	119	119
			R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
Refrigerant	Type (Global Warming Potential)		4.8 (10.0)	5.3 (11.1)	5.3 (11.1)	4.8 (10.0)	5.3 (11.1)	5.3 (11.1)
	Charge	kg (CO2eq-T)	9.52	9.52	9.52	9.52	9.52	9.52
Connection pipe diameter	Liquid	mm	15.88	15.88	19.05	15.88	15.88	19.05
	Gas		180	180	180	180	180	180
Total pipe length		m	50/40 (Outdoor unit: Upper/Lower)			50/40 (Outdoor unit: Upper/Lower)		
Max. height difference			50/40 (Outdoor unit: Upper/Lower)			50/40 (Outdoor unit: Upper/Lower)		
			-5 to 46			-5 to 46		
Operating Range	Cooling	°C	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.  
 The protective function may work when using it outside the operation range.


#### Dimensions

(Unit: mm)




### Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



### Easier installation

Connection check function: Wiring connections and address settings can be checked thanks to the quick check run function.








## Heat Pump for Small-capacity type

# VRF J-IVL


### System configuration example

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.



\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

### External static pressure

External static pressure is available up to 60 Pa for 14/16/18 HP. (30 Pa for 8/10 HP, 40 Pa for 12 HP)  
Capacities are slightly decreased relative to the rated values during high static pressure operations.



### Advanced high-efficiency technology

**Ø570 mm Large propeller fan**  
A large-diameter propeller fan with our proprietary blade design reduces draft loss, which results in high-efficiency and low noise operation.

**DC inverter control**  
The active filter module improves efficiency.

**DC fan motor**  
A small, multi-stage DC fan motor provides high-efficiency and low noise operation.

**Subcooling heat exchanger**  
The dual-tube heat exchanger improves cooling performance.

**Large heat exchanger**  
The large 2.6-row heat exchanger substantially improves heat-exchanging performance.

**Scroll compressor**  
The combination of a scroll compressor with a wide rotational frequency range from 15 to 130 rps and our proprietary sensorless sine-wave control that smoothly controls the input power into the motor achieves more energy-efficient and quieter operation.



Fujitsu General offers a perfect total air conditioning system for small office buildings with multiple small rooms, taking into consideration energy savings, low noise, comfortable air volume, usage and purpose, and centralized control.


# VRF J-IVL

Image: 8/10/12 HP models

## Slim & Compact design



## Various installation methods



### Installation

#### Low noise level in consideration of nearby residents

Front air discharge type with a width of about 1,000 mm, allowing for flexible installation even in narrow spaces.



### Narrow space behind building

#### Space saving

Small and thin, allowing for direct ground or wall mounting installations even in narrow alleys.




### Installation on the back street of a building

#### Flexible installation

Slim, low-body front air discharge meets the requirements for installation even in tight spaces. Installation flexibility without blocking the windows of buildings contributes to substantial space savings, even when multiple units are installed.


### Efficiency in actual operating conditions

The use of a large heat exchanger and a high-efficiency Scroll compressor achieves class-leading EER/COP (Max. Heating) in all models.



### Long pipe length

Our advanced refrigerant control technology extends the maximum allowable length of refrigerant piping to 400 m. This provides high flexibility in system design.



### Up to 42 indoor units\* can be connected.


The combination of smaller but sufficiently powerful indoor units and a new outdoor unit with an optimized heat exchanging structure makes it possible to connect up to 42 indoor units, which is the best in its class.

\*: 18 HP model



### Class-leading low operating sound

The top-class low operating noise makes it ideal for use in densely populated areas. These low operating sound models are ideal for installation in densely populated areas.



8,10,12 HP: AJH072LELDH / AJH090LELDH / AJH108LELDH  
14,16,18 HP: AJH126LELDH / AJH144LELDH / AJH162LELDH




### Specifications

Rated capacity range	HP	8	10	12	14	16	18
Model name		AJH072LELDH	AJH090LELDH	AJH108LELDH	AJH126LELDH	AJH144LELDH	AJH162LELDH
Maximum connectable indoor units		1-20	1-25	1-30	1-36	1-40	1-42
Power source		3-phase, ~400V, 50Hz					
Capacity	Cooling	22.4	28.0	33.5	40.0	45.0	50.0
	Nominal Heating	22.4	28.0	33.5	40.0	45.0	50.0
	Max. Heating	25.0	31.5	37.5	45.0	50.0	55.0
Input power	Cooling	6.30	8.59	10.42	12.12	14.96	18.52
	Nominal Heating	4.65	6.61	8.18	9.71	11.81	13.66
	Max. Heating	5.45	8.29	10.25	11.81	14.29	16.66
EER	Cooling	3.56	3.26	3.22	3.30	3.01	2.70
	Nominal Heating	4.82	4.24	4.10	4.12	3.81	3.66
COP	Max. Heating	4.56	3.80	3.66	3.81	3.50	3.30
	Cooling	7.62	7.50	7.27	7.27	7.00	6.29
SCOP	Heating	3.89	3.61	3.63	3.53	3.51	3.54
ηc	Cooling	301.8	297.0	287.8	287.8	277.0	248.6
	Heating	152.6	141.4	142.2	138.2	137.4	138.6
ηh	Heating	152.6	141.4	142.2	138.2	137.4	138.6
Airflow rate		8,400	9,000	11,000/12,100	13,000	14,000	14,800/15,300
Sound pressure level/Power level	Cooling	52/66	54/69	59/73	62/75	64/77	65/79
	Heating	54/66	57/70	62/75	63/76	65/78	68/82
Net Dimensions	Height	1,428	1,428	1,428	1,638	1,638	1,638
	Width	1,080	1,080	1,080	1,080	1,080	1,080
	Depth	480	480	480	480	480	480
Weight		170	177	178	213	213	217
	Type (Global Warming Potential)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
Refrigerant	Charge	7.0 (14.6)	7.5 (15.7)	7.5 (15.7)	11.0 (23.0)	11.0 (23.0)	11.8 (24.6)
	Liquid	9.52	9.52	12.70	12.70	12.70	12.70
Connection pipe diameter	Gas	19.05	22.20	28.58	28.58	28.58	28.58
	Total pipe length	400	400	400	400	400	400
Max. height difference		50/40 (Outdoor unit: Upper/Lower)					
	Operating Range	Cooling	-15 to 46	-15 to 46	-15 to 46	-5 to 46*	-5 to 46*
	Heating	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.  
Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.  
\* The cooling operation range of -15 to 46°C is allowed only when all of the indoor units connected to the system are higher than capacity of 5.6kW.

### Dimensions

(Unit: mm)






**Heat Recovery**  
Modular type


VRF **VR-IV**

**Highly energy-efficient operation**

Our heat recovery systems achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.




Our heat recovery systems achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.



**New intelligent refrigerant control**

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.



\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

**Increase in the number of connectable indoor units**

Capacity range of connectable indoor units

New model (VR-IV)	25%* to 150%
Current model (VR-II)	50% to 150%

\*: For modular type, 25% to 49.9% operation in the entire system is available. (by one unit operation)

Increased number of connectable indoor units and space saving combinations (Unit)

HP	10	12	14	16	...	28	30	32	...	48	
New model (VR-IV)	21	26	30	34	...	60	64	64	...	64	
Current model (VR-II)	15	16	17	21	24	...	42	45	48	...	64

**The energy-saving technology that boosted operation efficiency**

- Powerful large propeller fan**  
The fan uses CFD\* technology to achieve both high performance and low noise operation.  
\*CFD: Computational Fluid Dynamics
- 3-phase DC fan motor**  
The use of a DC fan motor with sophisticated driver control improves energy efficiency substantially. In addition, this motor operates quietly.
- Subcooling heat exchanger**  
High heat exchange efficiency is achieved by using an internal projection-shape double-pipe construction.
- High-efficient, large-capacity DC twin-rotary compressor**  
Large-capacity high-efficient DC twin-rotary compressor with excellent intermediate capability.
- Sine-wave DC inverter control**  
High-efficiency is realized by the adoption of reduced switching loss IPM.
- 4-face heat exchanger**  
The 4-face heat exchanger increases the effective surface area and significantly improves heat-exchanging efficiency.
- Front intake port (Corner cut air inlet structure)**  
In multiple outdoor unit installations, the unique front intake design improves airflow into the heat exchanger.

## Extended connection ratio (applicable to multiple tenants)


Especially useful when starting partial air conditioning in a building under construction. Installation can be added flexibly for each tenant.



### Stand-alone

Current model (VR-II)


**Example** 50% of 12HP minimum connected indoor unit capacity is required



Installation is possible even for tenants who have not yet started operations.

### New model (VR-IV)

**Example** 25% of 12HP minimum connected indoor unit capacity is required



Installation and commissioning can be added flexibly to meet the opening dates of other tenants.

### Modular type


One outdoor unit operates effectively for the capacities of connectable indoor units in the entire system. (Each of the multiple outdoor units does not dare to operate at 25% capacity: any one of the outdoor units will operate at 50% and the remaining units will each output 0%, i.e., stop operating.)

**Example:** One 10HP outdoor unit performs 25% of the total 20HP outdoor units system.  
One 10HP outdoor unit performs 50% of its capacity  
→ Two outdoor units do not perform 25% of the operation.



## Additional installation is possible without changing the main pipe.

A main pipe of a diameter that can be used for the final system is installed at the beginning of the installation. Duplication of the work will be avoided as there is no need to change the main pipe as in the previous model.



## All-inverter compressor


### Large-capacity DC inverter compressor

Large-capacity high-efficient DC twin-rotary compressor with excellent intermediate capability.





### High-efficiency compressor speed control

The compressor speed control in 0.1 Hz increments ensures a comfortable space with less change in room temperature and less energy loss.



### Efficiency in actual operating conditions


Class-leading high COP (Maximum) The use of our proprietary heat exchanger structure and high-efficiency DC twin-rotary compressors achieves the class-leading coefficient of performance (COP) in every combination.



\* These specifications are determined by Cassette combination.  
\* Multiple outdoor units are not certified by Eurovent.


### Multiple outdoor operation control

When multiple outdoor units are connected, each compressor carries out sophisticated operation. Instead of operating one compressor at full load to distribute the refrigerant to one heat exchanger, all compressors operate at partial load to distribute the refrigerant to all heat exchangers, thereby improving the efficiency of the entire system.




### Heat exchanger refrigerant control

The heat exchanger in the outdoor unit is divided into two parts, upper and lower. The efficiency of the heat exchanger has been improved by adopting an optimum refrigerant path control where the refrigerant is distributed more into the top heat exchanger as this is where there is a greater air flow intake.



### Flexible pipe connection

More flexible refrigerant pipe work is possible due to the use of various piping and RB unit connections, for adjustments to the floor layout and building structure.





• An RB unit can be placed between the first branch and an indoor unit.  
• The maximum height difference between RB units is 15 m.  
No RB Unit is required for cooling only use.

### Flexible installation of RB unit

Small and slim design with a height of 198 mm makes it easy to install in tight spaces with height constraints.

- A drain pipe is not required.
- Different positions of a control box can be chosen to accommodate installation conditions.
- Series connection for simplified installation



#### Easy maintenance in tight spaces

Maintenance can be performed from the side.

The electrical box can be accessed and serviced by sliding down the front cover.

Parts can be accessed and replaced easily even in tight spaces inside the ceiling.

Outdoor units lineup • Combinations other than those listed below are not recommended.

Space saving combination

22.4kW (8HP) AJH072GALDH UNIT : AJH072GALDH	28.0kW (10HP) AJH090GALDH UNIT : AJH090GALDH	33.5kW (12HP) AJH108GALDH UNIT : AJH108GALDH	40.0kW (14HP) AJH126GALDH UNIT : AJH126GALDH	45.0kW (16HP) AJH144GALDH UNIT : AJH144GALDH
50.4kW (18HP) AJH162GALDH UNIT : AJH090/072GALDH	56.0kW (20HP) AJH180GALDH UNIT : AJH090/090GALDH	61.5kW (22HP) AJH198GALDH UNIT : AJH108/090GALDH	67.0kW (24HP) AJH216GALDH UNIT : AJH108/108GALDH	73.0kW (26HP) AJH234GALDH UNIT : AJH144/090GALDH
78.5kW (28HP) AJH252GALDH UNIT : AJH144/108GALDH	85.0kW (30HP) AJH270GALDH UNIT : AJH144/126GALDH	90.0kW (32HP) AJH288GALDH UNIT : AJH144/144GALDH	95.0kW (34HP) AJH306GALDH UNIT : AJH108/108/090GALDH	100.5kW (36HP) AJH324GALDH UNIT : AJH108/108/108GALDH
106.5kW (38HP) AJH342GALDH UNIT : AJH144/108/090GALDH	112.0kW (40HP) AJH360GALDH UNIT : AJH144/108/108GALDH	118.0kW (42HP) AJH378GALDH UNIT : AJH144/144/090GALDH	123.5kW (44HP) AJH396GALDH UNIT : AJH144/144/108GALDH	130.0kW (46HP) AJH414GALDH UNIT : AJH144/144/126GALDH
135.0kW (48HP) AJH432GALDH UNIT : AJH144/144/144GALDH				

Energy efficiency combination

44.8kW (16HP) AJH144GALDHH UNIT : AJH072/072GALDH	62.4kW (22HP) AJH198GALDHH UNIT : AJH126/072GALDH	67.2kW (24HP) AJH216GALDHH UNIT : AJH072/072/072GALDH	72.8kW (26HP) AJH234GALDHH UNIT : AJH090/072/072GALDH	78.4kW (28HP) AJH252GALDHH UNIT : AJH090/090/072GALDH
84.0kW (30HP) AJH270GALDHH UNIT : AJH090/090/090GALDH	90.4kW (32HP) AJH288GALDHH UNIT : AJH126/090/072GALDH	96.0kW (34HP) AJH306GALDHH UNIT : AJH126/090/090GALDH	102.4kW (36HP) AJH324GALDHH UNIT : AJH126/126/072GALDH	108.0kW (38HP) AJH342GALDHH UNIT : AJH126/126/090GALDH
113.0kW (40HP) AJH360GALDHH UNIT : AJH144/126/090GALDH	120.0kW (42HP) AJH378GALDHH UNIT : AJH126/126/126GALDH	125.0kW (44HP) AJH396GALDHH UNIT : AJH144/126/126GALDH		

8,10,12HP : AJH072GALDH / AJH090GALDH / AJH108GALDH  
14,16HP : AJH126GALDH / AJH144GALDH




8, 10, 12 HP

14, 16 HP





Dimensions

(Unit: mm)

8, 10, 12 HP



14, 16 HP



Outdoor units specifications

Space saving combination

Table with columns for Rated capacity range, HP, and various model units (8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48). Rows include Model name, Unit 1-3, Maximum connectable indoor units\*1, Connectable capacity range, Power source, Capacity, Input power, EER, COP, SEER, SCOP, ηc, ηh, Air flow rate, Sound pressure level, Max. External static pressure, Compressor motor output, Heat exchanger fin, Net Dimensions, Weight, Refrigerant, Connection pipe diameter, and Operating Range.

Energy Efficiency Combination

Table with columns for Rated capacity range, HP, and various model units (16, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44). Rows include Model name, Unit 1-3, Maximum connectable indoor units\*1, Connectable capacity range, Power source, Capacity, Input power, EER, COP, SEER, SCOP, ηc, ηh, Air flow rate, Sound pressure level, Max. External static pressure, Compressor motor output, Heat exchanger fin, Net Dimensions, Weight, Refrigerant, Connection pipe diameter, and Operating Range.

Note: Specifications are based on the following conditions. Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB. Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB. Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.

When cooling operation is being conducted at an outdoor air temperature below -5°C, the outdoor unit must be installed in a position that is higher than or equal to that of the indoor units. \* These specifications are determined by ducted combination. \* Multiple outdoor units are not certified by Eurovent.

\*1: Minimum connectable indoor unit number is 2. \*2: The noise level is the value measured in an anechoic room. When measured in an actual installation, the measured value is typically larger than the indicated value due to ambient noise and reflections.

\*3: If the capacity range of the connectable indoor units is between 25% and 49.9%, do not open the three-way valve except for the unit to be operated. In addition, do not connect the power line.






**Heat Pump**  
Modular type

**VRF V-IV**


**System configuration example**

- Suitable for air conditioning midsize and large buildings. Connecting each outdoor unit makes it possible to create a high-capacity system.
- Multiple indoor units are connected with separation tubes and headers.



**New intelligent refrigerant control**

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with subtle control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.




\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.


**Efficiency in actual operating conditions**

The use of our proprietary heat exchanger structure and high-efficiency DC twin-rotary compressors achieves the class-leading coefficient of performance (COP) in every combination.

Space saving combination



Energy efficiency combination



\* These specifications are determined by Cassette combination.

\* Multiple outdoor units are not certified by Eurovent.

**The energy-saving technology that boosted operation efficiency**

- Powerful large propeller fan**  
The fan uses CFD\* technology to achieve both high performance and low noise operation. \*CFD: Computational Fluid Dynamics
- 3-phase DC fan motor**  
The use of a DC fan motor with sophisticated driver control improves energy efficiency substantially. In addition, low noise is realized by the DC fan motor.
- Sine-wave DC inverter control**  
High-efficiency is realized by the adoption of reduced switching loss IPM.
- 4-face heat exchanger**  
The 4-face heat exchanger increases the effective surface area and significantly improves heat-exchanging efficiency.
- Subcooling heat exchanger**  
High heat exchange efficiency is achieved by using an internal projection-shape double-pipe construction.
- High-efficient, large-capacity DC twin-rotary compressor**  
Large-capacity high-efficient DC twin-rotary compressor with excellent intermediate capability.
- Front intake port (Corner cut air inlet structure)**  
In multiple outdoor unit installations, the unique front intake design improves airflow into the heat exchanger.

Outdoor units lineup - Combinations other than those listed below are not recommended.

Space saving combination

22.4 kW (8 HP) AJH072LALDH UNIT: AJH072LALDH	28.0 kW (10 HP) AJH090LALDH UNIT: AJH090LALDH	33.5 kW (12 HP) AJH108LALDH UNIT: AJH108LALDH	40.0 kW (14 HP) AJH126LALDH UNIT: AJH126LALDH	45.0 kW (16 HP) AJH144LALDH UNIT: AJH144LALDH
50.4 kW (18 HP) AJH162LALDH UNIT: AJH090/072LALDH	56.0 kW (20 HP) AJH180LALDH UNIT: AJH090/090LALDH	62.4 kW (22 HP) AJH198LALDH UNIT: AJH126/072LALDH	68.0 kW (24 HP) AJH216LALDH UNIT: AJH126/090LALDH	73.0 kW (26 HP) AJH234LALDH UNIT: AJH144/090LALDH
78.5 kW (28 HP) AJH252LALDH UNIT: AJH144/108LALDH	85.0 kW (30 HP) AJH270LALDH UNIT: AJH144/126LALDH	90.0 kW (32 HP) AJH288LALDH UNIT: AJH144/144LALDH	95.4 kW (34 HP) AJH306LALDH UNIT: AJH144/090/072LALDH	101.0 kW (36 HP) AJH324LALDH UNIT: AJH144/090/090LALDH
106.5 kW (38 HP) AJH342LALDH UNIT: AJH144/108/090LALDH	113.0 kW (40 HP) AJH360LALDH UNIT: AJH144/126/090LALDH	118.0 kW (42 HP) AJH378LALDH UNIT: AJH144/144/090LALDH	123.5 kW (44 HP) AJH396LALDH UNIT: AJH144/144/108LALDH	130.0 kW (46 HP) AJH414LALDH UNIT: AJH144/144/126LALDH
135.0 kW (48 HP) AJH432LALDH UNIT: AJH144/144/144LALDH				

Energy efficiency combination

44.8 kW (16 HP) AJH144LALDHH UNIT: AJH072/072LALDH	55.9 kW (20 HP) AJH180LALDHH UNIT: AJH108/072LALDH	67.2 kW (24 HP) AJH216LALDHH UNIT: AJH072/072/072LALDH	72.8 kW (26 HP) AJH234LALDHH UNIT: AJH090/072/072LALDH	78.3 kW (28 HP) AJH252LALDHH UNIT: AJH108/072/072LALDH
84.8 kW (30 HP) AJH270LALDHH UNIT: AJH126/072/072LALDH	89.4 kW (32 HP) AJH288LALDHH UNIT: AJH108/108/072LALDH	95.9 kW (34 HP) AJH306LALDHH UNIT: AJH126/108/072LALDH	100.5 kW (36 HP) AJH324LALDHH UNIT: AJH108/108/108LALDH	107.0 kW (38 HP) AJH342LALDHH UNIT: AJH126/108/108LALDH
113.5 kW (40 HP) AJH360LALDHH UNIT: AJH126/126/108LALDH	120.0 kW (42 HP) AJH378LALDHH UNIT: AJH126/126/126LALDH	125.0 kW (44 HP) AJH396LALDHH UNIT: AJH144/126/126LALDH		

8, 10 HP: AJH072LALDH / AJH090LALDH  
12, 14, 16 HP: AJH108LALDH / AJH126LALDH / AJH144LALDH




8, 10 HP

12, 14, 16 HP





Dimensions

(Unit: mm)

8, 10 HP



12, 14, 16 HP



Outdoor unit specifications

Space saving combination

Rated capacity range			HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	
Model name				AJH072LALDH	AJH090LALDH	AJH108LALDH	AJH126LALDH	AJH144LALDH	AJH162LALDH	AJH180LALDH	AJH198LALDH	AJH216LALDH	AJH234LALDH	AJH252LALDH	AJH270LALDH	AJH288LALDH	AJH306LALDH	AJH324LALDH	AJH342LALDH	AJH360LALDH	AJH378LALDH	AJH396LALDH	AJH414LALDH	AJH432LALDH	
Unit 1				AJH072LALDH	AJH090LALDH	AJH108LALDH	AJH126LALDH	AJH144LALDH	AJH162LALDH	AJH180LALDH	AJH198LALDH	AJH216LALDH	AJH234LALDH	AJH252LALDH	AJH270LALDH	AJH288LALDH	AJH306LALDH	AJH324LALDH	AJH342LALDH	AJH360LALDH	AJH378LALDH	AJH396LALDH	AJH414LALDH	AJH432LALDH	
Unit 2				AJH072LALDH	AJH090LALDH	AJH108LALDH	AJH126LALDH	AJH144LALDH	AJH162LALDH	AJH180LALDH	AJH198LALDH	AJH216LALDH	AJH234LALDH	AJH252LALDH	AJH270LALDH	AJH288LALDH	AJH306LALDH	AJH324LALDH	AJH342LALDH	AJH360LALDH	AJH378LALDH	AJH396LALDH	AJH414LALDH	AJH432LALDH	
Unit 3				AJH072LALDH	AJH090LALDH	AJH108LALDH	AJH126LALDH	AJH144LALDH	AJH162LALDH	AJH180LALDH	AJH198LALDH	AJH216LALDH	AJH234LALDH	AJH252LALDH	AJH270LALDH	AJH288LALDH	AJH306LALDH	AJH324LALDH	AJH342LALDH	AJH360LALDH	AJH378LALDH	AJH396LALDH	AJH414LALDH	AJH432LALDH	
Maximum connectable indoor units*1				17	21	26	30	34	39	43	47	52	56	60	64	64	64	64	64	64	64	64	64	64	
Connectable capacity range of indoor units			kW	11.2-33.6	14.0-42.0	16.8-50.2	20.0-60.0	22.5-67.5	25.2-75.6	28.0-84.0	31.2-93.6	34.0-102.0	36.5-109.5	39.3-117.7	42.5-127.5	45.0-135.0	47.7-143.1	50.5-151.5	53.3-159.7	56.5-169.5	59.0-177.0	61.8-185.2	65.0-195.0	67.5-202.5	
Power source				3-phase, 4-wire, ~400 V, 50 Hz												3-phase, 4-wire, ~400 V, 50 Hz									
Capacity	Cooling	kW		22.4	28.0	33.5	40.0	45.0	50.4	56.0	62.4	68.0	73.0	78.5	85.0	90.0	95.4	101.0	106.5	113.0	118.0	123.5	130.0	135.0	
	Nominal Heating			22.4	28.0	33.5	40.0	45.0	50.4	56.0	62.4	68.0	73.0	78.5	85.0	90.0	95.4	101.0	106.5	113.0	118.0	123.5	130.0	135.0	
	Max. Heating			25.0	31.5	37.5	45.0	48.0	56.5	63.0	70.0	76.5	79.5	85.5	93.0	96.0	104.5	111.0	117.0	124.5	127.5	133.5	141.0	144.0	
Input power	Cooling	kW		5.95	9.06	9.54	13.18	16.74	15.01	18.12	19.13	22.24	25.80	26.28	29.92	33.48	31.75	34.86	35.34	38.98	42.54	43.02	46.66	50.22	
	Nominal Heating			5.42	7.44	7.76	11.74	13.76	12.86	14.88	17.16	19.18	21.20	21.52	25.50	27.52	26.62	28.64	28.96	32.94	34.96	35.28	39.26	41.28	
	Max. Heating			6.26	8.98	9.48	14.00	15.02	17.96	20.26	22.98	24.00	24.50	29.02	30.04	30.26	32.98	33.48	38.00	39.02	39.52	44.04	45.06		
EER	Cooling	W/W		3.76	3.09	3.51	3.03	2.68	3.36	3.09	3.26	3.06	2.83	2.99	2.84	2.69	3.00	2.90	3.01	2.90	2.77	2.87	2.79	2.69	
COP	Nominal Heating			4.13	3.76	4.31	3.41	3.27	3.92	3.76	3.64	3.55	3.44	3.65	3.33	3.27	3.58	3.53	3.68	3.43	3.38	3.50	3.31	3.27	
	Max. Heating			3.99	3.50	3.95	3.21	3.19	3.71	3.51	3.46	3.33	3.31	3.49	3.20	3.20	3.45	3.37	3.49	3.28	3.27	3.38	3.20	3.20	
SEER	Cooling		7.09	6.56	7.33	6.67	6.18	6.83	6.56	6.64	6.62	6.37	6.76	6.43	6.18	6.61	6.43	6.69	6.47	6.31	6.56	6.34	6.18		
SCOP	Heating		3.83	3.80	4.19	4.19	4.27	3.82	3.80	4.05	4.00	4.04	4.23	4.23	4.27	3.97	3.96	4.09	4.09	4.11	4.24	4.24	4.27		
ηc	Cooling	%		281.0	259.0	290.0	264.0	244.0	270.0	259.0	262.5	261.5	251.5	267.0	254.0	244.0	261.3	254.0	264.3	255.7	249.0	259.3	250.7	244.0	
	Heating			150.0	149.0	165.0	165.0	168.0	149.0	159.0	157.0	158.5	166.5	166.5	168.0	155.7	155.3	160.7	160.7	167.0	161.7	167.0	167.0	168.0	
Air flow rate	High	m³/h		11,100	11,100	13,000	13,000	13,700	11,100×2	11,100 × 2	13,000 + 11,100	13,000 + 11,100	13,700 + 11,100	13,700 + 13,000	13,700 + 13,000	13,700 × 2	13,700+11,100×2	13,700+13,000+11,100	13,700 + 13,000 + 11,100	13,700 × 2 + 11,100	13,700×2+13,000	13,700 × 3	13,700 × 3		
	Power level			58 / 79	58 / 79	58 / 81	62 / 84	63 / 86	61 / 82	61 / 82	63 / 85	63 / 85	66 / 87	64 / 87	64 / 87	66 / 88	66 / 89	65 / 87	65 / 87	65 / 88	66 / 89	67 / 89	67 / 90	67 / 90	68 / 91
Max. External static pressure		Pa		82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	
Compressor motor output		kW		7.5	7.5	11.0	11.0	11.0	7.5×2	7.5 × 2	11.0 + 7.5	11.0 + 7.5	11.0 + 7.5	11.0 × 2	11.0 × 2	11.0 × 2	11.0 × 2	11.0 × 2 + 7.5	11.0 × 2 + 7.5	11.0 × 2 + 7.5	11.0 × 2 + 7.5	11.0 × 2 + 7.5	11.0 × 3	11.0 × 3	
Heat exchanger fin				Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	
Net Dimensions	Height	mm		1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
	Width			930	930	1,240	1,240	1,240	930 × 2	930 × 2	1,240 + 930	1,240 + 930	1,240 + 930	1,240 × 2	1,240 × 2	1,240 × 2	1,240 × 2	1,240 + 930 × 2	1,240 + 930 × 2	1,240 × 2 + 930	1,240 × 2 + 930	1,240 × 2 + 930	1,240 × 3	1,240 × 3	1,240 × 3
	Depth			765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765
Weight		kg		252	252	275	275	275	252 × 2	252 × 2	275 + 252	275 + 252	275 + 252	275 × 2	275 × 2	275 × 2	275 × 2 + 252	275 × 2 + 252	275 × 2 + 252	275 × 2 + 252	275 × 2 + 252	275 × 3	275 × 3	275 × 3	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge	kg (CO2eq-T)		11.7 (24.4)	11.7 (24.4)	11.8 (24.6)	11.8 (24.6)	11.8 (24.6)	11.7 × 2 (24.4 × 2)	11.7 × 2 (24.4 × 2)	11.8 + 11.7 (24.6 + 24.4)	11.8 + 11.7 (24.6 + 24.4)	11.8 × 2 (24.6 × 2)	11.8 × 2 (24.6 × 2)	11.8 × 2 (24.6 × 2)	11.8 × 2 (24.6 × 2)	11.8 + 11.7 × 2 (24.6 + 24.4 × 2)	11.8 + 11.7 × 2 (24.6 + 24.4 × 2)	11.8 × 2 + 11.7 (24.6 × 2 + 24.4)	11.8 × 2 + 11.7 (24.6 × 2 + 24.4)	11.8 × 2 + 11.7 (24.6 × 2 + 24.4)	11.8 × 3 (24.6 × 3)	11.8 × 3 (24.6 × 3)	11.8 × 3 (24.6 × 3)	
Connection pipe diameter	Liquid	mm		12.70	12.70	12.70	12.70	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	
	Gas			22.22	22.22	28.58	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27	41.27	41.27
Operating Range	Cooling	°CDB		-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	
	Heating			-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Energy Efficiency Combination

Rated capacity range			HP	16	20	24	26	28	30	32	34	36	38	40	42	44
Model name				AJH144LALDHH	AJH180LALDHH	AJH216LALDHH	AJH234LALDHH	AJH252LALDHH	AJH270LALDHH	AJH288LALDHH	AJH306LALDHH	AJH324LALDHH	AJH342LALDHH	AJH360LALDHH	AJH378LALDHH	AJH396LALDHH
Unit 1				AJH072LALDH	AJH108LALDH	AJH126LALDH	AJH090LALDH	AJH108LALDH	AJH126LALDH	AJH108LALDH	AJH126LALDH	AJH108LALDH	AJH126LALDH	AJH108LALDH	AJH126LALDH	AJH108LALDH
Unit 2				AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH
Unit 3				AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH	AJH072LALDH
Maximum connectable indoor units*1				34	43	52	56	60	64	64	64	64	64	64	64	64
Connectable capacity range of indoor units			kW	22.4-67.2	28.0-83.8	33.6-100.8	36.4-109.2	39.2-117.4	42.4-127.2	44.7-134.1	48.0-143.8	50.3-150.7	53.5-160.5	56.8-170.2	60.0-180.0	62.5-187.5
Power source				3-phase, 4-wire, ~400 V, 50 Hz												
Capacity	Cooling	kW		44.8	55.9	67.2	72.8	78.3	84.8	89.4	95.9	100.5	107.0	113.5	120.0	125.0
	Nominal Heating			44.8	55.9	67.2	72.8	78.3	84.8	89.4	95.9	100.5	107.0	113.5	120.0	125.0
	Max. Heating			50.0	62.5	75.0	81.5	87.5	95.0	100.0	107.0	112.5	120.5	127.5	135.0	138.0
Input power	Cooling	kW		11.90	15.49	17.85	20.96	21.44	25.08	25.03	28.67	28.62	32.26	35.90	39.54	43.10
	Nominal Heating			10.84	13.18	16.26	18.28	18.60	22.58	20.94	24.92	23.28	27.26	31.24	35.22	37.24
	Max. Heating			12.52	15.74	18.78	21.50	22.00	26.52	25.22	29.74	28.44	32.96	37.48	42.00	43.02
EER	Cooling	W/W		3.76	3.61	3.76	3.47	3.65	3.38	3.57	3.34	3.51	3.32	3.16	3.03	2.90
COP	Nominal Heating			4.13	4.24	4.13	3.98	4.21	3.76	4.27	3.85	4.32	3.93	3.63	3.41	3.36
	Max. Heating			3.99	3.97	3.99	3.79	3.98	3.58	3.97	3.61	3.96	3.64	3.40	3.21	3.21
SEER	Cooling		7.09	7.21	7.09	6.91	7.17									

# VRF INDOOR UNITS







17 types and 95 models available to meet the requirements of any building design.

Indoor units for the VRF Systems are compact, highly efficient, quiet, and user-friendly. Fujitsu General offers a variety of types and capacities for its indoor units that are easy to install and maintain. In addition, a variety of optional parts are available to provide an even more desirable air conditioning experience to users.

- V-058 VRF Indoor Unit Lineup for J-VS
- V-060 Compact Cassette Grid type
- V-062 Low Static Pressure Duct Slim Duct/Slim Concealed Floor
- V-064 Wall-mounted type
  
- V-066 VRF Indoor Unit Lineup for J-IVS, J-IV, J-IVL, VR-IV, V-IV
- V-068 Compact Cassette Grid type
- V-070 Cassette Slim type Circular Flow
- V-072 Cassette Large type Circular Flow
- V-074 Cassette One-way Flow type
- V-076 3D Flow Cassette
- V-078 Low Static Pressure Duct Mini Duct
- V-080 Low Static Pressure Duct Slim Duct/Slim Concealed Floor
- V-082 Low Static Pressure Duct
- V-084 Medium Static Pressure Duct
- V-086 High Static Pressure Duct
- V-088 Compact Floor
- V-090 Floor/Ceiling
- V-092 Ceiling
- V-094 Wall-mounted (EEV Internal/external)



# VRF Indoor Unit Lineup for J-VS

Capacity range (kW)			1.1	1.7	2.2	2.8	3.6	4.0	4.5	5.6	7.1	
Class			4	5	7	9	12	14	14	18	24	
Cassette	Compact type	Compact Grid type/Standard type	 AUXB004HLAH	AUXB005HLAH	AUXB007HLAH	AUXB009HLAH	AUXB012HLAH		AUXB014HLAH	AUXB018HLAH		
		High Efficiency*1				AUXN009HLAH	AUXN012HLAH		AUXN014HLAH			
Duct	Low Static Pressure Duct	Slim Duct (With drain pump)	 004 - 014    018    024	ARXD004HLAH	ARXD005HLAH	ARXD007HLAH	ARXD009HLAH	ARXD012HLAH		ARXD014HLAH	ARXD018HLAH	ARXD024HLAH
		High Efficiency*1	 009 - 014			ARXP009HLAH	ARXP012HLAH		ARXP014HLAH			
Wall-mounted type	Wall-mounted type	Wall-mounted type	 004 - 014	ASHA004HCAH	ASHA005HCAH	ASHA007HCAH	ASHA009HCAH	ASHA012HCAH	ASHA014HCAH			
		Wall-mounted type (EEV external)	 004 - 014	ASHE004HCAH	ASHE005HCAH	ASHE007HCAH	ASHE009HCAH	ASHE012HCAH	ASHE014HCAH			
			This model requires the EV kit to be connected.			This model requires the EV kit to be connected.						

\*1: Production by order  
 Specifications and design are subject to change without notice.  
 \*Products other than ducts can be connected to J-IV, J-IVS, J-IVL, V-IV, VR-IV


# Compact Cassette

Grid type



## Compact and stylish panel

The compact and stylish panel fits nicely into a grid type ceiling. The linear design is a perfect fit into a grid of 620 mm x 620 mm in the ceiling.



## Easy maintenance

You can access the unit for maintenance just by removing a ceiling panel right next to the grille. As no inspection hole needs to be cut through the ceiling, no additional construction cost is incurred.



The air inlet grille can be installed to open in any direction for easy maintenance.



## Flexible installation

The unit fits nicely into the decor of a grid type ceiling and can be installed near a lighting or a ventilation opening.



## High ceiling mode

The cassette can be installed up to a height of 3.0 m. (012/014/018).

Model code	Maximum height from floor to ceiling (m)	
	Standard mode	High ceiling mode
004	2.7	-
005	2.7	-
007	2.7	-
009	2.7	-
012	2.7	3.0
014	2.7	3.0
018	2.7	3.0

Model: AUXB004HLAH / AUXB005HLAH / AUXB007HLAH / AUXB009HLAH  
 AUXB012HLAH / AUXB014HLAH / AUXB018HLAH  
 AUXN009HLAH / AUXN012HLAH / AUXN014HLAH \* Production by order



## Specifications


Model name		AUXB004HLAH	AUXB005HLAH	AUXB007HLAH	AUXB009HLAH	AUXB012HLAH	AUXB014HLAH	AUXB018HLAH	AUXN009HLAH	AUXN012HLAH	AUXN014HLAH
Power source		Single phase, 220-240V, 50Hz						Single phase, 220-240V, 50Hz			
Capacity	Cooling	1.1	1.7	2.2	2.8	3.6	4.5	5.6	2.8	3.6	4.5
	Heating	1.3	1.9	2.8	3.2	4.1	5.0	6.3	3.2	4.1	5.0
Input power		21	21	23	24	27	33	50	41	71	81
Airflow rate (Cooling / Heating)*	High	530	530	540	550	600	680	820	750	970	1,030
	Med-High	490 / 480	490 / 480	500	520	560	620	660	550	600	680
	Med	450 / 430	450 / 430	460	480	520	560	590	480	520	560
	Med-Low	420 / 380	420 / 380	420	440	480	500	520	440	480	500
	Low	390 / 340	390 / 340	390	400	430	440	460	400	430	440
	Quiet	350 / 300	350 / 300	350	350	390	390	400	350	390	390
Sound pressure level (Cooling / Heating)*	High	34	34	34	35	37	39	45	42	49	50
	Med-High	32 / 31	32 / 31	32	33	34	37	39	35	37	39
	Med	30 / 29	30 / 29	30	31	33	34	36	31	33	34
	Med-Low	28 / 26	28 / 26	28	29	31	32	33	29	31	32
	Low	27 / 24	27 / 24	27	27	29	30	30	27	29	30
	Quiet	25 / 21	25 / 21	25	25	27	27	27	25	27	27
Net Dimensions (H x W x D)		245 x 570 x 570						245 x 570 x 570			
Weight		14.5	14.5	15	15	15.5	15.5	17	15	15.5	15.5
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas (Flare)	9.52	9.52	9.52	9.52	12.70	12.70	12.70	9.52	12.70	12.70
Drain Hose Diameter (I.D./O.D.)		25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Cassette Grille	Model name	UTG-UFGH-W						UTG-UFGH-W			
	Net Dimensions (H x W x D)	49 x 620 x 620						49 x 620 x 620			
	Weight	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3

Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
 \*The value is the same for cooling and heating if there is one value.

## Optional parts


\*For more details, please refer to the chapter "Optional parts".

- Wireless remote controller: UTY-LNVC
- Fresh Air Intake Kit: UTZ-VXAA
- Insulation kit for high humidity: UTZ-KXGC
- Silver Ion Filter: UTD-HFAA
- Remote sensor kit: UTY-XSZX21
- Cassette Grille: UTG-UFGH-W
- WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
- Gas sensor kit: UTY-SGZH
- Expansion kit: UTZ-JXXA
- Air Outlet Shutter Plate: UTR-YDZB



## Dimensions

(Unit: mm)




# Low Static Pressure Duct Slim Duct




## Slim design

Slim design allows for installation in a tight ceiling space.



## Air intake

Air intake direction can be selected to match the installation site.



## Wide range of static pressures

The use of a DC fan motor makes it possible to adjust the static pressure between 0 and 90 Pa. The static pressure range can be changed by a remote controller.




\* 024 model static pressure range is 0 to 50 Pa.

## Auto louver grille kit (option)

The optional clean-looking flat Auto louver blends into any interior and provides a comfortable airflow.



## Filter (Accessory)



Model: ARXD004HLAH / ARXD005HLAH / ARXD007HLAH / ARXD009HLAH  
ARXD012HLAH / ARXD014HLAH / ARXD018HLAH / ARXD024HLAH  
ARXP009HLAH / ARXP012HLAH / ARXP014HLAH \* Production by order



ARXD004/005/007/009/012/014HLAH  
ARXP009/012/014HLAH



ARXK018HLAH



ARXD024HLAH

## Specifications

Model name	ARXD004HLAH	ARXD005HLAH	ARXD007HLAH	ARXD009HLAH	ARXD012HLAH	ARXD014HLAH	ARXD018HLAH	ARXD024HLAH	ARXP009HLAH	ARXP012HLAH	ARXP014HLAH		
Power source	Single phase, 220-240V, 50Hz												
Capacity	Cooling	1.1	1.7	2.2	2.8	3.6	4.5	5.6	7.1	2.8	3.6	4.5	
	Heating	1.3	1.9	2.8	3.2	4.0	5.0	6.3	8.0	3.2	4.0	5.0	
Input power	W	38	38	41	47	48	84	76	107	77	128	128	
Airflow rate	High	530	530	550	600	580	790	930	1,250	770	940	940	
	Med-High	480	480	520	550	550	720	880	1,180	630	810	810	
	Med	440	440	480	500	520	640	780	1,060	530	660	660	
	Med-Low	410	410	450	460	480	560	670	930	480	580	580	
	Low	370	370	400	400	430	470	580	810	430	490	490	
Quiet	320	320	360	360	350	370	510	640	380	390	390		
Static pressure range	Pa	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 50	0 to 25	0 to 25	0 to 25	
Standard static pressure	Pa	25	25	25	25	25	25	25	25	25	25	25	
Sound pressure level	High	26	26	28	29	30	34	34	35	36	40	40	
	Med-High	26	26	26	27	28	32	31	32	32	38	38	
	Med	25	25	25	25	27	30	29	30	28	33	33	
	Med-Low	24	24	24	24	26	28	27	27	27	31	31	
	Low	22	22	22	22	24	25	25	24	25	27	27	
Quiet	21	21	21	21	22	22	23	21	23	24	24		
Net Dimensions (H × W × D)	mm	198 × 700 × 620						198 × 900 × 620		198 × 1,100 × 620		198 × 700 × 620	
Weight	kg	16	16	16.5	16.5	17	17	21	25	16.5	17	17	
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	9.52	6.35	6.35	6.35	
	Gas (Flare)	9.52	9.52	9.52	9.52	12.70	12.70	12.70	15.88	9.52	12.70	12.70	
Drain Hose Diameter (I.D./O.D.)	mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	


Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
\*1: This value is under cooling operation.

## Optional parts

\*For more details, please refer to the chapter "Optional parts".


Wireless remote controller: UTY-LNVG*	Auto Louver Grille Kit: UTD-GXTA-W (004-014)
Remote sensor unit: UTY-XSZXZ1	UTD-GXTB-W (018)
IR receiver unit: UTY-TRHX	UTD-GXTC-W (024)
WLAN adapter: UTY-TFSXJ3	Silver Ion Filter: UTD-HFTA (004-014)
UTY-TFSXZ1	UTD-HFTB (018)
FG-AC-WIF1Z1	UTD-HFTC (024)
UTZ-JXXA	Gas sensor kit: UTY-SGZH

\*IR receiver unit (UTY-TRHX) is required.




## Dimensions

(Unit: mm)



	ARXD 004-014HLAH	ARXD018HLAH	ARXD024HLAH
a	574	774	974
b	P200x2=400	P200x3=600	P200x4=800
c	734	934	1,134
d	700	900	1,100
e	650	850	1,050
f	P100x6=600	P100x8=800	P100x10=1,000

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.





# Wall-mounted type



## Highly-efficiency, compact design

The 004-014 models share the same design. The high-density and large heat exchanger achieves a highly-efficiency and compact design. The compact body blends in well with conference rooms and offices, providing comfortable air conditioning.

### High-density heat exchanger




## More comfortable airflow

The unique power diffuser provides comfortable air conditioning.

### Heating

The vertical airflow provides powerful floor-level heating.




### Cooling

The left/right airflow avoids blowing cool air directly at the occupants in a room.




## Quiet operation & 6-Step fan speed control

The airflow pattern achieves significant noise reduction. Multistep airflow adjustment to suit the environment



- 6-Step Speed
- High
- Med-High
- Med
- Med-Low
- Low
- Quiet




\* Remote controller is compatible with the following:  
 UTY-RVRG / UTY-LNNG / UTY-RNRG25 / UTY-RLRG / UTY-RSRG / UTY-RHRG / UTY-DCGG22 / UTY-ALGX21 / UTY-APGX21

## The Occupancy sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* If you want to use the Occupancy sensor control function, you need an setting device that can set the Occupancy sensor control function. For example: Wired RC (Touch panel).



Model: ASHA004HCAH / ASHA005HCAH / ASHA007HCAH / ASHA009HCAH / ASHA012HCAH / ASHA014HCAH

[external EEV]

ASHE004HCAH / ASHE005HCAH / ASHE007HCAH / ASHE009HCAH / ASHE012HCAH / ASHE014HCAH



## Specifications

Model name		ASHA004HCAH	ASHA005HCAH	ASHA007HCAH	ASHA009HCAH	ASHA012HCAH	ASHA014HCAH	ASHE004HCAH	ASHE005HCAH	ASHE007HCAH	ASHE009HCAH	ASHE012HCAH	ASHE014HCAH
Power source		Single phase, 220-240V, 50Hz						Single phase, 220-240V, 50Hz					
Capacity	Cooling	1.1	1.7	2.2	2.8	3.6	4.0	1.1	1.7	2.2	2.8	3.6	4.0
	Heating	1.3	1.9	2.8	3.2	4.0	4.5	1.3	1.9	2.8	3.2	4.0	4.5
Input power		12	12	16	19	25	35	12	12	16	19	25	35
Airflow rate	High	450	450	550	590	660	770	450	450	550	590	660	770
	Med-High	430	430	490	550	590	710	430	430	490	550	590	710
	Med	400	400	450	490	550	650	400	400	450	490	550	650
	Med-Low	380	380	390	420	510	590	380	380	390	420	510	590
	Low	360	360	360	360	450	530	360	360	360	360	450	530
Sound pressure level	Quiet	310	310	320	320	320	320	310	310	320	320	320	320
	High	31	31	34	37	40	44	31	31	34	37	40	44
	Med-High	30	30	32	34	37	42	30	30	32	34	37	42
	Med	28	28	30	32	34	40	28	28	30	32	34	40
	Med-Low	27	27	28	29	33	37	27	27	28	29	33	37
Low	26	26	26	26	30	34	26	26	26	26	30	34	
Quiet	22	22	22	22	22	22	22	22	22	22	22	22	
Net Dimensions (H × W × D)		mm 268 × 840 × 203						mm 268 × 840 × 203					
Weight		kg 8						kg 8					
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas (Flare)	9.52	9.52	9.52	9.52	12.70	12.70	9.52	9.52	9.52	9.52	12.70	12.70
Drain Hose Diameter (I.D./O.D.)		mm 13.8/15.8 to16.7						mm 13.8/15.8 to16.7					
EV kit (optional)		-						UTR-EV09XC / UTR-EV14XC					

Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
 When connecting ASH\*004G\*\*H, ASH\*007G\*\*H, ASH\*009G\*\*H to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø12.70 mm.

## Optional parts

\*For more details, please refer to the chapter "Optional parts".


Wireless remote controller: UTY-LNNG  
 Silver Ion Filter: UTR-FA16-5

Expansion kit: UTY-JXXA  
 Remote sensor kit: UTY-XSZX21

WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3,FG-AC-WIFI21  
 Gas sensor kit: UTY-SGZH

## Dimensions

(Unit: mm)





# VRF Indoor Unit Lineup for J-IVS J-IV J-IVL VR-IV V-IV

Capacity range (kW)			1.1	2.2	2.8	3.6	4.0	4.5	5.6	7.1	9.0	10.0	11.2	12.5	14.0	18.0	22.4	25.0	28.0		
Class			4	7	9	12	14	14	18	24	30	34	36	45	54	60	72	90	96		
Cassette	Compact type	Compact Grid type/Standard type		AUXB 004 GLEH	AUXB 007 GLEH	AUXB 009 GLEH	AUXB 012 GLEH		AUXB 014 GLEH	AUXB 018 GLEH	AUXB 024 GLEH										
	Slim type	Circular Flow								AUXM 018 GLEH	AUXM 024 GLEH	AUXM 030 GLEH									
	Large type	Circular Flow								AUXK 018 GLEH	AUXK 024 GLEH	AUXK 030 GLEH	AUXK 034 GLEH	AUXK 036 GLEH	AUXK 045 GLEH	AUXK 054 GLEH					
	One-way Flow type	One-way Flow	 004 - 012    014 - 024	AUXV 004 GLEH	AUXV 007 GLEH	AUXV 009 GLEH	AUXV 012 GLEH		AUXV 014 GLEH	AUXV 018 GLEH	AUXV 024 GLEH										
	3D Flow type	3D Flow								AUXS 018 GLEH	AUXS 024 GLEH										
Duct	Low Static Pressure Duct	Mini Duct (With drain pump)	 004 - 014    018    024	ARXK 004 GLGH	ARXK 007 GLGH	ARXK 009 GLGH	ARXK 012 GLGH		ARXK 014 GLGH	ARXK 018 GLGH	ARXK 024 GLGH										
		Slim Duct (With drain pump)	 04/007 - 014    018    024	ARXD 04 GALH*2	ARXD 007 GLEH	ARXD 009 GLEH	ARXD 012 GLEH		ARXD 014 GLEH	ARXD 018 GLEH	ARXD 024 GLEH										
		High Efficiency*3								ARXP 018 GLFH		ARXP 030 GLFH									
	Medium static pressure duct	Normal									ARXA 024 GLEH	ARXA 030 GLEH		ARXA 036 GLEH	ARXA 045 GLEH						
	High Static Pressure Duct	Normal	 036/45 - 60    072 - 090    096												ARXC 036 GTEH	ARXC 045 GTEH		ARXC 060 GTEH*1	ARXC 072 GTEH*1	ARXC 090 GTEH*1	ARXC 096 GTEH*1
Floor	Floor (*Same as Ceiling models)					ABHA 012 GTEH			ABHA 014 GTEH	ABHA 018 GTEH	ABHA 024 GTEH										
	Slim Concealed Floor (*Same as Slim Duct models)	 04/007 - 014    018    024	ARXD 04 GALH*2	ARXD 007 GLEH	ARXD 009 GLEH	ARXD 012 GLEH		ARXD 014 GLEH	ARXD 018 GLEH	ARXD 024 GLEH											
	Compact Floor		AGHA 004 GCGH	AGHA 007 GCGH	AGHA 009 GCGH	AGHA 012 GCGH		AGHA 014 GCGH													
	Compact Floor (EEV external)		AGHE 004 GCEH	AGHE 007 GCEH	AGHE 009 GCEH	AGHE 012 GCEH		AGHE 014 GCEH													
			This model requires the EV kit to be connected.																		
Ceiling		 012 - 024    030 - 054				ABHA 012 GTEH			ABHA 014 GTEH	ABHA 018 GTEH	ABHA 024 GTEH	ABHA 030 GTEH		ABHA 036 GTEH	ABHA 045 GTEH	ABHA 054 GTEH					
Wall-mounted type	Wall-mounted type	 004 - 014    18 - 24    030 - 034	ASHA 004 GCGH	ASHA 007 GCGH	ASHA 009 GCGH	ASHA 012 GCGH		ASHA 014 GCGH		ASHA 18 GBCH	ASHA 24 GBCH	ASHA 030 GTEH	ASHA 034 GTEH								
	Wall-mounted type (EEV external)	 004 - 014	ASHE 004 GCEH	ASHE 007 GCEH	ASHE 009 GCEH	ASHE 012 GCEH		ASHE 014 GCEH													
			This model requires the EV kit to be connected.																		

\*1: ARXC060/072/090/096G cannot be connected to J-IVS/J-IV Series.  
 \*2: ARXD04GALH cannot be connected to J-IVS/J-IV/J-IVL/VR-IV Series.  
 \*3: Production by order  
 Specifications and design are subject to change without notice.


# Compact Cassette

Grid type



## Compact and stylish panel

The compact and stylish panel fits nicely into a grid type ceiling. The linear design is a perfect fit into a grid of 620 mm x 620 mm in the ceiling.



## Easy maintenance

You can access the unit for maintenance just by removing a ceiling panel right next to the grille. As no inspection hole needs to be cut through the ceiling, no additional construction cost is incurred.



The air inlet grille can be installed to open in any direction for easy maintenance.



## Flexible installation

The unit fits nicely into the decor of a grid type ceiling and can be installed near a lighting or a ventilation opening.



## High ceiling mode

The cassette can be installed up to a height of 3.0 m. (012/014/018/024).

Model code	Maximum height from floor to ceiling (m)	
	Standard mode	High ceiling mode
004	2.7	-
007	2.7	-
009	2.7	-
012	2.7	3.0
014	2.7	3.0
018	2.7	3.0
024	2.7	3.0

**Model: AUXB004GLEH / AUXB007GLEH / AUXB009GLEH  
AUXB012GLEH / AUXB014GLEH / AUXB018GLEH  
AUXB024GLEH**



## Specifications


Model name		AUXB004GLEH	AUXB007GLEH	AUXB009GLEH	AUXB012GLEH	AUXB014GLEH	AUXB018GLEH	AUXB024GLEH
Power source		Single phase, ~230 V, 50 Hz						
Capacity	Cooling	1.1	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	1.3	2.8	3.2	4.1	5.0	6.3	8.0
Input power		23	25	25	29	35	36	84
Airflow rate	High	530/530	540	550	600	680	710	1,030
	Med-High	490/480	500	520	560	620	660	910
	Med	450/430	460	480	520	560	590	790
	Med-Low	420/380	420	440	480	500	520	680
	Low	390/340	390	400	430	440	460	560
	Quiet	350/300	350	350	390	390	400	450
Sound pressure level	High	34/34	34	35	37	38	41	50
	Med-High	32/31	32	33	34	37	39	46
	Med	30/29	30	31	33	34	36	43
	Med-Low	28/26	28	29	31	32	33	39
	Low	27/24	27	27	29	30	30	35
	Quiet	25/21	25	25	27	27	27	30
Net Dimensions (H x W x D)		mm 245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570
Weight		kg 14.5	15	15	15	15	17	17
Connection pipe diameter	Liquid (Flare)	mm 6.35	6.35	6.35	6.35	6.35	6.35	9.52
	Gas (Flare)	mm 9.52	9.52	9.52	12.70	12.70	12.70	15.88
Drain Hose Diameter (I.D./O.D.)		25/32						
Cassette Grille	Model name	UTG-UFGE-W/UTG-UFGC-W						
	Net Dimensions (H x W x D)	mm 49 x 620 x 620/50 x 700 x 700						
	Weight	kg 2.3/2.6						

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
\*1: This value is under cooling operation.

## Optional parts


\*For more details, please refer to the chapter "Optional parts".

Air Outlet Shutter Plate:	UTR-YDZB	Cassette Grille:	UTG-UFGE-W, UTG-UFGC-W
Fresh Air Intake Kit:	UTZ-VXAA	External power supply unit:	UTZ-GXXA, UTZ-GXXC*
Insulation kit for high humidity:	UTZ-KXGC	WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3,
Silver Ion Filter:	UTD-HFAA		FG-AC-WIF1Z1
Remote sensor kit:	UTY-XSZXZ1		



## Dimensions

(Unit: mm)




# Cassette Slim type

Circular Flow




## Unique circular flow design

This Cassette type air conditioner is equipped with a high performance DC fan motor, a turbo fan, and a louver to propel powerful airflows in all directions.



## Uniform temperature air conditioning

Achieve a comfortable air conditioning spread to every corner of the room thanks to the circular flow and wide vertical airflow.



## Individual louver control

Each louver can be set individually by the Touch panel wired remote controller so the user can enjoy the comfort of different directional airflows according to the room layout.

\* UTY-RNRGZ5 Wired remote controller with touch panel and UTY-DCGGZ3 Central remote controller only



Comfortable air conditioning by preventing direct blowing of cold air and by providing swinging air flow simultaneously.

Provides efficient air conditioning based on the room layout

## The Human sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* UTY-RNRGZ5 Wired remote controller with touch panel and UTY-DCGGZ3 Central remote controller only



Human sensor (Optional)

2 modes are available to choose from:

- Auto economy mode** The air conditioner switches to operate on reduced power when it detects that the room is unoccupied.
- Auto-off mode** The air conditioner stops operating when it detects that the room is unoccupied.

Model: AUXM018GLEH / AUXM024GLEH / AUXM030GLEH



## Specifications

Model name		AUXM018GLEH	AUXM024GLEH	AUXM030GLEH
Power source		Single phase, ~230 V, 50 Hz		
Capacity	Cooling	5.6	7.1	9.0
	Heating	6.3	8.0	10.0
Input power		20	25	49
Airflow rate	High	1,050	1,120	1,470
	Med-High	930	1,050	1,160
	Med	900	930	1,070
	Med-Low	870	900	930
	Low	810	870	900
	Quiet	780	780	780
Sound pressure level	High	33	35	40
	Med-High	32	33	36
	Med	31	32	34
	Med-Low	30	31	32
	Low	29	30	31
	Quiet	28	28	28
Dimensions (H × W × D)		246 × 840 × 840		
Weight		24.0	24.5	24.5
Connection pipe diameter	Liquid (Flare)	6.35	9.52	9.52
	Gas (Flare)	12.70	15.88	15.88
Drain Hose Diameter (I.D./O.D.)		25/32		
Cassette Grille	Model name	UTG-UKGC-W/UTG-UKGA-B		
	Dimensions (H × W × D)	53 × 950 × 950		
	Weight	6.0		

Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].  
 When AUX\*018GLEH is connected to an outdoor unit other than one of the J-IVL Series, the pipe diameter should be Ø9.52/Ø15.88 mm (Liquid/Gas).  
 When connecting AUXK036GLEH, AUXK045GLEH, and AUXK054GLEH to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø19.05 mm.


## Optional parts

\*For more details, please refer to the chapter "Optional parts".

Human sensor Kit: UTY-SHZXC	Air Outlet Shutter Plate: UTR-YDZK	IR Receiver Unit: UTY-LBHXD
Wide Panel: UTG-AKXA-W	Insulation kit for high humidity: UTZ-KXRA	WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
Panel Spacer: UTG-BKXA-W	Cassette Grille: UTG-UKGC-W, UTG-UKGA-B	Silver Ion Filter: UTD-HFRA
Fresh air intake kit: UTZ-VXRA	External power supply unit: UTZ-GXXA, UTZ-GXXC*	Remote sensor kit: UTY-XSZXZ1

## Dimensions

(Unit: mm)




# Cassette Large type

Circular Flow




## Unique circular flow design

This Cassette type air conditioner is equipped with a high performance DC fan motor, a turbo fan, and a louver to propel powerful airflows in all directions.



## Uniform temperature air conditioning

Achieve a comfortable air conditioning spread to every corner of the room thanks to the circular flow and wide vertical airflow.



## Individual louver control

Each louver can be set individually by the Touch panel wired remote controller so the user can enjoy the comfort of different directional airflows according to the room layout.

\* UTY-RNRGZ5 Wired remote controller with touch panel and  
\* UTY-DCGGZ3 Central remote controller only



Comfortable air conditioning by preventing direct blowing of cold air and by providing swinging air flow simultaneously.

Provides efficient air conditioning based on the room layout

## The Human sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* UTY-RNRGZ5 Wired remote controller with touch panel and  
\* UTY-DCGGZ3 Central remote controller only



Human sensor (Optional)

2 modes are available to choose from:

- Auto economy mode** The air conditioner switches to operate on reduced power when it detects that the room is unoccupied.
- Auto-off mode** The air conditioner stops operating when it detects that the room is unoccupied.

**Model: AUXK018GLEH / AUXK024GLEH / AUXK030GLEH  
AUXK034GLEH / AUXK036GLEH / AUXK045GLEH  
AUXK054GLEH**



## Specifications

Model name	AUXK018GLEH	AUXK024GLEH	AUXK030GLEH	AUXK034GLEH	AUXK036GLEH	AUXK045GLEH	AUXK054GLEH			
Power source	Single phase, ~230 V, 50 Hz									
Capacity	Cooling	5.6	7.1	9.0	10.0	11.2	12.5			
	Heating	6.3	8.0	10.0	11.2	12.5	14.0			
Input power	kW		40	40	47	47	61	89	116	
Airflow rate	High	m <sup>3</sup> /h	1,420	1,420	1,440	1,440	1,620	1,820	2,040	
			Med-High	1,360	1,360	1,400	1,400	1,500	1,590	1,800
			Med	1,300	1,300	1,340	1,340	1,400	1,500	1,590
			Med-Low	1,270	1,270	1,300	1,300	1,340	1,400	1,440
			Low	1,200	1,200	1,280	1,280	1,280	1,300	1,300
Sound pressure level	Quiet	dB(A)	1,150	1,150	1,150	1,150	1,150	1,150	1,150	
			High	38	38	39	39	41	44	47
			Med-High	37	37	38	38	40	42	45
			Med	36	36	37	37	38	40	42
			Med-Low	35	35	36	36	37	38	39
Low	34	34	35	35	36	36	36			
Quiet	33	33	33	33	33	33	33			
Dimensions (H × W × D)	mm		288 × 840 × 840							
Weight	kg		26.5	26.5	29.5	29.5	29.5	29.5		
Connection pipe diameter	Liquid (Flare)	mm		6.35	9.52	9.52	9.52	9.52	9.52	
	Gas (Flare)	mm		12.70	15.88	15.88	15.88	15.88	15.88	
Drain Hose Diameter (I.D./O.D.)			25/32							
Cassette Grille	Model name	UTG-UKGC-W/UTG-UKGA-B								
	Dimensions (H × W × D)	mm		53 × 950 × 950						
	Weight	kg		6.0						

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].  
When AUX\*018GLEH is connected to an outdoor unit other than one of the J-IVL Series, the pipe diameter should be Ø9.52/Ø15.88 mm (Liquid/Gas).  
When connecting AUXK036GLEH, AUXK045GLEH, and AUXK054GLEH to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø19.05 mm.


## Optional parts

\*For more details, please refer to the chapter "Optional parts".

Human sensor Kit: UTY-SHZXC	Air Outlet Shutter Plate: UTR-YDZK	IR Receiver Unit: UTY-LBHXD
Wide Panel: UTG-AKXA-W	Insulation kit for high humidity: UTZ-KXRA	WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
Panel Spacer: UTG-BKXA-W	Cassette Grille: UTG-UKGC-W, UTG-UKGA-B	Silver Ion Filter: UTD-HFRA
Fresh air intake kit: UTZ-VXRA	External power supply unit: UTZ-GXXA, UTZ-GXXC*	Remote sensor kit: UTY-XSZXZ1

## Dimensions

(Unit: mm)



# Cassette

## One-way Flow type




### Compact chassis size

The compact size allows easy installation in a variety of commercial facilities and environments.

- The height of the chassis is less than 200 mm for all models.
- All 4 to 12 kBtu models are less than 1,000 mm wide.
- The depth of the chassis is 570 mm, which fits nicely into a grid type ceiling.


Dimensions (Panel size) (Unit: mm)

	4	7	9	12	14	18	24
H		198 (43)				198 (43)	
W		785 (950)				1,190 (1,360)	
D		570 (620)				570 (620)	



### Wide airflow range


A large flap with a wide range of movements, equipped with louvers arranged triangularly, sends air into every corner of the room.



In cooling mode, the left/right airflow reaches every corner of the room without directly touching the human body to provide comfortable air conditioning.



In heating mode, warm air is directed downward toward the floor to warm the feet and lower body, while the head is kept relatively cool.



Note: This is a conceptual drawing. The performance of an air conditioner may vary depending on where it is installed, the size of the room, and its distance from the wall.

### Quiet mode

The low operating noise makes the model ideal for use in hotel rooms.



Model: AUXV004GLEH / AUXV007GLEH / AUXV009GLEH  
 AUXV012GLEH / AUXV014GLEH / AUXV018GLEH  
 AUXV024GLEH



AUXV004/007/009/012GLEH



AUXV014/018/024GLEH

### Specifications

Model name		AUXV004GLEH	AUXV007GLEH	AUXV009GLEH	AUXV012GLEH	AUXV014GLEH	AUXV018GLEH	AUXV024GLEH
Power source		Single phase, ~230 V, 50 Hz						
Capacity	Cooling	1.1	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	1.3	2.8	3.2	4.0	5.0	6.3	8.0
Input power		30/30	42/42	42/42	60/60	38/38	56/56	99/99
Airflow rate*	High	460	550	550	670	720	890	1,150
	Med-High	440	440	440	520	660	840	1,020
	Med	420	420	420	480	630	770	940
	Med-Low	400	400	400	450	600	710	790
	Low	380	380	380	410	580	660	700
	Quiet	360	360	360	360	550	580	610
Sound pressure level*	High	38	42	42	45	37	44	49
	Med-High	37	37	37	41	36	43	47
	Med	36	36	36	39	35	40	45
	Med-Low	35	35	35	38	34	38	42
	Low	33	33	33	36	33	36	39
	Quiet	32	32	32	32	32	34	36
Net Dimensions (H × W × D)		mm 198 × 785 × 570	198 × 785 × 570	198 × 785 × 570	198 × 785 × 570	198 × 1,190 × 570	198 × 1,190 × 570	198 × 1,190 × 570
Weight		kg 18	19	19	19	26	26	27
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	9.52
	Gas (Flare)	9.52	9.52	9.52	12.70	12.70	12.70	15.88
Drain Hose Diameter (I.D./O.D.)					25/32			
Cassette Grille	Model name	UTG-UNGA-W			UTG-UNGB-W			
	Net Dimensions (H × W × D)	mm 43 × 950 × 620			43 × 1,360 × 620			
Weight		kg 6.5			8.5			

Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]


### Optional parts

\*For more details, please refer to the chapter "Optional parts".

- WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIFI21  
 IR Receiver Unit: UTY-TRHX  
 Cassette Grille: UTG-UNGA-W (004-012), UTG-UNGB-W (014-024)  
 External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
 Remote sensor kit: UTY-XSXZ1


### Flexible Installation

The L-shaped pipe kit allows for more flexible installation. Equipped with a built-in drain pump as standard, which enables a maximum pipe height difference of 700 m from the ceiling.



### Dimensions

(Unit: mm)



	AUXV 004 / 007 / 009 / 012 GLEH	AUXV 014 / 018 / 024 GLEH
a	950	1,360
b	920	1,330
c	752	1,152
d	785	1,190

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## 3D Flow Cassette




### 3 individually controlled air outlet ports

The Comfortable airflow setting enables the left and right air outlet ports as well as the wide center port to work together to provide a comfortable room environment.


#### Temperature distribution during cooling and heating (when set to Comfortable airflow)



**Testing conditions:** Model AUXS024GLEH running cooling operation with the air volume set to "Hi" to maintain the room temperature at 18°C with the outdoor temperature at 35°C, tested in our 40m<sup>2</sup> environmental test room




**Testing conditions:** Model AUXS024GLEH running heating operation with the air volume set to "Hi" to maintain the room temperature at 30°C with the outdoor temperature at 7°C, tested in our 40m<sup>2</sup> environmental test room



\*1: Announced 2018. In the category of room air conditioners for the home (source: Fujitsu General Limited).

### Individual airflow setting

The individual airflow setting function optimizes the airflow direction to match the room layout.



Adjusts airflows from the side air outlet ports to match the layout and usage of the room to minimize the amount of wasted airflow.



The airflow is optimally controlled to provide improved comfort in a narrow room.

#### Individual control of air outlet ports


Individual airflow can be set using a Wired remote controller with touch panel, Design type and Central remote controller\*. The airflow from each air outlet port can be set individually.



\* Feature available only on UTY-RNRGZ5 Wired remote controller with touch panel and UTY-DCGGZ3 Central remote controller

### High energy saving

The structural design to take in a larger volume of air and blow air out more smoothly reduces air blowing loss and achieves class-leading energy-saving performance.



\*: 018 model

Model: AUXS018GLEH / AUXS024GLEH



### Specifications

Model name		AUXS018GLEH	AUXS024GLEH
Power source		Single phase, ~230 V, 50 Hz	
Capacity	Cooling	5.60	7.10
	Heating	6.30	8.00
Input power		20/28	34/43
Airflow rate*	High	750/870	950/1,040
	Med-High	710/830	890/990
	Med	690/780	860/930
	Med-Low	660/740	810/880
	Low	630/700	770/840
	Quiet	540/540	540/540
Sound pressure level*	High	38/41	43/46
	Med-High	36/40	42/45
	Med	35/39	41/43
	Med-Low	35/37	40/42
	Low	33/36	38/40
	Quiet	29/29	29/29
Net Dimensions (H × W × D)		mm 200 × 1,240 × 500	200 × 1,240 × 500
Weight		kg 25	25
Connection pipe diameter	Liquid (Flare)	mm 6.35	9.52
	Gas (Flare)	mm 12.70	15.88
Drain Hose Diameter (I.D./O.D.)		25/32	
Cassette Grille	Model name	UTG-USGA-W	
	Net Dimensions (H × W × D)	mm 85 × 1,350 × 580	
	Weight	kg 11.5	

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
\*: Applicable to cooling and heating operation

### Optional parts

WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
IR Receiver Unit: UTY-TRHX




Cassette Grille: UTG-USGA-W  
Remote sensor kit: UTY-XSZXZ1

\*For more details, please refer to the chapter "Optional parts".

External power supply unit: UTZ-GXXA, UTZ-GXXC\*

### Dimensions

(Unit: mm)




# Low Static Pressure Duct Mini Duct (With drain pump)




## Space saving design

- Fits into a space 198 mm high and 450 mm deep
- 30% smaller than previous-generation models
- Weighs 16 kg, 10% lighter




## Optimum airflow path and low noise operation

The stabilized airflow reduces the noise level significantly.




## 6-speed control\*

Multistep airflow adjustment allows installation in a quiet location.



## Easy to design and maintain for drain

Indoor unit design for easy maintenance. Parts can be replaced from the side of the unit where maintenance is easier.



Model: ARXK004GLGH / ARXK007GLGH / ARXK009GLGH  
ARXK012GLGH / ARXK014GLGH / ARXK018GLGH  
ARXK024GLGH



## Specifications

Model name	ARXK004GLGH	ARXK007GLGH	ARXK009GLGH	ARXK012GLGH	ARXK014GLGH	ARXK018GLGH	ARXK024GLGH
Power source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling	1.1	2.2	2.8	3.6	4.5	7.1
	Heating	1.3	2.8	3.2	4.0	5.0	8.0
Input power	W	26	28	28	35	66	80
Airflow rate	High	460	460	460	550	760	1,160
	Med-High	440	440	440	520	660	1,060
	Med	420	420	420	480	560	960
	Med-Low	400	400	400	450	490	860
	Low	370	370	370	410	410	750
Quiet	340	340	340	340	340	470	610
Static pressure range	Pa	0 to 30	0 to 30	0 to 30	0 to 30	0 to 50	0 to 50
Standard static pressure		10	10	10	10	15	15
Sound pressure level	High	25	26	26	29	34	32
	Med-High	24	25	25	27	31	30
	Med	23	24	24	26	28	28
	Med-Low	22	23	23	25	26	27
	Low	21	22	22	24	24	25
Quiet	20	21	21	22	22	22	
Net Dimensions (H × W × D)	mm	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 900 × 450
Weight	kg	14.5	15.5	15.5	16	16	22.5
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	9.52
	Gas (Flare)	9.52	9.52	9.52	12.70	12.70	15.88
Drain Hose Diameter (I.D./O.D.)				25/32			

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].


## Optional parts

\*For more details, please refer to the chapter "Optional parts".

- Remote sensor unit: UTY-XSZXZ1
- IR receiver unit: UTY-TRHX
- Silver Ion Filter: UTD-HFTA (004-014), UTD-HFTB (018), UTD-HFTC (024)
- External power supply unit: UTZ-GXXA, UTZ-GXXC\*
- Auto Louver Grille Kit: UTD-GXTA-W (004-014), UTD-GXTB-W (018), UTD-GXTC-W (024)
- WLAN adapter: FG-AC-WIFI21, UTY-TFSXJ3, UTY-TFSXZ1 (007-024)


## Auto Louver Grille Kit (Optional)

The slim design of the unit provides comfortable cooling and heating air conditioning over a wide area. The optional automatic louver grille, which fits nicely into any interior decor, provides comfortable air conditioning (Optional).



## Dimensions

(Unit: mm)



	ARXK004-014GLGH	ARXK018GLGH	ARXK024GLGH
a	575	775	975
b	P200x2=400	P200x3=600	P200x4=800
c	752	952	1,152
d	700	900	1,100
e	650	850	1,050
f	P100x6=600	P100x8=800	P100x10=1,000


\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

# Low Static Pressure Duct Slim Duct/ Slim Concealed Floor




## Slim design

Slim design allows for installation in a tight ceiling space.




## Air intake

Air intake direction can be selected to match the installation site.




## Flexible installation

Ceiling concealed



Floor concealed



## Wide range of static pressures

The use of a DC fan motor makes it possible to adjust the static pressure between 0 and 90 Pa. The static pressure range can be changed by a remote controller.




Static pressure range  
**0 to 90 Pa**


\*024 model static pressure range is 0 to 50 Pa.

## Filter (Accessory)

ARXD04/007/009/012/014/018 ARXD024



Model: ARXD04GALH / ARXD007GLEH / ARXD009GLEH  
ARXD012GLEH / ARXD014GLEH / ARXD018GLEH  
ARXD024GLEH



## Specifications


Model name	ARXD04GALH*	ARXD007GLEH	ARXD009GLEH	ARXD012GLEH	ARXD014GLEH	ARXD018GLEH	ARXD024GLEH	
Power source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	1.1	2.2	2.8	3.6	4.5	7.1	
	Heating	1.3	2.8	3.2	4.0	5.0	8.0	
Input power	W	40	44	50	54	92	122	
Airflow rate	High	510	550	600	600	800	1,330	
	Med-High	-	480	510	530	680	1,140	
	Med	400/470*	440	460	490	600	1,020	
	Med-Low	-	410	420	450	520	900	
	Low	320/440*	370	370	410	440	780	
Quiet	-	320	320	340	340	470	610	
Static pressure range	Pa	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 50	
Standard static pressure	High	26	28	29	30	34	35	
	Med-High	-	26	27	28	32	31	
Sound pressure level	Med	21/25*	25	25	27	30	29	
	Med-Low	-	24	24	26	28	27	
	Low	20/22*	22	22	24	25	24	
	Quiet	-	21	21	22	22	23	
	Quiet	-	21	21	22	22	23	
Net Dimensions (H x W x D)	mm	198 x 700 x 620	198 x 700 x 620	198 x 700 x 620	198 x 700 x 620	198 x 700 x 620	198 x 900 x 620	
Weight	kg	17	17	17	18	18	22	
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	9.52	
	Gas (Flare)	12.70	9.52	9.52	12.70	12.70	15.88	
Drain Hose Diameter (I.D./O.D.)		25/32						

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].  
\*1: This value is under cooling operation.  
\*: ARXD04GALH cannot be connected to J-IVS/J-IVJ/IVL/VR-IV Series.

## Optional parts


\*For more details, please refer to the chapter "Optional parts".

Remote sensor unit:	UTY-XSZXZ1	External power supply unit:	UTZ-GXXA, UTZ-GXXC*
IR receiver unit:	UTB-YWC (04) UTY-TRHX (007-024)	Auto Louver Grille Kit:	UTD-GXTA-W (04, 007-014) UTD-GXTB-W (018) UTD-GXTC-W (024)
WLAN adapter:	UTY-TFSXJ3 (007-024) UTY-TFSXZ1 (007-024) FG-RC-WIF1Z2 (04) FG-AC-WIF1Z1 (007-024)	Silver Ion Filter:	UTD-HFTA (04, 007-014) UTD-HFTB (018) UTD-HFTC (024)




## Dimensions

(Unit: mm)



	ARXD04GALH ARXD007-014GLEH	ARXD018GLEH	ARXD024GLEH
a	574	774	974
b	P200x2=400	P200x3=600	P200x4=800
c	734	934	1,134
d	700	900	1,100
e	650	850	1,050
f	P100x6=600	P100x8=800	P100x10=1,000

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.






# Low Static Pressure Duct

High Efficiency



## Slim & Compact design


The slim and compact design of the indoor unit, with the control box mounted on the side, allows installation in narrow spaces.



## Easy maintenance


Structural improvement has been developed by making the bottom panel in two pieces, front and rear. The internal fan casing is also manufactured in two pieces—upper and lower. The motor and fan can be easily accessed and maintained by removing the rear panel and the lower casing with the main chassis remaining in place.

See below for rear-suction type




## Installation styles


Embedded in Ceiling



Hanging from Ceiling




A drain pipe can be installed on either the left or right side of the unit



## High-efficiency DC fan motor achieves low-energy consumption.

Improved motor efficiency from previous model.




## Wide range of static pressures

Static pressures can be changed in the range of 0 to 80 Pa.

Static pressure range  
**0 to 80 Pa**

Model: ARXP018GLFH / ARXP030GLFH \* Production by order



## Specifications

Model name		ARXP018GLFH	ARXP030GLFH
Power source		Single-phase, ~220V, 50Hz	
Capacity	Cooling	5.6	9.0
	Heating	6.3	10.0
Input power		128	228
Airflow rate	High	1,540 / 1,440	1,940 / 1,660
	Med-High	1,460 / 1,380	1,810 / 1,580
	Med	1,380 / 1,320	1,680 / 1,510
	Med-Low	1,300 / 1,260	1,550 / 1,440
	Low	1,220 / 1,200	1,420 / 1,370
Quiet		1,150 / 1,150	1,300 / 1,300
Static pressure range		0 to 80	0 to 80
Standard static pressure		40	50
Sound pressure level	High	35 / 34	39 / 36
	Med-High	34 / 32	38 / 35
	Med	32 / 31	36 / 34
	Med-Low	31 / 30	34 / 33
	Low	29 / 29	32 / 31
Quiet		28 / 28	30 / 30
Net Dimensions (H × W × D)		270 × 1,135 × 700	270 × 1,135 × 700
Weight		40	40
Connection pipe diameter	Liquid (Flare)	6.35	9.52
	Gas (Flare)	12.70	15.88
Drain Hose Diameter (I.D./O.D.)		25/32	

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].

## Optional parts

\*For more details, please refer to the chapter "Optional parts".


Long-life filter: UTD-LF25NA  
Flange (square): UTD-SF045T  
Flange (round): UTD-RF204

External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
Remote sensor unit: UTY-XSXZ1  
IR receiver unit: UTY-TRHX

Drain pump unit: UTZ-PX1NBA  
WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
Silver Ion Filter: UTD-HFND

## Dimensions

(Unit: mm)




\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

# Medium Static Pressure Duct Normal



## Slim & Compact design


The slim and compact design of the indoor unit, with the control box mounted on the side, allows installation in narrow spaces.



## Easy maintenance


Structural improvement has been developed by making the bottom panel in two pieces, front and rear. The internal fan casing is also manufactured in two pieces—upper and lower. The motor and fan can be easily accessed and maintained by removing the rear panel and the lower casing with the main chassis remaining in place.

See below for rear-suction type




## Installation styles


Embedded in Ceiling



Hanging from Ceiling




A drain pipe can be installed on either the left or right side of the unit



## High-efficiency DC fan motor achieves low-energy consumption.

Improved motor efficiency from previous model.




## Wide range of static pressures

Static pressures can be changed in the range of 0 to 150 Pa.

Static pressure range  
**0 to 150 Pa**

Model: ARXA024GLEH / ARXA030GLEH / ARXA036GLEH / ARXA045GLEH



## Specifications

Model name		ARXA024GLEH	ARXA030GLEH	ARXA036GLEH	ARXA045GLEH
Power source		Single phase, ~230 V, 50 Hz			
Capacity	Cooling	7.1	9.0	11.2	12.5
	Heating	8.0	10.0	12.5	14.0
Input power		94	108	194	240
Airflow rate	High	1,280	1,410	1,840	1,970
	Med-High	1,180	1,350	1,750	1,910
	Med	1,090	1,280	1,660	1,860
	Med-Low	1,000	1,240	1,600	1,780
	Low	920	1,190	1,530	1,710
Quiet		840	1,150	1,470	1,640
Static pressure range		0 to 150	0 to 150	0 to 150	0 to 150
Standard static pressure		40	50	50	60
Sound pressure level	High	31	34	37	41
	Med-High	29	33	36	40
	Med	27	32	35	38
	Med-Low	26	31	35	38
	Low	24	30	34	37
Quiet		23	29	33	36
Net Dimensions (H × W × D)		mm 270 × 1,135 × 700	mm 270 × 1,135 × 700	mm 270 × 1,135 × 700	mm 270 × 1,135 × 700
Weight		kg 36	kg 40	kg 40	kg 40
Connection pipe diameter	Liquid (Flare)	9.52	9.52	9.52	9.52
	Gas (Flare)	15.88	15.88	15.88	15.88
Drain Hose Diameter (I.D./O.D.)		25/32			

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].

## Optional parts

\*For more details, please refer to the chapter "Optional parts".


Long-life filter: UTD-LF25NA  
Flange (square): UTD-SF045T  
Flange (round): UTD-RF204

External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
Remote sensor unit: UTY-XSZXZ1  
IR receiver unit: UTY-TRHX

Drain pump unit: UTZ-PX1NBA  
WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
Silver Ion Filter: UTD-HFND

## Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

# High Static Pressure Duct Normal



Model: ARXC036GTEH / ARXC045GTEH / ARXC060GTEH  
ARXC072GTEH / ARXC090GTEH / ARXC096GTEH




## Static pressure mode selection

The use of a DC fan motor makes it possible to adjust the static pressure between 0 to 200 Pa (ARXC036) / 250 Pa (ARXC045/060) / 300 Pa (ARXC072/090/096)



## Easy installation (Compact & Lightweight)


The indoor unit is designed to be compact and light by reducing the basic chassis size and the overall material weight.



## Low noise


Models: ARXC036/ARXC045/ARXC060

The corners of the front panel and fan casing of the indoor unit are shaved to reduce air turbulence. The use of a plastic case and fan reduces the noise level generated by the unit.



## High-efficiency DC fan motor achieves low energy consumption.

Improved motor efficiency compared to the previous model



## Specifications


Model name	ARXC036GTEH	ARXC045GTEH	ARXC060GTEH*	ARXC072GTEH*	ARXC090GTEH*	ARXC096GTEH*
Power source	Single phase, ~230 V, 50 Hz					
Capacity	Cooling	11.2	12.5	18.0	22.4	28.0
	Heating	12.5	14.0	20.0	25.0	31.5
Input power	W	207	715	730	681	838
Airflow rate	High	1,990	3,500	3,500	3,900	4,850
	Med	1,680	3,000	3,000	3,300	4,250
	Low	1,330	2,460	2,460	3,000	3,600
Static pressure range	Pa	0 to 200	100 to 250	100 to 250	0 to 300	0 to 300
Standard static pressure	Pa	100	100	100	150	150
Sound pressure level	High	42	49	49	47	48
	Med	36	45	45	43	46
	Low	32	42	42	40	44
Net Dimensions (H × W × D)	mm	400 × 1,050 × 500	400 × 1,050 × 500	400 × 1,050 × 500	450 × 1,587 × 700	450 × 1,587 × 700
Weight	kg	40	46	46	84	84
Connection pipe diameter	Liquid	9.52 (Flare)	9.52 (Flare)	9.52 (Flare)	9.52 (Flare)	9.52 (Flare)
	Gas	15.88 (Flare)	15.88 (Flare)	15.88 (Flare)	19.05 (Flare)	19.05 (Flare)
Drain Hose Diameter (I.D./O.D.)						25/32

Note: Specifications are based on the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
\*: ARXC060/072/090/096G cannot be connected to J-IV/J-IVS Series.

## Optional parts

Long-life filter: UTD-LF60KA (036/045/060) External power supply unit: UTZ-GXXA, UTZ-GXXC\* IR receiver unit: UTY-TRHX Remote sensor unit: UTY-XSZXZ1 WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1 Silver Ion Filter: UTD-HFKB (036/045/060)

## Dimensions




# Compact floor




## 2-fan and wide airflow

A 2-fan individual vertical airflow cools or warms the entire room comfortably.




## Flexible and easy installation

The compact and whole-surface suction design provides flexible installation options, including floor-standing, embedded, partially embedded, and wall-mounted installation to match the room layout.




## Quiet operation

6-fan speed control for quiet operation (via 2-wire controller)



## Flexible pipe connection enables draining and piping in 6 directions

The drain hose and pipe can be connected to the unit in the right, left, straight in depth, or downward direction.



**Model: AGHA004GCGH / AGHA007GCGH / AGHA009GCGH / AGHA012GCGH / AGHA014GCGH**  
**[external EEV]**  
**AGHE004GCEH / AGHE007GCEH / AGHE009GCEH / AGHE012GCEH / AGHE014GCEH**



## Specifications

Model name	AGHA004GCGH	AGHA007GCGH	AGHA009GCGH	AGHA012GCGH	AGHA014GCGH	AGHE004GCEH	AGHE007GCEH	AGHE009GCEH	AGHE012GCEH	AGHE014GCEH	
Power source	Single phase, ~230 V, 50 Hz					Single phase, ~230 V, 50 Hz					
Capacity	Cooling	1.1	2.2	2.8	3.6	4.0	1.1	2.2	2.8	3.6	4.0
	Heating	1.3	2.8	3.2	4.0	4.5	1.3	2.8	3.2	4.0	4.5
Input power	W					W					
Airflow rate	High	380/430	470	500	590	670	380/430	470	500	590	670
	Med-High	350	420	450	520	590	350	420	450	520	590
	Med	320	390	400	470	520	320	390	400	470	520
	Med-Low	310	360	360	420	450	310	360	360	420	450
	Low	280	330	330	390	390	280	330	330	390	390
Sound pressure level	High	35/36	37	38	42	46	35/36	37	38	42	46
	Med-High	33	35	36	39	42	33	35	36	39	42
	Med	31	33	34	37	39	31	33	34	37	39
	Med-Low	30	31	31	35	36	30	31	31	35	36
	Low	28	29	29	33	33	28	29	29	33	33
Quiet	22	22	22	30	30	22	22	22	30	30	
Net Dimensions (H × W × D)	mm					mm					
Weight	kg					kg					
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	
	Gas (Flare)	9.52	9.52	9.52	12.70	12.70	9.52	9.52	9.52	12.70	
Drain Hose Diameter (I.D./O.D.)	mm					mm					
EV kit (optional)											


Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
 When connecting AGHA004/007/009GCGH, AGHE004/007/009GCEH to an outdoor unit other than an outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø12.70 mm.

## Optional parts

Partially concealing kit: UTR-STA  
 Silver Ion Filter: UTR-FA03-S  
 External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
 WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1

## Dimensions

(Unit: mm)



# Floor/Ceiling



## Flexible installation

### Example of floor standing installation

Floor standing console with the back against the wall



### Example of ceiling installation


Under ceiling




## Double auto swing

The combination of horizontal and vertical swings enables 3-dimensional control of the airflow direction.

RIGHT and LEFT SWING



UP and DOWN SWING



## High-power DC fan motor

- High power
- Wide rotation range
- High-efficiency



## Compact design

Symmetrical, slim and compact design.



Model: ABHA012GTEH / ABHA014GTEH / ABHA018GTEH / ABHA024GTEH



Floor standing



## Specifications

Model name			ABHA012GTEH	ABHA014GTEH	ABHA018GTEH	ABHA024GTEH
Power source			Single phase, ~230 V, 50 Hz			
Capacity	Cooling	kW	3.6	4.5	5.6	7.1
	Heating		4.0	5.0	6.3	8.0
Input power			30	42	74	99
Airflow rate	High	m <sup>3</sup> /h	660	780	1,000	1,000
	Med-High		620	740	910	930
	Med		580	690	830	870
	Med-Low		550	640	750	800
	Low		520	600	660	740
	Quiet		490	550	580	680
Sound pressure level	High	dB(A)	36	40	46	47
	Med-High		34	39	44	45
	Med		33	38	42	43
	Med-Low		31	36	40	41
	Low		29	35	37	39
	Quiet		28	34	35	37
Net Dimensions (H × W × D)	mm		199 × 990 × 655	199 × 990 × 655	199 × 990 × 655	199 × 990 × 655
Weight	kg		25	26	26	27
Connection pipe diameter	Liquid (Flare)	mm	6.35	6.35	6.35	9.52
	Gas (Flare)		12.70	12.70	12.70	15.88
Drain Hose Diameter (I.D./O.D.)			25/32			

Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

## Optional parts


\*For more details, please refer to the chapter "Optional parts".

External power supply unit: UTZ-GXXA, UTZ-GXXC\*

WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIFI21

## Dimensions

(Unit: mm)



# Ceiling



Model: ABHA030GTEH / ABHA036GTEH / ABHA045GTEH / ABHA054GTEH



### Specifications

Model name		ABHA030GTEH	ABHA036GTEH	ABHA045GTEH	ABHA054GTEH
Power source		Single phase, ~230 V, 50 Hz			
Capacity	Cooling	9.0	11.2	12.5	14.0
	Heating	10.0	12.5	14.0	16.0
Input power		66	85	131	180
Airflow rate	High	1,630	1,690	2,010	2,270
	Med-High	1,520	1,560	1,840	2,070
	Med	1,420	1,450	1,690	1,860
	Med-Low	1,320	1,360	1,530	1,660
	Low	1,220	1,270	1,380	1,470
	Quiet	1,140	1,170	1,230	1,280
Sound pressure level	High	42	45	48	51
	Med-High	40	41	46	49
	Med	39	39	45	46
	Med-Low	37	38	41	43
	Low	35	36	38	40
	Quiet	33	34	35	36
Net Dimensions (H × W × D)		mm 240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700
Weight		kg 46	48	48	48
Connection pipe diameter	Liquid (Flare)	9.52	9.52	9.52	9.52
	Gas (Flare)	15.88	15.88	15.88	15.88
Drain Hose Diameter (I.D./O.D.)		25/32			

Note: Specifications are subject to the following conditions:  
 Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
 Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
 Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

### Installation

**Open**

General installation with indoor unit installed on the ceiling

**Concealed**


Installation with indoor unit embedded into the ceiling

**Wall-mounted type** (Locally Available)

Wall-mounting brackets are used to mount the indoor unit on the wall. (Locally available)  
This type of installation is used when the ceiling space is insufficient.

### Double auto swing and wide airflow

Auto airflow direction and auto swing




### High-power DC fan motor

- High power
- Wide rotation range
- High-efficiency




### Long airflow

Long airflow provides comfort in every corner of a large room.



### Fresh air intake




### Slim & Compact design



### Optional parts


\*For more details, please refer to the chapter "Optional parts".

- Drain pump unit: UTR-DPB24T
- Flange: UTD-RF204
- External power supply unit: UTZ-GXXA, UTZ-GXXC\*
- WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIFI21



### Dimensions

(Unit: mm)





# Wall-mounted type



## Highly-efficiency, compact design

The 004-014 models share the same design. The high-density and large heat exchanger achieves a highly-efficiency and compact design. The compact body blends in well with conference rooms and offices, providing comfortable air conditioning.

High-density heat exchanger



## More comfortable airflow

The unique power diffuser provides comfortable air conditioning.

### Heating

The vertical airflow provides powerful floor-level heating.




### Cooling

The left/right airflow avoids blowing cool air directly at the occupants in a room.




## Quiet operation & 6-Step fan speed control

The airflow pattern achieves significant noise reduction. Multistep airflow adjustment to suit the environment



- 6-Step Speed
- High
- Med-High
- Med
- Med-Low
- Low
- Quiet




\* Remote controller is compatible with the following:  
UTY-RVRG / UTY-LNVG / UTY-RNRG25 / UTY-RLRG / UTY-RSRG / UTY-RHRG / UTY-DCGG22 / UTY-ALGX21 / UTY-APGX21

## The Human sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* If you want to use the 'Occupancy sensor control' function, you need a setting device that can set the 'Occupancy sensor control' function. For example: Wired RC (Touch panel).



**Model: ASHA004GCGH / ASHA007GCGH / ASHA009GCGH  
ASHA012GCGH / ASHA014GCGH**  
[external EEV]  
**ASHE004GCEH / ASHE007GCEH / ASHE009GCEH  
ASHE012GCEH / ASHE014GCEH**



## Specifications

Model name	ASHA004GCGH	ASHA007GCGH	ASHA009GCGH	ASHA012GCGH	ASHA014GCGH	ASHE004GCEH	ASHE007GCEH	ASHE009GCEH	ASHE012GCEH	ASHE014GCEH	
Power source	Single phase, ~230 V, 50 Hz					Single phase, ~230 V, 50 Hz					
Capacity	Cooling	1.1	2.2	2.8	3.6	4.0	1.1	2.2	2.8	3.6	4.0
	Heating	1.3	2.8	3.2	4.0	4.5	1.3	2.8	3.2	4.0	4.5
Input power		12	19	20	25	36	12	19	34	25	36
		450	550	610	690	800	450	550	610	690	800
Airflow rate	High	430	510	560	610	740	430	510	560	610	740
	Med-High	400	470	510	560	680	400	470	510	560	680
	Med	380	410	440	530	610	380	410	440	530	610
	Med-Low	360	360	360	470	550	360	360	360	470	550
	Low	310	310	310	330	330	310	310	310	330	330
	Quiet	31	34	37	40	44	31	35	43	40	44
Sound pressure level	High	30	32	35	37	42	30	32	38	37	42
	Med-High	28	30	32	35	40	28	30	34	35	40
	Med	27	28	29	33	37	27	27	29	33	37
	Med-Low	26	26	26	30	34	26	24	24	30	34
	Low	22	22	22	24	24	22	22	22	24	24
	Quiet										
Net Dimensions (H x W x D)	mm	268 x 840 x 203					268 x 840 x 203				
Weight	kg	8.0	8.5	8.5	8.5	8.5	8.0	8.5	8.5	8.5	8.5
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas (Flare)	9.52	9.52	9.52	12.70	12.70	9.52	9.52	9.52	12.70	12.70
Drain Hose Diameter (I.D./O.D.)		13.8/15.8 to16.7					13.8/15.8 to16.7				
EV kit (optional)		-					UTR-EV09XB		UTR-EV14XB		

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]  
When connecting ASH\*004G\*\*H, ASH\*007G\*\*H, ASH\*009G\*\*H to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø12.70 mm.

## Optional parts

\*For more details, please refer to the chapter "Optional parts".


External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
Silver Ion Filter: UTR-FA16-5

Remote sensor kit: UTY-XSZX21

WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIFI21

## Dimensions

(Unit: mm)




# Wall-mounted type



## Powerful & Comfort airflow


### Powerful Airflow

(ASHA030GTEH)



### Power diffuser


(ASHA18/24GBCH)



## The Human sensor contributes to further energy savings (ASHA030/034GTEH only)



Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* If you want to use the Human sensor control' function, you need an setting device that can set the Human sensor control' function. For example: Wired RC (Touch panel).



## 6-step fan speed control for quiet operation

The airflow pattern achieves significant noise reduction. A 6-step sound level setting allows for multiple-step silent operations.



\* Remote controller is compatible with the following:  
UTY-RVRG / UTY-LNVG / UTY-RNRG25 / UTY-RLRG / UTY-RSRG / UTY-RHRG / UTY-DCGG22 / UTY-ALGX21 / UTY-APGX21

Model: ASHA18GBCH / ASHA24GBCH  
ASHA030GTEH / ASHA034GTEH



ASHA18/24GBCH



ASHA030/034GTEH

## Specifications

Model name		ASHA18GBCH	ASHA24GBCH	ASHA030GTEH	ASHA034GTEH
Power source		Single phase, ~230 V, 50 Hz			
Capacity	Cooling	5.6	7.1	9.0	10.0
	Heating	6.3	8.0	10.0	11.2
Input power		32	60	74	103
Airflow rate	High	840	1,100	1,440	1,620/1,520
	Med-High	-	-	1,200	1,300
	Med	770	910	1,050	1,120
	Med-Low	-	-	940	980
	Low	690	730	890	890
	Quiet	-	-	700	700
Sound pressure level	High	41	48	53	55/54
	Med-High	-	-	49	51
	Med	39	43	45	47
	Med-Low	-	-	42	43
	Low	35	35	39	39
	Quiet	-	-	33	33
Net Dimensions (H x W x D)		mm 320 x 998 x 238	320 x 998 x 238	340 x 1,150 x 280	340 x 1,150 x 280
Weight		kg 15	15	18	18
Connection pipe diameter	Liquid (Flare)	6.35	9.52	9.52	9.52
	Gas (Flare)	12.70	15.88	15.88	15.88
Drain Hose Diameter (I.D./O.D.)		12/16		13.8/15.8 to16.7	

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].  
When connecting ASHA18GBCH to an outdoor unit other than the outdoor unit of the J-IVL Series, the pipe diameter should be Ø9.52/Ø15.88 mm (Liquid/Gas).

## Optional parts


\*For more details, please refer to the chapter "Optional parts".

External power supply unit: UTY-GXXA (030/034), UTY-GXXC\* (030/034)      WLAN adapter: UTY-TFSXJ3 (030/034), UTY-TFSXZ1 (030/034)      Silver Ion Filter: UTR-FA13-3  
Remote sensor kit: UTY-XSZX21      FG-RC-WIF1Z2 (18/24), FG-AC-WIF1Z1 (030/034)


## Dimensions

(Unit: mm)


Models: ASHA18/ASHA24



Models: ASHA030/ASHA034







Efficient heat exchange combined with fresh ventilation

The use of a high-efficiency heat-exchanging process achieves outstanding energy efficiency and quiet operation. The heat-exchanging mode or the normal ventilation mode can be appropriately selected according to the air conditioning requirements of the space to create a comfortable air-conditioned space.













# Residential, Commercial & Light Commercial VENTILATION

## VENTILATION Lineup

- Vn-002 Energy Recovery Ventilator
- Vn-004 DX kit for Air handling applications
  - for VRF Outdoor unit
- Vn-006 DX kit for Air handling applications
  - for Single Split Outdoor Units



## Lineup

Airflow rate (m <sup>3</sup> /h)	250		350		500		800		1000			
Energy Recovery Ventilator												
	UTZ-BD025C		UTZ-BD035C		UTZ-BD050C		UTZ-BD080C		UTZ-BD100C			
Connectable capacity class (kW)	5.0	6.3	8.0	10.0	12.5	14.0	20.0	25.0	40.0	50.0		
DX kit for Air handling applications for VRF Outdoor unit												
	EUV unit UTP-VX30A	Control unit UTY-VDGX	EUV unit UTP-VX60A	Control unit UTY-VDGX	EUV unit UTP-VX90A	Control unit UTY-VDGX	EUV unit UTP-VX90A×2	Control unit UTY-VDGX				
Connectable capacity class (kW)	2.5 - 22.0											
DX kit for Air handling applications for Single Split Outdoor Units												
	UTY-XDZX											

# Energy Recovery Ventilator



The energy recovery ventilator unit provides energy efficiency for comfort and improved savings.


## Heat exchange ventilation and normal ventilation

### Heat exchange ventilation

When a room is cooled or heated, the exhausted cooling or heating energy is recovered by heat exchange ventilation.

### Normal ventilation

Used when the indoor space does not require cooling or heating, i.e., when there is little temperature difference between the indoor and outdoor environments.




A high-efficiency counter-flow heat-exchanging element is used in the setup.

## Energy efficiency and ecology

The use of a counter-flow heat-exchanging element, designed to recover up to 77% of heat from the outgoing air, significantly reduces energy consumption. The air conditioning load is reduced by approximately 20%, which results in substantial savings in energy cost.

## Comparison of heat-exchanging elements

Air flows in a straight line through a cross-flow element. In contrast, air flows for a longer time (a longer distance) through a counter-flow element to achieve more consistent heat-exchanging performance.



## Quiet operation

Significantly lower noise levels are achieved by reducing pressure loss.

**25.5dB**  
(UTZ-BD035C)

## Extended range of external static pressure

The use of a powerful fan motor improves the external static pressure. This allows it to be installed in a variety of buildings.


## Slim design for easier installation

The use of a counter-flow heat-exchanging element made it possible to design a quieter, slimmer unit.



## Reverse-mountable direct air supply and exhaust system

Simplifies the duct design, due to its straight ducts for air supply and exhaust. Since each unit can be mounted facing opposite directions, only one inspection hole is needed for two units. This makes duct work easier and more flexible.



## Simple remote operation

Easy operation with connected liquid crystal switch

- Power On/Off
- Air volume High/Low
- Heat exchange ventilation and normal ventilation
- On/Off Timer
- Clean filter display



**Model: UTZ-BD025C/UTZ-BD035C/UTZ-BD050C/UTZ-BD080C/UTZ-BD100C**




## Specifications

Rated flow rate		250 m <sup>3</sup> /h	350 m <sup>3</sup> /h	500 m <sup>3</sup> /h	800 m <sup>3</sup> /h	1000 m <sup>3</sup> /h		
Model name		UTZ-BD025C	UTZ-BD035C	UTZ-BD050C	UTZ-BD080C	UTZ-BD100C		
Power source		Single phase, ~220 to 240 V, 50 Hz						
Heat Exchange Ventilation	Input power	(Extra high)/High/Low	W	128/123/96	190/185/168	289/225/185	418/378/295	464/432/311
	Airflow rate	(Extra high)/High/Low	m <sup>3</sup> /h	250/25/190	350/350/240	500/500/440	800/800/630	1,000/1,000/700
	External static pressure	(Extra high)/High/Low	Pa	105/95/45	140/60/45	120/60/35	140/110/55	105/80/75
	Temperature exchange efficiency	(Extra high)/High/Low	%	75/75/77	75/75/78	75/75/76	75/75/76	75/75/79
	Energy exchange efficiency cooling	(Extra high)/High/Low	%	63/63/65	66/66/71	62/62/64	65/65/68	65/65/70
	Energy exchange efficiency heat pump	(Extra high)/High/Low	%	70/70/72	69/69/73	67/67/69	71/71/74	71/71/76
Normal Ventilation	Sound pressure level	(Extra high)/High/Low	dB*	31.5/30.5/26.5	33.0/31.0/25.5	37.5/35.5/32.5	37.5/37.0/34.5	38.5/37.5/34.5
	Input power	(Extra high)/High/Low	W	128/123/96	190/185/168	289/225/185	418/378/295	464/432/311
	Airflow rate	(Extra high)/High/Low	m <sup>3</sup> /h	250/25/190	350/350/240	500/500/440	800/800/630	1,000/1,000/700
	External static pressure	(Extra high)/High/Low	Pa	105/95/45	140/60/45	120/60/35	140/110/55	105/80/75
Sound pressure level	(Extra high)/High/Low	dB*	31.5/30.5/26.5	33.0/31.0/25.5	38.5/38.0/32.5	37.5/37.0/34.5	40.5/39.5/36.5	
Dimensions	W × D × H	mm	882 × 599 × 270	1,050 × 804 × 317	1,090 × 904 × 317	1,322 × 884 × 388	1,322 × 1,134 × 388	
Weight		kg	29	49	57	71	83	
Outlet duct diameter		mm	150	150	200	250	250	
Operating range		°C	-10 to 40	-10 to 40	-10 to 40	-10 to 40	-10 to 40	
Maximum humidity		%	85	85	85	85	85	

\* Noise level measured 1.5 m below the center of the unit

## Dimensions

(Unit: mm)




	UTZ-BD025C	UTZ-BD035C	UTZ-BD050C	UTZ-BD080C	UTZ-BD100C
A	810	978	1,018	1,250	1,250
B	599	804	904	884	1,134
C	315	580	640	428	678
D	142	112	132	228	228
E	600	600	600	600	600
F	655	860	960	940	1,190
G	19	19	19	19	19
H	270	317	317	388	388
I	135	159	159	194	194
J	159	182	182	218	218
K	882	1,050	1,090	1,322	1,322
L	414	470	470	612	612
M	95	70	70	85	85
N	Ø164	Ø164	Ø210	Ø258	Ø258
O	Ø144	Ø144	Ø194	Ø242	Ø242

# DX kit for Air handling applications for VRF Outdoor unit



With these kits, air handling units (AHUs) and fan coil units (FCUs) from other manufacturers can be incorporated into Fujitsu General VRF systems, or one AHU can be connected to one Fujitsu General VRF dedicated outdoor unit to control outdoor ventilation and room temperatures.


## Multiple temperature sensors optimally control an Air handling unit and a fan coil unit.



When connected to an Air handling unit, the temperature of supply air is controlled by a discharge air sensor.


When connected to a fan coil unit, the room temperature is controlled by the discharge air sensor.

### Application as part of a VRF system




## Supports a wide range of capacity classes

- Two EEV units can be connected in parallel to large-capacity units of up to 20 HP (50 kW). (UTP-LX180A separation tube required)
- Connectable capacity range: 5 kW to 50 kW




## A variety of control options that meet application requirements

Central control enabled by our VRF controllers or central management controllers



Central control from external controllers



\*DDC stands for Direct Digital Controller

## Summary of functions

### Inputs

- On/Off
- Setting temperature
- Capacity demand
- Heating/Cooling operation modes
- Fault information

### Outputs

- On/Off indication
- Fan On/Off indication
- Thermostat On/Off indication
- Defrost indication
- Fault indication


### MODBUS® Control

Can be controlled via a MODBUS®-enabled BMS using an optional interface.


## Installation requirements

- Connectable VRF Series: All VRF Series
- Capacity range of connectable DX kit systems with outdoor units: 50 to 100% of capacity
- Capacity range of connectable DX kit systems with indoor units: 30% or less of capacity
- Max. wire length from a control unit: 10 m
- Max. pipe length between EEV unit and indoor unit: 5 m
- A control unit (IP54 class) and an EEV unit can be installed outdoors.

### Connectable capacity




### Pipe and wire length



### Optional separation tube to connect two EEV units: UTP-LX180A



### Control unit: UTY-VDGX EEV unit: UTP-VX30A/UTP-VX60A/UTP-VX90A



## Specifications

Connectable capacity class		5.0 kW	6.3 kW	8.0 kW	10.0 kW	12.5 kW	14.0 kW	20.0 kW	25.0 kW	40.0 kW	50.0 kW
Capacity	Cooling	5.6	6.3	8.0	10.0	12.5	14.0	22.4	25.0	40.0	50.4
	Heating	6.3	7.1	9.0	11.2	14.0	16.0	25.0	28.0	45.0	56.5

Control unit		UTY-VDGX	
Power source	V/∅/Hz	230/1/50	
Dimensions (H × W × D)	mm	400 × 400 × 120	

EEV unit		UTP-VX30A	UTP-VX60A	UTP-VX90A	UTP-VX90A × 2
Connection pipe diameter (Liquid)	mm	∅9.53	∅12.70	∅12.70	∅12.70
Dimensions (H × W × D)	mm	160 × 220 × 90			

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m Voltage: 230 [V].


## DX kit for Air handling applications for Single Split Outdoor Units



With this kit, other manufacturers' Air handling units (AHUs) and fan coil units (FCUs) can be incorporated into Fujitsu General Split outdoor units.

### Flexible connectivity

This kit allows connections to third-party equipment. This control unit can also be used in conjunction with Fujitsu General single-split outdoor units, providing a perfect solution when a stand-alone Air handling unit is needed.



### Supports a wide range of capacity classes

Capable of connecting large capacities in the range of 2.5 kW to 22.0 kW (Nominal)



### Mobile devices allow for operation from anywhere

Can be operated and managed remotely using your smartphone or tablet.



### Summary of functions

#### Inputs

- On/Off
- Heating/Cooling operation modes
- Capacity demand (analogue 0 to 10 V)
- Heat exchanger temperature

#### Outputs


- Status of Compressor, Defrost, and Errors (Potential free relays)
- Status indicator with LED

#### Wireless LAN Control

Wireless LAN control through cloud connectivity enables secure remote monitoring and control from anywhere.

### Easy installation

- Compact DIN rail mountable enclosure for easy installation
- No expansion device required
- No separate external power supply required



Model: UTY-XDZX



### Specifications

R410A models

Capacity (Nominal)			12	14	18	24	30	36	45	54	60	72	90
	Cooling	Heating	kW										
			3.5	4.3	5.2	6.8	8.5	9.4	12.1	13.3	15.0	19.0	22.0
			4.1	5.0	6.0	7.8	10.0	10.8	13.3	15.8	18.0	22.4	27.0

R32 models

Capacity (Nominal)			09	12	14	18	22	24	30	36	45	54
	Cooling	Heating	kW									
			2.5	3.5	4.3	5.2	6.0	6.8	8.5	9.4	12.1	13.3
			3.2	4.1	5.0	6.0	7.0	7.5	10.0	10.8	13.3	15.8

Model name		UTY-XDZX	
Power source	V/Ø/Hz	230/1/50	
Dimensions (H × W × D)	mm	90.2 × 53.3 × 57.5	
Weight	g	110	

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 5.0 m Voltage: 230 [V].

## Light Commercial & Commercial, Residential

# CONTROL SYSTEM & OPTIONAL PARTS

- C-002 Control System Overview
- C-006 Best control solution for each building structure
- C-008 Comparison table of controllers
- C-050 Controller System List
- C-058 Optional Parts Overview
- C-066 Optional parts list
- C-070 Function list

A wide product lineup to meet a variety of needs

We can flexibly meet customer needs through a variety of offerings including wired and wireless individual remote controllers, central remote controllers that simultaneously control multiple indoor units, and a variety of converters that link with other systems.

### CONTROL SYSTEM

#### INDIVIDUAL CONTROL

- C-010 Wired remote controller (Design type)
- C-012 Wired remote controller (with touch panel)
- C-014 Wired remote controller / Compact wired remote controller
- C-015 Wired remote controller
- C-016 Simple remote controller
- C-017 Wireless remote controller
- C-018 IR receiver unit

#### CONVERTERS/ADAPTERS

- C-020 WLAN adapter
- C-024 Multiple protocol WLAN adapter

#### CENTRALIZED CONTROL

- C-025 Home central remote controller
- C-026 Central remote controller
- C-028 Touch panel controller
- C-032 System controller **Software** / System controller lite **Software**

#### CONVERTERS/ADAPTERS

- C-036 MODBUS® converter for indoor unit
- C-037 MODBUS® interface
- C-038 MODBUS® converter for VRF
- C-039 BACnet® interface
- C-040 BACnet® gateway **Software**
- C-041 BACnet® gateway **Hardware**
- C-042 BACnet®/MODBUS® router
- C-043 BACnet®/MODBUS® cloud device
- C-044 KNX® converter for indoor unit / KNX® converter for VRF
- C-045 KNX® interface
- C-046 Network converter for single-split type
- C-047 Network converter for LONWORKS™
- C-048 External switch controller / Signal amplifier

### Optional parts

- C-060 Silver ion filter
- C-061 Auto louver grille kit
- C-062 Pressure sensor kit
- C-063 External power supply unit  
AIR BEAM radiation air outlet unit
- C-064 Gas sensor kit
- C-074 Separation tube and other piping products

 SPLIT

 MULTI-SPLIT

 VRF J Series

 VRF V Series

# Control System Overview

for Split & Multi-split

All indoor units\* are equipped with a wireless or wired remote controller as standard. Additional options are available, such as individual remote controllers and central remote controllers. The easy-to-operate central remote controller makes it simple to control the operation mode, temperature, airflow volume, timer, and other functions of each indoor unit from a single location.

\* Except for some products



## Air Conditioning Individual control

**NEW**

**Wired remote controller**  
A built-in thermo sensor monitors and controls room temperature accurately.

**Wireless remote controller**  
Simple and versatile operations with a choice of 4 different types of timers

**Simple remote controller**  
Compact remote controller with basic functionality

**For Ceiling type**

IR receiver unit  
Wireless remote controller

**For Duct type**

IR receiver unit  
Wireless remote controller

**For Cassette type**

IR receiver unit  
Wireless remote controller

**IR receiver unit**  
This IR receiver unit enables a wireless remote controller to control a duct-type indoor unit.



## Air Conditioning Centralized control

**Home central remote controller for 5 & 6-unit Multi-split type**  
Enables individual and central control.

## Converters / Adapters

For external control via BMS/Home Automation Systems

- MODBUS® converter for indoor units**  
UTY-VMSX
- MODBUS® interface for indoor units**
- KNX® converter for indoor units**  
UTY-VKSX
- KNX® interface for indoor units**
- WLAN adapter**
- Network converter**

DC power supply type  
UTY-VTGX

AC power supply type  
UTY-VTGXV

## Online Control (Wireless Control via Smartphone/Tablet)

With the WLAN adapter and the AIRSTAGE Mobile app, you can control the heating and cooling of your home anytime, anywhere.

**WLAN adapter**  
The dedicated WLAN adapter enables the air conditioner to be operated by smartphone or tablet computer.

**AIRSTAGE Mobile** [Download Free](#)

Download on the [App Store](#) | [Google play](#)

**Simple, user-friendly interface design**  
The designed screen display makes it easier than ever to operate.

# Control System Overview

for VRF

To meet the diverse needs of customers, we offer a variety of control options for our VRF systems, such as individual control, centralized control, and building management system (BMS) options.

## Air Conditioning Individual control



**Wired remote controller (Design type)**  
UTY-RVRG



**Wired remote controller (with touch panel)**  
UTY-RNRGZ5



**Wired remote controller**  
UTY-RLRG



**Compact wired remote controller**  
UTY-RCRGZ1



**Simple remote controller**  
UTY-RSRG  
UTY-RHRG  
Without operation mode



**Wireless Remote Controller**  
UTY-LNVG  
UTY-LNHG



For Duct type

### IR receiver unit

UTB-YWC  
for duct type


UTY-TRHX  
for One-way flow cassette Series/  
3D flow cassette Series/  
duct type



for Circular flow  
cassette Series

UTY-LBHXD  
for Circular flow cassette Series

## Air Conditioning Centralized control



**System controller (Software)**  
UTY-APGXZ1/UTY-ALGXZ1 (Lite version) **Up to 1600<sup>\*2</sup> Indoor units**

\*1: Echelon® U10 USB Network Interface  
\*2: The Lite version controls up to 400 indoor units.



**Touch panel controller**  
UTY-DTGGZ1 **Up to 400 Indoor units**



**Central remote controller**  
UTY-DCGGZ3 **Up to 100 Indoor units**



## Converters / Adapters

For external control via BMS/Home Automation Systems

**BACnet® gateway**  
UTY-ABGXZ1 **Software**




**VTY-VBGX (Hardware)**



**BACnet® interface for Indoor units**  
FG-IR-BMG1Z1



**Network converter (For LONWORKS™)**  
UTY-VLGX



**MODBUS® converter for Indoor units**  
UTY-VMSX



**for VRF**  
UTY-VMGX



**KNX® converter for Indoor units**  
UTY-VKSX





**for VRF**  
UTY-VKGX



**WLAN adapter**  
UTY-TFSXJ3 / UTY-TFSXZ1



**External switch controller**  
UTY-TERX



\*3: BMS/BAS: Building Management System/Building Automation System

## Converters / Adapters for system expansion


**Network converter DC power supply type**  
UTY-VTGX **Single split**



**Network converter AC power supply type**  
UTY-VTGXV **Single split**



**Signal amplifier**  
UTY-VSGXZ1



# Best control solution for each building structure

Fujitsu General provides the best control solutions suitable for various building structures.

## SHOP

Type	Individual control			Centralized control			Integrating control (Interface)			
	Wired remote controller	Central remote controller	Touch panel controller	System controller	Network converter for LonWorks™	MODBUS® Converter	KNX® converter			
	UTY-RVRG UTY-RNRGZ5 UTY-RLRG UTY-RVNGM UTY-RCRGZ1	UTY-DCGGZ3	UTY-DTGGZ1	UTY-APGXZ1 UTY-ALGXZ1	UTY-VLGX	UTY-VMGX	UTY-VKGX			
Automatic control of air conditioning (Schedule timer, Weekly timer, etc.)	•	•	•	•						
Controls limited to staff: Remote controller prohibition, Setting temperature range limitation, etc.		•	•	•	•	•	•			•
Group control		•	•	•						
Advanced energy saving: Peak cut, Operation of indoor unit rotation, etc.				•						
Remote monitoring management		•	•	•						
Manage multiple sites		•	•	•						
Monitor energy consumption				•						
Control third-party products				•						
Integrate Fujitsu General air conditioning into BMS					•	•	•			

## HOTEL

Type	Individual control			Centralized control			Integrating control (Interface)				
	Wired remote controller	Simple remote controller	Wireless remote controller	Central remote controller	Touch panel controller	System controller	BACnet® gateway	Network converter for LonWorks™	MODBUS® converter	KNX® converter	External switch controller
	UTY-RVRG UTY-RNRGZ5 UTY-RLRG UTY-RCRGZ1	UTY-RSRG UTY-RHRG	UTY-LNVG UTY-LNHG UTY-LNTG	UTY-DCGGZ3	UTY-DTGGZ1	UTY-APGXZ1 UTY-ALGXZ1	UTY-ABGXZ1 UTY-VBGX	UTY-VLGX	UTY-VMGX	UTY-VKGX	UTY-TERX
Local control for hotel guests	•	•	•								
Centralized air conditioning control for common areas				•	•	•	•	•	•	•	
Limited control for hotel guests				•	•	•	•	•	•	•	
Remote monitoring management				•	•	•					
Advanced energy saving: Peak cut, Operation of indoor unit rotation, etc.						•	•				
Monitor energy consumption						•					
Control third-party products						•					
Integrate Fujitsu General air conditioning into BMS							•	•	•	•	
Interlock with window contact											•
Interlock with key card											•

## OFFICE

Type	Individual control			Centralized control			Integrating control (Interface)				
	Wired remote controller	Simple remote controller	Wireless remote controller	Central remote controller	Touch panel controller	System controller	BACnet® gateway	Network converter for LonWorks™	MODBUS® converter	KNX® converter	External switch controller
	UTY-RVRG UTY-RNRGZ5 UTY-RLRG UTY-RCRGZ1	UTY-RSRG UTY-RHRG	UTY-LNVG UTY-LNHG UTY-LNTG	UTY-DCGGZ3	UTY-DTGGZ1	UTY-APGXZ1 UTY-ALGXZ1	UTY-ABGXZ1 UTY-VBGX	UTY-VLGX	UTY-VMGX	UTY-VKGX	UTY-TERX
Local control for office staff	•	•	•	•							
Automatic control of air conditioning (Schedule timer, Weekly timer, etc.)	•		•	•	•	•	•				
Centralized air conditioning control for management				•	•	•	•	•	•	•	
Controls limited to staff: Remote controller prohibition, Setting temperature range limitation, etc.				•	•	•	•	•	•	•	
Advanced energy saving: Peak cut, Operation of indoor unit rotation, etc.						•	•				
Remote monitoring management				•	•	•					
Electricity charge apportionment					•	•	•				
Monitor energy consumption						•					
Control third-party products						•					
Integrate Fujitsu General air conditioning into BMS							•	•	•	•	
Interlock with door contact											•
Interlock with Human sensor for meeting room				•							•



# Comparison table of controllers

Item																
	Wired remote controller (Design type)	Wired remote controller (with touch panel)	Wired remote controller	Wired remote controller	Compact wired remote controller	Simple Remote Controller		Simple remote controller*1	Wireless remote controller	Wireless remote controller	Wireless remote controller	Home central remote controller (for 5/6-unit multi-split type)	Central remote controller	Touch panel controller	System controller Lite Software	System controller Software
Model name	UTY-RVRG	UTY-RNRGZ5	UTY-RLRG	UTY-RVNGM	UTY-RCRGZ1	UTY-RSRG		UTY-RHRG	UTY-LNTG	UTY-LNVG	UTY-LNHG	UTY-DMMGM	UTY-DCGGZ3	UTY-DTGGZ1	UTY-ALGXZ1	UTY-APGXZ1
Maximum number of controllable remote controller groups	1	1	1	1	1	1		1	1	1	1	1	100	400	400	1600
Maximum number of controllable indoor units	16	16	16	16	1	16		16	16	16	16	8	100	400	400	1600
Maximum number of controllable groups	-	-	-	-	-	-		-	-	-	-	-	50	400	400	1600
Air conditioning control functions	ON/OFF	●	●	●	●	●		●	●	●	●	●	●	●	●	●
	Operation mode setting	●	●	●	●	●		-	●	●	●	●	●	●	●	●
	Fan speed control	●	●	●	●	●		●	●	●	●	●	●	●	●	●
	Room temperature setting	●	●	●	●	●		●	●	●	●	●	●	●	●	●
	Setting temperature range limitation	●	●	●	●	-		●	-	-	-	-	●	●	●	●
	Test operation	●	●	●	●	●		●	●	●	●	●	-	●	●	-
	Vertical louver setting	●	●	●	●	●		●	●	●	●	●	-	●	●	●
	Horizontal louver setting	●	●	●	●	●		-	-	●	●	●	-	●	●	●
	Individual louver control	●	●	-	-	●		-	-	-	-	-	-	●*3	-	-
	Group setting	-	-	-	-	-		-	-	-	-	-	-	●	●	●
	Remote controller prohibition	-	-	-	-	-		-	-	-	-	-	●	●	●	●
	Anti-freeze setting	●	●	-	-	●		-	-	-	-	-	-	●	●	●
	Set temperature auto return	●	●	●	●	-		-	-	-	-	-	-	●	-	-
	Economy mode setting	●	●	●	●	●		-	●	●	●	●	●	●	●	●
	Human sensor control	●	●	-	-	-		-	-	-	-	-	●	●	●	●
	Displayed items	Error	●	●	●	●	●		●	-	-	-	●	●	●	●
Defrosting		●	●	●	●	●		●	-	-	-	-	●	●	●	●
Current time		●	●	●	●	-		-	●	●	●	●	●	●	●	●
Day of week		●	●	●	●	-		-	-	-	-	-	●	●	●	●
Remote controller prohibition		●	●	●	●	●		●	-	-	-	-	●	●	●	●
Address display		●	●	●	●	●		●	-	-	-	-	-	●	●	●
Room temperature		●	●	-	●	●		●	-	-	-	-	●*4	●*4	●*4	●*4
Multiple language support		●	●	-	●	-		-	-	-	-	-	●	●	●	●
Setting for daylight saving time		●	●	-	●	-		-	-	-	-	-	●	●	●	●
Name registration		●	●	-	-	-		-	-	-	-	-	●	●	●	●
Backlighting		●	●	-	●	●		●	-	●	-	●	●	●	●	-
2D floor layout/3D building display		-	-	-	-	-		-	-	-	-	-	-	-	-	●
Refrigerant leak detector		-	-	-	-	-		-	-	-	-	-	●	●	●	●
Refrigerant Cycle Monitor		●	●	-	-	-		-	-	-	-	-	-	-	-	-
Logo Display		●	-	-	-	-		-	-	-	-	-	-	-	-	-
Limited Visibility of Settings		●	-	-	-	-		-	-	-	-	-	-	-	-	-
Timer	Schedule timer	Period	Week	Week	Week	Week	-	-	-	-	-	Week	Year	Year	Year	Year
		ON/OFF, Temp, Low noise mode*5, Times per day	8	8	4	8	-	-	-	-	-	4	20	20	144	144
	ON/OFF timer	-	●	●	●	●(OFF only)	-	-	●	●	●	-	-	-	-	-
	Sleep timer	-	-	-	-	-	-	-	●	●	●	-	-	-	-	-
	Program timer	-	-	-	-	-	-	-	●	●	●	-	-	-	-	-
	Auto-off timer	●	●	●	●	-	-	-	-	-	-	-	●	●	-	-
Day off	●	●	●	●	-	-	-	-	-	-	●	●	●	●	●	
Minimum unit of timer setting (minutes)	1 • 10	10 • 30	30	30	-	-	-	5	5	5	5	10	10	10	10	
Control	Remote monitoring management system	-	-	-	-	-		-	-	-	-	-	●	●	●	●
	Electricity charge apportionment	-	-	-	-	-		-	-	-	-	-	-	○	○	●
	Error history	●	●	●	●	-		-	-	-	-	-	●	●	●	●
	Emergency stop	-	-	-	-	-		-	-	-	-	-	●*2	●*2	-	-
	Remote monitoring management	-	-	-	-	-		-	-	-	-	-	●	●	○	●
	Energy-saving management	-	-	-	-	-		-	-	-	-	-	-	-	○	○
	E-mail notification in case of failure	-	-	-	-	-		-	-	-	-	-	●	●	●	●
Key lock	● Child lock	● Child lock	● Child lock	● Child lock	-	-		-	-	-	-	● Child lock	● Password setting	● Password setting	● Password setting	● Password setting
Low noise mode	-	-	-	-	-		-	-	-	-	-	●	●	●	●	

\*1 "Operation mode" setting not available.  
 \*2 Available only for external input control.  
 \*3 Monitoring sites can be set up. The main unit side can only be operated to cancel the settings.  
 \*4 Available only when using Wired remote controller.  
 \*5 UTY-DCGGZ3 only  
 ●: Supported ○: Optional function -/: Unsupported

# Wired remote controller (Design type)

UTY-RVRG



NEW



Up to  
**16** indoor units  
Up to  
**1** group



reddot winner 2024



## Simple and stylish design that harmonizes with the space

- The new stylish design controller, UTY-RVRG, enables intuitive operation with touch screen. It is compatible with many 2-wired indoor units.

## Harmonizes with the Installation Space

When not in use, the controller is a part of the interior décor. This is achieved by using mirrors, glass, and clear panels, and it appears to be one with the wall. The sleek and stylish design won the 2022 Good Design Award and was selected as a finalist for the 2023 IDEA award.



## Intuitive operation

The touch screen is easily operated by swiping vertically and horizontally, and users can operate the controller without using manuals.



## Status LED Colors

When not in use, the operation mode is indicated through LED lamp colors shown under the controller. The LED lamp can be switched ON and OFF to avoid glare at night.



## Features: Wired Remote Controller (Design type)

### Refrigerant cycle monitor

The controller will display specific sensor values of outdoor and indoor units for maintenance and service support.


- \* Display screen example
- \* This function is only supported by split units, using the H-Serial communication protocol! Example: ASH30KMTB



### Logo Display

The controller can display hotel logos when not in use. Images are sent via Bluetooth® connection where data is saved in the flash memory built into each controller.

- \* Color display available




### AIRSTAGE Remo Set application (free download)

Set up your new Wired Remote Controller via Bluetooth from your smartphone (or directly at the controller).


#### Features:

- Initial configuration
- Function setting
- Custom logo import
- Copy settings between controllers



### Initial Settings / Indoor Unit Function

The initial controller settings and indoor unit function settings can be sent from a smartphone by pairing with the controller via Bluetooth. It also can read the setting values of a paired controller, and send a copy of them to one or more additional controllers, significantly reducing installation time.



\*Smartphone : Wired Remote Controller = 1 : 1

### Specifications

Model name	UTY-RVRG
Power Source	DC12V
Dimensions (H × W × D) (mm)	121.5 × 116 × 26
Weight (g)	225

# Wired remote controller (with touch panel)

UTY-RNRGZ5



Up to  
**16** indoor units  
Up to  
**1** group

## Easy operation due to large high-resolution STN-LCD touch panel screen

- Touch screen LCD
- Built-in daily/weekly timer (ON/OFF, temperature, modes)
- Backlit screen for easy operation in the dark.
- Room temperature display
- Controls up to 16 indoor units
- Supports 12 languages: Chinese, Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, and Turkish
- Nonpolar 2-core type

## High performance and compact size

A single remote controller controls each connected indoor unit and provides a weekly timer function and a variety of energy-saving options.



## Accurate control for comfort

A thermo sensor built into the remote controller monitors room temperature accurately.




Room temperature display  
Room temperature sensor

## Energy saving controls

### Custom Auto


- Maintains 2 separate setpoints for heating and cooling operations.
- Automatically switches between heating and cooling modes.

\* Not available for some models



### Auto-off timer

- While the Auto-off timer is activated, if the set off time is specified as, for example, one hour, the power will automatically turn off one hour after the start of operation.
- A desired time frame can be specified for the Auto-off timer.
- The off-time can be set from 30 to 240 minutes.



e.g.) Between 17:00 and 24:00 (over time hours), when the 1 hour set off time has elapsed, the system will automatically turn off the indoor unit as it has been judged to be "forgotten to turn off."  
Set off time for over time hours: 1 hour

### 2-setting weekly timer

### Set temperature auto return


### Setting temperature range limitation

## Features: Wired Remote Controller (Touch Panel)

### Refrigerant cycle monitor (option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.


\* This function is only supported by split units, using the H-Serial communication protocol! Example: ASHH30KMTB



## Multi System Control\*1


### 1) Lead Lag Operation

Standby Indoor Unit can be selected in lead lag operation. By this, the Indoor units will last longer than operating by nonstop.




### 2) Back up operation

In case of unexpected Indoor unit error, other Indoor units will start providing back up operation.



### 3) Lag Operation

In case of unexpected room temperature rise, other Indoor Units will start providing lag operation.



\*1: "Lead Lag Setting" is an easy-to-use function for room temperature control when using multiple indoor units, while reducing the burden placed on each indoor unit. If you wish to make use of this function, ensure you use indoor units equipped with a "Special Cooling" function. For Split products with "Special Cooling" function, refer to S-068 to S-071. If you use indoor units that do not have a "Special Cooling" function, under certain conditions, there is a chance that "Backup operation" may not operate correctly, and the "Lead Lag Setting" function will not give the expected results. Additionally, for rooms that require strict conditions, such as server rooms, please consider other appropriate measures. Please note that we will not provide compensation for any damages suffered to your appliances or data as a result of using this function. For more details, please confirm with your nearest retail store.

## Specifications

Model name	UTY-RNRGZ5
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 20.4
Weight (g)	220

DC 12 V is supplied by the indoor unit.

## Wired remote controller

UTY-RLRG



- ON/OFF/Weekly timer settings
- A built-in thermo sensor monitors and controls room temperature accurately.
- When something goes wrong, an error code is displayed.
- 16 error codes from the most recent one will be kept in the history. (Last 16 error codes can be accessed)
- Nonpolar 2-core type

Up to  
**16** indoor units  
Up to  
**1** group


### High performance and compact size

A single remote controller controls each connected indoor unit and provides a weekly timer function and a variety of energy-saving options.



### Visually intuitive operation

- The operation mode, set temperature, and fan speed are shown prominently on the top screen.
- Each function to be set is indicated by an icon.
- The control guide makes it simple and straightforward to operate a remote controller.



## Compact wired remote controller

UTY-RCRGZ1




- Simple design that matches stylish interiors
- The body of the controller, which is easy to install, is designed to conform to the European standard junction box.
- Can be operated both by wireless and wired remote controller.
- Nonpolar 2-core type

Up to  
**1** indoor units  
Up to  
**1** group


### Large screen and simple display

- Large screen but compact size
- Large, easy-to-read letters are used.
- The controls are simple and easy to understand.




### System overview

VRF connection



RAC connection



### Specifications

Model name	UTY-RLRG	UTY-RCRGZ1
Power source	12 V DC	12 V DC
Dimensions (H × W × D) (mm)	120 × 120 × 17	86 × 86 × 44
Weight (g)	170	135

12 V DC supplied by an indoor unit

## Wired remote controller

UTY-RVNGM




Up to  
**16** indoor units  
Up to  
**1** group

### Hi-grade individual control with a wide range of functions.

- 3.7-inch backlit LCD screen.
- Supports energy-saving functions with simple operation.
- Supports 9 languages: English, French, German, Greek, Italian, Portuguese, Russian, Spanish, and Turkish

### Visually intuitive operation

- Each function is displayed as an icon.
- Main functions are indicated by large icons: "Mode," "Set Temp," and "Fan"
- Easy operation with control guide display
- Simple operation with easy 4-way navigation pad



### High performance and compact size

- A single remote controller controls each connected indoor unit and provides a variety of energy-saving options.



## Wired remote controller

UTY-RNNGM




Up to  
**16** indoor units  
Up to  
**1** group

### Accurate control for comfort

A thermo sensor built into the remote controller monitors room temperature accurately. The wired remote controller and an optional Remote sensor can be installed in any location to meet any requirement.

#### Examples of sensor changes



### Built-in timer

**Weekly timer:** ON/OFF time can be set to operate twice for each day of the week.  
**Temperature setback timer:** Sets the time to change the temperature setting and the time to hold the setting for each day of the week.  
At "Weekly timer" + "Temperature setback timer" setup


### Specifications

Model name	UTY-RVNGM	UTY-RNNGM
Power source	12 V DC	12 V DC
Dimensions (H × W × D) (mm)	120 × 120 × 21.3	120 × 120 × 18
Weight (g)	220	160

12 V DC supplied by an indoor unit

## Simple remote controller

UTY-RSRG / UTY-RHRG (without operation mode)





### Compact remote controller with basic functionality

- Up to 16 indoor units can be controlled with one remote controller.
- Suitable for hotels or offices as it is easily operated with no complex functions.
- Simple design that matches stylish interiors
- Large LCD screen and easy-to-use control buttons
- Backlight: White backlight makes it easy to operate in the dark.
- Nonpolar 2-core type

Up to  
**16 indoor units**  
Up to  
**1 group**

### Supports a variety of applications

- **Vertical louver control:** Adjusts the vertical airflow direction of a duct-type indoor unit with an auto louver or a cassette type installed in a hotel room or a conference room.
- **Setting temperature range limitation:** Enables an indoor unit to operate in an energy-saving manner in a small building not equipped with a central remote controller.
- **Built-in room temperature sensor:** Monitors and controls room temperature accuracy.



## Wireless remote controller

UTY-LNTG



### Simple and versatile operations with a choice of 4 different types of timers

- Controls up to 16 indoor units.

Up to  
**16 indoor units**  
Up to  
**1 group**  
Up to  
**4 different daily timers**

### Built-in timer

4 timer programs: ON/OFF/Program/Sleep  
Program timer: Sets ON/OFF time once for every 24 hours.  
Sleep timer: Adjusts the set temperature automatically while the sleep timer is on.

### Easy installation and operation

Different codes can be assigned to up to 4 indoor units to prevent a mix-up.  
Wide and precise transmitting range

#### Specifications

Model name	UTY-RSRG	UTY-RHRG	UTY-LNTG
Power source	12 V DC	12 V DC	3.0V (1.5V R03/LR03/AAA x 2)
Dimensions (H × W × D) (mm)	120 × 75 × 19.4	120 × 75 × 19.4	205 × 61 × 17
Weight (g)	120	120	125

12 V DC supplied by an indoor unit

## Wireless remote controller

UTY-LNVG



NEW



Up to  
**16 indoor units**  
Up to  
**1 group**  
Up to  
**4 different daily timers**

### New stylish design with backlight

- It has adopted a new simple and stylish design.
- The built-in backlight allows the screen to be seen even in dark rooms.

### Built-in timer

4 timer programs: ON/OFF/Program/Sleep  
Program timer: Sets ON/OFF time once for every 24 hours.  
Sleep timer: Adjusts the set temperature automatically while the sleep timer is on.

### Error diagnosis

It can detect the reason for system errors easily.  
When an error is detected, the error code number can be checked using the remote controller display.

### Precise control

The setting temperature can be adjusted precisely depending on the environment as the controller can set the temperature via 0.5 °C\*.  
\*Depends on the indoor unit

## Wireless remote controller

UTY-LNHG



Up to  
**16 indoor units**  
Up to  
**1 group**  
Up to  
**4 different daily timers**

### Simple and versatile operations with a choice of 4 different types of timers

- Controls up to 16 indoor units.

### Built-in timer

4 timer programs: ON/OFF/Program/Sleep  
Program timer: Sets ON/OFF time once for every 24 hours.  
Sleep timer: Adjusts the set temperature automatically while the sleep timer is on.

### Easy installation and operation

Different codes can be assigned to up to 4 indoor units to prevent a mix-up.  
Wide and precise transmitting range


#### Specifications

Model name	UTY-LNVG	UTY-LNHG
Battery	3.0V (1.5V R03/LR03/AAA x 2)	3.0V (1.5V R03/LR03/AAA x 2)
Dimensions (H × W × D) (mm)	181 × 58 × 17	170 × 56 × 19
Weight (g)	116	85

12 V DC supplied by an indoor unit

## IR receiver unit for duct type

UTY-LRHGM / UTY-LBTGM



The wireless remote controller controls duct type indoor units.

## IR receiver unit for cassette


UTY-LBTGC



Cassette type indoor unit can be controlled with a Wireless remote controller.

## IR receiver unit for ceiling type

UTY-LBTGH



The wireless remote controller controls ceiling type indoor units.

### Specifications

< Wireless Remote Controller >

Model name	UTY-LRHGM	UTY-LBTGM	UTY-LBTGC	UTY-LBTGH
Battery	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)
Dimensions (H x W x D) (mm)	170 x 56 x 19	205 x 61 x 17	205 x 61 x 17	205 x 61 x 17
Weight (g)	85	125	125	125

< IR Receiver Unit >

Battery	DC5V	DC5V	DC5V	DC5V
Dimensions (H x W x D) (mm)	145 x 90 x 30	145 x 90 x 30	—*	—*
Weight (g)	150	150	140	100

DC 5 V is supplied the indoor unit.  
\*It will replace the parts of the indoor unit to be connected.


## IR receiver unit for duct type

UTB-YWC / UTY-TRHX



The wireless remote controller controls duct type\* indoor units.

\*Large airflow duct types do not work with this IR receiver unit.




\*A separate wireless remote control (model: UTY-LNHG) is required.

## IR receiver unit for cassette

UTY-LBHXD / UTY-TRHX



Cassette type indoor unit can be controlled with a Wireless remote controller.



\*A separate wireless remote control (model: UTY-LNVG or UTY-LNHG) is required.

### Specifications

< Wireless Remote Controller >

Model name	UTB-YWC	UTY-LBHXD	UTY-TRHX
Battery	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)
Dimensions (H x W x D) (mm)	170 x 56 x 19	170 x 56 x 19	170 x 56 x 19
Weight (g)	85	85	85

< IR Receiver Unit >

Battery	DC5V	DC5V	DC5V
Dimensions (H x W x D) (mm)	145 x 90 x 30	—*	145 x 90 x 30
Weight (g)	150	140	150

DC 5 V is supplied the indoor unit.  
\*It will replace the parts of the indoor unit to be connected.

# WLAN adapter

UTY-TFSXH3 / UTY-TFSXJ3



USB type for single split models  
UTY-TFSXH3



UTY-TFSXJ3  
(CN connector type)

Up to  
**1** indoor unit



## AIRSTAGE Mobile

“AIRSTAGE Mobile” is an application software that enables you to manage the Fujitsu General’s air conditioner(s) with a mobile device from anywhere.

- Maximum 5 accounts per 1 indoor unit
- Room / Outdoor temperature display
- Can be used for a Single / Multi and VRF indoor units.
- No separate external power supply required
- “AIRSTAGE Mobile” is an application software that enables you to operate the Fujitsu General’s air conditioners with a mobile device.



### User Friendly for Everyone

Enjoy easy-to-use centralized operation of air conditioners via a smartphone anytime, anywhere



Image\*



House Owner



Shop Owner



Commercial Building Owner

### Main Functions

- ON / OFF
- Operation mode
- Fan speed
- Louver position
- Set temperature control
- Weekly timer
- Room temperature display
- Outdoor temperature display
- Error display

\*Contents of display differ depending on the type of indoor unit.

### New Design!

Ease of use is pursued to achieve a stylish design.

The more legible and accessible timer UI enables effortless schedule management.



Mode change



Fan speed change




Weekly timer

### Features: AIRSTAGE Mobile

#### Centralized operation for flexible remote management of all air conditioners

AIRSTAGE Mobile is ideal for a wide range of applications, from large residential buildings to smaller commercial spaces such as offices and stores. Anyone who has a smartphone and an adapter can easily manage the system at a low cost.




#### Hierarchical group management

Multiple air conditioners can be combined into a single group for centralized operation. Several groups can also be organized at once. Grouping the air conditioners by building, floor, or room makes it easy for users to monitor their operation status and operate them quickly.



#### Operate air conditioner and check its operation status just by talking to it

Connecting with a smart speaker allows the user to operate the air conditioner and check its operation status just by talking to it.



\* The new WLAN adapters for AIRSTAGE Mobile are upper compatible for the indoor units that can connect the existing WLAN adapters for FGLair.

	CN connector type	USB type
for FGLair	UTY-TFSXZ1	UTY-TFSXF2
for AIRSTAGE Mobile	UTY-TFSXJ3	UTY-TFSXH3

#### Specifications

Model name	UTY-TFSXJ3(CN connector type)	UTY-TFSXH3
Dimensions (H × W × D) (mm)	71 × 38 × 15	56.7 × 34 × 9.72
Weight (g)	35	30

# WLAN adapter

UTY-TFNXZ1 / UTY-TFSXZ1 / UTY-TFSXF2



USB type for single-split models  
UTY-TFSXF2




UTY-TFNXZ1  
(3-wire RC-line type)  
UTY-TFSXZ1  
(CN connector type)

Up to  
**1 indoor unit**




- This interface provides the most advanced solution for the remote management of an air conditioning system by using smartphones, tablets, and computers.
- No separate external power supply required
- Can be used for a Single / Multi and VRF indoor units.




## Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed control
- Louver position (airflow direction setting)
- Timer operation setting (Weekly timer)
- Economy mode setting




## Multiple air conditioning management

- Manage multiple air conditioning systems in different locations.



## Error alert and e-mail notice

- E-mail notification alerts
- Air conditioning malfunction alert
- Enables quick service response when errors occur.



## WLAN adapter (USB type)

**UTY-TFSXF2**

A compact USB type is available. No need for specialized installation. Easily installed on the indoor unit.



### Specifications

Model name	UTY-TFNXZ1(3-wire RC-line type)	UTY-TFSXZ1(CN connector type)	UTY-TFSXF2
Dimensions (H × W × D) (mm)	71 × 38 × 15	71 × 38 × 15	56.7 × 34 × 9.72
Weight (g)	35	35	30

# WLAN adapter

FG-RC-WIF1Z2 / FG-IR-WIF1Z1 / FG-AC-WIF1Z1



FG-RC-WIF1Z2  
(3-wire RC-line type)



FG-AC-WIF1Z1  
(CN connector type)



FG-IR-WIF1Z1  
(IR type)


Up to  
**1 indoor unit**

## AC Cloud Control


- This interface provides the most advanced solution for the remote management of an air conditioning system by using smartphones, tablets, and computers.
- No separate external power supply required

## Installation example


[3-wire RC-line type/CN connector type]



[IR type] Connection to wall-mounted type



[IR type] Connects to the product with the optional receiver kit



\*IR receiver required.

## Basic control

- Turning air conditioner on and off
- Mode select (Heat, Cool, Dry, Auto, Fan)
- Louver position (airflow direction setting)
- Fan speed control
- Room temperature display
- Setting temperature
- Multiple language support
- One single scene is created.

## Advanced control (optional functions)

- Climate-based operation modes (ECO, Comfort, and Powerful) (to be available in the future)
- Schedule functions (ON/OFF, modes, set temperature, fan speed, louver position)
- Setting temperature range limitation
- Multiple Scenes and Calendars are created.
- Smart Speaker compatibility
- Advanced internet service connections

## Notification and operation history

- E-mail notification alerts
- Air conditioning malfunction alert
- Connectivity monitoring and alert
- Operation history (to be available in the future)

### Specifications

Model name	FG-RC-WIF1Z2 (3-wire RC-line type)	FG-AC-WIF1Z1 (CN connector type)	FG-IR-WIF1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	108 × 70 × 28	81 × 78 × 28	127 × 50 × 17
Weight (g)	80	76	80



# Multiple protocol WLAN adapter

FG-RC-WMP1Z1 / FG-IR-WMP1Z1 / FG-AC-WMP1Z1



**Intesis**  
BY HBS NETWORKS



FG-RC-WMP1Z1 (3-wire RC-line type)

**Intesis**  
BY HBS NETWORKS



FG-AC-WMP1Z1 (CN connector type)

**Intesis**  
BY HBS NETWORKS



FG-IR-WMP1Z1 (IR type)

Up to  
**1** indoor unit

### Specifications

Model name	FG-RC-WMP1Z1 (3-wire RC-line type)	FG-AC-WMP1Z1 (CN connector type)	FG-IR-WMP1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	70 × 100 × 28	127 × 50 × 17	81 × 78 × 28
Weight (g)	98	80	76

# Multiple protocol LAN adapter

FG-TL-MBS16Z1



**Intesis**  
BY HBS NETWORKS



FG-TL-MBS16Z1 (VRF type)

Up to  
**16** indoor units

### Specifications

Model name	FG-TL-MBS16Z1 (VRF type)
Power supply	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA.*
Input power (W)	1.7
Dimensions (H × W × D) (mm)	90 × 88 × 56
Weight (g)	330


\*24 V DC power supply is recommended.

## AC Cloud Control


- Air conditioner control of Home Automation systems via wireless LAN connection.
- No separate external power supply required

### Installation example

[3-wire RC-line type/CN connector type]



[IR type]



\*IR receiver required for other than wall-mounted type.

# Home central remote controller

UTY-DMMGM / UTY-DMMGM1




Up to  
**1** multi-split system  
Up to  
**6** indoor units

## For 5-unit and 6-unit multi-split type

- Batched control of up to 6 indoor units For all indoor units connected to the remote controllers, the Home central remote controller sets room temperature, airflow volume, and remote controller prohibition from other remote controllers at once.
- Supports 9 languages: English, French, German, Greek, Italian, Portuguese, Russian, Spanish, and Turkish.
- Large backlit LED screen
- Large, easy-to-see operation panel


### Example of system configuration



## Home central remote controller

### Weekly timer

Up to 4 ON/OFF settings can be programmed per day. Two weekly patterns can be set, one for the cooling season and the other for the heating season.



### Low noise operation

You can choose from 4 low noise levels depending on the installation environment. ON/OFF timing of low noise mode can be set with the timer.

### 10 °C heat operation

When you leave the house, the air conditioner runs a minimum heating operation to maintain the room temperature at 10°C.


\*Consult your dealer for conditions of use.

### Economy operation

When you select energy-saving economy mode, the temperature setting for the indoor unit increases (during cooling operation) or decreases (during heating operation) by 1°C and the maximum electric value of the outdoor unit is suppressed.

### Prohibiting local control, including settings such as child lock

The Home central remote controller is equipped with a lock function to prevent unauthorized operation from the remote controllers of the indoor unit in each room. The Home central remote controller is equipped with a child lock to prevent children from accidentally turning the air conditioner on or off or changing its settings.



### Specifications

Model name	UTY-DMMGM/UTY-DMMGM1
Power source	12 V DC
Dimensions (H × W × D) (mm)	120 × 120 × 21.3
Weight (g)	220

12 V DC supplied by an indoor unit

# Central remote controller

UTY-DCGGZ3



NEW



Up to 100 indoor units  
Up to 50 groups



## For tenants in small to midsize commercial premises

- Individual control and monitoring of up to 100 indoor units
- 7.0inch TFT color screen
- Visually intuitive operation
- Room temperature display by indoor unit sensor & remote controller sensor
- 50 Remote Controller Groups Display & remote controller group rename
- Supports 14 languages: Chinese (Simplified/Traditional), Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Turkish, and Thai (Remote Management only)

## Easy operation

### Air conditioning management by detecting room temperatures of each room

The room temperature detected with indoor unit sensor or remote controller sensor can be displayed. New model can detect the room temperature by indoor units sensors even if wired remote controllers are not connected to the indoor units.



\*Room temperature is displayed only when indoor unit operates.

## 50 Remote Controller Groups Display


The group display and the 50 remote controller groups display can be switched easily. Users can choose which display is better, depending on the situation.

### Group Display



Manage & Monitor by each Groups

### 50 Remote Controller Groups Display



Manage & Monitor by 50 Remote Controller Groups




## Remote Controller Groups Rename

The remote controller group names can be changed. Users can know easily where the air conditioning is located by changing the remote controller group names.



## Features: Central Remote Controller

- Easy intuitive operation from the touch panel display.
- All functions can be accessed through the monitoring screen showing a pop-up window for detailed operation.



Monitoring screen

Individual setting

### Added individual wind direction control


Individual wind direction control has been added.  
Circular Flow cassette / 3D Flow cassette



Circular flow cassette

### Human sensor Compatible

Human sensor setting  
• Auto save  
• Auto on / off  
• Auto off detection time  
• Enable and disable




## Remote Management

### Remote monitoring / Remote operation

New central remote controller can control your tenant's air conditioner anytime and anywhere. When the central remote controller manages the indoor units of some tenants, air conditioning of each tenant can be managed separately online.

### Increased the Number of Accounts



### Trouble support function

#### Display error details

Display descriptive explanation when an error occurs



### Sensor value monitoring function

Monitor sensor data of indoor unit / outdoor unit, send mail

### Notify room temperature by email\*


Notify by e-mail when the temperature around the air conditioner is too high or too low

\*This function is available only when using wired remote controller.

## Schedule management

### Annual schedule

- An annual schedule can be arranged for each remote controller group or user-defined group.
- Allows for the programming of special settings for weekends, holidays, and store closings throughout the year.



### low noise schedule

Low noise operation of outdoor units can be scheduled.



### Automatic return to set temperature

A function that automatically returns the changed temperature to its original value over time.

## Specifications

Model name	UTY-DCGGZ3
Power Supply	100-240 V 50/60 Hz
Dimensions (H × W × D) (mm)	134.6 × 216.2 × 37.9
Weight (g)	800

# Touch panel controller

UTY-DTGGZ1




- Large 7.5-inch TFT color LCD screen
- Touch screen operation
- Stylish design to fit nicely into any room environment
- Controls up to 400 indoor units.
- Icon or list view can be selected in monitoring mode.
- Supports 7 languages: Chinese, English, French, German, Polish, Russian, and Spanish.
- Mounted with LAN adapter for remote control & operation, external input/output with emergency stop and batch ON/OFF

Up to  
**400** indoor units  
Up to  
**100** outdoor units  
Up to  
**400** groups

## Easy operation

- Wide range of simple-to-understand icons
- Operate by pressing the icons on the screen with your finger or a stylus.
- The color on the back identifies the current control operation; blue is for monitoring and green is for operational control.



## Easy maintenance

- The flat touch panel can be easily cleaned.
- Touch panel controller with non-glare coating to prevent finger marks
- Front cover for easy removal.




## Easy installation

- The touch panel controller can be mounted on a wall.
- Flat back surface enables easy installation anywhere on a wall.
- No additional parts or components required for installation




## Controls up to 400 indoor units.



## Features:

### Control & monitoring

- Control and monitor Fujitsu General air conditioners via LAN or internet.
- Users and tenants can manage their assigned equipment from anywhere by computer or tablet.
- When something goes wrong, an error notice is sent by e-mail for prompt troubleshooting.



### Smartphone


Model name	Browser
Nexus 6P (Android 7.1.1)	Google Chrome 5.5
iPhone 7 (iOS 10.1)	Safari 10

### Tablet

Model name	Browser
iPad Pro 9.7 inch (iOS 10.2.1)	Safari 10


## Flexible access permissions can be granted to users at each point level.

The administrator can register multiple users and permit them to access any indoor unit and any functions.



## Additional languages


Supports 7 languages as standard: Chinese, English, French, German, Polish, Russian, and Spanish. Create a language database to integrate additional languages into the remote device. The added languages will only be displayed on the remote device and cannot be added to the Touch panel controller.



## Electricity charge apportionment (Option: UTY-PTGXA)

- Energy cost can be calculated and allocated to each billing user in proportion to the amount of energy used for air conditioning.

- Apportionment charge/bill calculation
- Tenant (block) setting
- Common facilities apportionment setting
- Rated power consumption allotment
- Individual calculations for cooling and heating
- Electricity meter supported



\* An electricity usage meter can be connected to an external input connector of the Touch panel controller. In that case, the meter cannot be connected to an outdoor unit at the same time.

Features:


### Automatic setting for daylight saving time

**Functions provided**

- 1) Schedule setting for daylight saving time
  - It prevents the user from forgetting to set daylight saving time. In addition, it saves time and effort for the user.



**Automatic clock adjustment**

- 2) Time can be set for all controllers in a batch automatically.



### Outdoor unit low noise operation

You can choose from 4 low noise levels depending on the installation environment. ON/OFF timing of low noise mode can be set with the timer.




### Energy-saving controls

**Custom Auto**

- Maintains 2 separate setpoints for heating and cooling operations.
- Automatically switches between heating and cooling modes.
- \* Not available for some models



Cooling set temp. 28°C, Heating set temp. 18°C



### Refrigerant leak detector

Refrigerant leakage status is indicated by the management equipment. A pop-up message is displayed to notify the user, and the refrigerant is shut off.



Pop-up highlighting

### FUNCTIONS SUMMARY

	UTY-DTGGZ1	Monitoring side
<b>Air conditioning control functions</b>		
ON/OFF	●	●
Operation mode setting*	●	●
Fan speed control	●	●
Room temperature setting	●	●
Setting temperature range limitation	●	●
Test operation	●	●
Vertical louver setting	●	●
Horizontal louver setting	●	●
Individual louver control	●*1	●
Group setting	●	●
Remote controller prohibition	●	●
Anti-freeze setting	●	●
Set temperature auto return	—	●
Energy-saving controls	—	●
Economy mode setting	●	●
Human sensor control	—	●
<b>Displayed items</b>		
Error	●	●
Defrosting	●	●
Current time	●	●
Day of week	●	●
Remote controller prohibition	●	●
Cooling/heating priority	●	●
Address display	●	●
Room temperature	●*3	●*3
Multiple language support	●	●
Setting for daylight saving time	●	●
Time zone setting	●	●
Name registration	●	●
Backlighting	●	●
Language setting	7	7+other
Filter sign reset	●	●
Memory operations	●	●
Refrigerant leak detector	●	●

●: Supported ○: Optional function —: Not supported  
 \*1 Only setting cancellation can be operated.  
 \*2 Only available for external input control.  
 \*3 Available only when using a Wired remote controller.

### Specifications

	UTY-DTGGZ1
Power supply	Single phase ~100 to 240 V 50/60 Hz
Dimensions (H × W × D) (mm)	260 × 246 × 54
Weight (g)	2,150
Interfaces	Transmission/LAN/USB/EXT IN/EXT OUT/Reset SW

		UTY-DTGGZ1	Monitoring side
<b>Timer</b>			
	Period	Year	Year
Schedule timer	ON/OFF, Temp, Mode, Times per day	20	20
	ON/OFF timer	-	-
Sleep timer		-	-
Program timer		-	-
Auto-off timer		—	●
Day off		●	●
Minimum unit of timer setting (minutes)		10	10
<b>Control</b>			
Remote monitoring management system		●	●
Electricity charge apportionment		○	○
Error history		●	●
Emergency stop		●*2	●*2
Remote monitoring management		—	●
Energy-saving management		-	-
E-mail notification in case of failure		—	●
Key lock		● Password setting	-
Low noise mode		●	●

# System controller

UTY-APGXZ1 (Software)

Up to  
**4** VRF network systems  
Up to  
**400** outdoor units  
Up to  
**1,600** indoor units

**System controller enables advanced integrated monitoring and control of VRF network systems operating in small to large buildings.**

- Up to 1,600 indoor units and 400 outdoor units on up to 4 VRF network systems can be controlled.
- To accommodate facility management needs, the system controller offers—in addition to precise air conditioning control—remote central control, electricity charge apportionment, schedule management, and energy-saving options for VRF network systems.
- Supports 7 languages: Chinese, English, French, German, Polish, Russian, and Spanish.



# System controller lite

UTY-ALGXZ1 (Software)

Up to  
**1** VRF network system  
Up to  
**100** outdoor units  
Up to  
**400** indoor units

**System controller Lite offers a set of standard functions to manage air conditioners operating in a small or midsize building.**


- Up to 400 indoor units and 100 outdoor units on a VRF network system can be controlled.
- In addition to precise air conditioning control, a variety of applications are available as options to offer a wider range of control.
- Supports 7 languages: Chinese, English, French, German, Polish, Russian, and Spanish.



## Visually intuitive operation

**Click & Operate:** The visual representation of the property is shown on the screen from the perspective most suitable for operation (Click & Operate) You can select from among 4 display options: site, building, floor, and list.

**Freely define groups for batched control:** Indoor units can be grouped for simplified batch control from the tree menu. They can be grouped by organizational hierarchy, such as by division, department, and section.




## Features:

### Third-party devices connected via MODBUS® can be controlled.

**Standard** for System Controller **Option** for System controller Lite UTY-PLGXX2

When a MODBUS® adapter (locally available) is connected to a computer, electrical equipment and devices supported by MODBUS® can be monitored and controlled centrally from the computer. The central control can reduce wasted energy throughout an entire building resulting from a failure to turn equipment off during or after work, as well as reduce the need for on-site patrols.



## Wide-ranging operation and data management

**Standard** System controller and System controller Lite

### Schedule management

- An annual schedule can be arranged for each remote controller group or user-defined group.
- ON/OFF, operation mode, remote controller prohibition, and temperature settings can be programmed for up to 143 times per day at 10-minute intervals and for up to 101 configurations for each remote controller group.
- Settings can be programmed for a period that spans midnight.
- Allows for the programming of special settings for weekends, holidays, and store closings throughout the year.
- Low noise operation of outdoor units can be scheduled.

### Wide-ranging control of indoor and outdoor units

- The operation status and mode of each indoor unit are displayed.
- Turn on and off each indoor unit and switch its operation mode.
- Setting temperature range limitation
- Low noise setting of outdoor units

### Remote controller prohibition

Prohibits the operation mode, temperature setting, or ON/OFF of an indoor unit.

### Error alert and e-mail notice

When something goes wrong, an error message is shown in a popup on a computer display with a chime, and an e-mail notice is sent. Errors of the past one year are logged and can be reviewed.

### Operation and control history


A history of operation status and control can be maintained and retrieved.

### Importing and exporting databases

Only an administrator is authorized to import and export registration, layout, and image data.

### Automatic clock adjustment

Time can be set for all controllers in batch automatically.




## Electricity charge apportionment

**Standard** on System controller

**Option** System controller Lite UTY-PLGXA2

### Electricity charge apportionment method

This is a method to calculate monthly energy costs to be allocated to each tenant based on the amount of energy used by their air conditioners. The first step is to determine exactly how much energy is consumed by air conditioners in each tenant space. The second step is to divide the total energy charge billed by an electric power company based on the amount of energy used by each tenant to determine the energy cost to be allocated to each of them. (See figure on right) The calculation takes into consideration such factors as the number of unused rooms and nighttime electricity rate, which are shown in detail on an energy cost allocation schedule.




**Features:**

**Remote monitoring management**


- Standard** on System controller
- Option** System controller Lite UTU-PLGXR2

The System controller can be used on site or remotely over networks for remote central control. The System controller requires 2 software programs working together: The VRF controller runs on site and communicates with the VRF system; The VRF explorer, which runs at a remote location, provides a user interface and communicates with the VRF controller. The VRF controller and the VRF explorer run on a single computer or on different computers connected on a network. A computer running VRF explorer can centrally control up to 10 VRF system sites having up to 20 buildings each.

**On site central control**



**Remote central control**



**Energy-saving management**

- Option** System controller UTU-PEGXZ1
- Option** System controller Lite UTU-PLGXZ2

A variety of energy-saving options can be selected depending on the season, weather, and time of day. Excellent energy-saving operation is performed while keeping users comfortable.



Main screen for energy-saving management

Energy saving graph data: This chart compares the energy consumption for the current month with the previous month and with the same month of the previous year to keep track of the energy-saving performance.

**Indoor unit rotation**

Indoor units can be automatically rotated to operate within a group in accordance with a predetermined annual schedule to reduce power consumption while keeping users comfortable. The operation stoppage rate can be selected for an indoor unit.

**Peak-cut mode**

The system controller monitors the connected power meter and controls the energy to maintain the target power consumption set for each time period by changing the set temperature of the indoor units or turning off the thermostat so as to keep the users comfortable. Indoor units to be controlled can be grouped in many ways, and the control level can be set for each group.

**Capacity saving for outdoor unit**

The upper limit on the capacity of an outdoor unit can be adjusted to reduce power consumption during a hot summer or cold winter by averaging out the power-saving performance of each refrigerant system. The upper limit on capacity can be set at 50% of the rated capacity or more.

**Summary of functions**

Functions	Type	System controller		System controller Lite					
		UTY-APGXZ1	Option UTY-PEGXZ1	UTY-ALGXZ1	Option UTY-PLGXR2	Option UTY-PLGXA2	Option UTY-PLGXZ2	Option UTY-PLGXX2	
Specifications	Max. number of VRF networks supported	4	—	1	—	—	—	—	
	Max. number of indoor unit and remote controller groups per VRF network	400	—	400	—	—	—	—	
	Max. number of outdoor units per VRF network	100	—	100	—	—	—	—	
	Max. number of indoor units and remote controller groups per System controller	1600	—	400	—	—	—	—	
Site supervision	Multiple site display	10	—	10	—	—	—	—	
	Number of buildings per site	20	—	—	—	—	—	—	
	Number of floors per site	200	—	—	—	—	—	—	
	Number of floors per building	50	—	—	—	—	—	—	
	3D graphical layout view	●	—	—	—	—	—	—	
	2D graphical layout view	●	—	—	—	—	—	—	
Error management	List display	●	—	●	—	—	—	—	
	Tree display	●	—	●	—	—	—	—	
	Group display	●	—	●	—	—	—	—	
History	Error notification	●	—	●	—	—	—	—	
	Audible alarm	●	—	●	—	—	—	—	
Operation control	E-mail notification of errors	●	—	●	—	—	—	—	
	Individual control	Error history	●	—	●	—	—	—	—
		Operation history	●	—	●	—	—	—	—
		Control history	●	—	●	—	—	—	—
		ON/OFF	●	—	●	—	—	—	—
		Operation mode*	●	—	●	—	—	—	—
		Room temperature	●	—	●	—	—	—	—
		Fan speed	●	—	●	—	—	—	—
		Airflow direction	●	—	●	—	—	—	—
		Economy mode	●	—	●	—	—	—	—
		Setting temperature range limitation	●	—	●	—	—	—	—
	Individual management	Anti-freeze	●	—	●	—	—	—	—
		Low noise setting of outdoor units	●	—	●	—	—	—	—
		Remote controller prohibition	●	—	●	—	—	—	—
	Other	Setting temperature range limitation	●	—	●	—	—	—	—
		Filter sign reset	●	—	●	—	—	—	—
		memory operations	●	—	●	—	—	—	—
Pattern operations		●	—	●	—	—	—	—	
Schedule	Annual Schedule	●	—	●	—	—	—	—	
	Setting for a specific date	●	—	●	—	—	—	—	
	ON/OFF per day	72	—	72	—	—	—	—	
	ON/OFF per week	504	—	504	—	—	—	—	
	Day off	●	—	●	—	—	—	—	
Remote monitoring management	Minimum unit of timer setting (minutes)	10	—	10	—	—	—	—	
	Weekly schedule for low noise mode	●	—	●	—	—	—	—	
	Web Operation	●	—	●	—	—	—	—	
	Remote monitoring	●	—	●	—	—	—	—	
	Remote operation control	●	—	●	—	—	—	—	
	Remote function setting	●	—	●	—	—	—	—	
	Apportionment charge/bill calculation	●	—	●	—	—	—	—	
	Tenant (block) setting	●	—	●	—	—	—	—	
	Common facilities apportionment setting	●	—	●	—	—	—	—	
	Rated power consumption allotment	●	—	●	—	—	—	—	
Electricity charge apportionment	Individual calculations for cooling and heating	—	●	—	●	—	—	—	
	Electricity meter supported	—	●	—	●	—	—	—	
	Indoor unit rotation	—	●	—	●	—	—	—	
	Peak cut control	—	●	—	●	—	—	—	
	Capacity saving for outdoor unit	—	●	—	●	—	—	—	
	Record of energy-saving operation	—	●	—	●	—	—	—	
Energy-saving management	Information on energy saving	—	●	—	●	—	—	—	
	Power consumption monitor	—	●	—	●	—	—	—	
	Electricity meter supported	—	●	—	●	—	—	—	
	Monitor	●	—	●	—	—	—	—	
Control of external devices	Control	●	—	●	—	—	—	—	
	Importing and exporting databases	●	—	●	—	—	—	—	
	Automatic clock adjustment	●	—	●	—	—	—	—	
Others	Multiple language support	7 languages	—	7 languages	—	—	—	—	
	Refrigerant leak detector	●	—	●	—	—	—	—	
	Power shutdown	●	—	●	—	—	—	—	
	—	●	—	●	—	—	—	—	
	—	●	—	●	—	—	—	—	

●: Available - : Not available

**Computer requirements**

The specifications required for the computer are shown in the table below:

	System controller	System controller Lite
<b>Operating system</b>	<ul style="list-style-type: none"> <li>Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit)</li> </ul> Supports 7 languages: English, Chinese, French, German, Russian, Spanish, and Polish	<ul style="list-style-type: none"> <li>Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit)</li> </ul> Supports 7 languages: English, Chinese, French, German, Russian, Spanish, and Polish
<b>CPU</b>	Intel® Core™ i3 2 GHz or higher	Intel® Core™ i3 2 GHz or higher
<b>Memory</b>	<ul style="list-style-type: none"> <li>2 GB or more (for Windows® 7 [32-bit])</li> <li>4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)</li> </ul>	<ul style="list-style-type: none"> <li>2 GB or more (for Windows® 7 [32-bit])</li> <li>4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)</li> </ul>
<b>HDD</b>	40 GB or more of free space	40 GB or more of free space
<b>Displayed items</b>	1024 × 768 or higher resolution	1024 × 768 or higher resolution
<b>Interfaces</b>	<ul style="list-style-type: none"> <li>Ethernet port (for getting access to the internet using LAN) or a modem (for getting access to the internet via landline)</li> <li>Up to 6 USB ports (Only required for a server computer working as a VRF controller)</li> <li>Maximum of 2 USB ports are required to connect to a White-USB-key/WibuKey</li> <li>Up to 4 USB ports required to connect to an Echelon® U10 USB network interface</li> <li>* Maximum number of required USB ports depends on the applicable system configuration.</li> </ul>	<ul style="list-style-type: none"> <li>Ethernet port (for getting access to the internet using LAN) or a modem (for getting access to the internet via landline)</li> <li>Up to 6 USB ports (Only required for a server computer working as a VRF controller)</li> <li>Maximum of 4 USB ports are required to connect to a White-USB-key/WibuKey</li> <li>1 USB port is required for an Echelon® U10 USB Network interface</li> <li>* The maximum number of required USB ports depends on the applicable system configuration.</li> </ul>
<b>Graphic accelerator</b>	Microsoft® DirectX® 9.0c compatible	Microsoft® DirectX® 9.0c compatible
<b>Software</b>	Adobe® Acrobat Reader® 9.0 or later	Adobe® Acrobat Reader® 9.0 or later

\* Echelon® U10 USB Network interface – TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)

**Packing list**

Type	For System controller			For System controller Lite			
	System controller	Option Energy manager	System controller Lite	Remote access	Option Electricity charge apportionment	Option Energy saving	Option Centralized control
Model name	UTY-APGXZ1	UTY-PEGXZ1	UTY-ALGXZ1	UTY-PLGXR2	UTY-PLGXA2	UTY-PLGXZ2	UTY-PLGXX2
White-USB-key	1	1	1	1	1	1	1

\*1: Software protection key to be inserted in a USB slot running System controller or System controller Lite. System controller or System controller Lite may only run on a PC with a WHITE-USB-KEY. However, a WHITE-USB-KEY is not required for remote VRF explorer software.

# MODBUS® converter for indoor unit


UTY-VMSX



Up to  
**1** indoor unit


**MODBUS® converter enables air conditioners to be fully integrated into a MODBUS® network.**

- Simple installation due to small and compact size.
- No separate external power supply required.
- The MODBUS® converter must be connected to an indoor unit on a one-to-one basis.
- The MODBUS® converter enables central monitoring and control of air conditioners from BMS, central, or home controller.



## Easy Installation

Easy to install with minimal wiring and without the need for a power supply cable to the converter



## Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed control
- Louver position (airflow direction setting)
- Room temperature setting and display
- Economy mode setting
- Error status

## Specifications

Model name	UTY-VMSX
Power supply	12 V DC
Input power (W)	Max. 1.2 W
Dimensions (H × W × D) (mm)	140 × 117 × 43
Weight (g)	200
Maximum number of connectable indoor units per MODBUS® converter	1

## Modbus communication specifications

Transfer mode	RTU mode
Communication speed	9600/19200 bps
Data bit	8
Parity	even/odd/none
Stop bit	1/2 (no parity)
Network	RS485
Maximum cable length	1000 m (3280 ft)

# MODBUS® interface

FG-RC-MBS1Z1 / FG-AC-MBS1Z1 / FG-IR-BMG1Z1



FG-RC-MBS1Z1  
(3-wire RC-line type)



FG-AC-MBS1Z1  
(CN connector type)




FG-IR-BMG1Z1  
(IR type)

Up to  
**1** indoor unit

**MODBUS® interface enables air conditioners to be fully integrated into a MODBUS® network.**


- Small, compact, and easy to install on DIN rails.
- No separate external power supply required.
- MODBUS® interface enables central monitoring and control of air conditioners from BMS.

## Installation example



The MODBUS® interface can be used with or without a Wired remote controller.

## [IR type] Connection to wall-mounted type




## Specifications

Model name	FG-RC-MBS1Z1 (3-wire RC-line type)	FG-AC-MBS1Z1 (CN connector type)	FG-IR-BMG1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 53 × 58	93 × 60 × 21
Weight (g)	85	85	55

# MODBUS® convertor for VRF

UTY-VMGX / FG-TL-MBS16Z1



UTY-VMGX

Up to  
**9** units per VRF system  
Up to  
**100** outdoor units  
Up to  
**128** indoor units

**MODBUS® convertor enables air conditioners to be fully integrated into a MODBUS® network.**



- Compact and lightweight design
- Direct connection to MODBUS® network
- MODBUS® convertor enables central monitoring and control of air conditioners from BMS or a central controller.
- Up to 9 converters can be connected to a VRF network (UTY-VMGX). Simultaneous control, such as Power ON/OFF and temperature setting, can be performed for each zone.
- If a connection error occurs after installation work is completed, the source of the error can be located easily.

### Installation example



FG-TL-MBS16Z1

Up to  
**16** indoor units  
Up to  
**16** outdoor units  
Up to  
**128** indoor units



### Specifications

Model name	UTY-VMGX	FG-TL-MBS16Z1
Power supply	Single phase ~220 to 240 V 50/60 Hz	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA.*
Input power (W)	Max. 2	1.7
Dimensions (H × W × D) (mm)	54 × 260 × 150	90 × 88 × 56
Weight (g)	1,100	330

\*24 V DC power supply is recommended.

# BACnet® interface

FG-AC-BAC1Z1 / FG-IR-BMG1Z1



FG-AC-BAC1Z1 (CN connector type)




FG-IR-BMG1Z1 (IR type)


Up to  
**1** indoor unit

- BACnet® interface connects BMS and a Fujitsu General split/multi-split/VRF system.
- Compatible with BACnet® (ANSI/ASHRAE-135-2012) application-specific controller (B-ASC)
- Compatible with BACnet®/IP over Ethernet.

### Installation example



### [IR type] Connection to wall-mounted type



### Specifications

Model name	FG-AC-BAC1Z1 (CN connector type)	FG-IR-BMG1Z1 (IR type)
Number of controllable groups	1	1
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 60 × 21
Weight (g)	85	55

12 V DC supplied by an indoor unit



# BACnet® gateway

UTY-ABGXZ1 (Software)



White-USB-key  
(Software Protection Key)




BACnet® is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BI is a registered trademark of BACnet International.

Up to  
**4** VRF network systems  
Up to  
**400** outdoor units  
Up to  
**1,600** indoor units

- A medium to large BMS can be connected to a VRF network system via BACnet®, a standard communication protocol for open networks.
- Up to 1,600 indoor units on up to 4 VRF network systems (up to 400 indoor units and 100 outdoor units per system) can be connected to a single BACnet® gateway.
- The VRF network system can be controlled or monitored from BMS via BACnet® gateway.
- Compatible with BACnet® (ANSI/ASHRAE-135-2014) application specific controller (B-ASC).
- Compatible with BACnet®/IP over Ethernet.
- Scheduling, alarm and event setting, and energy cost allocation are provided on the BACnet® gateway.
- The VRF network system can be connected to a computer via a U10 USB interface. Note that Fujitsu General does not supply a U10 USB interface or a computer. They must be purchased separately by the user.
- Corresponds to 7 different languages: English, Chinese, French, German, Spanish, Russian, Polish.

## Installation example



\*1: U10 USB network interface available from Echelon® Corporation.

## Computer requirements

	UTY-ABGXZ1
Operating system	<ul style="list-style-type: none"> <li>• Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>• Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>• Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit)</li> </ul> Supported languages: Chinese, English, French, German, Polish, Russian, and Spanish
CPU	Intel® Core™ i3 2 GHz or higher
Memory	<ul style="list-style-type: none"> <li>• 2 GB or more (for Windows® 7 [32-bit])</li> <li>• 4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)</li> </ul>
HDD	40 GB or more of free space
Displayed items	1024 × 768 or higher resolution
Interfaces	<ul style="list-style-type: none"> <li>• Ethernet port (for getting access to the internet using LAN)</li> <li>• Up to 5 USB ports</li> <li>- 1 USB port required to connect to a White-USB-key/WibuKey</li> <li>- Up to 4 USB ports required to connect to an Echelon® U10 USB network interface</li> <li>* The maximum number of required USB ports varies depending on the applicable system configuration.</li> </ul>
Software	Adobe® Acrobat Reader® 9.0 or later

• Echelon® U10 USB Network interface - TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)

## Packing list

Name and shape	Quantity	Application
White-USB-key	1	Includes the software, user's manual, and license for BACnet® gateway.

# BACnet® gateway

UTY-VBGX (Hardware)




BACnet® is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BI is a registered trademark of BACnet International.

Up to  
**1** VRF network system  
Up to  
**32** refrigerant systems  
Up to  
**128** indoor units

- BACnet® gateway connects BMS and a Fujitsu General VRF system.
- Up to 128 indoor units and 32 refrigerant systems can be connected to a single BACnet® gateway.
- Compatible with BACnet® (ANSI/ASHRAE-135-2012) application-specific controller (B-ASC)
- Compatible with BACnet®/IP over Ethernet.

## Installation example



Max.128 indoor units & Max.32 refrigerant systems

## Specifications

Model name	UTY-VBGX
Number of controllable indoor units	128
Number of controllable refrigerant systems	32
Number of controllable VRF networks	1
Number of connectable units / one VRF network	4
Power supply	Single phase, 100-240 V, 50/60 Hz
Power consumption (W)	4.6 (max.)
Dimensions (H × W × D) (mm)	59.6 × 270.4 × 176
Weight (g)	1200

# BACnet®/MODBUS® router

FG-RTR-BAC32Z1 / FG-RTR-MBS32Z1



FG-RTR-BAC32Z1 (BAC net)




FG-RTR-MBS32Z1 (MODBUS®)

## Routing between BaCnet® MS/TP and BaCnet® IP networks


- Routing between BaCnet® MS/TP and BaCnet® IP networks
- Routing between MODBUS® RTU and MODBUS® TCP networks

## Installation example

[BaCnet® type]



[MODBUS® type]



### Specifications

Model name	FG-RTR-BAC32Z1 (MS/TP to IP)	FG-RTR-MBS32Z1 (RTU to TCP)
Number of routable devices (max.)	32	32
Power supply	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA
Power consumption (W)	1.7	1.7
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 53 × 58
Weight (g)	150	150

# BACnet®/MODBUS® cloud device


FG-CLD-BMG4Z1 / FG-CLD-BMG8Z1 / FG-CLD-BMG16Z1 / FG-CLD-BMG32Z1



FG-CLD-BMG4Z1

- The most powerful configuration tool common to all BACnet® gateways provides the system integrators with the power to configure and monitor their systems in an easy and reliable manner.
- A simple, easy-to-use description for the ST Cloud Web and App User Interface, with all widgets customizable to the user's needs, enabling system integrators to easily offer the best user experience to customers who are in control of their BaCnet® or MODBUS® devices.

## Installation example



\*BMS: Building Management System

## Gateway features

- BaCnet® IP/MSTP or MODBUS® TCP/RTU connectivity
- Up to 32 devices can be connected to each gateway.
- Up to 12 widgets per device
- Easy device configuration with Intesis MAPS

## Next-generation services

- Industrial-grade connectivity now for building automation
- Fast and scalable real-time edge connectivity over HMS HubTM
- Full data control and protection
- Secure and remote updates during the application lifetime

## System Features

- Monitor and control all devices in an intuitive way
- Comes with a native iOS and Android app and a web interface
- Create scenes and interact with multiple concurrent devices
- Calendar that shows the daily planned installation commands
- Notifications keep you updated about system status
- Device sharing and usage permissions management
- Multiple site management from a common dashboard

### Specifications

Model name	FG-CLD-BMG4Z1	FG-CLD-BMG8Z1	FG-CLD-BMG16Z1	FG-CLD-BMG32Z1
Number of connectable BaCnet® (IP/MSTP) or MODBUS® (TCP/RTU) devices	4	8	16	32
Power supply	9 to 24 V DC, 50/60Hz	9 to 24 V DC, 50/60Hz	9 to 24 V DC, 50/60Hz	9 to 24 V DC, 50/60Hz
Power consumption (W)	1.7	1.7	1.7	1.7
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 53 × 58	93 × 53 × 58	93 × 53 × 58
Weight (g)	150	150	150	150

## KNX® converter for indoor unit

UTY-VKSX




Up to  
**1** indoor unit

**KNX® Converter enables individual control of an indoor unit.**


- The new KNX® converter connects a central or home controller and a Fujitsu General indoor unit.
- Compact and lightweight design

### Installation example



## KNX® converter for VRF

UTY-VKGX / FG-TL-KNX16Z1



UTY-VKGX

Up to  
**100** outdoor units  
Up to  
**128** indoor units




FG-TL-KNX16Z1

Up to  
**16** outdoor units  
Up to  
**16** indoor units

**KNX® converter enables centralized control of a system.**

- KNX® converter connects a central or home controller and a Fujitsu General VRF system.
- Up to 128 indoor units and 100 outdoor units can be connected to a single KNX® converter. (UTY-VKGX)

### Installation example



### Specifications

Model name	UTY-VKSX	UTY-VKGX	FG-TL-KNX16Z1
Power supply	12 V DC	Single phase ~220 to 240 V 50/60 Hz	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA.*
Input power (W)	0.6	1.5	1.6
Dimensions (H × W × D) (mm)	140 × 117 × 43	54 × 260 × 150	90 × 88 × 56
Weight (g)	215	1,200	340

\*24 V DC power supply is recommended.

## KNX® interface

FG-RC-KNX1Z1 / FG-AC-KNX1Z1 / FG-IR-KNX1Z1



### Intesis®



FG-RC-KNX1Z1  
(3-wire RC-line type)

### Intesis®



FG-AC-KNX1Z1  
(CN connector type)

### Intesis®



FG-IR-KNX1Z1  
(IR type)


Up to  
**1** indoor unit

**The KNX® interface enables air conditioners to be fully integrated into a KNX® network system.**


- Simple installation due to small and compact size.
- No separate external power supply required (only KNX® bus power required)

### Installation example

[3-wire RC-line type/CN connector type]



[IR type] Connection to wall-mounted type



[IR type] Connection to a product other than wall-mounted type



### Specifications


Model name	FG-RC-KNX1Z1 (3-wire RC-line type)	FG-AC-KNX1Z1 (CN connector type)	FG-IR-KNX1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	70 × 70 × 28	45 × 59 × 21	81 × 78 × 28
Weight (g)	70	35	76

## Network converter for single-split type

UTY-VTGX / UTY-VTGXV



UTY-VTGX  
DC power supply type




UTY-VTGXV  
AC power supply type

Up to  
**16** single indoor units  
Up to  
**1** group  
Up to  
**100** Network Converters


- A network converter is required when connecting a single-split system to a VRF network system.
- Compact and lightweight design
- Connectable to both nonpolar 2-core and polar 3-core remote controllers

### Installation example


- A 1-remote-controller type and a 2-remote-controller type are available.
- Power supply (220 to 240 V AC, 50/60 Hz) is required for the 2-remote-controllers type.



- Both nonpolar 2-core and polar 3-core type Wired remote controllers can be connected.



- Central control can be provided for single-split systems. (Up to 100 network converters can be connected in a VRF network system)




### Specifications

Model name	UTY-VTGX		UTY-VTGXV
	Power supply	Polar 3-core 12 V DC	Nonpolar 2-core DC 12 V
Input power (W)	Max. 1.2 W		Max. 3
Dimensions (H × W × D) (mm)	140 × 117 × 43		54 × 260 × 150
Weight (g)	250		1,100

## Network converter for LONWORKS™


UTY-VLGX



Up to  
**4** units to BMS  
Up to  
**100** outdoor units  
Up to  
**128** indoor units

- Connects the VRF network system to a LONWORKS™ open network to manage small and mid-sized BMS and VRF network system.
- The UTY-VLGX enables centralized monitoring and control of VRF network system from a BMS via a LONWORKS™ interface.
- Up to 128 Indoor units can be connected to one network converter for LONWORKS™

### Installation example



### Specifications

Model name	UTY-VLGX
Power supply	Single phase ~208 to 240 V 50/60 Hz
Power consumption (W)	4.5
Dimensions (H × W × D) (mm)	67 × 288 × 211
Weight (g)	1,500

### Transmission specifications (BMS side)

Transmission speed	78 kbps
Transceiver	FT-X1 (available from Echelon® Corporation)
Transmission line form	Free topology
Terminal resistor	None (converter to be attached at the terminal of a network)

## External switch controller

UTY-TERX




Up to  
**1** group

**Air conditioner switching can be controlled by connecting this external switch controller to other sensor switches.**

- In combination with a commercially available card-key switch or other sensors, this External switch controller enables the control of ON/OFF, room temperature, and fan speed of connected air conditioners as well as master control functions. This makes this product an ideal choice for use in hotel rooms.
- Card key or other sensor switches are locally available.
- The set temperature can be specified at two points each for cooling and heating operations (4 points in total).

### Installation example


Human sensor monitors the movement of a person in a room. When it detects that the person has left the room, it switches the air conditioner to low-capacity mode. When a person returns to the room, the air conditioner returns to the previous operation mode.



Human sensor equipment needs to be purchased separately. Human sensor is not mounted on an External switch controller.


## Signal amplifier

UTY-VSGXZ1



- The transmission line can be extended up to 3,600 m using multiple Signal amplifiers.
- Up to 8 Signal amplifiers can be added in a VRF network system.
- A Signal amplifier is required.
  - (1) When the total wiring length of the transmission line exceeds 500 m.
  - (2) When the total number of units on the transmission line exceeds 64.


### Installation example



### Specifications

Model name	UTY-VSGXZ1	UTY-TERX
Power supply	Single phase ~208 to 240 V 50/60 Hz	6.5 to 16 V DC
Power consumption (W)	4.5	-
Dimensions (H × W × D) (mm)	67 × 288 × 211	140 × 117 × 43
Weight (g)	1,500	250

12 V DC supplied by an indoor unit



# Controller system list (available) for Split/Multi-split

Controller Options/Accessories:



Type	Refrigerant	Indoor unit																								Outdoor unit	
		Wall-mounted									Cassette		Duct										Multi-split				Single phase
		Designer Range		Standard Range			ECO Range				Compact 4-way flow Range	Circular flow Range	Slim	Medium static pressure (High-Efficiency & Comfort)	Medium static pressure (Compact)	Medium static pressure (Standard)	High static pressure	BIG	Floor	Ceiling	Wall-mounted	Compact cassette	Mini duct	Slim duct	5/6-unit multi-split		
	ASHH07/09/12/14KGTG, ASHG07/09/12/14KGTG, ASHG07/09/12/14KGTG, ASHG07/09/12/14KGTG	ASHG 07/09/12/14 KETI, KETI-B, KETE, KETE-B	ASHH07/09/12/14KMG, ASHG07/09/12/14KMG, ASHG07/09/12/14KMG	ASHG 18/24KMT	ASHH 30/36KMTB	ASHH 07/09/12 KNCA	ASHG 07/09/12 KPCE	ASHH 07/09/12 KLTA	AUXG 09/12/14/18/22/24 KVLA	AUXG 18/22/24/30/36/45/54 KRLB	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18/22/24/30/36/45/54 KMIAP	ARXG 12/14/18/22/24/30/36/45/54 KHTAP	ARXG 22KMLB, ARXG 24/30/36/45 KMLA	ARXG 45/54KHTB	ARHG 60LHTA	ARHG 72/90LHTA	AGHG 09/12/14 KVCA	ABHG 18/22/24/30/36/45/54 KRTA	ASHH 05KNCA	ASHG 22KMT	AUXG 07KVLA	ARXG 07/09/12/14/18 KSLAP	ARXG 07KLLAP	ADHG 36KBTAS		
																									ADHG 45LBLA6		
Wired remote controller				●						●																	
				●						●																	
				●						●																	
				●						●																	
				●						●																	
				●						●																	
Simple remote controller				●						●																	
				●						●																	
Home central remote controller																										●	
Wireless remote controller										●																●	
IR receiver unit with Wireless remote controller																											

\*1: Available only when the WLAN adapter (UY-TFSXF2) is removed. \*2: Available only when the WLAN adapter (UY-TFSXZ1) is removed. \*3: Consult your dealer for conditions of use.

# Controller system list (available) for Split/Multi-split

Controller Options/Accessories:



Type	Refrigerant	Indoor unit																		Outdoor unit																
		Wall-mounted						Cassette		Duct								Multi-split		Single phase																
		Designer Range	Standard Range		ECO Range		Compact 4-way flow Range	Circular flow Range	Slim	Medium static pressure (High-Efficiency & Comfort)	Medium static pressure (Compact)	Medium static pressure (Standard)	High static pressure		BIG	Floor	Ceiling	Wall-mounted	Compact cassette	Mini duct	Slim duct	5/6-unit multi-split														
ASHH07/09/12/14KGTG, ASHG07/09/12/14KGT, ASHG07/09/12/14KTE	ASHG 07/09/12/14 KETE, KETE-B	ASHH07/09/12/14KMG, ASHG07/09/12/14KMC, ASHG07/09/12/14KMCE	ASHG 18/24KMT	ASHH 30/36KMTB	ASHH 07/09/12 KNCA	ASHG 07/09/12 KPCE	ASHH 07/09/12 KLTA	AUXG 09/12/14/18/22/24 KVLJA	AUXG 18/22/24/30/36/45/54 KRLB	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18/22/24/30/36/45/54 KMTAP	ARXG 12/14/18/22/24/30/36/45/54 KHTAP	ARXG 22KMLB, ARXG 24/30/36/45 KMLA	ARXG 45/54KHTB	ARHC 60LHTA	ARHC 72/90LHTA	AGHG 09/12/14 KVCA	ABHG 18/22/24/30/36/45/54 KRTA	ASHH 05KNCA	ASHG 22KMTE	AUXG 07KVLJA	ARXG 07/09/12/14/18 KSLAP	ARXG 07KLLAP	ADHG 36KBTAS												
R410A																								ADHG 45LBLA6												
Interfaces	MODBUS® Converter	● UTY-VMSX																		● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX	● UTY-VMSX			
	MODBUS® interface	● FG-AC-MBS1Z1																		● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-AC-MBS1Z1	● FG-RC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-AC-MBS1Z1	● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1	● FG-RC-MBS1Z1 ● FG-AC-MBS1Z1		
Interfaces	IR type	● FG-IR-BMG1Z1																		● FG-IR-BMG1Z1+ ● UTY-LBTGC	● FG-IR-BMG1Z1+ ● UTY-LBTGM	● FG-IR-BMG1Z1+ ● UTY-LRHGM	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGH	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGH	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGM	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGM	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGM	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGM	● FG-IR-BMG1Z1	● FG-IR-BMG1Z1+ ● UTY-LBTGM
	3-wire RC-line type CN connector type	● FG-AC-KNX1Z1																		● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	● FG-RC-KNX1Z1 ● FG-AC-KNX1Z1	
Interfaces	IR type	● FG-IR-KNX1Z1																		● FG-IR-KNX1Z1+ ● UTY-LBTGC	● FG-IR-KNX1Z1+ ● UTY-LBTGM	● FG-IR-KNX1Z1+ ● UTY-LRHGM	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGH	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGH	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGM	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGM	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGM	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGM	● FG-IR-KNX1Z1	● FG-IR-KNX1Z1+ ● UTY-LBTGM
	3-wire RC-line type <sup>1</sup> CN connector type	● UTY-TFSXJ3 ● UTY-TFSXZ1																		● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFNXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	● UTY-TFSXJ3 ● UTY-TFSXZ1	
WLAN adapter	USB type <sup>3</sup>	● Accessory (KGTG, KGTF, KETF, KETF-B, KMCG, KMCF) ● UTY-TFSXH3, UTY-TFSXF2 (KGTG, KETE, KETE-B, KMCE)																		● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2	● Accessory	● UTY-TFSXH3 ● UTY-TFSXF2
	3-wire RC-line type CN connector type	● FG-AC-WIF1Z1																		● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	● FG-RC-WIF1Z2 ● FG-AC-WIF1Z1	
WLAN adapter	IR type	● FG-IR-WIF1Z1																		● FG-IR-WIF1Z1+ ● UTY-LBTGC	● FG-IR-WIF1Z1+ ● UTY-LBTGM	● FG-IR-WIF1Z1+ ● UTY-LRHGM	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGH	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGH	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGM	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGM	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGM	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGM	● FG-IR-WIF1Z1	● FG-IR-WIF1Z1+ ● UTY-LBTGM
	3-wire RC-line type CN connector type	● FG-AC-WMP1Z1																		● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	● FG-RC-WMP1Z1 ● FG-AC-WMP1Z1	
WLAN adapter	IR type	● FG-IR-WMP1Z1																		● FG-IR-WMP1Z1+ ● UTY-LBTGC	● FG-IR-WMP1Z1+ ● UTY-LBTGM	● FG-IR-WMP1Z1+ ● UTY-LRHGM	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGH	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGH	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGM	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGM	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGM	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGM	● FG-IR-WMP1Z1	● FG-IR-WMP1Z1+ ● UTY-LBTGM
	External switch controller	● UTY-TERX+UTY-TWRXZ2																		● UTY-TERX	● UTY-TERX	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	● UTY-TERX	● UTY-TERX+ ● UTY-TWRXZ3	
Network converter for single-split type	DC power supply type	● UTY-VTGX+UTY-TWRXZ2 ● UTY-VTGXV+UTY-TWRXZ2																		● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	
	AC power supply type	● UTY-VTGX+UTY-TWRXZ2 ● UTY-VTGXV+UTY-TWRXZ2																		● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	● UTY-VTGX ● UTY-VTGXV	● UTY-VTGX+ ● UTY-TWRXZ3 ● UTY-VTGXV+ ● UTY-TWRXZ3	

\*There are no optional parts for the KL Series.

\*1: Available only when the WLAN adapter (UY-TFSXF2) is removed. \*2 Available only when the WLAN adapter (UTY-TFSXZ1) is removed.

\*3: For compatibility of the new WLAN adapters with the indoor units which are not listed in this catalogue, please refer to page C-021.

# Controller system list (available) for VRF

Controller Options:



Type	Refrigerant	Indoor unit												Indoor unit										
		Cassette		Slim type		Large type		Duct				Duct		Floor		Ceiling		Wall-mounted						
		One-way flow	3D flow	Compact Grid type/Standard type		Circular flow		Mini (With drain pump)	Low static pressure duct			Low static pressure duct	Medium static pressure	High static pressure	-	External EEV	Ceiling/Floor	Ceiling	-	External EEV	-	External EEV	-	-
		High Efficiency																						
				AUXB 004/005/007/009/012/014/018HLAH	AUXN 009/012/014HLAH				ARXD 004/005/007/009/012/014/018/024HLAH	ARXP 009/012/014HLAH														
				AUXB 004/007/009/012/014/018/024GLEH		AUXM 018/024/030GLEH	AUXK 018/024/030/034/036/045/054GLEH	ARXK 004/007/009/012/014/018/024GLGH	ARXD 04GALH	ARXD 007/009/012/014/018/024GLEH														
Wired remote controller																								
Simple remote controller																								
Wireless remote controller																								
IR receiver unit																								
Central remote controller																								
System controller, System controller Lite																								



# Controller system list (available) for VRF

Controller Options:



Type	Refrigerant	Indoor unit														Indoor unit									
		Cassette				Duct				Duct			Floor		Ceiling/Floor		Ceiling		Wall-mounted						
		One-way flow	3D flow	Compact Grid type/Standard type		Slim type	Large type	Low static pressure duct				High Efficiency	High Efficiency	Normal	Normal	-	external EEV	Ceiling/Floor	Ceiling	-	external EEV	-	external EEV	-	-
				Grid type	High Efficiency			Mini (With drain pump)	Slim (With drain pump)		Low static pressure duct														
AUXB 004/005/007/ 009/012/014/ 018HLAH	AUXN 009/012/014 HLAH	AUXM 018/024/030 GLEH	AUXK 018/024/030/ 034/036/045/ 054GLEH	ARXK 004/007/009/ 012/014/018/ 024CLGH	ARXD 04GALH	ARXD 007/009/012/ 014/018/024 GLEH	ARXP 018/030 GLFH		ARXA 024/030/ 036/045 GLEH	ARXC 036/045/060/ 072/090/096 GTEH	AGHA 004/007/ 009/012/014 CCGH	AGHE 004/007/ 009/012/014 GCEH	ABHA 012/014/ 018/024 GTEH	ABHA 030/036/ 045/054 GTEH	ASHA 004/007/009 GCGH	ASHE 004/007/009 GCEH	ASHA 012/014GCGH	ASHE 012/014GCEH	ASHA 18/24GBCH	ASHA 030/034GTEH					
Interfacing		UTY-ABGXZ1, UTY-VBGX														UTY-ABGXZ1, UTY-VBGX									
		FG-AC-BAC1Z1				FG-AC-BAC1Z1				FG-AC-BAC1Z1		FG-AC-BAC1Z1		FG-AC-BAC1Z1		FG-AC-BAC1Z1		FG-AC-BAC1Z1							
BACnet* gateway		FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1	FG-IR-BMG1Z1+ UTY-LBHDX	FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1+ UTB-YWC	FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1		FG-IR-BMG1Z1									
		UTY-VLGX				UTY-VLGX		UTY-VLGX		UTY-VLGX		UTY-VLGX		UTY-VLGX		UTY-VLGX									
MODBUS* Converter		UTY-VMSX				UTY-VMSX		UTY-VMSX		UTY-VMSX		UTY-VMSX		UTY-VMSX		UTY-VMSX									
		UTY-VMGX FG-TL-MBS1Z1				UTY-VMGX FG-TL-MBS1Z1		UTY-VMGX FG-TL-MBS1Z1		UTY-VMGX FG-TL-MBS1Z1		UTY-VMGX FG-TL-MBS1Z1		UTY-VMGX FG-TL-MBS1Z1		UTY-VMGX FG-TL-MBS1Z1									
MODBUS* interface		FG-AC-MBS1Z1				FG-RC-MBS1Z1		FG-AC-MBS1Z1		FG-AC-MBS1Z1		FG-AC-MBS1Z1		FG-AC-MBS1Z1		FG-RC-MBS1Z1		FG-AC-MBS1Z1							
		FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1	FG-IR-BMG1Z1+ UTY-LBHDX	FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1+ UTB-YWC	FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1		FG-IR-BMG1Z1									
KNX* converter		UTY-VKSX				UTY-VKSX		UTY-VKSX		UTY-VKSX		UTY-VKSX		UTY-VKSX		UTY-VKSX									
		UTY-VKGX FG-TL-KNX1Z1				UTY-VKGX FG-TL-KNX1Z1		UTY-VKGX FG-TL-KNX1Z1		UTY-VKGX FG-TL-KNX1Z1		UTY-VKGX FG-TL-KNX1Z1		UTY-VKGX FG-TL-KNX1Z1		UTY-VKGX FG-TL-KNX1Z1									
KNX* interface		FG-AC-KNX1Z1				FG-RC-KNX1Z1		FG-AC-KNX1Z1		FG-AC-KNX1Z1		FG-AC-KNX1Z1		FG-AC-KNX1Z1		FG-RC-KNX1Z1		FG-AC-KNX1Z1							
		FG-IR-KNX1Z1+ UTY-TRHX	FG-IR-KNX1Z1	FG-IR-KNX1Z1+ UTY-LBHDX	FG-IR-KNX1Z1+ UTY-TRHX	FG-IR-KNX1Z1+ UTB-YWC	FG-IR-KNX1Z1+ UTY-TRHX	FG-IR-KNX1Z1+ UTY-TRHX		FG-IR-KNX1Z1+ UTY-TRHX		FG-IR-KNX1Z1+ UTY-TRHX		FG-IR-KNX1Z1		FG-IR-KNX1Z1									
WLAN adapter		UTY-TFSXJ3 UTY-TFSXZ1				UTY-TFSXJ3 UTY-TFSXZ1		UTY-TFSXJ3 UTY-TFSXZ1		UTY-TFSXJ3 UTY-TFSXZ1		UTY-TFSXJ3 UTY-TFSXZ1		UTY-TFSXJ3 UTY-TFSXZ1		UTY-TFSXJ3 UTY-TFSXZ1		UTY-TFSXJ3 UTY-TFSXZ1							
		FG-AC-WIF1Z1				FG-RC-WIF1Z2		FG-AC-WIF1Z1		FG-AC-WIF1Z1		FG-AC-WIF1Z1		FG-AC-WIF1Z1		FG-RC-WIF1Z2		FG-AC-WIF1Z1							
		FG-IR-WIF1Z1+ UTY-TRHX	FG-IR-WIF1Z1	FG-IR-WIF1Z1+ UTY-LBHDX	FG-IR-WIF1Z1+ UTY-TRHX	FG-IR-WIF1Z1+ UTB-YWC	FG-IR-WIF1Z1+ UTY-TRHX	FG-IR-WIF1Z1+ UTY-TRHX		FG-IR-WIF1Z1+ UTY-TRHX		FG-IR-WIF1Z1+ UTY-TRHX		FG-IR-WIF1Z1		FG-IR-WIF1Z1									
		FG-AC-WMP1Z1				FG-RC-WMP1Z1		FG-AC-WMP1Z1		FG-AC-WMP1Z1		FG-AC-WMP1Z1		FG-AC-WMP1Z1		FG-RC-WMP1Z1		FG-AC-WMP1Z1							
		FG-IR-WMP1Z1+ UTY-TRHX	FG-IR-WMP1Z1	FG-IR-WMP1Z1+ UTY-LBHDX	FG-IR-WMP1Z1+ UTY-TRHX	FG-IR-WMP1Z1+ UTB-YWC	FG-IR-WMP1Z1+ UTY-TRHX	FG-IR-WMP1Z1+ UTY-TRHX		FG-IR-WMP1Z1+ UTY-TRHX		FG-IR-WMP1Z1+ UTY-TRHX		FG-IR-WMP1Z1		FG-IR-WMP1Z1									
External switch controller		UTY-TERX				UTY-TERX		UTY-TERX		UTY-TERX		UTY-TERX		UTY-TERX		UTY-TERX									

\*1: For compatibility of the new WLAN adapters with the indoor units which are not listed in this catalogue, please refer to page C-021.

# Optional parts Overview


For Split & Multi-split, VRF

A variety of optional parts are available to enable installation of the selected indoor unit properly according to the environment.

## Optional Parts For Cassette



**Human sensor kit**  
A built-in thermo sensor monitors and controls room temperature accurately.




**Cassette grille**  
A lineup of cassette grilles that match a variety of interiors. A grid ceiling-type cassette grille has been added to the lineup.




**Silver ion filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.\*




**Fresh air intake kit**  
Fresh air can be taken in by a fan connected to an external control unit.




**Insulation kit for high humidity**  
Insulation kit for high humidity is used when the installation location is in a high humidity environment.



**Air outlet shutter plate**  
Airflow directions can be changed to 3 directions using the Air outlet shutter plate depending on the installation location.



**Wide Panel**  
When a cassette type is installed in a narrow space in the ceiling, the wide panel fills in that space.




**Panel spacer**  
If the ceiling space is tight and the main body protrudes from the ceiling surface, a panel spacer can be used as a decorative trim.

## Optional Parts For V-IV



**Pressure sensor kit**  
When installed, the height difference between the outdoor unit and indoor unit can be allowed up to 110 m.



## Optional Parts For R32 VRF products



**Gas Sensor kit**  
Used to ensure standards compliance and safety when R32 VRF products are installed.



**Expansion kit**  
Connect to indoor units to expand the number of inputs and outputs when using multiple safety devices or external input / output functions.

## Optional Parts For Floor



**Half concealed kit**  
Used to half conceal a floor type indoor unit in the wall.



**Silver ion filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.\*



## Optional Parts For Duct & Ceiling



**Auto louver grille kit**  
The optional clean-looking flat Auto louver grille blends into any interior and provides a comfortable airflow.




**Remote sensor unit**  
The remote sensor provides additional convenience.




**Silver ion filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.\*



**Long-life filter**  
Captures grit and dust. Long-life design with consideration of running costs.



**Flange**  
Flanges are used when connecting a medium static pressure duct type and a ceiling type with air intake and exhaust ducts.




**Drain pump unit**  
Drains water that has accumulated during operation.

## Connection Parts



**Communication kit**  
Required for a wall-mounted type when the External connect kit set or a Wired remote controller is connected to the indoor unit.



**External connect kit & set**  
Connect the printed circuit board (PCB) to external devices.



**External input and output PCB**  
For Wall-mounted, Duct, or Cassette type, these parts are required when the external input and output function is used.



**Connection Units**  
Connection units are available to separate the pipes when connecting multiple indoor units in a Multi-split type or VRF system.



**External input and output PCB box & bracket**  
Box and bracket for installing the External input and output PCB.



**External power supply unit**  
The External power supply unit protects the increment in the system even if the power supply for some of the indoor units is shut down.

\*Not a result of experiments in an actual use environment. Silver ion filter inhibits activity or growth of microorganism, but do not prevent infection.

# Silver Ion Filter

UTR-FA16-5 / UTR-FA13-3 / UTR-FA03-5 / UTD-HFAA / UTD-HFRA / UTD-HFTA / UTD-HFTB / UTD-HFTC / UTD-HFNC / UTD-HFNB / UTD-HFNA / UTD-HFND / UTD-HFKB / UTD-HFKA



For Wall mounted / Floor  
UTR-FA16-5 / UTR-FA13-3  
UTR-FA03-5

For Cassette  
UTD-HFAA / UTD-HFRA


For Duct  
UTD-HFTA / UTD-HFTB  
UTD-HFTC / UTD-HFNC  
UTD-HFNB / UTD-HFNA  
UTD-HFND / UTD-HFKB  
UTD-HFKA

The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.

(Not a result of experiments in an actual use environment. Silver ion filter inhibits activity or growth of microorganism, but do not prevent infection.)

The silver ion filter inhibits the activities of viruses\*1, bacteria\*2 and molds\*3 trapped on the filter.


(Only effective when the microorganism is trapped on the filter with dust or droplet)



\*1 [Testing organization] Kitasato Research Center for Environmental Science [Test Report] No. 2020\_0408 [Test virus] Escherichia coli phage Qbeta NBRC 20012 (1 type) [Test Method] Based on the antiviral test method for textile products (JIS L 1922) [Test results] Inhibited by at least 99% in 24 hours. Not tested to prevent transmission of SARS-CoV-2.  
 \*2 [Testing organization] Kitasato Research Center for Environmental Science [Test Report] No. 2020\_0409 [Test bacteria] Escherichia coli NBRC 3972 (1 type) [Test Method] Based on the determination of antibacterial activity and efficacy of textile products (JIS L 1902) [Test results] The growth of the test bacteria was inhibited by 24 hours testing  
 \*3 [Testing organization] Kitasato Research Center for Environmental Science [Test Report] No. 2020\_0410 [Test fungi] Aspergillus Niger NBRC 105649 and other fungi (3 types) [Test Method] Based on the test for fungus resistance (JIS Z 2911) [Test results] The growth of the fungus was inhibited by 28 days testing

The filter is easily removable\* and hand-washable.

(\*Wall mounted and floor models only)



\*4 Hand-washing or vacuuming by 3 months is recommended. Cleaning frequency varies depending on the environment of use.

## Specifications

Model name	For Wall mounted / Floor				for Cassette	
	UTR-FA16-5	UTR-FA13-3	UTR-FA03-5	UTD-HFAA	UTD-HFRA	
Net Dimension (H × W × D)	mm	35 × 210 × 6	50 × 364 × 6	43 × 272 × 6	350 × 125 × 6	550 × 136 × 6
Weight	g	2	2	2	7	23
Quantity		2	2	2	1	1

Model name	for Duct									
	UTD-HFTA	UTD-HFTB	UTD-HFTC	UTD-HFNC	UTD-HFNB	UTD-HFNA	UTD-HFND	UTD-HFKB	UTD-HFKA	
Net Dimension (H × W × D)	mm	290 × 70 × 6	390 × 70 × 6	290 × 70 × 6 390 × 70 × 6	620 × 88 × 6	420 × 88 × 6	620 × 88 × 6	500 × 79 × 6	420 × 125 × 6	620 × 108 × 6
Weight	g	6	8	10	8	10	16	12	16	20
Quantity		2	2	3	1	2	2	2	2	2

# Auto louver grille kit

UTD-GXTA-W / UTD-GXTB-W / UTD-GXTC-W




The optional clean-looking flat Auto louver grille kit blends into any interior and provides a comfortable airflow.




## Flexible Control

- The Auto louver grille of the indoor unit can be operated in conjunction with the remote control of the indoor unit.
- Vertical auto swing
- Auto airflow direction and auto swing
- 4 steps selectable
- Auto-closing louver  
The louvers will automatically close when the indoor unit stops operating.



## Dimensions



Model name	W1	W2	H1	H2	D1	D2
UTD-GXTA-W	683	645	180	148	9	84
UTD-GXTB-W	883	845				
UTD-GXTC-W	1,083	1,045				

Unit: mm

## Specifications

Model name	UTD-GXTA-W		UTD-GXTB-W		UTD-GXTC-W		
Applicable indoor unit	SPLIT & MULTI-SPLIT ARHC07/09LLTA ARXG07/09/12/14KSLAP ARXG07/09/12/14KLLAP ARHG07/09LSLAP		ARXG18KSLAP ARXG18KLLAP		ARXD024GLEH ARXD024HLAH ARXK024GLGH		
	VRF ARXD007/009/012/014GLEH ARXK004/007/009/012/014GLGH ARXD04GALH ARXD004/005/007/009/012/014HLAH ARXP009/012/014HLAH		ARXD018GLEH ARXD018HLAH ARXK018GLGH				
Power supply	Connecting with Control box of indoor unit						
Fixing Auto louver grille	Screwed to Flange or Square duct						
Extension Square duct limit	1.0 m (Max. duct length between indoor unit and Auto louver grille)						
Net Dimensions (H × W × D)	mm	180 × 683 × (84 + 9)		180 × 883 × (84 + 9)		180 × 1,083 × (84 + 9)	
Weight	Net	kg (lbs)		2.0 (4.4)		2.5 (5.6)	3.0 (6.7)
Accessories	Fitting Flame, etc.						
Operating range	Cooling	°C		18 to 32			
	Heating	% RH		80 % or less			
		°C		16 to 30			


# Pressure sensor kit

UTY-SPWX




## Design flexibility

The height difference between the outdoor unit and the indoor unit is normally 50 m for the V-IV Series, but can be extended to 110 m by installing the Pressure sensor kit. (Can only be connected to the V-IV Series. Also, it can only be connected to outdoor units using outdoor unit software compatible with the product.)



## System overview



## Pressure sensor kit

Pressure sensor kit (Converter)	Refrigerant pressure sensor	Joint pipe

## Specifications

Model name	UTY-SPWX
Power supply	9 to 16 V DC
Dimensions (H x W x D) (mm)	140 x 117 x 43
Weight (g)	200

# External power supply unit

UTZ-GXXA / UTZ-GXXC




## The External power supply unit protects the increment in the system even if the power supply for some of the indoor units is shut down.

Connects to the External power supply unit to supply power to the indoor unit from the auxiliary power supply. This allows for continuous operation without system errors. Built-in relays reduce installation time and cost. The UTZ-GXXC have a built-in relay, which reduces installation time and cost.

## High reliability

- A: Interruption of the main power supply is detected by the power cut-off detection part.
- B: Supplies power for driving the expansion valve of the indoor unit. (12 V or 5 V DC)
- C: Gives notification of the power supply from the External power supply unit.



## Note

- When changing the power supply voltage to 24 V AC, use a power transformer with an insulated structure that complies with the regulations\* of the installation region.
  - A powered-off indoor unit driven by the External power supply unit is treated in the same way as an operation-off unit in the electricity charge appointment function. If standby power is generated, the result of the electricity charge appointment may not be zero.
- \* UL Class II or IEC 61558 Class III, for example.

## Specifications


Model name	UTZ-GXXA	UTZ-GXXC
Power supply	24 V AC 50/60 Hz	
Dimensions (H x W x D) (mm)	97 x 200 x 178	
Weight (g)	800	

# AIR BEAM Radiation air outlet unit


\*Production by order  
Contact us for more details.



## Key component



## Cross-section view



Airflow rate (m <sup>3</sup> /h)	180 (160-215)	270 (240-325)
Grid	600 x 2	600 x 3
AIR BEAM For system ceiling (Integrated type)	KS-180	KS-270

# Gas sensor kit

UTY-SGZH



NEW




## Enhanced disaster safety measures

The system is designed to meet the environmental safety requirements specified in the IEC 603352-40 standard for the use of R32 refrigerant. The environment requiring safety measures is determined by the size of the room in relation to the amount of refrigerant required.

For example, if the system is designed for maximum pipe length and the refrigerant charge is 6 kg, safety measures are required for rooms of 15 m<sup>2</sup> or less.

For Example: Total pipe length 120m



**Shut off valve kit**  
UTP-GX027A, UTP-GX060A

Block the path to prevent refrigerant flow in the event of a refrigerant leakage.

**Gas sensor kit**  
UTY-SGZH\*


Gas Sensor kit Used to ensure standards compliance and safety when R32 VRF products are installed.  
\*Connection cable (UTY-XWZXZL) is required.

**Expansion kit**  
UTZ-JXXA

Used to ensure standards compliance and safety when R32 VRF products are installed.

## Conditions requiring safety measures

The graph below will help you determine if a safety design is required when installing R32 VRF products. The amount of refrigerant in a refrigerant system determines the floor area, and if the room to be conditioned by the system is less than that area, a “shut off valve kit” and a “gas sensor kit” must be installed.




## Features: Gas sensor kit

### Refrigerant leak detector connection pattern


1) Corresponds to the case where the classification of air conditioner installation differs from property to property.

Installation position of “Shut off valve kit”


- A** Indoor unit 1~4 in one room
- B** Indoor units 1, 2 and 3, 4, if they are set up in two separate rooms.
- C** Indoor units 1~4 are installed in different rooms.



2) Multiple rooms or areas are air conditioned using ducted airflow paths



3) When operating multiple indoor units with a remote control group



## Specifications

Model name	UTY-SGZH
Dimensions (H × W × D) (mm)	80 × 130 × 35
Weight (g)	500



# Optional parts list for VRF



Type	Refrigerant	Indoor unit																		V-IV Series								
		Cassette						Duct						Indoor unit														
		One-way flow	3D flow	Compact grid type/ Standard type		Slim type	Large type	Low static pressure duct						Floor	external EEV	Floor/Ceiling	Ceiling	Wall-mounted										
				High Efficiency	Circular flow			Mini (With drain pump)	Slim (With drain pump)		High Efficiency	Low static pressure duct	Medium static pressure					High static pressure	external EEV		external EEV	external EEV	external EEV					
ARXB 004/005/007/009/012/014/018/HLAH	AUXN 009/012/014/HLAH	ARXD 004/005/007/009/012/014/018/024 HLAH	ARXP 009/012/014 HLAH		ARXP 018/030 GLFH	ARXA 024/030/036/045 GLEH	ARXC 036/045/060 GTEH		ARXC 072/090/096 GTEH	AGHA 004/007/009/012/014 GCGH				AGHE 004/007/009/012/014 GCEH	ABHA 012/014/018/024 GTEH	ABHA 030/036/045/054 GTEH	ASHA 004/007/009/012/014 GCGH			ASHE 004/007/009/012/014 GCEH				ASHA 18/24GBCH	ASHA 030/034GTEH			
Human sensor kit						●	UTY-SHZXC																					
Remote sensor unit						●	UTY-XSZXZ1																●	UTY-XSZXZ1				
Cassette grille				●		●																						
Auto louver grille kit										●	UTD-GXTA-W (4-14), UTD-GXTB-W (18), UTD-GXTC-W (24)																	
Silver ion filter					●		●		●					●		●			●			●			●			
Long-life filter														●		●												
Flange																												
Drain Pump Unit																												
Wide Panel																												
Panel spacer																												
Fresh air intake kit*1																												
Air outlet shutter plate																												
Insulation kit for high humidity																												
Half concealed kit																												
External power supply unit																												
Pressure sensor kit																												
Gas sensor kit																												





# Function list for VRF





## External input and output function/External connect kit

Type	Refrigerant	Indoor unit														Indoor unit				Outdoor unit						controller	Other										
		Cassette		Duct				Floor								Wall-mounted				J-V5	J-IVL	J-IV	J-IVS	V-IV	VR-IV	Central remote controller	RB unit										
		One-way flow	3D flow	Slim type		Large type	Low static pressure			Low static pressure	Medium static pressure	High static pressure	-	EEV external	Floor/Ceiling	-	EEV external	-	-																		
				Compact grid type/Standard type	High Efficiency		Circular flow	Mini (With drain pump)	Slim (With drain pump)																			High Efficiency	High Efficiency	Normal	Normal						
	R32	AUXB 004/005/007/009/012/014/018/HLAH	AUXN 009/012/014/HLAH			ARXD 004/005/007/009/012/014/018/024/HLAH	ARXP 009/012/014/HLAH									ASHA 004/005/007/009/012/014/HCAH	ASHE 004/005/007/009/012/014/HCAH				AJH 040/045/054/KCTAH																
	R410A	AUXV 004/007/009/012/014/018/024GLEH	AUXS 018/024GLEH	AUXB 004/007/009/012/014/018/024GLEH		AUXM 018/024/030GLEH	AUXK 018/024/030/034/036/045/054GLEH	ARXK 004/007/009/012/014/018/024GLEH	ARXD 007/009/012/014/018/024GLEH	ARXP 018/030GLEH	ARXA 024/030/036/045GLEH	ARXC 036/045/060/072/090/096GTEH	AGHA 004/007/009/012/014/GCGH	AGHE 004/007/009/012/014/GCEH		ABHA 012/014/018/024GTEH	ABHA 030/036/045/054GTEH	ASHA 004/007/009/012/014/GCGH	ASHE 004/007/009/012/014/GCEH	ASHA 18/24GBCH	ASHA 030/034GTEH	AJH 072/090/108/126/144/162LELDH	AJH 040/045/054/LBLDH	AJH 040/045/054/LCLDH	AJH 072/090/108/126/144/162/LALDH	AJH 072/090/108/126/144/GALDH	UTY-DCCGZ3	UTP-RX01AH	UTP-RX01BH	UTP-RX01CH	UTP-RX08BH	UTP-RX12AH					
Indoor	Operation/Stop							● UTY-XWZXZD ○ UTY-XWZXZB								● UTY-XWZXZD ○ UTY-XWZXZB																					
	All On/All Off																																	● UTY-XWZXZ7 ○ UTY-XWZXZ8			
	Group stop																																		● UTY-XWZXZ6		
	Forced stop																																			● UTY-XWZXZD ○ UTY-XWZXZB	
	Emergency stop																																			● UTY-XWZXZD ○ UTY-XWZXZB	
	Forced thermostat off																																			● UTY-XWZXZ7 ○ UTY-XWZXZ8	
	Low noise mode operation																																			● UTY-XWZXZ6	
	Cooling/Heating priority																																			● UTY-XWZXZ6 ○ UTY-XWZXZ8	
	Outdoor unit operation peak control																																				● UTY-XWZXZ6
	Power usage information from electricity meter																																				● UTY-XWZXZ6 ○ UTY-XWZXZ8
Indoor	Operation status																																			● UTY-XWZXZC	
	Error status																																			● UTY-XWZXZC	
	Indoor unit fan operation status																																			● UTY-XWZXZC	
	Auxiliary heater output																																		● UTY-XWZXZC		
	Base pan heater																																			● UTY-XWZXZ9	
Outdoor	Expansion kit			● UTZ-JXXA (HLAH)				● UTZ-JXXA (HLAH)																												● UTZ-JXXA (HCAH)	

\*2: The Touch panel controller has the functions of dry contact and voltage application, but the external connection kit described above is not necessary because the touch panel controller has an external input terminal block. ●: Dry Contact ○: Apply Voltage

### For VRF

<p><b>NEW</b> Expansion kit</p>  <p>UTZ-JXXA</p>	<p><b>NEW</b> Connection Cable</p>  <p>UTY-XWZXZL</p>
---	--

### Communication system

External connect kit		For indoor unit	For outdoor unit	For RB unit	Central remote controller	For Touch panel controller
UTY-XWZXZ7		UTY-XWZXZD		UTY-XWZXZ6		UTY-XWZXZA
UTY-XWZXZB		UTY-XWZXZE		UTY-XWZXZ9	UTY-XWZXZB	
UTY-XWZXZC			UTY-XWZXZF			
					UTY-XWZXZ8	
					UTY-XWZXZA	

# Separation tube



## For SPLIT/MULTI-SPLIT/SIMULTANEOUS MULTI-SPLIT

Separation tube	
UTP-SX236A / UTP-SX254A For 3-phase simultaneous multi-split  UTP-SX272A For Simultaneous multi-split Twin / Triple / Double Twin  	UTP-SX354A For 3-phase simultaneous multi-split  UTP-SX372A For Simultaneous multi-split Twin / Triple / Double Twin  

## for VRF

Separation tube			
UTP-AX054A Gas pipe  Liquid pipe 	UTP-AX090A Gas pipe  Liquid pipe 	UTP-AX180A Gas pipe  Liquid pipe 	UTP-AX567A Gas pipe  Liquid pipe 
UTP-BX090A Suction Gas pipe  Discharge Gas pipe  Liquid pipe 	UTP-BX180A Suction Gas pipe  Discharge Gas pipe  Liquid pipe 	UTP-BX567A Suction Gas pipe  Discharge Gas pipe  Liquid pipe 	UTP-LX180A For DX kit 

## Header

UTR-H0906L / UTR-H1806L Gas pipe  Liquid pipe 	UTR-H0908L / UTR-H1808L Gas pipe  Liquid pipe 	UTP-J0906A / UTP-J1806A Suction gas pipe  Discharge gas pipe  Liquid pipe 	UTP-J0908A / UTP-J1808A Suction gas pipe  Discharge gas pipe  Liquid pipe 
--	--	--	--

## Outdoor unit branch kit

Outdoor unit branch kit		Separation tube for RB unit	
UTP-CX567A Gas Pipe  Liquid Pipe 	UTP-DX567A Suction Gas Pipe  Discharge Gas Pipe  Liquid Pipe 	UTP-EX060A Gas Pipe  Liquid Pipe 	UTP-EX096A Gas Pipe  Liquid Pipe 



## for VRF

EV kit		Shut off valve kit	
Model name $\leq 09$ : UTR-EV09XB Model name $\geq 12$ : UTR-EV14XB for compact wall-mounted type  	<b>NEW</b> Model name $\leq 09$ : UTR-EV09XC <b>NEW</b> Model name $\leq 12$ : UTR-EV14XC for R32 VRF wall-mounted type  	<b>NEW</b> UTP-GX027A for R32 VRF indoor unit  	<b>NEW</b> UTP-GX060A for R32 VRF outdoor unit  

## RB unit

UTP-RX01AH / UTP-RX01BH / UTP-RX01CH Single type  	UTP-RX04BH Multi-split type  	UTP-RX08AH Multi-split type  	UTP-RX12AH Multi-split type  
---	--	--	--

## Specifications

### Separation tube

Model name	UTP-AX054A	UTP-AX090A	UTP-AX180A	UTP-AX567A
Total cooling capacity of indoor unit (kW)	19.6 or less	28.0 or less	28.1 to 56.0	56.1 or more
Model name	UTP-BX090A	UTP-BX180A	UTP-BX567A	
Total cooling capacity of indoor unit (kW)	28.0 or less	28.1 to 56.0	56.1 or more	

### Header

Model name	3-6 Branches	UTR-H0906L	UTR-H1806L
	3-8 Branches	UTR-H0908L	UTR-H1808L
Total cooling capacity of indoor unit (kW)		28.0 or less	28.1 to 56.0
Model name	3-6 Branches	UTP-J0906A	UTP-J1806A
	3-8 Branches	UTP-J0908A	UTP-J1808A
Total cooling capacity of indoor unit (kW)		28.0 or less	28.1 to 56.0

### Outdoor unit branch kit

Model name	UTP-CX567A (for V-IV)	UTP-DX567A (for VR-IV)
Number of outdoor units	2 outdoor units	1
	3 outdoor units	2

### EV kit

Model name	UTR-EV09XB		UTR-EV14XB		UTR-EV09XC	UTR-EV14XC
Application model	ASHE004GCEH ASHE007GCEH ASHE009GCEH	AGHE004GCEH AGHE007GCEH AGHE009GCEH	ASHE012GCEH ASHE014GCEH	AGHE012GCEH AGHE014GCEH	ASHE004HCAH ASHE005HCAH ASHE007HCAH ASHE009HCAH	ASHE012HCAH ASHE014HCAH

### RB unit

Type	Single type				Multi-split type	
Model name	UTP-RX01AH	UTP-RX01BH	UTP-RX01CH	UTP-RX04BH	UTP-RX08AH	UTP-RX12AH
Power source	230/1/50					
Input power	W					
Number of branches	1	1	1	4	8	12
Maximum capacity of connectable indoor units (Q)	kW					
Maximum capacity of connectable indoor units per branch (Q)	kW					
Maximum Connectable Indoor Units per Branch	3	8	8	8	7	7
Dimensions (H × W × D)	mm					
	198 × 298 × 268			260 × 658 × 428		298 × 660 × 618
	298 × 990 × 618					

\*1: When two RB units are connected in series (8 branches in total), the maximum capacity of the connectable indoor units is up to 56.0 kW.

### Shut off valve kit

Model name	UTP-GX027A		UTP-GX060A
Power source	230/1/50		230/1/50
Input power	W		W
Number of branches	1		1
Maximum number of connectable Expansion kit	kW		kW
Maximum capacity of connectable indoor units (Q)	kW		kW
Maximum capacity of Connectable Indoor Units per Branch (Q)	kW		kW
Dimensions (H × W × D)	mm		mm
	250 × 540 × 267		250 × 540 × 267

## Residential AIR TO WATER

- W-002 AIR TO WATER Overview
- W-004 AIR TO WATER Lineup for Monobloc type
- W-006 AIR TO WATER Lineup for Split type
- W-008 Benefits
- W-010 Home Heating & Domestic Hot Water Supply
- W-012 Solutions System Configuration for Monobloc Type
- W-014 Monobloc Type
  - Comfort Series
- W-018 Split type Overview
- W-020 Split Type
  - Comfort Series
  - Super High Power Series
  - High Power Series
- W-026 Split DHW Integrated Type
  - Comfort Series
  - Super High Power Series
  - High Power Series
- W-032 Comfort Control for Split Type
- W-034 Simple installation
- W-036 Comfort Control for Monobloc Type
- W-038 System Configuration
- W-040 Case Studies
- W-042 Control Overview for Split type
- W-044 Optional Parts Overview for Split type
- W-046 Optional parts list for Monobloc type
- W-048 Optional parts list for Split type



AIR TO WATER  
Residential



FUJITSU GENERAL LIMITED

# AIR TO WATER Overview


## Solutions that meet a variety of needs

Water heated by Air to water using clean energy is delivered reliably and comfortably throughout the house, including the living room.



## Heat Pump System Framework

Heat is absorbed from the atmosphere by expanding the refrigerant. Higher-temperature heat is generated by compressing the refrigerant, and the indoor unit transfers that heat to the water.




## Our Goal

### Decarbonisation

European Commission is committed to decarbonisation and has a national target of “**Net Zero**” carbon emissions by 2050.

We need to reduce carbon emissions with green technology products and increase carbon absorption by working to extend nature.




Fujitsu General's ATW system will provide the best solutions that are friendly to the environment and people with products conscious of decarbonisation.

## The Choice of ATW


### Optimized refrigerant cycle operation

Super High Power and High Power Series deliver high performance and efficiency with twin sensors and hot water heating technology.

#### Split Type




#### Split DHW Integrated Type



### What is a heat pump?


A heat pump extracts heat energy from the atmosphere. It requires only 1 kWh of electricity to generate 3 to 5 kWh of thermal energy.



### Primary energy usage reduced substantially












Proportion of primary energy converted into heating energy is 100%

#### Primary Energy Consumption\*




\* The amount of electricity loss varies according to the power plant. Typical energy efficiency of a power plant: 36%

# AIR TO WATER Lineup for Monobloc type

Type	Monobloc Control Box type Comfort Series	Monobloc Wall hung type Comfort Series	Monobloc DHW Integrated type Comfort Series	
Indoor unit	 <b>NEW</b>	 <b>NEW</b>	 <b>NEW</b>	
Outdoor unit	 	 	 	
Capacity range	5 kW    8/10 kW	5 kW    8/10 kW	5 kW    8/10 kW	
System outline	<p><b>Indoor unit</b> Control box consists of the hot water circuit controller and the user interface. It is not connected to the water pipe.</p> <p><b>Outdoor unit</b></p> <ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -5°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to Three independent control circuits.*</li> <li>Operating range is -20 to 35°C in heating.</li> </ul>	<p><b>Indoor unit</b> Wall hung indoor unit includes the expansion tank, buffer tank, backup heater and water pump. It contributes to the ease of installation.</p> <p><b>Outdoor unit</b></p> <ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -5°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to Three independent control circuits.*</li> <li>Operating range is -20 to 35°C in heating.</li> </ul>	<p><b>Indoor unit</b> DHW integrated indoor unit has a 190L hot water tank. It is easy to set up the system for heating and hot water supply.</p> <p><b>Outdoor unit</b></p> <ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -5°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Heating and DHW supply in one system.</li> <li>Up to Three independent control circuits.*</li> <li>Operating range is -20 to 35°C in heating.</li> </ul>	
Power source	Single phase, ~230 V, 50 Hz	Single phase, ~230 V, 50 Hz	Single phase, ~230 V, 50 Hz	
Capacity	5 kW	UTW-SCBHC WPHG050KRF	WSHP100KR3 WPHG050KRF	WGHP100KR3-19 WPHG050KRF
	6 kW			
	8 kW	UTW-SCBHC WPHG080KRF	WSHP100KR3 WPHG080KRF	WGHP100KR3-19 WPHG080KRF
	10 kW	UTW-SCBHC WPHG100KRF	WSHP100KR3 WPHG100KRF	WGHP100KR3-19 WPHG100KRF
	11 kW			
	14 kW			
	15 kW			
	16 kW			
17 kW				
Approval		●	●	●
				

\* Please refer to page W-044 and W-045 for optional parts information.



Outdoor unit  
Single phase  
8/10 kW

## New Stylish Design

The outdoor unit of monobloc type has adopted a new design with black and dark gray colors. It blends in with the landscape, harmonizing with various installation locations.

# AIR TO WATER Lineup for Split type

Type	Split Type Wall Hung type				Split DHW Integrated Type									
	Comfort Series		Super High Power Series	High Power Series		Comfort Series		Super High Power Series	High Power Series					
Hydraulic unit														
Outdoor unit														
Capacity range	5/6 kW	8 kW	10 kW	16 kW		11/14 kW	11/14/16 kW	5/6 kW	8 kW	10 kW	16 kW	11/14 kW	11/14/16 kW	
System outline	<ul style="list-style-type: none"> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Heating and DHW supply in one system.*</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -20 to 35°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> </ul>		<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -22°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>		<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to two independent control circuits.*</li> <li>Cascade connection is possible for up to three systems.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>		<ul style="list-style-type: none"> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Heating and DHW supply in one system.</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -20 to 35°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> </ul>		<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -22°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Space saving heating and DHW supply in a single Hydraulic unit</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>		<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Space saving heating and DHW supply in a single Hydraulic unit</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>			
Power source	Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz		Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz	
Capacity	5 kW	WSHA050ML3 WOHA060KLT						WGHA050ML3 WOHA060KLT						
	6 kW	WSHA080ML3 WOHA060KLT						WGHA080ML3 WOHA060KLT						
	8 kW	WSHA080ML3 WOHA080KLT						WGHA080ML3 WOHA080KLT						
	10 kW	WSHA100ML3 WOHA100KLT						WGHA100ML3 WOHA100KLT						
	11 kW			WSHG140DG WOHG112LHT		WSHG140DG WOHK112LCTA						WGHG140DG WOHG112LHT		WGHG140DG WOHK112LCTA
	14 kW			WSHG140DG WOHG140LCTA		WSHG140DG WOHK140LCTA						WGHG140DG WOHG140LCTA		WGHG140DG WOHK140LCTA
	16 kW			WSHG160DJ6 WOHG160LJL		WSHG140DG WOHK160LCTA				WGHG160DJ6 WOHG160LJL				WGHG140DG WOHK160LCTA
Approval														


\* Please refer to page W-046 and W-047 for optional parts information.

# Benefits

**Less**  
CO<sub>2</sub> Emissions

Air to water is an environmentally friendly system that emits substantially less carbon dioxide than conventional gas and hydrocarbon combustion systems.

### Average annual CO<sub>2</sub> emissions




\*Calculations based on energy efficiency data provided by the European Programme for Energy Efficiency in EU-27: 89% for fuel boilers; 93% for gas boiler

**Low**  
Running Cost

High-efficiency heat pump technology keeps the running cost of an Air to water system.

### Average annual running cost



\*The running cost may vary depending on a system's installation, geographical location, and operating conditions.

**Clean**  
and Healthy

As an Air to water system does not use a burner to heat water, it does not produce NOx or other harmful substances.



Environmentally friendly heating system



**Easy**  
Installation and Maintenance

All components are built into a compact outdoor unit or a Hydraulic unit.



**Well-designed Hydraulic unit**  
The sophisticated arrangement of Hydraulic units makes piping and maintenance work easy.

## Energy Efficiency Standards Product labels

**Space heaters**

- Product identifier
- Trademark
- Symbol for space heating
- Efficiency class in low temperature operation
- Efficiency class at medium temperature operation
- Efficiency class with a comparative scale from A+++ (most efficient) to G (least efficient)
- Temperature map of Europe showing the three climate zones and their respective rated heat output
- Outdoor and indoor (if applicable) sound power level
- Year label issued
- EU regulation No.

**Combination heaters**

- Symbol for hot water heating
- Efficiency class with a comparative scale from A+ (most efficient) to G (least efficient) for hot water heating
- A symbol indicating that the system is to operate only during off-peak periods

### The Ecodesign Directive Lot 1 Regulation 813/2013

The Ecodesign directive defines a regulatory framework for improving the environmental performance of energy-related products (ErP) through design.

Since September 26, 2015, the Ecodesign Directive has applied to space heaters, including heat pumps and fossil fuel fired boilers, combination heaters for space and hot water heating, water heaters, and water storage tanks.

All of these products must meet minimum requirements for energy efficiency\*1 and maximum sound power level. The minimum energy efficiency class were raised on September 26, 2017, and the maximum sound levels were lowered on September 26, 2018.

\*1: Energy efficiency is expressed in terms of seasonal space heating efficiencies ( $\eta_s$ ). The value is based upon the Seasonal Coefficient of Performance (SCOP).

### The Energy Labelling Directive (EU) No. 811/2013

Energy label is intended to enable consumers to make direct comparisons of energy use and product features. All labels should indicate the product identifier, efficiency class, sound power level, and heat output. Heat generators are rated A+++ to D. There are two different product labels. One for space heaters and one for combination heaters.

### Seasonal space heating Energy efficiency class

	Except low temp. HP 55°C	Low temp. HP 35°C
A+++	$\eta_s \geq 150$	$\eta_s \geq 175$
A++	$125 \leq \eta_s < 150$	$150 \leq \eta_s < 175$
A+	$98 \leq \eta_s < 125$	$123 \leq \eta_s < 150$
A	$90 \leq \eta_s < 98$	$115 \leq \eta_s < 123$
B	$82 \leq \eta_s < 90$	$107 \leq \eta_s < 115$
C	$75 \leq \eta_s < 82$	$100 \leq \eta_s < 107$
D	$36 \leq \eta_s < 75$	$61 \leq \eta_s < 100$
E	$34 \leq \eta_s < 36$	$59 \leq \eta_s < 61$
F	$30 \leq \eta_s < 34$	$55 \leq \eta_s < 59$
G	$\eta_s < 30$	$\eta_s < 55$

### EHPA Quality Label



Fujitsu General's Air to water<sup>2</sup> has acquired the EHPA Quality Label<sup>3</sup> through testing in accordance with the International Standards EN14511 and EN17025. The EHPA Quality Label<sup>3</sup> is a label that shows the end-consumer a quality heat pump unit on the market.

<sup>2</sup>: 3-phase High Power Series only  
<sup>3</sup>: Learn more about the validity of the mark at [www.ehpa.org/quality/quality-label/](http://www.ehpa.org/quality/quality-label/)

### SG ready Label



SG ready is a label issued to heat pumps and their control technologies that meet the requirements set by BWP<sup>4</sup>, and technologies that conform to their standards can be integrated into a smart grid. SG ready labeled heat pumps receive signals from the power grid and PV systems with regard to energy and renewable energy sources such as wind, solar, and water. All of Fujitsu General's new heat pump series are SG ready compatible.

<sup>4</sup>: BWP: Bundesverband Wärmepumpe e. V (Federal German Heat Pump Association)

### The CEN Heat Pump KEYMARK




The Heat Pump KEYMARK is a full certificate supporting the quality of heat pumps in the European market. The Heat Pump KEYMARK is a voluntary, independent, European certification mark (ISO Type 5 Certification) for all heat pumps, combination heat pumps, and hot water heaters (as covered by Ecodesign, EU Regulation 813/2013 and 814/2013). Fujitsu General's Air to water<sup>5</sup> has acquired the KEYMARK certificate<sup>6</sup>.

<sup>5</sup>: R32 refrigerant comfort model only  
<sup>6</sup>: Learn more about the validity of the mark at [www.heatpumpkeymark.com/about/](http://www.heatpumpkeymark.com/about/)

# Home Heating & Domestic Hot Water Supply

A wide range of products to suit regional characteristics, family structures, and usage patterns. We provide a variety of products to meet the needs of customers from the heating-centered High Power Series to the reasonably priced Compact Series.



Water flow temperature  
**60°C**

Super High Power Series  
High Power Series

## High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C.

## Floor heating and domestic hot water supply

Outdoor units and hydraulic indoor units can be installed flexibly and easily. Hydraulic units installed inside the house prevent the circulating water from freezing. More units can be cascaded together to provide a greater heating capacity with greater flexibility.\*

\*1: High Power Series only



## Adopting R32 refrigerant

R32 refrigerant is an environmentally friendly refrigerant with a significantly lower Global Warming Potential (GWP) than conventional refrigerants.




## + DHW tank

A DHW tank (optional) can be connected to supply hot water.

## + Boiler

By combining with an existing boiler, powerful heating can be achieved even at low outdoor temperature.

\* Please refer to page W-038 and W-039 for optional parts information.




Stylish space saving solution with built-in DHW tank



## Built-in DHW tank saves a great deal of space.

Existing boilers can be replaced easily. A higher heating capacity can be achieved with the flexibility to cascade more units.



## Smart control

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.




# Solutions

## System Configuration

for Monobloc Type

Monobloc type with fewer pipe works and easy installation. It provides a wide variety of solutions to meet the usage environment.




### High water flow temperature

The plate heat exchanger with high heat exchange performance enables high water temperatures to flow even in low outdoor temperatures. It can adequately heat a room in cold regions.

### Control box

The built-in heat pump controller makes it easy to set the temperature.

### System example



### Individual remote control

An optional wireless thermostat allows remote control of the ATW system away from the indoor units. Can also be operated from mobile apps.





### Cost saving

Using heat pumps for heating when basic electricity rates are low saves money and is environmentally friendly.



### Water heating

In the case of a shortage of hot water, boilers (locally available) can warm water instantly. The auxiliary burning by the boiler (locally available) can also warm temperatures higher than the capacity of the heat pump system.



\* Only when connected to the control box.

NEW


# Monobloc Type

Comfort Series



## High water flow temperature

Plate heat exchanger with high heat exchange performance improves energy-related product performance, achieving high energy efficiency. All classes achieved top rank A+++\* energy efficiency class.




## High energy saving

Plate heat exchanger with high heat exchange performance improves energy-related product performance, achieving high energy efficiency. All classes achieved top rank A+++\* energy efficiency class.

Energy efficiency class



\*Temperature application: Heating temp. 35°C



## Quiet operation

In the outdoor unit, a larger fan and a sound-insulating structure in the compressor part reduce the maximum operating noise. The new monobloc outdoor unit can operate silently at 52dB(A)\* with high energy efficiency.

\*050 models



Quiet operation  
**52 dB(A)**  
050 models

## Quick start setup

The quick start setup from the HMI enables high-efficiency operation of the ATW system quickly and easily. It can be set up in only a few steps without difficulty.

## Schedule function

The new HMI can manage the heating system and DHW separately and has a schedule function. As the setting temperature and operating time can be managed individually, the ATW system can operate depending on the lifestyle of each day of the week.


## Remote connectivity and control

Via app "Cozy touch", you can manage and control of electric heaters, electric water heaters, heat pump water heaters, heat pumps.  
\* Cozytouch is a service of Group Atlantic



## Easy Pipe Work

No refrigerant piping work is required as the outdoor unit is an integrated unit. The hot water unit comes standard with the outdoor unit. Installation requires only hydraulic connection work, making installation easy.



Larger fan



Compressor

## Easy Maintenance

It can be maintained simply by removing the side panel and facilitates maintenance by access from one direction. The compact and lightweight panel makes it easy to remove.



Side panel

## Low Noise Operation

A larger fan and a sound-insulating structure in the compressor part of the outdoor unit reduce the maximum operating noise. For 080/100 models, the built-in compressor box suppresses the noise more. You don't need to worry about operating in quiet environments like at night.

**Control box:**  
**UTW-SCBHC**  
**Outdoor unit:**  
**WPHG050KRF/WPHG080KR**  
**WPHG100KRF**



**Wall Hung:**  
**WSHP100KR3**  
**DHW Integrated:**  
**WGHP100KR3-19**  
**Outdoor unit:**  
**WPHG050KRF/WPHG080KR**  
**WPHG100KRF**



**Specifications**

Model Name	Hydraulic unit		Control box				
	Outdoor unit		UTW-SCBHC	UTW-SCBHC	UTW-SCBHC	UTW-SCBHC	
Capacity Range			WPHG050KRF	WPHG080KRF	WPHG100KRF	WPHG100KRF	
7°C/35°C floor heating *1	Heating capacity	kW	5.00	8.00	10.00		
	Input power		0.97	1.54	2.05		
	COP		5.15	5.19	4.88		
7°C/55°C radiator *1	Heating capacity	kW	5.00	8.00	10.00		
	Input power		1.64	2.62	3.36		
	COP		3.04	3.05	2.98		
-7°C/55°C radiator *1	Heating capacity	kW	4.80	7.50	8.50		
	Input power		2.25	3.50	3.97		
	COP		2.13	2.14	2.14		
35°C/18°C cooling mode *1	Cooling capacity	kW	5.45	7.79	9.40		
	Input power		1.25	1.69	2.40		
	EER		4.35	4.62	3.91		
<b>Space heating characteristics*2</b>							
Temperature application	°C	55	35	55	35	55	35
Energy efficiency class		A++	A+++	A++	A+++	A++	A+++
Rated heat output (P <sub>rated</sub> )	kW	6	6	9	9	10	10
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	143	200	144	205	146	206
Annual energy consumption	kWh	3,110	2,364	4,880	3,571	5,480	4,018
Sound power level*3   Outdoor unit	dB(A)	52	52	56	56	57	57
<b>Control box specifications</b>							
Power source	Single phase, 230 V, 50 Hz						
Dimensions H × W × D	mm	483 × 370 × 222		483 × 370 × 222		483 × 370 × 222	
Weight (Net)	kg	10					
<b>Outdoor unit specifications</b>							
Power source	Single phase, 230 V, 50 Hz						
Current	Max.	A	14.6	19.1	20.6		
Water flow temperature range	Max.	°C	60	60	60		
Dimensions H × W × D	mm	798 × 1,080 × 480		1,008 × 1,080 × 480		1,008 × 1,080 × 480	
Weight (Net)	kg	85					
Refrigerant	Type (Global Warming Potential)	R32 (675)		R32 (675)		R32 (675)	
	Charge	kg	0.88	1.47	1.47		
Connection pipe   Diameter	Water	mm	Ø25.4		Ø25.4		
	Heating	°C	-20 to 35		-20 to 35		

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
 \*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)  
 \*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.

**Specifications**


Model Name	Indoor unit	Wall Hung			DHW Integrated			
		WSHP100KR3	WSHP100KR3	WSHP100KR3	WGHP100KR3-19	WGHP100KR3-19	WGHP100KR3-19	
Capacity Range	Outdoor unit	WPHG050KRF	WPHG080KRF	WPHG100KRF	WPHG050KRF	WPHG080KRF	WPHG100KRF	
7°C/35°C floor heating*1	Heating capacity	kW	5.00	8.00	10.00	5.00	8.00	10.00
	Input power		1.00	1.57	2.13	1.00	1.57	2.13
	COP		4.99	5.08	4.70	4.99	5.08	4.70
7°C/55°C radiator*1	Heating capacity	kW	5.00	8.00	10.00	5.00	8.00	10.00
	Input power		1.72	2.62	3.40	1.72	2.62	3.40
	COP		2.91	3.05	2.94	2.91	3.05	2.94
-7°C/55°C radiator*1	Heating capacity	kW	4.80	7.50	8.50	4.80	7.50	8.50
	Input power		2.51	3.62	4.11	2.51	3.62	4.11
	EER		1.91	2.07	2.07	1.91	2.07	2.07
35°C/18°C cooling mode*1	Cooling capacity	kW	5.35	7.69	9.30	5.35	7.69	9.30
	Input power		1.26	1.72	2.47	1.26	1.72	2.47
	EER		4.23	4.47	3.77	4.23	4.47	3.77
<b>Space heating characteristics*2</b>								
Temperature application	°C	55	35	55	35	55	35	
Energy efficiency class		A++	A+++	A++	A+++	A++	A+++	
Rated heat output (P <sub>rated</sub> )	kW	5.5(6)	5.8(6)	8.7(9)	9.0(9)	10.2(10)	10.2(10)	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	133	189	139	195	141	195	
Annual energy consumption	kWh	3,355	2,503	5,078	3,764	5,685	4,269	
Sound power level*3   Outdoor unit	dB(A)	52	52	56	56	57	57	
<b>Wall hung / DHW integrated specifications</b>								
Power source	Single phase, 230 V, 50 Hz							
Dimensions H × W × D	mm	737 × 448 × 469		737 × 448 × 469		1755 × 598 × 623		
Weight (Net)	kg	34.0		34.0		130.0		
Water circulation	Min./Max.	L/min		L/min		L/min		
DHW capacity	L	-		-		190.0		
Electrical heater capacity	Heating	kW		kW		kW		
Buffer tank capacity	L	16		16		16		
Expansion vessel capacity	L	12		12		12		
Water flow temperature range	Max.	°C		°C		°C		
Water pipe connection diameter	Flow/Return	mm		mm		mm		
Backup heater	Capacity	kW		kW		kW		
Declared load profile		-		-		L		
Efficiency η <sub>DHW</sub>	%	-		-		124		
Time to boil		-		-		1h45min		
COP(EN16147)		-		-		3.10		
<b>Outdoor unit specifications</b>								
Power source	Single phase, 230 V, 50 Hz							
Current	Max.	A	14.6	19.1	20.6	14.6		
Water flow temperature range	Max.	°C	60	60	60	60		
Dimensions H × W × D	mm	798 × 1,080 × 480		1,008 × 1,080 × 480		1,008 × 1,080 × 480		
Weight (Net)	kg	85						
Refrigerant	Type (Global Warming Potential)	R32 (675)		R32 (675)		R32 (675)		
	Charge	kg	0.88	1.47	1.47	0.88		
Connection pipe   Diameter	Water	mm	Ø25.4		Ø25.4			
	Heating	°C	-20 to 35		-20 to 35			

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
 \*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)  
 \*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.


**Dimensions**

(Unit: mm)


**Control box:**  
 UTW-SCBHC




**Wall Hung:**  
 WSHP100KR3




**DHW Integrated:**  
 WGHP100KR3-19



**Outdoor unit:**  
 WPHG050KRF



WPHG080KRF/WPHG100KRF




# Split type Overview

## High-Efficiency Technology

Twin-Rotary Compressor




High-durability coaxial heat exchanger





### For Outdoor unit

#### Twin-Rotary Compressor with Linear Control Injection Port

The compressor achieves a high condensing temperature without overheating the discharge gas temperature due to the Linear control injection process used during compression. This makes the condensing temperature higher than in a normal circuit. Higher water temperatures can be achieved by controlling the injection volume according to usage conditions.



DC inverter technology controls temperatures precisely.



### For Hydraulic unit

#### Stainless steel buffer tank

Heat exchange amount is 25% higher than the previous model. Energy-saving performance has also been improved.

- Anti-corrosion protection
- No flow switch required
- Anti-freeze protection not required

#### Class A Pump

Energy-saving pump with the ability to adjust the flow rate and pressure to a constant level



# Split Type

Comfort Series



**Hydraulic indoor unit:**  
**WSHA050ML3 / WSHA080ML3 / WSHA100ML3**  
**Outdoor unit:**  
**WOHA060KLT / WOHA080KLT / WOHA100KLT**



### Specifications

Model Name	Hydraulic unit		WSHA050ML3		WSHA080ML3		WSHA080ML3		WSHA100ML3	
	Outdoor unit		WOHA060KLT		WOHA060KLT		WOHA080KLT		WOHA100KLT	
<b>Capacity Range</b>			5		6		8		10	
7°C/35°C floor heating *1	Heating capacity	kW	4.50		5.50		7.50		9.50	
	Input power		0.949		1.18		1.69		2.11	
	COP		4.74		4.65		4.43		4.50	
2°C/35°C floor heating *1	Heating capacity	kW	4.50		5.30		6.30		9.30	
	Input power		1.33		1.65		1.96		3.08	
	COP		3.39		3.22		3.21		3.02	
-7°C/35°C floor heating *1	Heating capacity	kW	4.40		5.00		5.70		8.90	
	Input power		1.59		1.90		2.13		3.36	
	COP		2.76		2.63		2.68		2.65	
-7°C/55°C Radiator *1	Heating capacity	kW	3.90		4.25		5.30		8.00	
	Input power		2.11		2.25		2.79		4.10	
	COP		1.85		1.89		1.90		1.95	

### Space heating characteristics\*2

Temperature application	°C	55	35	55	35	55	35	55	35
Energy efficiency class		A++	A+++	A++	A+++	A++	A+++	A++	A+++
Rated heat output (P <sub>rated</sub> )	kW	5	5	5	6	6	7	8	9
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	125	175	125	175	128	177	130	178
Annual energy consumption	kWh	3,035	2,322	3,411	2,594	3,903	2,982	5,083	3,875
Sound power level*3	Hydraulic unit	40		40		40		40	
	Outdoor unit	57		57		60		62	

### Hydraulic unit specifications

Power source		Single phase, ~230 V, 50 Hz			
Dimensions H × W × D	mm	847 × 450 × 493		847 × 450 × 493	
Weight (Net)	kg	47		47	
Water circulation	Min./Max. L/min	7.6/22.0		8.5/22.0	
Buffer tank capacity	L	16		16	
Expansion vessel capacity	L	8		8	
Water flow temperature range	Max. °C	55		55	
Water pipe connection diameter	Flow/Return mm	Ø25.4/Ø25.4		Ø25.4/Ø25.4	
Backup heater	Capacity kW	3.0		3.0	

### Outdoor unit specifications

Power source		Single phase, ~230 V, 50 Hz				
Current	Max. A	13.0		18.0		
Dimensions H × W × D	mm	632 × 799 × 290		632 × 799 × 290		
Weight (Net)	kg	39		42		
Refrigerant	Type (Global Warming Potential)	R32 (675)		R32 (675)		
	Charge	0.97		1.02		
Additional refrigerant charge	g/m	25		25		
	mm	6.35		6.35		
Connection pipe	Diameter	Liquid	6.35		6.35	
		Gas	12.70		12.70	
	Length	Min./Max.	3/30		3/30	
	Length (Pre-charge)	m	15		15	
Operating range	Height difference	Max. m	20		20	
	Heating	°C	-20 to 35		-20 to 35	

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
 \*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)  
 \*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.

## High water flow temperature

The temperature of water flow is up to 55°C without a backup heater. Hot water supply temperature can be maintained even at -10°C outdoor temperature.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.



## High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.


Energy efficiency class



\*Temperature application: Heating temp. 35°C

### Seasonal space heating energy efficiency (η<sub>s</sub>)

Conditions: Outdoor Temp. 7°C Heating Temp. 35°C



Comfort Series 5 kW class

Comfort Series 8 kW class

Comfort Series 10 kW class

## Outdoor unit technology



**DC Fan Motor**  
High-performance, high-efficiency small DC fan motor mounted


**DC Twin-Rotary Compressor**  
High-efficiency DC twin-rotary compressor

**DC Inverter**  
DC inverter provides smooth water temperature control.


## Dimensions

(Unit: mm)


### Outdoor Unit: WOHA060KLT




### WOHA080KLT



### WOHA100KLT



### Hydraulic Indoor Unit: WSHA050ML3/WSHA080ML3/WSHA100ML3



# Split Type


Super High Power Series



## High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C. The system can supply 55°C water without a backup heater at an outdoor temperature of -22°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.



## High COP


Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

Energy efficiency class



### Seasonal space heating energy efficiency ( $\eta_s$ )

Conditions: Outdoor Temp. 7°C Heating Temp. 35°C



Single phase  
16 kW class

## Operating range extended to -25°C

Operating range improved down to -25°C outdoor temperature



Hydraulic indoor unit:  
**WSHG160DJ6**  
Outdoor unit:  
**WOHG160LJL**



### Specifications

Model Name	Hydraulic unit	WSHG160DJ6	
Capacity range	Outdoor unit	WOHG160LJL	
16			
7°C/35°C floor heating *1	Heating capacity	16.00	
	Input power	3.86	
	COP	4.15	
2°C/35°C floor heating *1	Heating capacity	13.30	
	Input power	4.25	
	COP	3.13	
-7°C/35°C floor heating*1	Heating capacity	14.50	
	Input power	5.27	
	COP	2.75	
-7°C/55°C Radiator*1	Heating capacity	10.90	
	Input power	5.89	
	COP	1.85	
<b>Space heating characteristics*2</b>			
Temperature application	°C	55	35
Energy efficiency class		A++	A++
Rated heat output ( $P_{rated}$ )	kW	14	16
Seasonal space heating energy efficiency ( $\eta_s$ )	%	125	163
Annual energy consumption	kWh	8,757	8,014
Sound power level	Hydraulic unit	45	45
	Outdoor unit	67	66
<b>Hydraulic unit specifications</b>			
Power source	Single phase, ~230 V, 50 Hz		
Dimensions H × W × D	mm	805 × 450 × 471	
Weight (Net)	kg	52.5	
Water circulation	Min./Max.	L/min 26.4/57.8	
Buffer tank capacity	L	22	
Expansion vessel capacity	L	10	
Water flow temperature range	Max.	°C 60	
Water pipe connection diameter	Flow/Return	mm $\varnothing$ 25.4/ $\varnothing$ 25.4	
Backup heater	Capacity	kW 6.0 (3.0 kW × 2 pcs.)	
<b>Outdoor unit specifications</b>			
Power source	Single phase, ~230 V, 50 Hz		
Current	Max.	A 28.0	
Dimensions H × W × D	mm	1,428 × 1,080 × 480	
Weight (Net)	kg	137	
Refrigerant	Type (Global Warming Potential)	R410A (2,088)	
	Charge	kg 3.80	
Additional refrigerant charge		g/m 50	
	Diameter	Liquid	mm $\varnothing$ 9.52
Connection pipe		Gas	mm $\varnothing$ 15.88
	Length	Min./Max.	m 5/30
	Length (Pre-charge)		m 15
Height difference	Max.	m 25/15 (Outdoor unit: Upper/Lower)	
	Heating	°C -25 to 35	

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ERP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

### Dimensions

(Unit: mm)

Outdoor Unit:  
WOHG160LJL

Hydraulic Indoor Unit:  
WSHG160DJ6



# Split Type

High Power Series



## High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.



## High COP


Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.



\*Temperature application: Heating temp. 35°C

### Seasonal space heating energy efficiency ( $\eta_s$ )

Conditions: Outdoor Temp. 7°C Heating Temp. 35°C



### Hydraulic indoor unit:

WSHG140DG

### Outdoor unit:

WOHG112LHT / WOHG140LCTA  
[3 phase] WOHK112LCTA /  
WOHK140LCTA /WOHK160LCTA



Hydraulic unit  
Single phase/  
3-phase



Outdoor unit  
Single phase  
11/14 kW



Outdoor unit  
3-phase  
11/14/16 kW

### Specifications

Model Name	Hydraulic unit		WSHG140DG		WSHG140DG		WSHG140DG		WSHG140DG	
	Outdoor unit		WOHG112LHT	WOHG140LCTA	WOHK112LCTA	WOHK140LCTA	WOHK140LCTA	WOHK160LCTA		
7°C/35°C floor heating *1	Heating capacity	kW	11	14	11	14	11	16		
			10.80	13.50	10.80	13.50	15.17			
			2.54	3.23	2.51	3.20	3.70			
2°C/35°C floor heating *1	Heating capacity	kW	11	14	11	14	11	16		
			10.77	12.00	10.77	13.00	13.50			
			3.44	3.87	3.40	4.15	4.34			
-7°C/35°C floor heating*1	Heating capacity	kW	11	14	11	14	11	16		
			10.38	11.54	10.38	12.20	13.50			
			4.32	5.08	4.28	5.13	5.40			
-7°C/55°C Radiator*1	Heating capacity	kW	11	14	11	14	11	16		
			7.57	9.20	7.43	10.10	11.00			
			4.57	5.08	5.09	5.65	6.29			
			COP		COP		COP			
			1.66		1.81		1.82			
			1.79		1.79		1.75			

### Space heating characteristics\*2

Temperature application	°C	55		35		55		35		55		35	
Energy efficiency class		A+	A++	A+	A+	A+	A++	A+	A++	A+	A++	A+	A+
Rated heat output (P <sub>rated</sub> )	kW	9	11	11	13	9	11	11	13	13	13	14	14
Seasonal space heating energy efficiency ( $\eta_s$ )	%	112	151	113	148	112	154	117	150	117	149	149	149
Annual energy consumption	kWh	6,704	6,062	8,041	6,824	6,669	5,930	7,803	6,738	9,062	7,408	7,408	7,408
Sound power level	Hydraulic unit	46		46		46		46		46		46	
	Outdoor unit	68		69		69		68		70		68	

### Hydraulic unit specifications

Power source	Single phase, ~230 V, 50 Hz				3-phase, ~400 V, 50 Hz			
Dimensions H × W × D	800 × 450 × 457				800 × 450 × 457			
Weight (Net)	40				40			
Water circulation	Min./Max.	L/min	19.5/39.0	24.4/48.7	19.5/39.0	24.4/48.7	27.4/54.8	
Buffer tank capacity	L	16	16	16				
Expansion vessel capacity	L	8	8	8				
Water flow temperature range	Max.	°C	60	60	60			
Water pipe connection diameter	Flow/Return	mm	Ø25.4/Ø25.4	Ø25.4/Ø25.4				
Backup heater	Capacity	kW	-	-	-			

### Outdoor unit specifications

Power source	Single phase, ~230 V, 50 Hz				3-phase, ~400 V, 50 Hz			
Current	Max.	A	22.0	25.0	9.0	9.5	10.5	
Dimensions H × W × D	mm				1,290 × 900 × 330			
Weight (Net)	kg				92			
Refrigerant	Type (Global Warming Potential)	R410A (2,088)						
	Charge	kg	2.50					
Additional refrigerant charge		g/m	50					
	Diameter	Liquid	Ø9.52					
Connection pipe	Gas	Ø15.88						
	Length	Min./Max.	m					
	Length (Pre-charge)	5/20						
Height difference	Max.	m						
	Heating	°C						
Operating range	-25 to 35							

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.

\*2: Information about ERP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

### Dimensions

(Unit: mm)




#### Outdoor Unit:

Single phase: WOHG112LHT/WOHG140LCTA

3 phase: WOHK112LCTA/WOHK140LCTA/WOHK160LCTA

#### Hydraulic Indoor Unit:

WSHG140DG



# Split DHW Integrated Type

Comfort Series



**Hydraulic indoor unit:**  
WGHA050ML3 / WGHA080ML3 / WGHA100ML3  
**Outdoor unit:**  
WOHA060KLT / WOHA080KLT / WOHA100KLT



### Specifications

Model Name	Hydraulic unit	WGHA050ML3	WGHA080ML3	WGHA080ML3	WGHA100ML3				
	Outdoor unit	WOHA060KLT	WOHA060KLT	WOHA080KLT	WOHA100KLT				
Capacity range		5	6	8	10				
7°C/35°C floor heating *1	Heating capacity	4.50	5.50	7.50	9.50				
	Input power	0.949	1.18	1.69	2.11				
	COP	4.74	4.65	4.43	4.50				
2°C/35°C floor heating *1	Heating capacity	4.50	5.30	6.30	9.30				
	Input power	1.33	1.65	1.96	3.08				
	COP	3.39	3.22	3.21	3.02				
-7°C/35°C floor heating *1	Heating capacity	4.40	5.00	5.70	8.90				
	Input power	1.59	1.90	2.13	3.36				
	COP	2.76	2.63	2.68	2.65				
-7°C/55°C Radiator *1	Heating capacity	3.90	4.25	5.30	8.00				
	Input power	2.11	2.25	2.79	4.10				
	COP	1.85	1.89	1.90	1.95				
<b>Space heating characteristics*2</b>									
Temperature application	°C	55	35	55	35	55	35	55	35
Energy efficiency class		A++	A+++	A++	A+++	A++	A+++	A++	A+++
Rated heat output (P <sub>rated</sub> )	kW	5	5	5	6	6	7	8	9
Seasonal space heating energy efficiency (η <sub>s</sub> )	%	125	175	125	175	128	177	130	178
Annual energy consumption	kWh	3,035	2,322	3,411	2,594	3,903	2,982	5,083	3,875
Sound power level*3	Hydraulic unit	40	-	40	-	40	-	40	-
	Outdoor unit	57	-	57	-	60	-	62	-
<b>Domestic hot water characteristics*2</b>									
Load profile		L		L		L		L	
Energy efficiency class		A+		A+		A+		A+	
Energy efficiency (n <sub>wh</sub> )	%	130		130		130		130	
Annual electricity consumption	kWh	793		793		793		793	
<b>Hydraulic unit specifications</b>									
Power source		Single phase, ~230 V, 50 Hz							
Dimensions H × W × D	mm	1,863 × 648 × 700	1,863 × 648 × 700	1,863 × 648 × 700	1,863 × 648 × 700				
Weight (Net)	kg	145	145	145	145				
Water circulation	Min./Max. L/min	7.6/22.0	8.5/22.0	10.0/22.0	13.2/30.0				
DHW capacity	L	190	190	190	190				
Electrical heater capacity	Heating	3.0	3.0	3.0	3.0				
	DHW	1.5	1.5	1.5	1.5				
Buffer tank capacity	L	16	16	16	16				
Expansion vessel capacity	L	8	8	8	8				
Water flow temperature range	Max. °C	55	55	55	55				
Water pipe connection diameter	Flow/Return mm	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4				
Hot water pipe connection diameter	mm	Ø19.05	Ø19.05	Ø19.05	Ø19.05				
<b>Outdoor unit specifications</b>									
Power source		Single phase, ~230 V, 50 Hz							
Current	Max. A	13.0	13.0	18.0	19.0				
Dimensions H × W × D	mm	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	998 × 940 × 320				
Weight (Net)	kg	39	39	42	62				
Refrigerant	Type (Global Warming Potential)	R32 (675)							
	Charge	0.97	0.97	1.02	1.63				
Additional refrigerant charge	g/m	25	25	25	20				
	Diameter	Liquid	6.35	6.35	6.35	9.52			
Connection pipe	Length	Gas	12.70	12.70	12.70	15.88			
	Length (Pre-charge)	Min./Max. m	3/30	3/30	3/30	3/30			
	Height difference	m	15	15	15	20			
	Max. m	20	20	20	20				
Operating range	Heating	°C	-20 to 35	-20 to 35	-20 to 35	-20 to 35			

## High water flow temperature

The temperature of water flow is up to 55°C without a backup heater. Hot water supply temperature can be maintained even at -10°C outdoor temperature.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.



## High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.


Energy efficiency class



\*Temperature application: Heating temp. 35°C

### Seasonal space heating energy efficiency (η<sub>s</sub>)

Conditions: Outdoor Temp. 7°C Heating Temp. 35°C



## Outdoor unit technology



**DC Fan Motor**  
High-performance, high-efficiency small DC fan motor mounted


**DC Twin-Rotary Compressor**  
High-efficiency DC twin-rotary compressor

**DC Inverter**  
DC inverter provides smooth water temperature control.


## Dimensions

(Unit: mm)


**Outdoor Unit:**  
WOHA060KLT




WOHA080KLT



WOHA100KLT



**Hydraulic Indoor Unit:**  
WGHA050ML3/WGHA080ML3/WGHA100ML3





# Split DHW Integrated Type


Super High Power Series



## High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C. The system can supply 55°C water without a backup heater at an outdoor temperature of -22°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.



## High COP


Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

Energy efficiency class



### Seasonal space heating energy efficiency ( $\eta_s$ )

Conditions: Outdoor Temp. 7°C Heating Temp. 35°C



## Operating range extended to -25°C

Operating range improved down to -25°C outdoor temperature

Stylish space saving solution with **Built-in High-performance DHW tank 190 L**

- Coil heat exchanger optimizes DHW supply performance.
- Temperature rises quickly due to the large surface of the exchanger.

### Hydraulic indoor unit:

**WGHG160DJ6**

### Outdoor unit:

**WOHG160LJL**



Hydraulic unit  
Single phase



Outdoor unit  
Single phase 16 kW

### Specifications


Model Name	Hydraulic unit	WGHG160DJ6	
Outdoor unit		WOHG160LJL	
<b>Capacity range</b>		16	
7°C/35°C floor heating *1	Heating capacity	16.00	
	Input power	3.86	
	COP	4.15	
2°C/35°C floor heating *1	Heating capacity	13.30	
	Input power	4.25	
	COP	3.13	
-7°C/35°C floor heating*1	Heating capacity	14.50	
	Input power	5.27	
	COP	2.75	
-7°C/55°C Radiator*1	Heating capacity	10.90	
	Input power	5.89	
	COP	1.85	
<b>Space heating characteristics*2</b>			
Temperature application	°C	55	35
Energy efficiency class		A++	A++
Rated heat output (P <sub>rated</sub> )	kW	14	16
Seasonal space heating energy efficiency ( $\eta_s$ )	%	125	163
Annual energy consumption	kWh	8,757	8,014
Sound power level	Hydraulic unit	45	45
	Outdoor unit	67	66
<b>Domestic hot water characteristics*2</b>			
Load profile		L	
Energy efficiency class		A	
Energy efficiency (n <sub>wh</sub> )	%	109	
Annual electricity consumption	kWh	941	
<b>Hydraulic unit specifications</b>			
Power source		Single phase, ~230 V, 50 Hz	
Dimensions H × W × D	mm	1,841 × 648 × 698	
Weight (Net)	kg	166	
Water circulation	Min./Max.	L/min	
		26.4/57.8	
DHW capacity	L	190	
Electrical heater capacity	Heating	6.0 (3.0 kW × 2 pcs.)	
	DHW	1.5	
Buffer tank capacity	L	22	
Expansion vessel capacity	L	12	
Water flow temperature range	Max.	°C	
		60	
Water pipe connection diameter	Flow/Return	mm	
		Ø25.4/Ø25.4	
Hot water pipe connection diameter		mm	
		Ø19.05	
<b>Outdoor unit specifications</b>			
Power source		Single phase, ~230 V, 50 Hz	
Current	Max.	A	
		28.0	
Dimensions H × W × D	mm	1,428 × 1,080 × 480	
Weight (Net)	kg	137	
Refrigerant	Type (Global Warming Potential)	R410A (2,088)	
	Charge	kg	
		3.80	
Additional refrigerant charge		g/m	
		50	
Connection pipe	Diameter	Liquid	Ø9.52
		Gas	Ø15.88
	Length	Min./Max.	m
			5/30
Length (Pre-charge)		m	
		15	
Height difference	Max.	m	
		25/15 (Outdoor unit: Upper/Lower)	
Operating range	Heating	°C	
		-25 to 35	

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)


### Dimensions

(Unit: mm)

**Outdoor Unit:**  
WOHG160LJL



**Hydraulic Indoor Unit:**  
WGHG160DJ6



# Split DHW Integrated Type

High Power Series



## High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.



## High COP


Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.



\*Temperature application: Heating temp. 35°C


### Seasonal space heating energy efficiency (η<sub>s</sub>)

Conditions: Outdoor Temp. 7°C Heating Temp. 35°C



## Optimized refrigerant cycle operation

The High Power Series deliver high performance and efficiency with twin sensors and hot water heating technology.



**Hydraulic indoor unit:**  
**WGHG140DG**  
**Outdoor unit:**  
**WOHG112LHT / WOHG140LCTA**  
**[3 phase] WOHK112LCTA / WOHK140LCTA / WOHK160LCTA**



## Specifications

Model Name	Hydraulic unit		WGHG140DG		WGHG140DG		WGHG140DG		WGHG140DG		WGHG140DG		
	Outdoor unit		WOHG112LHT	WOHG140LCTA	WOHK112LCTA	WOHK140LCTA	WOHK140LCTA	WOHK140LCTA	WOHK140LCTA	WOHK160LCTA	WOHK160LCTA	WOHK160LCTA	
<b>Capacity range</b>			11	14	11	14	14	16					
7°C/35°C floor heating *1	Heating capacity	kW	10.80	13.50	10.80	13.50	13.50	15.17					
	Input power		2.54	3.23	2.51	3.20	3.70						
	COP		4.25	4.18	4.30	4.22	4.10						
2°C/35°C floor heating *1	Heating capacity	kW	10.77	12.00	10.77	13.00	13.50						
	Input power		3.44	3.87	3.40	4.15	4.34						
	COP		3.13	3.10	3.17	3.13	3.11						
-7°C/35°C floor heating*1	Heating capacity	kW	10.38	11.54	10.38	12.20	13.50						
	Input power		4.32	5.08	4.28	5.13	5.40						
	COP		2.40	2.27	2.43	2.38	2.50						
-7°C/55°C Radiator*1	Heating capacity	kW	7.57	9.20	9.27	10.10	11.00						
	Input power		4.57	5.08	5.09	5.65	6.29						
	COP		1.66	1.81	1.82	1.79	1.75						
<b>Space heating characteristics*2</b>													
Temperature application	°C		55	35	55	35	55	35	55	35	55	35	
Energy efficiency class			A+	A++	A+	A+	A+	A++	A+	A++	A+	A+	
Rated heat output (P <sub>rated</sub> )	kW		9	11	11	13	9	11	11	13	13	14	
Seasonal space heating energy efficiency (η <sub>s</sub> )	%		112	151	113	148	112	154	117	150	117	149	
Annual energy consumption	kWh		6,704	6,062	8,041	6,824	6,669	5,930	7,803	6,738	9,062	7,408	
Sound power level	Hydraulic unit	dB(A)	46		46		46		46		46		
	Outdoor unit		68		69		69		68		70		
<b>Domestic hot water characteristics*2</b>													
Load profile	L												
Energy efficiency class	A												
Energy efficiency (η <sub>wh</sub> )	88												
Annual electricity consumption	kWh												
<b>Hydraulic unit specifications</b>													
Power source	Single phase, ~230 V, 50 Hz						3-phase, ~400 V, 50 Hz						
Dimensions H × W × D	mm						1,840 × 648 × 698						
Weight (Net)	kg						150						
Water circulation	Min./Max.	L/min		19.5/39.0	24.4/28.7	19.5/39.0	24.4/48.7	27.4/54.8					
DHW capacity	L												
Electrical heater capacity	Heating	kW											
	DHW	-											
Buffer tank capacity	L												
Expansion vessel capacity	L												
Water flow temperature range	Max.	°C											
Water pipe connection diameter	Flow/Return	mm											
Hot water pipe connection diameter	mm												
<b>Outdoor unit specifications</b>													
Power source	Single phase, ~230 V, 50 Hz						3-phase, ~400 V, 50 Hz						
Current	Max.	A		22.0	25.0	9.0	9.5	10.5					
Dimensions H × W × D	mm						1,290 × 900 × 330						
Weight (Net)	kg						92						
Refrigerant	Type (Global Warming Potential)	R410A (2,088)											
	Charge	kg											
Additional refrigerant charge	g/m												
	50												
Connection pipe	Diameter	Liquid	mm										
		Gas	mm										
	Length	Min./Max.	m										
	Length (Pre-charge)	m											
Height difference	Max.	m											
	Heating	°C											
Operating range	°C												
-25 to 35													

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.  
 \*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

## Dimensions

(Unit: mm)




### Outdoor Unit:

Single phase: WOHG112LHT/WOHG140LCTA

3 phase: WOHK112LCTA/WOHK140LCTA/WOHK160LCTA

### Hydraulic Indoor Unit:

WGHG140DG



# Comfort Control for split type

The high-grade heating controller automatically adjusts the flow temperature according to the climate conditions to maintain the room and domestic hot water temperatures at the desired levels.

## Hydraulic unit Controller 4 Heating modes


- 1. Automatic mode**  
Enables automatic switching between Comfort mode and Reduce mode according to time program
- 2. Reduce mode**  
Maintains water temperature at a lower level
- 3. Comfort mode**  
Maintains water temperature at a comfortable level
- 4. Protection mode**  
Activates frost protection in standby operation



## Useful Features


### Automatic heating curve control

Automatic temperature regulation according to heating curve (depending on heating terminal and outdoor temperature)



The heating curve will shift to adjust the room temperature setting.

Can be fine-adjusted when it is too warm or too cold.



### Quick recovery from defrosting

Maintains room temperature by boost start operation during defrosting.


### Auto changeover

When cooling mode is selected, the system automatically switches between cooling and heating modes depending on the outdoor temperature to serve as an all-season air conditioner.

### 2-zone independent control


2-zone independent control (For example, the individual control of 2 underfloor heating zones or the combination of 1 underfloor heating zone and 1 radiator zone)<sup>\*1</sup>

<sup>\*1</sup>: Optional parts required



### 2-stage low-noise mode

The outdoor unit can be switched to quiet mode, depending on the installation environment.  
<sup>\*</sup>Effective only for High Power Series



### Backup heater operation

Backup heater maintains a comfortable room temperature even when the outside temperature is low. The backup heater is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.

<sup>\*</sup> Optional parts is needed for High power Series.

## Energy Saving

### Time program

- The timer is easy to set.
- You can select the heating mode in conjunction with various times of the day.

### Day-weekly timer

- Allows up to 3 settings per day.
- Allows individual settings for each day of the week.

### Holiday timer


- Allows up to 8 settings.
- While you are away from home for an extended period during winter, the system prevents your room or house from freezing.

### Peak cut Function<sup>\*2</sup>

Sets the peak current value to reduce power consumption.

Mode	Ratio to reduce power consumption
1	100%
2	75%
3	50%
4	Almost 0%


<sup>\*</sup> Please refer to page W-038 and W-039 for optional parts information.



## Safety Features


### Anti-Legionella function

Prevents the growth of Legionella bacteria in the DHW tank to supply safe and clean hot water at all times.




### Anti-freeze function

When the outside temperature drops below a specified level, the compressor will self-activate and water will also be automatically circulated to prevent freezing.



### Emergency operation

If an outdoor unit fails to operate, a built-in backup heater or an external boiler is activated to supply an uninterrupted supply of hot water to the house.



### Error and Maintenance Alarm

Enables quick error-handling services and maintenance




- Error history saves 10 errors in memory
- Display telephone number of service company



# Simple installation

## Presetting configurations

A controller installed makes it easy to configure the system without having to set each component or unit individually.




8 simple patterns for system presetting (Pair of heating: 12 patterns)

Configuration (Parameter 5700)	Installation type
Presetting 1	1 heating circuit
Presetting 2	2 heating circuits
Presetting 3	1 heating circuit with boiler backup
Presetting 4	2 heating circuits with boiler backup
Presetting 5	1/2 heating circuit with buffer control
Presetting 6	1/2 heating circuit with buffer control and boiler backup
Presetting 7	Cascade connection Primary
Presetting 8	Cascade connection A
Presetting 9	Cascade connection B/C

- DHW & solar control auto detection
- Cascade connection only available in High Power models.

## Outdoor temperature simulation


It verifies that each unit operates properly under the set conditions and expected outdoor air temperature when the system is actually assembled.




The outdoor temperatures can be simulated in the range of -50°C to +50°C.

## Concrete floor drying

Allows the concrete surrounding the hot-water pipes to dry more quickly, shortening the construction period for underfloor heating installations.



## Controller with a large liquid crystal display and buttons for easy function setting



### Main operation flow and settings for installers and end users


	Flow Chart	Example Item
Installers	1 Install Setting	Pump speed setting, Configuration, Heating curve setting, Heat pump shut off
	2 Option Setting	Cooling kit, DHW kit, Boiler kit
	3 Convenient Function	Automatic heating curve setting, Underfloor controlled driving, Outdoor temperature adjustment, Maintenance period setting
	4 Workout Setting	Outdoor temperature simulator
	5 Confirmation	Checking operation (Heating and cooling, DHW, option)
End users	6 User Setting	Date and time, Time program, Operation temperature setting

# Easy Installation & Maintenance

- All hydraulic safety and control components are built in with no additional selection required.
- Lifting bars for installation free of difficulty or risk
- Easy access for maintenance
- Refrigerant pump down operation

## Maintenance Support


### Diagnostics functions for troubleshooting



# Comfort Control for Monobloc Type

## Controller with a clear color display and simple icons for easy function setting

**Color display**  
Shows all the information items related to the operation mode:  
Wi-Fi Connectivity / Operation / Pressure / Set temperature (DHW/Flow)  
Clock / Message / Service maintenance



**Operation indicator**  
Fixed white: Normal operation  
Flashing orange: Error

Menu access button

Navigation knob:  
Rotation: Menu navigation  
Press: Validation

Back button

**Main operation flow and settings for installers and end users**


	Flow Chart	Example Item
Installers	1 Install Setting	Pump speed setting, Configuration, Heating curve setting, Heat pump shut off
	2 Option Setting	Cooling kit, DHW kit, Boiler kit
	3 Convenient Function	Automatic heating curve setting, Underfloor controlled driving, Outdoor temperature adjustment, Maintenance period setting
	4 Workout Setting	Outdoor temperature simulator
	5 Confirmation	Checking operation (Heating and cooling, DHW, option)
End users	6 User Setting	Date and time, Time program, Operation temperature setting

## Useful Features

Flow temperature control with weather compensation


### Automatic heating curve control

Automatic temperature regulation according to heating curve (depending on heating terminal and outdoor temperature)



### Auto changeover

When Auto mode is selected, the system automatically switches between cooling and heating modes depending on the outdoor temperature to serve as an all-season air conditioner.




### Quick recovery from defrosting

Maintains room temperature by boost start operation during defrosting.

### 2-zone independent control

2-zone independent control (For example, the individual control of 2 underfloor heating zones or the combination of 1 underfloor heating zone and 1 radiator zone)\*\*2

\*1: Optional parts such as 2-zone kits, 3-zone kits, and thermostats are required  
\*2: 3 Zones can be controlled in the Control Box



### Backup heater operation

Backup heater maintains a comfortable room temperature even when the outside temperature is low. The backup heater is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.

## Energy Saving

### Away mode

It will set heating and DHW mode to the frost protection\* during the selected period:  
-If you activate away mode on HMI: You can choose start and end time/date.  
-If you activate away mode on Room thermostat (option): You can choose start and end time/date, as well as room setpoint during away period.  
\*: The protection mode automatically prevents an excessively sharp drop in room temperature.

### Holiday timer

- Allows up to 8 settings.
- While you are away from home for an extended period during winter, the system prevents your room or house from freezing.

## Safety Features

### Anti-freeze function

When the outside temperature drops below a specified level, the outdoor unit water pump will self-activate and water will also be automatically circulated to prevent freezing.


## Easy Installation & Maintenance

- All hydraulic safety and control components are built in with no additional selection required.
- Easy access for maintenance
- Refrigerant pump down operation

### Error and Maintenance Alarm


Enables quick error-handling services and maintenance

✖ Error ⚠ Warning



### Maintenance Support

Diagnostics functions for troubleshooting




In the event of an error, please note down the number and consult your heating engineer.

### Easy to set up


#### Easy Start

Choose language, set date and time. Answer questions from Easy Start.




### Remote connectivity and control

Via app "Cozy touch", you can manage and control of electric heaters, electric water heaters, heat pump water heaters, heat pumps.  
\* Cozytouch is a service of Group Atlantic




# System Configuration

## Split Type




## Split DHW Integrated Type




# Case Studies

## Split Type



**2-emitter simultaneous heating (Individual control)**  
Underfloor heating + Radiator



**Boiler connected to heating (Boiler + Heating)**




**2-emitter simultaneous heating & domestic hot water supply (Cascade)**




\*The hydraulic layouts shown are mainly representation. Please check with local dealer for actual hydraulic connections.

## Split DHW Integrated Type


**Single heating & domestic hot water supply**  
Radiator + domestic hot water supply



**2-emitter simultaneous heating (Individual control) & domestic hot water supply**  
Radiator + domestic hot water supply




**Boiler connected to heating (Boiler + Heating) and domestic hot water supply**



\*The hydraulic layouts shown are mainly representation. Please check with local dealer for actual hydraulic connections.

# Control Overview for Split type

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.





# Optional Parts Overview for Split type



Various optional parts are available to use ATW according to needs and environments.

## for Locally units



### Second circuit Kit

It can supply hot water at different temperatures to each two types of heating equipment, such as radiators and underfloor heating.

UTW-KZSXE\*1



UTW-KZDXE\*1



UTW-KZSXJ



UTW-KZDXJ

### Boiler connection kit

It can build hybrid systems using both boilers and heat pumps. Boiler and heat pumps are switched according to outside air temperature.



UTW-KBSXD



UTW-KBDXD



UTW-KBSXJ

\*1: The UTW-KREXD (Regulation extension kit) is not included but is required for connection.



## for Hydraulic unit



### Circulating pump

UTW-PHFYG

The high-output pump for replacement of the standard pump in the hydraulic unit. It can be used in properties with longer and more complex water piping.

### Cascade master/slave kit

Up to 3 hydraulic units can be connected for large-capacity use. It is need to install a primary kit in one unit and a secondary kit in one or two other units.



Cascade master kit (incl. LPB clip)



Cascade slave kit (incl. LPB clip)

### Cooling kit

Required when using ATW also for cooling operation. It is used to prevent condensation occurring in the indoor unit.



UTW-KCLXD



UTW-KCLXL

### Electrical backup heater relay



UTW-KBHL

It allows the backup heater for heating at 3 kW as standard can be used at 6 kW.

## for DHW




### DHW kit

UTW-KDWXD (External)  
Required to connect locally purchased DHW tanks to air to water.



### DHW tank

200 Liters: UTW-T20AXH / UTW-T20BXH  
300 Liters: UTW-T30AXH / UTW-T30BXH  
The BXH series is a more efficient tank than the AXH series.



UTW-KDEXE



UTW-KDEXL

### DHW expansion kit

The expansion vessel(18L) for connection to DHW water piping.

## for Outdoor unit



### Drain pan

UTW-KDPXB

It is used to collect and drain condensation water generated by outdoor units.


















### External connect kit











UTY-XWZXZ2 / UTY-XWZXZ3

The signal input (low noise mode, peak cut) and signal output (compressor operation, base pan heater control) for outdoor units are possible externally.



# Optional parts list for Monobloc type

Product Name	Model Name	Monobloc Type			
		Comfort Series			
		1Ø			
		Contoll Box	Wall Hung	DHW Integrated	Outdoor Unit
Second circuit kit 	UTW-KZSXQ		•		
DHW kit 	UTW-KDWXQ		•		
Second circuit kit 	UTW-KZDXQ			•	
DHW loop kit 	UTW-KDLXQ			•	
DHW expansion kit 	UTW-KDEXQ			•	
Outdoor temperature sensor 	UTW-KESXQ	•	•	•	
Condensation detection sensor 	UTW-KCDXQ	•	•	•	
Regulation extension kit 	UTW-KREXQ	•	•	•	
Electrical Backup heater relay 	UTW-KBHXQ		•	•	
Room thermostat Wired power supply 	UTW-C225XQ	•	•	•	
Room thermostat Battery power supply 	UTW-C228XQ	•	•	•	
Cover Plate for thermostat 	UTW-KCPXQ	•	•	•	
Drain pan 	UTW-KDPXQ				•
Antivibration Rubber feet 	UTW-KARXQ				•
Antifreezing valve for Monobloc 	UTW-KAVXQ				•

Product Name	Model Name	Monobloc Type			
		Comfort Series			
		1Ø			
		Contoll Box	Wall Hung	DHW Integrated	Outdoor Unit
Single circuit kit 	UTW-KZC1XQ	•			
Second circuit kit 	UTW-KZC2XQ	•			
Third circuit kit 	UTW-KZC3XQ	•			
Third circuit kit 					
Third circuit kit 					
Boiler connection kit 	UTW-KBCXQ	•			
DHW kit 	UTW-KDWCXQ	•			
Backup heater kit 	UTW-HB6CXQ	•			
DHW tank 200 Liters  300 Liters 	UTW-T20AXH UTW-T30AXH	•	•		
	UTW-T20BXH UTW-T30BXH	•	•		

# Optional Parts List for Split type

Product Name	Model Name	Split Type										Split DHW Integrated Type									
		Super High Power			High Power			R32 Comfort				Super High Power			High Power			R32 Comfort			
		1Ø	1Ø		3Ø		1Ø				1Ø	1Ø		3Ø		1Ø					
		16	11	14	11	14	16	5	6	8	10	16	11	14	11	14	16	5	6	8	10
Second circuit Kit	UTW-KZSX	-	●*1	●*1	●*1	●*1	●*1	●*1	●*1	●*1	-	-	-	-	-	-	-	-	-	-	-
	UTW-KZDX	-	-	-	-	-	-	-	-	-	-	●*1	●*1	●*1	●*1	●*1	●*1	●*1	●*1	●*1	●*1
	UTW-KZSXJ	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	UTW-KZDXJ	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
Boiler connection kit	UTW-KBSXD	-	●	●	●	●	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-
	UTW-KBDXD	-	-	-	-	-	-	-	-	-	-	●	●	●	●	●	●	●	●	●	●
	UTW-KBSXJ	●	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	-	-	-
Balancing vessel	UTW-TEVXA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
DHW kit	UTW-KDWXD (External)	●	●	●	●	●	●	●	●	●	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2
DHW tank	200 Liters 300 Liters UTW-T20AXH UTW-T30AXH	●	●	●	●	●	●	●	●	●	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2
	200 Liters 300 Liters UTW-T20BXH UTW-T30BXH	●	●	●	●	●	●	●	●	●	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2	-*2
DHW expansion kit	UTW-KDEXE	-	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-	-	-	-	-
	UTW-KDEXL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	●	●	●	●	●
Circulating pump	UTW-PHFXG	●	●	●	●	●	●	●	●	●	●	●	●	●	●	-	-	-	-	-	-
Cooling kit	UTW-KCLXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	-	-	-	-	-	-
	UTW-KCLXL	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	●	●	●	●	●
Regulation extension kit	UTW-KREXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Drain pan	UTW-KDPXB	-	-	-	-	-	-	●	●	●	●	-	-	-	-	●	●	●	●	●	●
Cascade master kit (incl. LPB clip)	UTW-KCMXE	-	●	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Cascade slave kit (incl. LPB clip)	UTW-KCSXE	-	●	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-


Product Name	Model Name	Split Type										Split DHW Integrated Type									
		Super High Power			High Power			R32 Comfort				Super High Power			High Power			R32 Comfort			
		1Ø	1Ø		3Ø		1Ø				1Ø	1Ø		3Ø		1Ø					
		16	11	14	11	14	16	5	6	8	10	16	11	14	11	14	16	5	6	8	10
HMI kit	UTW-KHMXE	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3
Remote controller	Wired UTW-C74TXF	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3
	UTW-C74HXF	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3
Room thermostat	Wired UTW-C55XA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Wireless UTW-C58XA	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4
Outdoor sensor transmitter	UTW-MOSXD	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4
RF modules for BSB-Port	UTW-MRCXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Web server	UTW-KW1XD	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5
	UTW-KW4XD	-	●*5	●*5	●*5	●*5	●*5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
LPB clip	UTW-KL1XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MODBUS® clip	UTW-KMBXJ	-	●*5	●*5	●*5	●*5	●*5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Service tool (incl. OCI700 Adapter)	UTW-KSTXD	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7
Service tool software	UTW-KPSXD	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8
External connect kit	UTY-XWZXZ2	-	●	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	UTY-XWZXZ3	●	-	-	-	-	-	-	-	-	-	-	-	-	-	●	-	-	-	-	●
Back-up Heater	UTW-HS6XG	-	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	UTW-HT9XG	-	-	-	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Electrical backup heater relay	UTW-KBHXL	-	-	-	-	-	-	●	●	●	●	-	-	-	-	●	●	●	●	●	●

●: Available    -: Not Available

\*1: The UTW-KREXD (Regulation extension kit) is not included but is required for connection.  
 \*2: Split DHW integrated type supplies DHW without the DHW kit and DHW tank.  
 \*3: Includes 21 languages with no need to prepare an RC for Eastern Europe separately.  
 C74TXF has a built-in room temperature sensor.  
 C74HXF has a built-in room temperature and humidity sensor.  
 \*4: UTW-MRCXD (RF modules) is required for the connection.  
 \*5: The connection of UTW-KW4XD for simultaneous control of multiple ATW units is only possible for cascade systems.  
 \*6: Additional Spare parts 9708302034 (Analogue interface PCB) and 109696 (connection wire) are required.  
 \*7: UTW-KL1XD (LPB clip) is required for the connection.  
 \*8: UTW-KW1XD or UTW-KW4XD (Web server) is required for the connection.

# SUPPORT

- Sp-002 VRF Support
- Sp-004 HVAC system design Support Tool
- Sp-006 Air To Water Support Tool
- Sp-008 Quick Service & Maintenance
- Sp-010 Service monitoring tool
- Sp-012 Service Tool
- Sp-013 Web monitoring tool



Service & Support Website  
<https://www.fujitsu-general.com/g-eu/support/>

Our knowledgeable sales and service representatives assist you, from product selection to installation and maintenance.

Category	Information material										Tool							
	Product sales training material	Product technical training material	Product news	Brochures	Promotional movies	Operation manuals	Design & Technical manuals	Certification data	2D CAD data	3D CAD (Revit) data	Installation manuals	Service manual	Air To Water Package label creator	Design simulator (Room air conditioner, Packaged air conditioner, and VRF)	Air To Water proposer	CFD simulation	Service tool and Web monitoring tool	Mobile technician
Product training	●	●																
Product information seeking			●	●	●	●	●											
Technical information seeking						●	●					●						
Model selection						●							●	●				
Design						●		●	●									
Verification																●		
Installation						●				●								
After-sales service											●						●	●

# VRF Support

Fujitsu General provides engineers and consultants with a wide range of product and technical information. In addition, we conduct research on new products and support design activities. We provide a wide range of support services from design to installation to maintain high quality.




## Training facilities

### Technical information

We provide equipment selection software that facilitates the design of air conditioning systems by providing performance data for the units and estimation for model selection.

**Features**

- Design & Technical manual
- Model selection & estimation
- Certification data
- 2D/3D CAD data




2D/3D CAD data

### Technical support

Technical support is offered at every stage, from design through to installation, to assist in optimizing air conditioning solutions.

**Features**

- CFD simulation
- Guidelines
- Commissioning support



CFD simulation



Commissioning support

### Product information

Information on new models is provided in the form of documents and movies in a timely manner for release, readily downloadable from the private section of our website. Contact your Fujitsu General representative for access information.

**Features**

- Product news
- Brochures & manuals
- Promotional movies



<https://www.fujitsu-general.com/g-eu/support/downloads/vrf/>



Fujitsu General regularly provides professional product, technical and service training at its training facilities worldwide. These research facilities also support the development of human resources with advanced technical skills.

**Features**

- Designing VRF systems
- On-site training for control systems


- 1 Head office training center in Japan
- 2 Training center in China
- 3 Asia training center in Singapore
- 4 Europe training center in the United Kingdom
- 5 Europe training center in Germany
- 6 America training center in the United States
- 7 Middle East training center in the UAE
- 8 Oceania training center in Australia

# HVAC system design Support tool

Put the charts and pens away and design your projects on a computer using the Design simulator. Everything from selecting indoor and outdoor units, allocating controls and optional parts through to designing the piping and wiring systems is made easier using the program's built-in features. Once the project design is complete, the Export function makes it easy to generate material lists, product specifications, and refrigerant calculations, and more. You can also export in Word, Excel, and Acrobat formats, as well as group CAD data related to your project.



## Design simulator




### Outputs in the format that matches the application

You can export your project information in a number of industry standard file formats.

- Word format (rtf) (doc)
- Excel format (csv)
- Acrobat format (pdf)
- 2D CAD data (DXF)

### Automatically create model selection information

- The required performance, type, and temperature conditions for each indoor unit are entered and then dragged and dropped onto the outdoor unit to automatically set each unit.
- Creates piping and wiring diagrams automatically to facilitate branching, grouping, and option settings.
- The additional refrigerant charging is automatically calculated when the pipe length is entered.
- Easy configuration of remote controller groups, central controller, and converters.
- The equipment list including the equipment information is created automatically.



### Update your Design simulator

The database can be updated easily online with the AutoUpdate function using FTP.

## BIM Building information modeling

### BIM files of Fujitsu General's products are available on BIMobject®


Fujitsu General is releasing BIM files of our products on the BIMobject® website BIMobject.com.

#### Outline of BIMobject®

BIMobject® is a game changer for the construction industry, offering development, maintenance, and syndication of objects on the world's largest BIM platform.

#### About BIM files

- BIM files can be viewed in Autodesk Revit® 2018 version or later.
- In each BIM file, the location of the connectors for the refrigerant and drain pipe is different.
- Each BIM file includes several family types.
- A catalog and specification sheet is available in Revit file format for each product.



#### Data content

- Shape (Size)
- Drain direction
- Pipe direction
- Power supply location
- It contains information about the above specifications.



Type catalog with product specifications




- Shape (Size)



\* To learn more about how to use BIM files, refer to the instructional video on each product page. [youtu.be/wfL-hwFQ7dM](https://youtu.be/wfL-hwFQ7dM)

# Air To Water (ATW) Support tool

Fujitsu General's software for ATW automatically creates a combination of ATW equipment by simply providing a few parameters. Supports multiple languages with an automatic update function.



## Air To Water proposer

Selecting models with detailed technical information

- Simply enter the region where the equipment will be installed, the required heating capacity, the method of heating and other factors, and the software will select the appropriate equipment automatically.

\* From now on, the name will be changed to the new name above.  
The current name is WATERSTAGE Proporsor.



The images of the optional items will help you configure your system correctly. If more than one ATW equipment is required, all relevant option items will be selected automatically.

The selected unit can be modified after reviewing the overall system configuration. The images and the list of devices are displayed at the same time, helping to avoid mistakes in device selection.



## Air To Water Package label creator

### Download Energy labels and Fiches from our website

ErP documents such as Energy labels, Product fiches, Package labels, Package lists, Information sheets, and EC Declarations can be searched for and downloaded from our website.

We will also provide an online service in the future so that installers can easily create various package labels and package fiches for different models.

\* From now on, the name will be changed to the new name above.  
The current name is WATERSTAGE Proporsor.



# Quick service & maintenance

In the unlikely event that a problem should occur with the unit or system, a wide variety of support tools are available to assist with prompt service and maintenance anytime, anywhere, including error code displays on the product, service tools to check the detailed status of the entire system, and remote monitoring tools using the internet.



## Easy maintenance & monitoring

### Designed for easy maintenance

The operating status of the air conditioner and detailed trouble conditions are displayed on the 7-segment indicator lamp on the outdoor unit printed circuit board (PCB) and on the screen of the remote controller. Check the status of the unit quickly for a prompt response.


- Display the operation mode at the time.
- Discharge temperature and pressure
- Compressor operation status
- "Address/Type/Number" of the outdoor unit
- Error code



### Error diagnosis by Service tool


Connect Service tool to check the status details of units, from single split to VRF, on a computer screen. Check the errors quickly for prompt countermeasures.

- Operating status/control
- Monitoring operating conditions
- Monitoring sensor data
- Indicating trend graphs
- Error history
- Indicating refrigerant circuit diagrams (for VRF)



### Remote monitoring

VRF system operating status and trouble status details can be monitored remotely at any time via the internet. Prompt coordination is available with service personnel.



## Mobile troubleshooting App for iOS and Android™ devices


We will release an App for troubleshooting tools for iPhone, iPod touch and other Apple devices, and Android products for Fujitsu General air conditioners (Room air conditioner/Packaged air conditioners VRF and ATW, "AIRSTAGE Mobile", and R32 calculation of allowable refrigerant capacity) Use Error Code Check, Troubleshooting, and Sensor Check to understand the status of your air conditioner.



## Service monitoring tool for Single split, Multi-split & Air to water




- A quick overview of the temperature sensor readings and the electronic expansion valves (EEVs), fans, compressors and other control components
- It is not always easy to read the temperature sensor and know the status of the control components. So let the Service monitoring tool judge them.
- Visualizes protected operations
- Troubleshoots intermittent problems effectively
- Provides proof of normal operation to customers during periodical maintenance



	UTY-ASSX
Dimensions (H × W × D) (mm)	60 × 160 × 160
Weight (g)	500



**NEW** AIRSTAGE Service Monitor Tool for Single-split, Multi-split, Air to water  
UTY-ASSXZ1




**Improved work efficiency**

AIRSTAGE Service Monitor Tool can diagnose the cause of the error for a wide range of products. It makes maintenance or service support faster and can also reduce the number of visits and maintenance costs.

\*The values in the pictures are examples.

**Bluetooth communication**

AIRSTAGE Service Monitor Tool can diagnose by the smart device\*1 and reduce the working time compared with diagnosis by PC. No need to connect a PC makes diagnosis easier even in narrow spaces.



\*1 Android only.  
You need to install the "AIRSTAGE Service Monitor Tool" app on your smart device.


**Compact and lightweight design**

New model is easy to carry by compact and lightweight design. The service personnel can visit the maintenance site with small luggage.



**New application with simple design**

New application for smart devices has been released. The stylish design makes the application easy to use for everyone.



AIRSTAGE Service Monitor Tool



**Refrigerant cycle diagram display**

The operating status can be displayed with a simple, clear diagram\*2 on the smart device. It reduces the time for diagnosis and makes diagnosis easier. It can complement abundant experience and advanced knowledge of refrigerant cycle. This shortens the training time for service personnel.

\*2 list and graph displays are also available



\*The values in the pictures are examples.

**Specifications**

	UTY-ASSXZ1
Dimensions (H x W x D) (mm)	20 x 35 x 60 (adapter)
Communication cable (cm)	60
Weight (g)	25 (adapter)
Communication method	Bluetooth 5.3
Max. communication distance (m)	10*3
Compatible device	Android8.0 or above

\*3 Depends on the environment

**Function List**

	UTY-ASSXZ1	UTY-ASSX	
Product specification	Outdoor unit PCB	Outdoor unit PCB	
Communication	Bluetooth	Wired	
Support product type	Split	●	
	Multi-split	●	
	ATW	●	
	VRF	—	
	—	—	
Function	Product distinction	●	
	Signal-type distinction	●	
	Operating status display	List	●
		Graph	●
		Refrigerant cycle diagram	—
	Adapter firmware update	●	
Adapter status monitoring	●		
Input and output of history data	●		

# Service tool

UTY-ASGXZ1

## Extensive monitoring and analysis functions that make installation and maintenance easier

- The operation status of the system can be monitored and analyzed to detect any malfunctions.
- Data on the operation status of the system can be stored on a computer to allow for remote access.
- Up to 400 indoor units in a single VRF network system can be controlled and monitored for a large building or hotel.
- This software can be connected to any point of transmission line with a USB adapter (locally available).

\* Saved data can be displayed offline. Note that the data saved by the following software applications cannot be displayed.

- UTR-YSTB/UTR-YSTC (Service tool)
- UTR-YMSA (Web monitoring tool)

## Automatic operation check for refrigeration cycles

Once installed, the Service tool automatically checks for refrigeration cycles. The self-diagnosis function determines whether each sensor value is normal, which reduces the need for manual checks. The result of a diagnosis can be provided in a report.

These sensor values are checked automatically:


- ✓ the discharge temperature is normal, "OK"
- ✓ the super heat volume is normal, "OK"
- ✓ the high pressure pipe value is normal, "OK"
- ✓ the low pressure pipe value is normal, "OK"

And the values for other items will also be diagnosed.

Use the result of a self-diagnosis only as a guide and use your own judgment to make a final decision.


## Remote technical support and maintenance

On-site check screen can be shared between on-site staff and a service technician in a remote location. When a service technician visits the site for troubleshooting, the system's operation status can be shared in real time with a remote service center for assistance. On-site staff can have an online chat with a remote service center to get further assistance.



## Trend charts

Previous-generation application could display only 3 sets of data from sensors. However, the current generation of the service tool displays multiple charts simultaneously so that refrigeration cycles can be monitored and checked in greater detail.



### Computer requirements

	UTY-ASGXZ1
Operating system	<ul style="list-style-type: none"> <li>• Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>• Microsoft® Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>• Microsoft® Windows® 10 Pro (32-bit or 64-bit)</li> </ul>
CPU	1 GHz or higher
Memory	<ul style="list-style-type: none"> <li>• 1 GB or more (for Windows® 7 [32-bit], Windows® 8.1 [32-bit], and Windows® 10 [32-bit])</li> <li>• 2 GB or more (for Windows® 7 [64-bit], Windows® 8.1 [64-bit], and Windows® 10 [64-bit])</li> </ul>
HDD	40 GB or more of free space
Screen resolution	1366 × 768 pixels or higher
Interface	<ul style="list-style-type: none"> <li>• USB port for U10 USB Network interface and software protection key</li> </ul>
Software	Internet Explorer® 11 or Microsoft Edge

### Packing list

Name	Quantity	Application
White-USB-key (Software protection key)	1	Software protection key to be connected to a USB port on a Service tool-installed computer. This software runs only on a computer with WibuKey.

- Computer requirements
- Echelon® U10 USB Network Interface - TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)

# Web monitoring tool


UTY-AMGXZ1

## Features

- Troubleshooting is performed by monitoring each air conditioning unit remotely during a periodical system check.
- An error notification is automatically transmitted to several locations via the internet\*1.
- Requires either a dedicated internet connection or landline to operate.
- The occurrence of an error can be confirmed through an error alert and equipment status information obtained from a remote location.
- Monitoring data can be downloaded in a remote location. These data can be accessed and displayed even when the service tool is in offline mode.
- Can be viewed on the monitoring computer's Web browser without installing any special software.


\*1: Internet e-mail access required.

## Web Monitoring System



## Supporting up to 4 VRF network systems

Up to 4 USB adapters can be connected to a computer, enabling the monitoring of up to 1,600 indoor units. Suitable for use in a large building or hotel.



### Computer requirements

	UTY-AMGXZ1
Operating system	<ul style="list-style-type: none"> <li>• Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>• Microsoft® Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>• Microsoft® Windows® 10 Pro (32-bit or 64-bit)</li> </ul>
CPU	1 GHz or higher
Memory	<ul style="list-style-type: none"> <li>• 1 GB or more (for Windows® 7 [32-bit], Windows® 8.1 [32-bit], and Windows® 10 [32-bit])</li> <li>• 2 GB or more (for Windows® 7 [64-bit], Windows® 8.1 [64-bit], and Windows® 10 [64-bit])</li> </ul>
HDD	40 GB or more of free space
Screen resolution	1366 × 768 pixels or higher
Interface	<ul style="list-style-type: none"> <li>• USB ports (one for U10 USB Network interface and up to 4 ports for software protection keys)</li> <li>• Interface for remote connection:                             <ul style="list-style-type: none"> <li>- Landline: Modem is required.</li> <li>- Internet using LAN: Ethernet port is required.</li> </ul> </li> </ul>
Software	Internet Explorer® 11 or Microsoft Edge

### Packing list

Name	Quantity	Application
White-USB-key (Software protection key)	1	Software protection key to be connected to a USB port on a Service tool-installed computer. This software runs only on a computer with WibuKey.

- Computer requirements
- Echelon® U10 USB Network Interface - TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)